SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cat

Sample ID SL-512-SA50-SB-0.0-0.5 **Date/Time** 9-26-13 / 0735

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Groups	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** ~~1YRR~~ <5%

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/Metamorphic Gravel)		N/A

Other _____

Is Staining Present Yes (NO)

Color brn (7.5YR 4/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-512	Subarea: 5D	Date Started: 9-26-13	Date Completed: 10/02/2013
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st NA= 6' (no refusal)
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand auger		Depth Drilled into Bedrock: NA
Radiological Background: γ- 13 $\alpha\beta$- 89	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/.05	0.0	13/81	SL-512 SA5D-SB 0.0-0.5	0735	SM	SILTY SAND, brown (7.5YR 4/3) mottled w/ (7.5YR 5/4) f grn, mod well sorted, quartz, dry, compacted & consolidated, hard, sli friable, sli clayey 70% SD, 20% SILT, 10% clay, tr amt igneous gravel (road material) — 0.5
		0.0	13/84				
1	HA	0.0	13/84			CL	
2		0.0	13/78			Sandy CL	~~SM 0101513~~ CLAY ~~w/ SAND~~, dk brn (7.5YR 3/2) mottled w/ brown (7.5YR 4/3), mod low to low plasticity, f to hard sli moist, some rootlet molds & burrows filled w/ calcium carbonate, 60% ~~SD~~ CLAY, 30% SD, 10% SILT SD is f grn quartz — 2
3		0.0	13/60			CL	CLAY, reddish brown (5YR 4/3) mottled w/ (5YR 4/4) and yel red (5YR 5/6), mod low plasticity to low plasticity, f to hard, sli moist, few rootlet molds & burrows filled w/ $CaCO_3$, 60% CLAY 20% SD, 20% SILT
4	1.0/1.0	0.0	13/60	SL-512 SA5D-SB 4.0-5.0	0800	CL	SANDY CLAY, same colors A.A, mod low plasticity, f to sli soft dry to sli moist, w/ rootlets & burrows filled w/ $CaCO_3$, 60% CLAY 30% SD, 10% SILT, SM 0101513 — 4.0
5		0.0	13/54				
	HA					CL	SANDY CLAY, yel brn (10YR 5/6) mottled w/ (10YR 5/4) and brn yel (10YR 6/6), mod low plasticity, mod soft to sli f grn, dry to sli moist, 60% CLAY 30% SD, 10% SILT SM 0101513 — 5.4
6		0.0	13/72				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of ___

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr: no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	Φ: diameter	bgs: below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID: DG-512	Subarea: 5D	Date Started: 9-26-13	Date Completed: 10-2-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 19.8
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{x}$=13 σ=89	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
6	4'-8' 4.0/4.0	0-6' see Pg 1 when 0-6' bgs was collected by Hardaugue on 9-26-13				CL	CONTINED W/ DPT ON 10-2-13 SANDY CLAY, A.A.
7		0.0	13/66				
8		0.0	13/42				
9		0.0	13/48			CL	8.2 CLAY w/SAND strong brown (7.5YR 4/6) mottled w/ brown (7.5YR 4/3), mod low plasticity, moist firm to hard, sli crumbly, dry, SD is fine and vf CLAY, F grnd, mod poorly ~~sorted~~ graded subrounded to subangular sand 70% CLAY 15% SD 15% SILT Few to some root molds & burrows infilled w/ $CaCO_3$ deposits, tr ants mottled w/ red (2.5YR 4/6) w/ depth ~~80% CLAY 15%~~
10		0.0	13/66				
11		0.0	13/54				
12		0.0	13/42				
13		00	13/78				
14		00	13/90			CL	13.6 CLAY brown (7.5YR 4/4) mottled w/ strong brown (7.5YR 4/6) & speckled w/ yel brn (10YR 5/6) & red yel (7.5YR 7/8), mod low to low plasticity, hard, well compacted; dry to sli moist; 85% CLAY 10% SILT 5% SD
15		0.0	13/96				

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-512	Subarea: 5D	Date Started: ~~10-2-13~~ 9-26-13	Date Completed: 10-2-13
Project: SSFL		Geologist: David Rojas	Total Depth: 19.8

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	See pg 2						CLAY A.A See Pg 2
16		0.0	13/108				
17	3.8/3.8	0.0	13/66				
18		0.0	13/60				GRADUAL CONTACT
						CL	SANDY CLAY, yel brn (10YR 5/6) mottled gy (10YR 5/1) and brn (10YR 4/3), mod low plasticity, Fm to hard, mod cemented; dry to sli moist 60% CLAY 30% SD 10% SILT SD is f-rn gnd, mod poorly sorted subangular quartz 18.0
19		0.0	13/72				Abrupt Contact
		0.0	13/78			SC	CLAYEY SAND, yel brn (10YR 5/6) mottled gy & It yel brn (10YR 4/4) & It yel brn (10YR 6/4), f-rn gnd w/ tr to few ang to coarse gnd becoming coarser w/ depth, mod plastic, sl to mod cemented, fractured smooth 19.2
							Refusal @ 19.8

dry to sl moist; 70% SD 25% CLAY 5% SILT becoming w/ depth → 80% SD 15% CLAY 5% SILT

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cole

Sample ID SL-512-SA5D-SB-4.0-5.0 **Date/Time** 9-26-13 / 0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): NONE
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color reddish brn (5YR 4/3)

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cruz

Sample ID SL-513-SA5D-SB-0.0-0.5 **Date/Time** 9-18-13 / 0730

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals		EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X SM 9/18/13
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM (9/10/13)	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 5C
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Limerock
~~Igneous~~/Metamorphic (Gravel) N/A
Lmst

Other _____

Is Staining Present Yes (No)

Color Brown (7.5YR 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mila Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-513	Subarea: 5D	Date Started: 9-18-13	Date Completed: 9-18-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/84489		Total Depth: 1st DPT = 17.0, 2nd DPT = 17.2
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{x}$ = 12 σ = 69	Borehole diameter: 2.25		
PID Background:	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Initial: Mill Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/66	SL-513 SA5D-SB 0.0-0.5	0730	GW GM	GRAVEL w/ SILT brown (7.5YR 5/3), fine-sized gravel limerock, SD is F gm mod poorly graded, SD = 40%
		0.0	12/84			CL	GRAVEL = 50% SILT = 10%, dry
1	2.5/3.5	0.0	12/96				CLAY w/SAND, dk brn (7.5YR 3/2), firm to hard, compacted low plasticity, crumbly, SD is F-m gm w/tr ant coarse gm, poorly graded subrounded to subangular quartz, tr ant calcareous, some org (roots)
2		0.0	12/90				CLAY = 80% SD = 20%, dry
3		0.0	12/84				
4		0.0	12/96				4.0
	3.5/4			SL-513 SA5D-SB 4.0-5.0	0740	CL	CLAY redd sh brn (5YR 4/4) mottled w/ yel red (5YR 5/6), mod firm, compacted, mod low plasticity, mod crumbly, 90% CLAY 10% SD tr ant silt, SD is F gm well sorted, quartz, tr ant calcareous lamentations whisps <1m few ant org (roots), dry
5		0.0	12/72				
6		0.0	12/84				
7		0.0	12/66				
							7.5
8		0.0	12/72			CL	SANDY CLAY, yel brn (10YR 5/8) mottled w/ dk yel brn (10YR 4/4), mod soft to sli firm, mod low plasticity, crumbly, SD is F gm well sorted quartz
9	3/4	0.0	12/78	SL-513 SA5D-SB 9.0-10.0	0750		CLAY = 60% SD = 30% SILT = 10%, dry
10		0.0	12/72				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG-513	Subarea: 5D	Date Started: 9-18-13	Date Completed: 9-18-13
Project: SSFL		Geologist: David Rojas	Total Depth: 17.2

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							SEE PG 1 FOR DESCRIPTION
11			12/66			CL	10.8 CLAY WITH SAND, H yel brn (10YR 6/4) mottled w/ brn (10YR 5/3) and ~~V~~ pale brn (10YR 6/3) tr amt brn yel (10YR 6/8), firm to sli soft, mod low plasticity, ~~tr amount fine~~ SAND calcareous and clay blebs & laminations. 70% CLAY 15% SD, 15% SILT, dry, becoming sandier w/ depth
12		0.0	12/72				
13	4/4	0.0	12/66				
14		0.0	12/60				
15		0.0	12/84				Abrupt contact 15
16		0.0	12/72	SL-513 SASD-SB 16.0-17.0	0800	SP SM	SAND w/ SILT, brn yel (10YR 6/6) mottled w/ yel brn (10YR 5/4) F-med gnd, mod well sorted, subrounded, quart, tr amt blebs of clayey sand decreasing w/ depth, clayey sand lense from 15.8-16.4' bls, 90% SD, 10% SILT
17	1.2/1.2	0.0	12/84				17.2

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G t.

Sample ID SL-513-SA5D-SB-4.0-5.0 Date/Time 9-18-13 / 0740

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	X SM9/613
Perchlorate Confirmation	EPA 6850/6860	X
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16 oz jars & 2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color reddish brown (5YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.E

Sample ID SL-513-SA5D-SB-9.0-10.0 Date/Time 9-18-13/0750

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	X SM 9/18/13
Perchlorate Confirmation	EPA 6850/6860	X
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
TPH	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
Other	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16 oz jars & 2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brown (10YR 5/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VGT

Sample ID SL-513-SA5A-SB-160-170 Date/Time 9-18-13/0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 16.0

End Depth 17.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X sm 10/3
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	X
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16oz jars & 2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brn. yel. 10YR 6/6

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GK

Sample ID SL-514-SA5D-SB-0.0-0.5 **Date/Time** 9-18-13/0850

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 45%

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
Other		

Is Staining Present Yes (No)

Color brown (7.5YR 5/3)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-514	5D	9-18-13	9-18-13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: 1st DPT = 13.0 2nd DPT = 13.6
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 αβ = 87	Borehole diameter: 2.25	
PID Background: 0.0 ppm	Depth to GW: NA	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/100	SL-514 SA5D-SB 0.0-0.5	0850	GP	GRAVEL w/ SILT & SAND, brown (7.5YR 5/3). Fine sized gravel, mineral, subangular to angular SD is f-gm, mod well sorted, subrounded to subangular quartz & carbonate, 45% Gravel, SD = 35% SILT = 20%
		0.0	12/60			GM	
1		0.0	12/72			CL	0.5
	1.5/3.5						CLAY ~~w/ SAND~~ brn (7.5YR 5/4) mottled w/ lt brn (7.5YR 6/4), firm to hard, compacted, low plasticity dry, 80% CLAY, 10% SAND, 10% SILT, SD is f-gm, well sorted, quartz tr ant org (roots),
2		0.0	12/84				
3		0.0	12/72				
						CL	3.2 CLAY w/ SAND strong brown (7.5YR 5/6) mottled w/ brn (7.5YR 4/4) firm, mod well compacted, mod low plasticity, dry 70% CLAY, 20% SD 10% SILT, SD is f-gm, well sorted, quartz
4		0.0	12/90	SL-514 SA5D-SB 4.0-5.0	0900		
5		0.0	12/60				
						CL	5.2 SANDY CLAY brn yel (10YR 6/6) mottled w/ yel brn (10YR 5/4), mod soft to sli firm, ~~mod~~ low plasticity, dry, SD is f-gm, well sorted quartz 55% CLAY, 35% SD, 10% SILT
6	3.5/4	0.0	12/60				
7		0.0	12/54				
						CL	7.0 CLAY w/ SAND brown (7.5YR 4/4) mottled w/ strong brown (7.5YR 5/6) and lt brn (7.5YR 6/3), mod soft to sli firm, mod low plasticity, dry, 70% CLAY, 20% SD, 10% SILT
8		0.0	12/78				
9	3.5/4	0.0	12/54				
10		0.0	12/60				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr: no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	φ: diameter	bgs: below ground surface

Location ID: DG-514	Subarea: SD	Date Started: 9-18-13	Date Completed: 9-18-13
Project: SSFL		Geologist: David Rojas	Total Depth: 13.8

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							SEE LITHOLOGY ON PG 1
11	SEE PG 1	0.0	12/72			CL	CLAY w/SAND, strong brown (7.5YR 5/6) mottled w/ brown (7.5YR 5/4) and yel red (5YR 5/6) firm to hard, mod low plasticity, SD is f-gm well sorted, subrounded, quartz, tr amt calcareous concretions, whispy, thin (<1mm), dry to sl moist 70% CLAY, 20% SD, 10% SILT — 11.0
12		0.0	12/72				
13	1.8/1.8	0.0	12/90				
~~CRM~~	X	0.0	12/90			SP-SM	SAND w/SILT, brn yel (10YR 4/6) mottled w/ yel brn (10YR 5/4), F-gm w/tr amt of m-gm mod well sorted, subrounded to subangular quartz, dry 90% SD 10% SILT — 13.0 — 13.8
							Refusal @ 13.8

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-514-SA5D-SB-4.0-5.0 Date/Time 9-18-13/0900

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** None

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Strong brown (7.5 YR 5/6)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7235

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-SI5-SASD-SB-00-05 HS Date/Time 9/9/13 @ 9:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6 - SS Sleeves
1 - ~~Hoa~~ @ 9/9/13
902

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-515	SD	9-9-13	9/9/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: (FT)
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM / DAN AGUA	23,23
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: γ=13 / βγ=84	Borehole diameter: 2.25 INCH	~~23~~ 9/9/13 0
PID Background: 0.0	Depth to GW: 0	Sampling Method:
Radiological Equipment Used:	PG Review & No.: #7735	MACRO CORE
✓ MicroR ✓ Alpha/Beta ✓ Pancake		Geologist: B/GOLDEN/IC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/76	SL-515-SA5D-SB-0.0	9:30	ML	SILT W/ SAND; DK BROWN (10YR 3/3) 80% SILT, SOFT, NON-PLASTIC, DRY; 20% SAND, F, PG, LOOSE; NO ODOR
1		0.0	13/66	0.5 MS			
	3.0			SL-815-SA5D-	9:40		
2	4.0	0.0	13/96	SB-0.0-0.5			
3		0.0	13/78				GRADATIONAL CONTACT
						CL	CLAY — STRONG BROWN (7.5YR 4/6) 100% HARD, LOW PLASTIC, SEMI MOIST, NO ODOR TRACE OF ROOT STRINGERS.
4		0.0	13/66	SL-515-SA5D-	9:50		
				SB-4.0-			
5	4.0	0.0	13/96	5.0			
	4.0						
6		0.0	13/90				
7		0.0	13/84				
8		0.0	13/88			CL	AS ABOVE W/ GRADUAL COLOR CHANGE TO REDISH BROWN (5YR 5/4)
9	4.0	0.0	13/79	SL-515-SA5D-	10:00		
	4.0			SB-9.0-			
10		0.0	13/96	10.0			

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG-515	50	9/9/13	9/9/13
Project: SSFL		**Geologist:** BKAPPUK	**Total Depth:**

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	4.0/4.0	0.0	13/90			CL	CLAY, REDDISH BROWN (5YR 5/4) 100% CLAY, HARD, LOW PLASTIC, SEMI MOIST, NO ODOR
12		0.0	13/90			CL	AS ABOVE
13		0.0	13/72				
14	4.0/4.0	0.0	13/108				
15		0.0	13/90				
16		0.0	13/90			CL	
17		0.0	13/108				
18	4.0/4.0	0.0	13/96				
19		0.0	13/78				
20		0.0	13/96				
21			84			CL	CLAY W/ SAND - MOTTLED YELLOWISH BROWN (10YR 5/6) & STRONG BROWN 7.5YR 5/6; 80% CLAY, FIRM, LOW PLASTIC, SEMI MOIST; 20% SAND, F, PC; TRACE WEATHERED LIMESTONE, NO ODOR

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID: DG515	Subarea: SD	Date Started: 9/9/13	Date Completed: 9/9/13
Project: SSFL		Geologist: B. KASPRZAK	Total Depth: 23 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	3.0					CL	CLAY W/ SAND - MOTTLED YELLOWISH BROWN (10YR 5/6) & STRONG BROWN (7.5YR 5/6) 80% CLAY, FIRM, LOW PLASTIC, SEMI MOIST, NO ODOR 20% SAND, F, PG; TRACE WEATHERED LIMESTONE
22	3.0	00	13/90	SU-515-SA5D-SB22.0-23.0	10:30		
23			13/84				REFUSAL AT 23 FT

Location ID:	Subarea:	Date Started:	Date Completed:

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller:	23FT
GPS collected? Yes or No	Drill Method:	Depth Drilled into Bedrock:
Radiological Background:	Borehole diameter:	
PID Background:	Depth to GW:	Sampling Method:
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:	Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
22		0.0	13/90				
23		0.0	13/84				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-B15-SA5D-SB-0.0-05 **Date/Time** 7/9/13 9:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-B15-SA5D-SB-0.0-0.5MS

Field Geologist B KASPRZAK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Biosolids	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 – SS Sleeves
1 – 4 oz VAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 10 YR 3/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-SI5-SASD-SB-4.0-5.0 Date/Time 9/9/13 @ 9:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler J. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - ~~EXPLOSIVES~~

2 - 16 OLVARS

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No) (NW) 9/9/13

Color ~~Strong brown 10YR 3/3~~ (7.5 YR 4/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.K

Sample ID SL-515-SA5D-SB-9.0-10.0 Date/Time 9/9/13 10:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Biology	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars

2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Reddish Brown 5YR 5/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GT

Sample ID SC-515-SA5D-SB-22.0-23.0 **Date/Time** 9/9/13 @ 10:30

Matrix (circle one): ~~Soil~~ Sediment Water

Start Depth 22.0

End Depth 23.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V. Cortez

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X (MA 9/9/13)
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars
2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellow Brown (10YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A.VIVIAN

Sample ID SL-516-~~SA5A~~ SA5D -SB-0.0-0.5 CC 11/15/13 Date/Time 11/15/2013 0835

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C.Cox

Sampler A.VIVIAN

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 100

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
(Other) SS Formation		

Is Staining Present Yes (No)

Color Brown (7.5 YR 4/3)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments None

11/15/13

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-516	SD	11/15/2013 0810	11/15/2013

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: 14.0, 14.0
Company Name: CDM SMITH	Drill Contractor/Driller: SAES	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: NA
Radiological Background: 14/92	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: NA	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Willie Hoffman #7735	Geologist: C. Cox

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	14/96	SL-516-SASD-SB-0.0-0.5	0835		SILT WITH SAND: Brown (7.5 YR 4/3), 85% silt, low plasticity, 15% sand, pg, f-m, mostly m, t gravel, sa-sr, max ϕ = 0.35", dry, no odor (FILL) t SS Formation
		0.0	10/78				
1		0.0	10/78				
2		0.0	10/108				
	3.0/4.0						
3		0.0	10/102			ML	Same as above: (Dark brown (7.5YR 3/3), 85% silt, low plasticity, 15% sand, pg, f-m, mostly fine, t SS formation clasts, t micaceous material, dry, no odor (FILL)
4		0.0	10/90	SL-516-SASD-SB-4.0-5.0-MS	0840		
				SL-816-SASD-SB 4.5-5.0	0845		Same as above: Reddish brown (2.5YR 4/4), 85% silt, ~~non~~ low plasticity, 15% sand, pg, f-m, mostly f, t micaceous material, t SS formation, chert max ϕ = 0.25" at 7.2', weathered, mottled coloring, dry, no odor (FILL)
5		0.0	10/120				
	3.7/4.0						
6		0.0	10/96				
7		0.0	10/108				
8		0.0	10/60				
	3.6/4.0						
9		0.0	11/54	SL-516-SASD-SB-9.0-10.0	0856	SM	SILTY SAND: Reddish brown (2.5YR 4/4), 75% sand, pg, f-m, mostly f, silt 25% non plastic, dry, no odor.

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG-516	5D	11/15/2013	11/15/2013
Project: SSFL		**Geologist:** C. Cox	**Total Depth:** 14.0', 14.0'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10		0.0	11/60			SM	Same as above: reddish yellow (5YR 6/6), 80% sand, f-m, mostly m, 20% silt, non plastic, micaceous material, weathered coloring, moist @ 10', no odor.
11		0.0	11/54				
12		0.0	11/84			ML	SILT WITH SAND: light olive brown (2.5Y 5/4), 80% silt, nonplastic, 20% sand, pg, f-m, mostly f, mottled coloring, moist, no odor
13	3.2/4.0	0.0	11/60	SL-516-SA5D-SB-13.0-14.0	0908		
14		0.0	11/90			SP-SM	POORLY GRADED SAND WITH SILT: Light olive brown (2.5Y 5/6), 90% sand (weathered formation), pg, f-m, mostly medium, 10% silt, non-plastic, moist, no odor
							Refusal at 14.0', 14.0'

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A. VIVIAN

Sample ID SL-516-~~SA5A 5.0-6.0~~ SA5D 4.0-5.0 -MS (CW 11/6/13 AW 11/15/13) Date/Time 11/15/2013 0840

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~5.0~~ 4.0 (AW 11/15/13 ~~5.5~~ 11/15/13)

End Depth ~~6.0~~ 5.0 (AW 11/15/13)

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. Cox

Sampler A. VIVIAN

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No (Call B/B)
2. **Percentage Fill (%)** 100
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
(Other) SS formation		

Is Staining Present Yes (No)

Color Reddish brown (2.5YR 4/4)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature [signature] **PG Registration #** [signature] #7735

Additional Comments None

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A. VIVIAN

Sample ID SL-816-~~SA5A~~ SA5D ~~5.0-6.0~~ 4.0-5.0 CW 11/15/13 AW 11/15/13 Date/Time 11/15/2013 0845

AW 11/15/13

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~5.0~~ 4.0 AW 11/15/13

End Depth ~~6.0~~ 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite: ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-516-SA5A-5.0-6.0 - MS

Field Geologist C. Cox

Sampler A. VIVIAN

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 100

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
(Other) SS Formation		

Is Staining Present Yes (No)

Color Reddish brown (2.5 YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** CA 7735

Additional Comments None

11/15/11

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

AW 11/15/13 FSDS Checked By A. VIVIAN

Sample ID SL-516-SA5D-~~10-11~~ 9.0-10.0 (Ceil 11/15/13) Date/Time 11/15/2013 0856

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~10.0~~ 9.0 (AW 11/15/13)

End Depth ~~11.0~~ 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. Cox

Sampler A. VIVIAN

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) NA

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color reddish brown (2.5YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments None

CE 4/19/11

NA ~ Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A. VIVIAN

Sample ID SL-516-SA5D-13.0-14.0 Date/Time 11/15/2013 0908

Matrix (circle one): (Soil) Sediment Water

Start Depth 13.0

End Depth 14.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. Cox

Sampler A. VIVIAN

Analysis

Group	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

Group	Parameters	Method	Analyze?
	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color light olive brown (2.5Y 5/6)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments None

11/5/15

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-518-SA5D-SB20-05 **Date/Time** 9/10/13 @ 13:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist R Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Enfos	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 5> Sleeves
1 - 4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color D. Brown 7.5 3/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-518	Subarea: SD	Date Started: 9/10/13	Date Completed: 9/10/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 16.0, 15.9, 16.1
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/Frodriguez		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: N/A
Radiological Background: α=13/$\beta\gamma$=70	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Julia Hoffman #7735		Geologist: KASPZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/90	SL-518-SA-SD-SB-0.0-0.5	13:20	CL	CLAY – DK BROWN (7.5YR 3/4) 80% CLAY, HARD, NON PLASTIC, DRY; 20% SILT TRACE $CaCO_3$ STRINGERS NO ODOR.
		0.0	13/60				
1		0.0	13/72				
	3.0/4.0						
2		0.0	13/84				
3		0.0	13/90				
4		0.0	13/96				
				SL-518-SA-SD-SB-4.0-5.0	13:30	CL	CLAY – STRONG BROWN (7.5YR 5/8) 90% CLAY, FIRM, NON PLASTIC, SEMI MOIST, 10% SAND F, PG TRACE $CaCO_3$ STRINGERS NO ODOR
5		0.0	13/72				
6	4.0/4.0	0.0	13/60				
7		0.0	13/54				
8		0.0	13/78			CL	CLAY W/ SAND – STRONG BROWN (7.5YR 5/8) 75% CLAY, SOFT, NON-PLASTIC, SEMI MOIST; 25% SAND F, PG; TRACE LIGNITE, NO ODOR
9	4.0/4.0	0.0	13/78	SL-518-SA-SD-SB-9.0-10.0	13:40		
10		0.0	96				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG 518	Subarea: ED	Date Started: 9/10/13	Date Completed: 9/10/13
Project: SSFL		Geologist: KASPRZYK	Total Depth: 16.0 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	4.0/4.0	0.0	13/84			CL	CLAY w/ SAND – Mottled Strong Brown (7.5 YR 5/8) & Lt Brown (7.5 YR 6/3); 75% CLAY, SOFT NON PLASTIC, SEMI MOIST, TRACE LIGNITE.
12		0.0	13/66				
13		0.0	13/60				
14		00	13/48				
15		00	13/66	4-518-SASD-13:50 SB-15.0-16.0		SP	ABRUPT CONTACT SAND – REDISH YELLOW (7.5 YR 6/8) LOOSE SAND, F-M, PG, SEMI MOIST, LOOSE, NO ODOR
16		00	13/60				REFUSAL AT 16.0 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. St

Sample ID SC-518-SA5D-SB-4.0-5.0 Date/Time 9/10/13 @ 13:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Jar/Other	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JARS
2-Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color STRONG BROWN 7.5YR5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Nicholas Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-518-SA5D-SB-9.0-10.0 Date/Time 9/10/13 @ 13:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (OPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist P. Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jars
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5YR5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-518-SA5D-SB-00 (15.0-16.0) (KW 9/10/13) **Date/Time** 9/10/13 @ 13:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 15.0

End Depth 16.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JARS
2-Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color REDDISH YELLOW 7.5YR 6/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-SS19-SA50-SR-0.0-0.5 **Date/Time** 9-11-13 @ 7:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKRASZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS Sleeves
1 - 40z JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No MW 9/11/13

2. **Percentage Fill (%)** TRACE (1%) SM 9/11/13

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/~~Metamorphic~~ Gravel)	N/A	
Other _____		

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments Framing NAIL Recovered from 12 FT BGS

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-519	SD	9/11/13	9/11/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 13.5, 13.5, 13.4
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM / R. PANIAGUA	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0.5 FT
Radiological Background: γ = 13 / αβ = 94	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACROCORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: KLASPZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/87	SL-519-SA5D-SB-0.0-0.5	7:40	CL	CLAY – DK BROWN (10YR 3/3); 80% CLAY, HARD, NON-PLASTIC, DRY, 20% SILT; TRACE IGNEOUS GRAVEL IN FIRST FOOT, F, WG, MAX SIZE 3/4 INCH, ROUND TO SUBANGULAR NO ODORS.
		0.0	13/60				
1	2.5 / 4.0	0.0	13/60				
2		0.0	13/72				
3		0.0	13/84				
4		0.0	13/90	SL-519-SA5D-SB-4.0-5.0 9/11/13	8:00	CL	CLAY – STRONG BROWN (7.5YR 5/8) 90% CLAY, SOFT, NON-PLASTIC, SEMI-MOIST 10% SAND, F, PG; NO ODOR
5		0.0	13/66				
	4.0						
6	4.0	0.0	13/44				
7		0.0	13/66				
8		0.0	13/78			CL	CLAY W/ SAND – BROWNISH YELLOW (10YR 6/8) 80% CLAY, SOFT, NON-PLASTIC, SEMI-MOIST, 20% SAND, F, PG; TRACE LIMESTONE FRAGMENTS, NO ODOR
9		0.0	B/84				
10		0.0	13/84				AS ABOVE MOTTLED W/ BROWN (10YR 4/4)

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG 519	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/12/13
Project: SSFL		Geologist:	Total Depth: 13.5'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11		0.0	14/96			CL	CLAY W/ SAND - MOTTLED BROWN/LIGHT YELLOW 10YR 6/8, BROWN 10YR 4/4, 80% CLAY, SOFT NON PLASTIC, SEMI MOIST; 20% SAND, F, PG; TRACE LIMESTONE FRAGMENTS (WEATHERED); NO ODORS
12		0.0	13/98				NOTE: FRAMING NAIL RECOVERED FROM 12 FT
13		0.0	13/84				9/11/13 (NB) YELLOWISH
		0.0	13/106			SW	SAND STONE - ~~STRONG~~ BROWN 10YR 5/8, 100% SAND, F, MG, DRY, HIGHLY WEATHERED. NO ODORS.
							REFUSAL AT 13.5 ON WEATHERED SAND STONE

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-519-SASD-SB-4.0-5.0 **Date/Time** 9-11-13 @ 08:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kacprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jars
2-Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color strong brown 7.5 YR 5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VGt

Sample ID SC-520-SASD-SB-00-05 Date/Time 9/11/13 @ 8:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler VCENTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS SLEEVES
1 - 4oz JAR

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** Trace

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/~~Metamorphic~~ Gravel		N/A
Other _____		

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DS-520	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/11/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 8.9, 8.9, 9.0
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.25 FT
Radiological Background: γ=13 / β=73	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Init.: Walter Hoffman #775		Geologist: KASPZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/88	SL-520-SA-SD-SB-0.0-0.5	8:50	CL	CLAY – DK Brown (10YR 3/3) – 80% CLAY, HARD, NON PLASTIC, DRY; 20% SILT, NO ODOR. TRACE IGNEOUS GRAVEL AT 1 FT, 1/2-INCH SUBANGULAR.
		0.0	13/72				
1	3.0	0.0	13/78				
	4.0						
2		0.0	13/72				
3		0.0	13/84				
4		0.0	13/84	SL-520-SA-SD-SB-4.0-5.0	9:00	CL	CLAY W/ SAND – STRONG BROWN (7.5YR 5/8); 80% Clay, SOFT, NON PLASTIC, SEMI MOIST, 20% SAND, F, PG; NO ODOR
5		0.0	13/60				
	4.0						
6		0.0	13/66				AS ABOVE – W/ CaCO3 STRINGERS AND TRACE OF LIMESTONE FRAGMENTS (WEATHERED).
7		0.0	13/78				
8		0.0	13/90	SL-520-SA-SD-SB-8.0-9.0	9:10	SP	SAND – U Pale Brown – (10YR 7/4); 100% Sand, F, PG, SEMI MOIST; NO Odor
		0.0	13/78				
9							REFUSAL AT 8.9 FT ON WEATHERED SANDSTONE.
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GT

Sample ID SL-520-SASD-4.0-5.0 **Date/Time** 9/11/13 @ 9:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V CONTOS

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

~~2 – 5g Sleeves~~ I.C. 9/11/13

2 – 16 oz Jar

2 Encores

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-520-SA5D-SB-8.0-8.0 **Date/Time** 9/11/13 9:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 8.0

End Depth 9.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Archive	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

~~4 GC Sleeves~~ VC 9/11/13

2-16oz JAR

2 ENCORES

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

CL RDP 9/16/13

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V. Pale Brown 10YR 7/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-521-SA5D-SB-0.0-0.5 Date/Time 9/11/13 @ 9:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kaspzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	VOCs	EPA 8270	
	SVOC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	Cyanide	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Asbestos	EPA 8151	
	Nitrate	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-55-Sleeves
1-4oz Jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Trista D. Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-521	SD	9/11/13	9/11/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 6.5, 6.4
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0 0
Radiological Background: γ=13 / αβ=73	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: KASPORK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/87	SL-521-SA5D-SB-0.0-0.5	9:45	CL	CLAY – DK BROWN (10YR 3/3) – 80% CLAY, HARD, NON PLASTIC, DRY, 20% SILT, NO ODORS
		0.0	13/54				
1	3.0 / 4.0	0.0	13/96				
2		0.0	13/90				
3		0.0	13/78				
4		0.0	13/102				
5	2.5 / 2.5	0.0	13/96	SL-521-SA5D-SB-5.5-6.5	9:55	CL	CLAY W/ SAND – BROWN (7.4YR 4/4); 80% CLAY SOFT, NON PLASTIC, DAMP MOIST; 20% SAND, F, PG.
							~~AS ABOVE~~ W/ CaCO3 STRINGERS & LIMESTONE FRAGMENTS
6		0.0	13/108			SP	SAND – V PALE BROWN (10YR 7/3); 100% SAND, F, PG, DRY, LOOSE
		0.0	13/102				REFUSAL AT 6.5 FT
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-521-SASD-SB-5.5-6.5 **Date/Time** 9/11/13 @ 9:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 5.5

End Depth 6.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): ~~DPT~~ Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Chloride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	PAHs	EPA 8270	
	PCBs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
		EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-Encore
2-16 oz Jars

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Pale Brown 10YR 7/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G

Sample ID SU522-SASD-SB-00-05 Date/Time 8/11/13 10:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Metals		EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Perchlorate	EPA 300.0/9056	
	SVOC	EPA 8270	
		EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCBs	EPA 8082	X
	Asbestos	EPA 314.0/331	
	Hexavalent Chromium	EPA 6850/6860	
		EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Perchlorate	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves

1-4oz Jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** ~~30%~~ 10% (NA) 9/12/13

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous)/Metamorphic Gravel		N/A
Other		

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength** (circle one)

(None) Slight Strong

2. **Odor Description** (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments W/A

NA – Not Applicable

Location ID: DG522	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/11/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 7.1, 7.0
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.5 FT
Radiological Background: α=13/β=84	Borehole diameter: 2.25 - INCH		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [signature] #7735		Geologist: KASPOVK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/100	SL-522 SA SD SB-0.0-0.5	10:15		SANDY (RD) 9/12/13
		0.0	13/78			CL	CLAY with GRAVEL - DK BROWN (10YR 3/3) 60% CLAY SOFT, NON PLASTIC DRY, 30% SAND, F, PG-LOOSE; 10% ½ INCH GRAVEL, FN, WG, MAX ¾ INCH NO ODOR
1		0.0	13/60				(RD) 9/12/13 CLAY - DK BROWN (10YR 3/3) 80% CLAY HARD, NON PLASTIC, DRY, 20% SILT NO ODOR. W/ $CaCO_3$ STRINGERS.
	4.0 / 4.0						
2		0.0	13/56				
3		0.0	13/54				
4		0.0	13/60				
						MS	SILTSTONE - V. PALE BROWN (10YR 8/3) HIGHLY WEATHERED, DRY, NO ODORS.
5		0.0	14/72			SP	SAND - V. PALE BROWN (10YR 8/3) - 100% SAND, F-M, PG, 100% DRY
						CL	CLAY - MOTTLED LT GRAY 10YR 7/1 & WHITE (10YR 8/1); 80% CLAY, SOFT, NON PLASTIC, SEMI-MOIST; 20% SAND, F, PG; EX WEATHERED LIMESTONE FRAGMENTS.
6		0.0	13/66	SL-522 SA SD - SB-6.0-7.0	10:25		
		0.0	13/80			MS	SILTSTONE - V. PALE BROWN (10YR 8/3) HIGHLY WEATHERED, DRY, NO ODOR
7							REFUSAL AT 7.0 ON WEATHERED BEDROCK
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.

Sample ID SG522-SA5D-SB-6.0-7.0 **Date/Time** 9/11/13 @ 10:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.0

End Depth 7.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FF FB RB

Parent Sample ID N/A

Field Geologist BKASPZYK

Sampler ✓ Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCT	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	Pesticides	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz Jars
2-Encore

SSFL Phase 3 – Field Data Sample Sheet (Sample Description)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Lt gray (10YR 7/1)

Odor

1. **Odor Strength (circle one)**
   (None) Slight [illegible]ong

2. **Odor Description (circle one)**
   Organic Petroleum [illegible]
   (N/A) Other

Moisture Condition (circle one)
Dry (Moist) [illegible]et

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SC-523-~~BASD~~-SB-00-0.5 **Date/Time** 9/11/13 @ 12:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZAK

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Enders	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS Sleeves
1 - for JAR

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic content

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color U PALE BROWN 10YR 7/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nila Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-523	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/11/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1.6, 1.7, 1.7
Company Name: CDM SMITH		Drill Contractor/Driller: STRONGARM	
GPS collected? Yes or No (4/4/13)		Drill Method: DPT	Depth Drilled into Bedrock: 1.0 FT
Radiological Background: 13/10 72		Borehole diameter: 2.25 inch	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Mike Hoffman # 7735	Geologist: KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/88	SL523-SA5D-SB-0.0-0.5	1220	CL	CLAY - DK BRN (10YR 3/3); 100% CLAY, HARD, N.P, DRY
		0.0	13/100			SP	SANDSTONE - V. PALE BROWN (10YR 7/4); 100% SAND, F, PG, POOR CEMENTATION (WEATHERED) DRY, NO ODOR.
1							
2							REFUSAL AT 1.7 FT ON BEDROCK.
3							
4							
5							
6							
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-524-SA5D-SB-0.0-0.5 Date/Time 9/4/13 / 8:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B. KASPZYK

Sampler U CORTES

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Soil/Sed	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 4 oz sleeves
1 - 4 oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) ~~No~~ ~~NA~~
2. **Percentage Fill (%)** Trace ~~20~~ ~~NA~~ 9/4/15

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous)	Metamorphic Gravel	N/A
Other _____		

Is Staining Present Yes (No)

Color DK. YELLOWISH BROWN 10YR 4/4

Odor

1. Odor Strength (circle one)

None (Slight) Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-524	5D	9-4-13	9-4-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/84489	Total Depth: 4.4, 6.2, 6.3, 6.0, 6.3
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM/F. RODRIGUEZ	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: α = 13/XBG 80	Borehole diameter: 2¼ INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: #7735	Geologist: BKASPOVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/81	SC-524-SA5D-SB-0.0-0.5	8:20	CL	CLAY – DK Yellowish Brown (10YR 4/4) 70% CLAY, U Hard, Non Plastic, dry 30% SILT, NO ODOR
	3.6/4.0	0.0	13/72				
1		0.0	13/72				Trace of QTZ/BIOTITE GRANITE @ 1 FT
2		0.0	13/54				
3		0.0	13/54				
4		0.0	13/78	SC-524-SA5D-SB-5.5-6.5-MS	8:35		ABRUPT CONTACT
5	2.4/2.4	0.0	13/66			SP	SAND – Brownish Yellow (10YR 6/8); 95% SAND, F, PG, LOOSE, DRY; 5% SILT, NO ODOR
6		0.0	13/72	SC-524-SA5D-SB-5.5-6.5	8:45		REFUSAL @ 6.4 FT
		0.0	13/72				
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. C. E

Sample ID SL-524-SA5D-SB-5.5-6.5-MS Date/Time 9-4-13/ 8:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 5.5

End Depth 6.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYC

Sampler V CRUZ

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X VLK 9/4/13
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Enscapes	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6 - 16 oz JARS

6 - ENCORE

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				(SP)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other NW 9/4/13

Is Staining Present Yes (No)

Color Brownish Yellow 10YR 6/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-824-SA5D-SB-5565 **Date/Time** 9-4-13 / 8:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 5.5

End Depth 6.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-524-SA5D-SB-5.5-6.5 MS

Field Geologist B KASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JARS
2- Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brownish Yellow 10YR 6/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7035

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Catz

Sample ID SL-525-SASD-SB-0.0-05 **Date/Time** 9/3/13 @ 9:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist KRASPOVIC

Sampler V Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS SLEEVES

1 4-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color ~~Light~~ Pale Brown 10YR 7/3 DACK (MB) 9/9/13

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Julie Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-525	Subarea: SD	Date Started: 9/3/13	Date Completed: 9/3/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 3.5/3.6/3.5
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F. Rodriguez		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: -0-
Radiological Background: 9:13 13.89	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW:		Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: Kaplan

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/60	SL525-SA5D-SB-0.0-0.5	9:15	ML	SILT - DK BROWN (10 YR 3/3); 90% SILT SOFT, LOOSE, NON-PLASTIC, DRY; 10% CLAY TRACE CONCRETE AT 1 FT.
1	3.6/4.0	0.0	13/72			ML	SILT - DK Brown (10 YR 3/3); 90% SILT Hard, Non PLASTIC, DRY; 10% SAND, Fine-coarse, WG, Trace Silt, No Odor.
2		0.0	13/78	SL-525-SA-5D-SB 3.5-3.5	9:25	SP	SAND - V. PALE BROWN (10 YR 7/3); 90%
3		0.0	13/64			SM	SAND, F-M, PG, DRY, 10% SILT, NO ODOR
4							SILTSTONE - WEATHERED
5							REFUSAL @ 3.6
6							
7							
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

(w) 9/3/13 FSDS Checked By _____

Sample ID SL-525-SASD-SB~~2.5~~ 3.5 Date/Time 9/3/13 09:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist R. KASPZYK

Sampler V. CARTER

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	✓
		EPA 6020	✓
		EPA 7471 (Soil)	✓
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	✓
	1,4 Dioxane	EPA 8270 SIM	✓ V.C. 9/3/13
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	✓
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	✓

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	✓
	TPH-EFH	EPA 8015	✓
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars

2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color V Pale Brown 10YR 7/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments W/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Steve Mydel

Sample ID SL-526-SASD-SB-0.0.05 Date/Time 08/29/13 / 14:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B KASPZYK

Sampler V. CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS SLEEVES
1 - 4 OZ JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Very Pale Brown 10YR 7/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-526	Subarea: SD	Date Started: 08-29-13	Date Completed: 8-29-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 4.5/4.0/4.0
Company Name: CDM SMITH	Drill Contractor/Driller:		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.5
Radiological Background: γ4/αβ 86	Borehole diameter: 2.5		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Macrocore
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Julie Hoffman #7735		Geologist: B KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	12/42	SL526-SA50-SB-0.0-0.5	14:00	SM	SAND, U. Pale Brown (10YR 7/4) 100% SAND, FINE, POR, LOOSE, DRY T. SILT, NO ODOR.
1		0.0	12/72				
	3.3/4N						
2		0.0	12/66				
3		0.0	12/66	SL526-SA50-SB-3.0-4.0	14:10		
4	0.5/0.5	0.0	12/66		9/24/13		WEATHERED SILTSTONE
		0.0	12/72				
5							

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √, GT

Sample ID SL-526-SA5D-SB-3.0-4.0 Date/Time 08-29-13 / 14:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0 ~~3.0~~ KW 8/29/13

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPRZYK

Sampler √ CORTES

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Liquids	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS SLEEVES (KW) 8/29/13
1-4 OZ JAR
2-16 OZ JAR
2-ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V. Pale Brown 10YR7/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicholas E. Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gil

Sample ID SL-527-SA505B-0.0-0.5 **Date/Time** 09/03/13 @ 0820

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYIC

Sampler V CORTES

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves
1 - 40z VAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-527	SD	09-03-13	09-03-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 5.2, 5.3, 5.5
Company Name: CDM SMITH	Drill Contractor/Driller: Strogan/F. Rodriguez	Depth Drilled into Bedrock:
GPS collected? (Yes) or No	Drill Method: DPT	0
Radiological Background: γ= 13 γ= 82	Borehole diameter: 2 1/4 inch	Sampling Method:
PID Background: 0.0	Depth to GW: N/A	MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: R KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/77	SL-527-SA5D-	8:20	ML	SILT - DARK BROWN (10YR 3/3), 90% SILT SOFT, NON PLASTIC, LOOSE, DRY; 10% CLAY NO ODOR
		0.0	13/60	SB 0.0 0.5			
1		0.0	13/60				
2	4.0 / 4.0	0.0	13/72				
3		0.0	13/90			ML	SILT, PALE BROWN (10YR 6/3) - 90% SILT, HARD NON PLASTIC, DRY; 10% Clay,
4	1.3	0.0	13/64	SL527-SA5D-SB4.0-5.0	8:35		AS ABOVE W/ SILTSTONE LENSE @ 3.6-4.0
5	1.3	0.0	13/54			ML	SILT - Yellowish Brown (10YR 5/6) 100% SILT, Hard, non plastic, DRY
						SP	Trace Clays SAND, yellowish brown, (10YR 6/6), 95% SAND, FINE, PG, loose, dry, 5% SILT, NO odor.
6							REFUSAL AT 5.3 FT
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

KR
9/3/13

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VGT

Sample ID SL-527-SASD-SB-4.0-5.0 **Date/Time** 09/03/13 / 08:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPERIK

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz VAR
2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10 YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-528-SA5D-SB-0.0-0.5 **Date/Time** 9-3-13 @ 9:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist KRASOWSKI

Sampler V Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2-4oz Sleeves
1-4oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No) 9/3/13

Color DK Brown 7.5YR 10YR 3/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG 528	5D	9/3/13	9/3/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: 3.3, 3.3, 3.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F Rodriguez	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: ~~3.3, 3.3, 3.3~~ 0
Radiological Background: B=13/AB=82	Borehole diameter: 2.25 inch	
PID Background: 0.0	Depth to GW: NA	Sampling Method: Macrocore
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Review & No.: Mike Hoffman #7735	Geologist: BRAGPLYIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/80	SL528-SA5D-SB-0.0-0.5	9:55	ML	SILT - DK BROWN (10YR 3/3) 90% SILT, ~~SOFT~~ LOOSE NON-PLASTIC, DRY, 10% CLAY, NO ODOR
1		0.0	13/66			SP	SAND W/ SILT - V PALE BROWN (10YR 7/3) COLOR GRADED FROM DK BROWN TO V. PALE BRN GRADUAL, IRON OXIDE STAIN AT 1.3 FT. 95% SAND, FINE, PG, LOOSE, DRY; 5% SILT NO ODOR
2	3.3/3.3	0.0	13/72	SL-528-SA5D-SB-2.5-3.5	10:05		
3		0.0	13/94			ML	SILTSTONE - WEATHERED, GRAY 7.5YR (5/1) HIGHLY BROKEN
							REFUSAL @ 3.3 FT
4							
5							
6							
7							
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

FC 9/13/13

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gotz

Sample ID SL-528-SASD-SB-2.5-3.5 **Date/Time** 9/3/13 @ 10:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JARS
2-Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				(SP)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V. Pale Brown 10 YR 7/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G

Sample ID SL-529-SASD-SB-0.0-.05 Date/Time 9/11/13 13:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B. Kasprzyk

Sampler ~~M~~. Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X (X) 9/6/13
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-4 Sleeves
1-4oz

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No) DK Brown 10YR 3/3

Color ~~Pale Brown 10YR 7/4~~ (KW) 9/11/13

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DS-529	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/11/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 4.0, 4.0, 3.8
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.25 ET
Radiological Background: B/ B = 75	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Julie Hoffman #7735		Geologist: KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/90	SL-529	1310	CL	CLAY - DK BROWN (10YR 3/3); 80% CLAY, HARD NON-PLASTIC, DRY; 20% SILT; NO ODOR
		0.0	13/72	SA-50 - SB-0.0			
1		0.0	13/66	0.5			GRADATIONAL CONTACT
	3.0					SM	SAND - U. Pale brown (10YR 7/4); 100% SAND, F, PG, LOOSE, DRY; NO ODOR.
2	4.0	0.0	13/84				
3		0.0	13/72	SL529 SAND SB 3.0 - 4.0	1315		
4		0.0	13/66				WEATHERED SANDSTONE
							REFUSAL AT 4 FT ON WEATHERED ROCK
5							
6							
7							
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-529-SA50-SB30-04.0 Date/Time 9/11/13 @ 13:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYK

Sampler VCortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-Encores
2-16oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Light Brown 10YR 7/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G K

Sample ID SL-530-SASD-SB-00-05 **Date/Time** 8/30/13 / 13:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasper

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Excess	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Archive	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-530	SD	8/30/13	8/30/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 2.0, 2.8, 3.5'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: -0-
Radiological Background: Y=14 / -B=77	Borehole diameter: 2.5 INCHES	
PID Background: 00	Depth to GW: NR	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #735	Geologist: B KAMPOFF

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		00	N/102	SL-530-SA SD-SB-0.0	1315	ML	SILT - brown (10 YR 4/3), 80% silt, 20% sand, non-plastic, dry, 10% clay, no odor
1		0.0	12/60	0.5			
		0.0	12/60				
	3.0					SP	SAND - yellowish brown (10 YR 5/6) 100% sand, f-m, PG, loose, dry, no odor
2	3.8	0.0	12/54	SL-530-SA SD-SB-2.5 3.5	1330		
3		0.0	12/72				
		0.0	12/74				
4							Refusal at 3.8 FT
5							
6							
7							
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	Φ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √ GE

Sample ID SL-530-SA50-SB-2.5-3.5 Date/Time 8/30/13 / 13:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
Chemistry	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-160z Jars
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10yr 5/6

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Stef Mypel

Sample ID SC-531-SA5D-SB-0.0-05 Date/Time 08-30-13 / 12:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Solids	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Liquids	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-402 JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10 YR 4/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG 531	Subarea: SD	Date Started: 08/30/13	Date Completed: 08/30/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 2.5, 2.0, 2.0
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: -0-
Radiological Background: 14/28 75	Borehole diameter: 2.5 inch		
PID Background: 00	Depth to GW: NA		Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: B. KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	14/98	SL-531-SA SD-SB-0.0	12:50	ML	SILT - Brown (10YR 4/3); 90% SILT; Soft NON-PLASTIC, DRY, 10% Clay NO ODOR
	2.5	0.0	12/54				
1	2.5	0.0	12/54	05			
						SP	SAND - Yellowish brown (10YR 5/6) 100% SAND, F-M, PG, LOOSE, DRY NO ODOR
2		0.0	12/60				
		0.0	12/56				
3							REFUSAL @ 2.5 FT
4							
5							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-532-SA5D-SB-00-0.5 **Date/Time** 08-30-13 / 12:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKaspryk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS Sleeves
1 - 4 oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Brown 10 YR 4/3

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG 532	50	08/30/13	08/30/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 3.0 2.5 3.0
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: Y=14/AB=98	Borehole diameter: 2¼ INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [signature] #1135	Geologist: KRASOVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	14/59	SL-532-		ML	SILT - BROWN (10YR 4/3); 90% SILT, SOFT, NON-PLASTIC, DRY; 10% CLAY, NO ODOR
		0.0	12/57	SA SD-SB-0.0	1220		
1		0.0	14/57	0.5			1
	3.0 3.0						
2		0.0	12/60	SL-532-		SP	SAND - Yellowish Brown (10YR 6/6) 100% SAND, F-M, PG, LOOSE, DRY. 2
				SA SD-	1230		NO ODORS.
3		0.0	12/66	SB-2.5-			3
				3.5			Refusal at 3.0 FT AS ABOVE
							REFUSAL ON 2ND PUSH AT 3.5 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. C

Sample ID SL-532-SA5D-SB-3.5-3.5 **Date/Time** 8-30-13 / 12:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Blasczyk

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
TPH	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jars
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10YR 6/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-~~553~~-533-SASD-SB-0.0-05 / SM83013 Date/Time 08-30-13 / 10:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KACZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Enpores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5g. Sleeves
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7035

Additional Comments N/A

NA – Not Applicable

Location ID: DG-533	Subarea: SD	Date Started: 08-30-13	Date Completed: 08-30-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 3.5, 3.5, 3.5
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/Vazquez		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 2.0 FT
Radiological Background: γ=14 / αβ=87	Borehole diameter: 2.5 IN		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Review & Nom: Julie Hoffman #7735		Geologist: B KAPPOK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	3.5	0.0	14/97	SL-553-SA SD-SB-0.0	10:15	ML	SILT – BROWN (10YR 4/3); 80% SILT, SOFT, NON-PLASTIC, DRY, 20% CLAY; TRACE SAND, FINE, PG; NO ODOR.
1	3.5	0.0	12/54	0.5			
2		0.0	12/66			SP	SANDSTONE – PALE BROWN (10YR 6/3) FN, PG DRY; W/ INTER BEDDED CLAY, HARD, NON PLASTIC (MAX THICKNESS 2-INCH) NO ODOR.
3		0.0	14/78	SL-533 SA SD-SB-2.5	10:30		
		0.0	12/84	3.5			
4							REFUSAL AT 3.5 FT
5							
6							
7							
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	Φ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-533-SASD-SB-25-35 SM83013 Date/Time 08-30-13 / 10:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 – Encore
2 – 4oz Jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Pale brown 10 YR 6/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Carter

Sample ID SL-534-SA5D-SB-0.0-0.5' **Date/Time** 08-30-13/09:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5'

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYIC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves

1-~~8 oz JAR~~ VS. 8/30/13

4 oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color Brown 10YR 5/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG 534	5D	08-30-13	08-30-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM/VAPEVOR	5.5, 7.5, 6.0
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: α=14 βγ=102	Borehole diameter: 2.5 INCH	0.5 FT
PID Background: 0.0	Depth to GW: NA	Sampling Method:
Radiological Equipment Used:	PG Reviewer's Name: Mike Hoffman #7735	MACRO CORE
✓ MicroR ✓ Alpha/Beta ✓ Pancake		Geologist: B KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	14/80	SL-534-SA 5D-SB-0.0-0.5	09:00	ML	SILT - BROWN (10YR 5/3) - 80% SILT, SOFT NON-PLASTIC, DRY; 10% SAND, FN, PG DRY LOOSE, TRACE FN GRAVEL, NO ODOR.
1		0.0	12/54				
2	4.0/4.0	0.0	12/60			SP	SAND - PALE BROWN (10YR 6/3) - 100% SAND, F-M, PG LOOSE, DRY, W/ INTERBEDDED WEATHERED SANDSTONE, NO ODOR.
3		0.0	12/60				
4		0.0	12/78				
5	1.5/1.5	0.0	12/54				
6	2.0/2.0	0.0	12/84	SL-534-SA 5D-SB-6.5-7.5	9:20		WEATHERED SANDSTONE
7		0.0	12/78				
		0.0	12/72				REFUSAL AT 7.5 FT
8							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GE

Sample ID GL-G34-SA5D-SB-6.5-7.5 **Date/Time** 8-30-13 / 09:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.5

End Depth 7.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B KASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X (and 9-3-13)
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Soil Jars	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars

2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		(N/A)
Other _____		

Is Staining Present Yes (No)

Color Pale Brown 10YR 6/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-535-SA50-SB-0.0-0.5 MS **Date/Time** 8-30-13 8:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Blaszyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

KK 8-30-13

~~1 - 40z JAR~~ KK 8/30/13

1 - 40z JAR

6 - 5G Sleeves

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color Brown 10 YR 5/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

Location ID: DG535	Subarea: SD	Date Started: 08-30-13	Date Completed: 08-30-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 3.5, 3.0, 3.5
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM		
GPS collected? (Yes) or No	Drill Method: DPT / Vacuum		Depth Drilled into Bedrock: 2 FT
Radiological Background: Y-14 -B-66	Borehole diameter: 2.5 INCH		
PID Background: 0.0	Depth to GW: NA		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Init: [signature] #7735		Geologist: B KASPRYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS (Burgoyne)	Description of Materials
		0.0	14/80	SL-585-SA50-	08:10	ML	ML - SILT - Brown (10YR 5/3) - 100% SILT, Soft, non plastic, dry
		0.0	12/66	SB-0.0-0.5MS			SANDSTONE - PALE BROWN (10YR 6/3); 50% WEATHERED SANDSTONE, FN, PG, HIGHLY BROKEN; 50% SAND, FN, PG, LOOSE, DRY.
1	3.5	0.0	12/66	SL-585-SA50-SB-0.0-0.5	0820	SP	
2	3.5	0.0	12/66				
				SL-585-SA50-SB-2.0-3.0	8:30		
3		0.0	12/72				
		0.0	12/66				
4							Refusal at 3.5
5							

NOTE: Boring offset 8FT EAST ~~WEST~~ of mark to avoid utilities. 9/30/13

CDM Smith — **BORING LOG AND SAMPLING RECORD** — Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cyk

Sample ID SL-835-SASD-SB-0.0-0.5 **Date/Time** 8-30-13 / 9:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-535-SASD-SB-0.0-0.5 MS

Field Geologist B. Kasprzyk

Sampler V Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs -	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	X (RL 9/20/13)
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-4 oz JAR
2-SS Sleeves

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 5/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Contes

Sample ID SC-535-SB5D-SB-2.0-3.0 **Date/Time** 8-30-13 / 08:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.0

End Depth 3.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKAGPZYK

Sampler V Contes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - EnCores
2 - 16 oz Jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				(SP)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color ~~Brown 10YR 5/3~~ PALE BROWN (10YR 6/3) 8-30-13

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-536-SASD-SB-0.0-0.5 Date/Time 08-28-13/11:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N.A

Field Geologist B Kasprzyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-55 sleeves V.C. 8/28/13
1-8 oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color PALE BROWN 10YR 6/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG 536	Subarea: SD	Date Started: 08-28-13	Date Completed: 08-28-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 2.4 4.5
Company Name: CDM SMITH	Drill Contractor/Driller: STRATA		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: 2.1 FS
Radiological Background: γ=12 / αβ= 92	Borehole diameter: 2.5 INCH		
PID Background: 0.0	Depth to GW: NA		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Note: [signature] #7735		Geologist: B KASPOVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0	12/90	SL-536-SA5D-SB-0.0-0.5	11:00	SP-SM	SAND: PALE BROWN (10YR 6/3), SAND 90% FINE, PG, LOOSE, DRY; SILT, 10%, SOFT, NON-PLASTIC; NO ODOR w/ SILT
1	1.9/2.4	0.0	12/66				
2		0.0	12/66				
		0.0	12/60			ML	SILT: PALE BROWN (10YR 6/3): SILT HARD NON-PLASTIC, DRY; W/ LAMINATED WEATHERED SILT STONE, NO ODOR
3	2.1/2.1	0.0	12/66	SL-536-SA5D-SB-3.5-4.5	12:00		
4		0.0	12/60				refusal at 4.5
		0.0	12/60				
5							
6							
7							
8							
9							
10							

8-28-13

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	Φ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By KB

Sample ID SL-536-SA5D-SB-3.5-4.5 **Date/Time** 08.28.13 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.5

End Depth 4.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BOB KASPZYK

Sampler VIDAL CORTEZ

Analysis

	Parameters	Method	Analyze?
Standard	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 904S (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Optional	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-OZ JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color PALE BROWN 10YR 6/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-537-SA5D-SB-0.0-0.5 Date/Time 08-28-13/ 10:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B KASPZYK

Sampler V. CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. SLEEVES
1 - Amber 4 oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 7.5 YR 4/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG537	SD	08-28-13	08-28-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 4.5/3.3/3.5
Company Name: CDM SMITH	Drill Contractor/Driller: STRINGARM	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: Y-12/αβ 79	Borehole diameter: 2.5 INCH	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Miller Hoffman #735	Geologist: BLASZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0	12/99	SL-537-SA5D-SB-0.0	10:20	CL	CLAY; BROWN (7.5YR 4/4) 90% CLAY, HARD, NON-PLASTIC, DRY, 10% SILT; NO ODOR.
1		0.0	12/48	05			
2	2.1/3.5	0.0	12/54			CL	AS ABOVE
3		0.0	12/60	SL-537-SA5D-SB-2.5-3.5	10:30		
4		0.0	12/60				
	0.5/0.5	0.0	12/66			SP-SM	SAND; BROWN (7.5YR 4/4) SAND 90%, FINE, AS COARSE, 10% SILT; DRY, NO ODOR.
5							REFUSAL AT 4.5 FT
6							
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-537-SA5D-SB 2.5-3.5 **Date/Time** 08-28-13 / 10:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kastyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - ENCORE
2 - 16 oz JARS

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color Brown 7.5 YR 4/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GT

Sample ID SL-538-SASD-SB-00-0.5 Date/Time 08-28-13/13:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V CORTES

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Chemistry	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Biological	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeve
~~1-4oz JAR~~ V.C. 8/28/13
1 4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color (7.5 YR 5/4) Brown

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Julia Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-538	SD	08-28-13	08-28-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 4.0 / 4.0
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: -0-
Radiological Background: ~~0~~ 13/YB 90	Borehole diameter: 2.5 INCH	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: MACROCORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Julie Hoffman #7735	Geologist: BKAGPOYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0	13/68	SL-SSB-SA5B-	~~11:35~~	CL	SANDY CLAY; Brown 7.5 YR 5/4 CLAY, 60%, Hard, non plastic, dry; SAND, 40% Fine, pg, loose, TRACE GRAVEL AT 0 - 0.5FT, NO odor
		0.0	12/68	SB-0.0 -	13:45		
1		0.0	12/48	~~#~~: 0.5			
	3.5						
2	~~3.5~~	0.0	12/54				
						SP SM	SAND W/ SILT; ~~PALE~~ Brown (10YR 6/3); SAND 90%, FINE-MED, pg, loose, dry; NO ODOR.
3		0.0	12/54	SL-SSB SA5B - SB-5.0 - 4.0	14:00		
4		0.0	12/96				REFUSAL AT 4.0 FT BGS
5							
6							
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. CRUZ

Sample ID SL-538-SASD-SB-3.0-4.0 **Date/Time** 08-28-13 14:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BRASPOYIC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color (10 YR 6/3) Pale Brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-539-SA5D-SB-0.0-0.5 **Date/Time** 08-29-13/ 09:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. KASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Archive	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - SS Sleeves
1 - 4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK BROWN 10YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-539	SD	08-29-13	08-29-13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 4, 4, 4
Company Name: CDM SMITH	Drill Contractor/Driller: STRATAPRM	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: α=12 γ=94	Borehole diameter: 2.5 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: [signature] #7735	Geologist: B KASPCVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	12/78	SL-539 SASD-SB-0.0-0.5	09:10	CL	CLAY - DARK BROWN (10YR 3/3); 90% CLAY, SOFT, NON-PLASTIC, DRY; 10% FINE SAND, PG, LOOSE, NO ODORS.
		0.0	12/54				
1		0.0	12/48				
	4.0						
2	4.0	0.0	12/54			SM	SILTY SAND - V. PALE BROWN (10YR 7/4), 80% SAND, FINE-MEDIUM, PG, LOOSE DRY; 20% SILT SOFT, NON-PLASTIC, NO ODORS
							W/ INTERBEDDED LENSES OF V. HARD CLAY MAX THICKNESS < 2 INCHES.
3		0.0	12/48	SL539-SA5D-SB-3.0-4.0	09:20		
4		0.0	12/60				SAND STONE IN SHOE AT 4.0 FT
							REFUSAL AT 4.0 FT
5							
6							
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-539-SA50-SB-3.0-4.0 Date/Time 08-29-13 / 09:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BOB KASPRZYK

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X HH 8/29/13
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz JAR

2 - ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color VERY PALE BROWN (10YR 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GE

Sample ID SL540-SA5D-SB-0.0-0.5 **Date/Time** 9/3/13 @ 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kacprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Soil Jars	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-402 JAR

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown (10YR 3/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

Location ID: DG 540	Subarea: SD	Date Started: 9/3/13	Date Completed: 9/6/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 6.2, 6.0, 6.1
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm / F Rodriguez		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.5 FT
Radiological Background: 9/3/13 7678	Borehole diameter: 2.25-inch		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mila Hoffman #7735		Geologist: B Kaupenc

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/84	SL-540-SA50-SB-0.0-0.5	12:00	SM	SILT - DK BROWN (10YR 3/3); 90% SILT, SOFT - LOOSE DRY NONPLASTIC, NO ODOR, 10% CLAY
1		0.0	13/68				
2	4.0/4.0	0.0	13/72			ML	SILT - DK BROWN (10YR 3/3); 90 SILT, HARD NON PLASTIC, SEMI MOIST, NO ODOR; 10% CLAY.
3		0.0	13/78			CL	CLAY W/ SAND - PALE BROWN (10YR 6/3) 70% CLAY, HARD, NON PLASTIC DRY; 25% SAND, F-C WG, SUBANG GRAINS, 5% SILT, NO ODOR (LK) 9/3/13
4		0.0	13/66				
5	2.2/2.2	0.0	13/66	SL-540-SA50-SB-5.0-6.05 (LK) 9/4/13	12:10	SP	SAND - V. PALE BROWN (10YR 7/3); 95% SAND F-M, PG, LOOSE, DRY, 5% SILT, NO ODORS
6		0.0	13/66			SM	SILTSTONE - V PALE BROWN (10YR 7/3), HIGHLY WEATHERED, FISSILE DRY. NO ODOR
7							REFUSAL AT 6.2 FT
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GE

Sample ID SL-540-SASD-SB-5.0-6.0 **Date/Time** 9-3-13 @ 12:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 5.0

End Depth 6.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kospyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz JAR
2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP (circled)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		(N/A)
Other _____		

Is Staining Present Yes (No)

Color Pale Brown (10YR 7/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-541-SASD-SB-0.0-0.5 Date/Time 9-3-13/ 13:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist R Knapp/V Cortes

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X Sm9/3/13
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-4 oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown (10YR 3/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-541	Subarea: SD	Date Started: 9/3/13	Date Completed: 9/3/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 3.6, 3.3, 2.5
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm/F. Rodriguez	
GPS collected? (Yes) or No		Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: 13 / VB-94		Borehole diameter: 2 1/4 inch	
PID Background: 0.0		Depth to GW: NA	Sampling Method: MacroCore
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & Sign: Mike Hoffman #7735	Geologist: B Kasprzyk

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/99	SL-541-SA-SD-SB-0.0	13:34	ML	SILT - DK BROWN (10YR 3/3) - 90% SILT, SOFT, LOOSE, NON PLASTIC DRY, 10% Clay
1		0.0	13/56				
		0.0	13/66	0.5		CL	CLAY w/SAND - BROWN (10YR 5/3); 85% Clay Hard, non plastic, dry; 15% Sand, fine, pg.
2	3.6 / 3.6	0.0	13/54				Gradational transition
3		0.0	13/66	SL-541-SASD-SB-3.5	13:45	SP	SAND w/SAND - V. pale brown (10YR 7/3) 95% SAND, Fine, pg, dry loose, 5% silt, NO odor.
4		0.0	13/72				Refusal at 3.6 FT
5							
6							
7							

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GK

Sample ID SL-541-SA5D-SB-25-3.5 Date/Time 9/13/13 / 13:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BRESNYAC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jar
2- Encore

NA – Not Applicable

SSFL Phase 3 -- Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V Pale Brown 10 yr 7/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G-T

Sample ID SL-542-SA5D-SB-0.0-05 **Date/Time** 08-29-13/13:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 – SS Sleeves
1 – 4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DU-542	SD	08-29-13	08-29-13

Client: DOE — Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 5 FT
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: Y 14/AD=89	Borehole diameter: 2.5 INCHES	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mark Hoffman #7735	Geologist: S KASPZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	14/64	SL-542-SA5D-SB-0.0-0.5	1325	CL	CLAY – BROWN (10YR 4/3); 70% CLAY, HARD, NON-PLASTIC DRY; 30% SILT, NO ODORS
1	3.4/4.0	0.0	14/42				
2		0.0	14/48				
3		0.0	14/42				
4		0.0	14/60	SL-542-SA5D-SB-4.0-5.0	1335	SP	SAND – V. PALE BROWN (10YR 7/4); 95% SAND, FINE, PG, DRY LOOSE, 5% SILT, NO ODOR
5	1.0/1.0	0.0	14/72				REFUSAL AT 5 FT

CDM Smith


BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials



CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J. GT

Sample ID SL-542-SA5D-SB-4.0-5.0 **Date/Time** 08-29-13 / 13:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYK

Sampler V CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz JARS
2 - ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP (circled)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Light Brown (10YR 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-543-SA5D-SB-0.0-0.5 Date/Time 08-29-13/ 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 5 g ~~SLEEVES~~ SLEEVES
(KH) 8-29-13
1 - 4 oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No) VC 8/29/13

Color ~~Brown 5/3~~ (10YR 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-543	Subarea: SD	Date Started: 08-29-13	Date Completed: 08-29-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 11.5, 7, 7
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: 1 FT
Radiological Background: 9213 YB274	Borehole diameter: 2.5 INCHES		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Macro core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Miller Hoffman #7735		Geologist: BKASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/95	SL-543 SA5D-SB-0.0	12:00		RK 8-29-13
		0.0	13/60			CL	CLAY ~~w/ SILT~~ – BROWN (10YR 5/3); 90% HARD, LOW PLASTIC DRY CLAY, 10% SILT, TRACE FINE PG, SAND; NO ODOR
1		0.0	13/60	0.5			
2	3.0/4.0	0.0	13/66				
3		0.0	13/78		4:29-13		
4		0.0	13/72	SL-543 SA5D-SB 4.0	12:10 12:30		RK
5	4.0/4.0	0.0	13/60	5.0			KH 8-29-13
6		0.0	13/48			SP	SAND – U. PALE BROWN (10YR 7/4); 100% SAND, FINE, PG, DRY. TRACE SILT, NO ODOR
7		0.0	13/54				
8		0.0	13/66				AS ABOVE
9	3.5/3.5	0.0	13/48				
10		0.0	13/54				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG-543	Subarea: SD	Date Started: 08-29-13	Date Completed: 0829-13
Project: SSFL		Geologist: B KASPZYK	Total Depth: 11.5 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							(H) 9/4
10		0.0	13/54			SP	SAND ~~WITH SILT~~ - V PALE BROWN (10YR7/4) 95% SAND, FINE, PG, LOOSE, DRY; 5% SILT; NO ODOR
11		0.0	13/60				WEATHERED SANDSTONE 11
							REFUSAL AT 11.5
12		0.0	13/66				12

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-543-SA5D-SB-4.0-5.0 **Date/Time** 08-29-13/12:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NONE

Field Geologist B KASPAR

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz JARS
2-ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color BROWN 10YR 5/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By

Sample ID SL-544-EA5D-SB-0.0-0.5 Date/Time 9/4/13 @ 9:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist K. KASPRZYK

Sampler V. CORTES

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Chemistry	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK BROWN 10YR3/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-544	Subarea: SD	Date Started: 9/4/13	Date Completed: 9/4/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 7.2, 7.3, 7.2, 1
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm / E. Rodriguez		Depth Drilled into Bedrock: ⌀
GPS collected? Yes or No	Drill Method: DPT		
Radiological Background: X = 13 / YB = 91	Borehole diameter: 2.25 INCH		Sampling Method: MACRO CORE
PID Background: 0.0	Depth to GW: -0-		
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: B KASPOK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/98	SL-544-SA5D-SB-0.0	9:40		CLAY – DARK BROWN (10YR3/3); 70% HARD, NON-PLASTIC, DRY, CLAY; 30% SILT; NO ODOR.
		0.0	13/78				
1	3.0 / 4.0	0.0	13/60	0.5		CL	
2		0.0	13/42				
3		0.0	13/78				
4		0.0	13/84				
5	5.2 / 3.3	0.0	13/72				
6		0.0	13/72	SL-544-SA5D-SB 6.5-7.5	9:50		GRADATIONAL CONTACT — SAND – Brownish Yellow (10YR6/8); 100%, F, PG, DRY, NO, ODOR.
7		0.0	13/60			SP	
8							REFUSAL AT 7.2 FT
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Skyler Mupel

Sample ID EL-544-SA5D-SB-6.5-7.5 Date/Time 9/4/13 @ 9:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.5

End Depth 7.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist K Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz JAR
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP (circled)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brownish yellow (10YR 6/8)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-SWS-SA50-SB-20-0.5 **Date/Time** 9-3-13 @ 12:50

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BRASPAUG

Sampler V. Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Emerging	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5 5 5 Leaves
1-402 JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK brown 10YR 3/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG545	Subarea: SD	Date Started: 9/3/13	Date Completed: 9-3-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 6.8, 7.0, 6.8
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F Rodriguez		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 0
Radiological Background: Y=13/XB=82	Borehole diameter: 2.25 inch		
PID Background:	Depth to GW: NA		Sampling Method: Macro core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Miller Hogan #7735		Geologist: B KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/71	SL545-SA5A-SB 0.0-0.5		ML	SILT – DK brown (10 YR 3/3) – 90% silt soft, loose, non plastic, dry; 10% clay; NO odor
1	3.0/4.0	0.0	13/72				
			13/48			CL	Clay – DK brown (10 YR 3/3); 80% clay Hard, non-plastic, DRY, 20% silt, no odor
2		0.0	13/66				
3		0.0	13/78				
4		0.0	13/72				
5	2.8/2.8	0.0	13/79 90	SL545-SA5D-SB-6.0-7D	1300	SP	SAND – U pale brown (10 YR 7/3); 95% SAND, F-M, PG, loose, dry no odor Trace of concrete @ 5.4 ft
6		0.0	13/66 90				
7			13/66				REFUSAL AT 7.0 FT

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C. 9/3/13

Sample ID SL-SS-SA5D-SB-~~5.0-6.0~~ 6.0-7.0 V.C. 9/3/13 Date/Time 9-3-13 @ 13:00

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~6.0~~ 6.0 V.C. 9/3/13

End Depth ~~6.0~~ 7.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. Kasprzyk

Sampler V. Cortez

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-160z JAR
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** Trace

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
(Concrete)	Wood	Glass
Igneous/Metamorphic Gravel		N/A

Other _____

Is Staining Present Yes (No)

Color Pale brown (10 yr 7/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By N. Cortes

Sample ID SL546-SA5D-SB0.0-0.5 Date/Time 9/4/13 13:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BRADYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS SLEEVES
1 4-OZ JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK. YL. BR. (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments _____

N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-546	5D	9-4-13	9/4/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F. Rodriguez	14.0, 13.8, 13.9
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: 13/70	Borehole diameter: 2.25 INCH	0
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [illegible] #7735	Geologist: B KASPRZAK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/94	SC-546-SA5D-SB-0.0-0.5	13:25		
		0.0	13/54				
1		0.0	13/72			CL	CLAY - DK YELLOWISH BROWN (10YR 4/4) 70% CLAY, HARD, NON-PLASTIC, DRY 30% SILT; NO ODOR.
	3.0						
2	4.0	0.0	13/54 78	9/4/13			
3		0.0	13/54				
4		0.0	13/66	SC-546-SA5D-SB-4.0-5.0	13:45	CL	SAME AS ABOVE
5		0.0	13/66				
	4.0						
6	4.0	0.0	13/60				
7		0.0	13/78			CL	AS ABOVE BUT LOW-PLASTIC AND SEMI MOIST.
8		0.0	13/66				
9	4.0	0.0	13/72				
	4.0					CL	CLAY - PALE BROWN (10YR 6/3), 90% CLAY, FIRM, LOW PLASTIC, SEMI MOIST 10% SAND, F, NG ~~CONSOLIDATED~~ DENSE, NO ODOR
10		0.0	13/78				

CDM Smith

BORING LOG AND SAMPLING RECORD (NW) 9/4/13

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG 546	Subarea: SD	Date Started: 9/4/13	Date Completed: 9/4/13
Project: SSFL		Geologist: [illegible]	Total Depth: 14.0

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	00	0.0	13/92			CL	CLAY – PALE BROWN (10YR 6/3) 90% CLAY, FIRM, LOW PLASTIC, SEMI-MOIST; 10% SAND, F, PG, DENSE; NO ODOR.
12		0.0	13/82				GRADUAL CONTACT
13	2.0/2.0	0.0	13/90			SM	SILTY SAND – PALE BROWN (10YR 6/3) 70% SAND, F, PG, SEMI MOIST, LOOSE, 30% SILT, SOFT, NON PLASTIC; NO ODOR
14		0.0	13/90				REFUSAL AT 14.0 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V Cortes

Sample ID SL-546-SA5D-SB-4.0-5.0 **Date/Time** 9/4/13 13:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Raspuzzi C

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyte?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Yellowish Brown 10YR 4/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-547-SASD-SB-0.0-0.5 Date/Time 9/4/13 @ 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist R Kaspzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enchos	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 5g SLEEVES

1 4-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Yellowish Brown (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Vivian Hoffman **PG Registration #** 7835

Additional Comments N/A

NA – Not Applicable

Location ID: DG-547	Subarea: SD	Date Started: 9-4-13	Date Completed: 9-4-13 (9/4/13 RS)
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 11.0
Company Name: CDM SMITH	Drill Contractor/Driller: ~~Strongarm~~/Rodriguez		~~8.0~~ 11.0/9.0/~~8.0~~/0.5
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 0.5 FT
Radiological Background: 4=13 / 18=79	Borehole diameter: 2.25 - NVC1		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: Macro core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Julie Hoffman #7735		Geologist: R. KASPRZAK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1		0.0	13/80	SL-547-SA5D-SB-0.0-0.5	12:00	CL	CLAY - DK YELLOWISH BROWN (10YR 4/4) 70% CLAY, HARD, NON-PLASTIC, DRY. 30% SILT; NO ODORS
		0.0	13/84				
		0.0	13/66				
2	3.0/4.0	0.0	13/72				
3		0.0	13/84				
4		0.0	13/96	SL-547-SA5D-SB-4.0-5.0	12:15		
5		0.0	13/66				
6	4.0/4.0	0.0	13/78				
7		0.0	13/72				
8		0.0	13/66				GRADUAL TRANSITION
9	4.0/4.0	0.0	13/84			SP	SAND - BROWNISH YELLOW (10YR 6/8); 95% SAND, F, PG, DRY; 5% SILT; NO ODOR
		0.0	13/84				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
DG-547	5D	9/4/13	9/4/13
Project: SSFL		**Geologist:** R KASPZYK	**Total Depth:** 11

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
						SW	SAND – BROWNISH YELLOW (10YR 6/8); 95% SAND, F, MG, DRY; 5% SILT; NO ODOR
11		00	13/72			ML	SILTSTONE – Brown Yellow (10YR 6/8) HIGHLY WEATHERED.

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-547-SASD-SB-4.0-5.0 **Date/Time** 9/4/13 @ 12:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BLASIAK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Inorganics	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Yellow Brown (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By P. Hartman

Sample ID SL-548-SASD-SB-0005 Date/Time 08/26/13 / 13:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler U. CORTES

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Biological	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** (0)

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 7.5 YR 3/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-548	SD	08-26-2013	08-27-2013

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: NA	22.6
GPS collected? (Yes) or No	Drill Method: HAND AUGER	Depth Drilled into Bedrock:
Radiological Background: 8-13 / AB = 96	Borehole diameter: 2.5 INCH	0
PID Background: 0.0	Depth to GW: NA	Sampling Method: SLIDE HAMMER
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PO Reviewer & No.: Mike Hoffman #7735	Geologist: B. KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	1/1	0.0	13/87	SL-548-SA5D-SB-0.0-0.5	13:00	ML	SILT: DARK BROWN 7.5YR 3/4; 95% SILT, NON-PLASTIC, FIRM, DRY, 5% SAND, FINE pgraded, NO ODOR.
1	1/1	0.0	13/60				SAME AS ABOVE BUT SOFT.
2	1/1	0.0	13/96				
3	1/1	00	13/66				
4	1/1	0.0	13/66	SL-548-SA5D-SB-4.0-5.0	14:35	ML	SAME AS ABOVE - LOW PLASTIC, SOFT
5	1/1	00	13/96				
6	1/1	0.0	13/96			ML	SAME AS ABOVE
7	1/1	0.0	13/54			ML	SILT; DK BROWN 7.5 YR 3/4; 100% LOW PLASTIC, MOIST, NO ODOR
8	1/1	00	13/96				
9	1/1	00	13/96			ML	
10		0.0	13/60				SILT; DK BROWN 7.5YR 3/4; 90% SILT; LOW PLASTIC, SOFT, 10% SAND, FINE, pgraded MOIST NO ODOR

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG 548	Subarea: SD	Date Started: 8-26-13	Date Completed: 8-27-13
Project: SSFL		Geologist: B KASPOK	Total Depth: 22.6

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	1/1	0.0	13/60			ML	SILT; STRONG BROWN (7.5YR 5/6); SOFT LOW PLASTIC, MOIST, T. SAND, FN, A gravel NO ODOR
12	1/1	0.0	13/72			ML	SILT: STRONG BROWN (7.5YR 4/4); 100% SOFT, LOW PLASTIC, MOIST, T. SAND, FN PG NO ODOR.
13	1/1	0.0	13/72			ML	SAME AS ABOVE - NON-PLASTIC
14	1/1	0.0	13/84			ML	SAME AS ABOVE -
15	1/1	0.0	13/72			ML	SAME AS ABOVE
16	1/1	0.0	13/90			ML	SAME AS ABOVE
17	1/1	0.0	13/66			ML	SAME AS ABOVE
18	1/1	0.0	13/84			ML	SAME AS ABOVE
19	1/1	0.0	13/66			ML	SAME AS ABOVE
20	1/1	0.0	13/84			ML	SAME AS ABOVE W/ TRACE SAND, PG; F
21	1/1	0.0	13/78			ML	SAME AS ABOVE W/ 10% SAND, PG; F

Location ID:	Subarea:	Date Started:	Date Completed:
DG 548	5D	8-27-13	8-27-13
Project: SSFL		Geologist:	Total Depth: 22.6

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	1/1					ML	SILT W/ SAND - REDDISH YELLOW (7.5 YR 6/6); 85% SILT, SOFT, NON-PLASTIC, MOIST; 15% SAND, F, PP, LOOSE, NO ODOR.
22		0.0	13/60				REFUSAL @ 22.6
22.6	0.6/1.0	0.0	13/12			ML	SAME AS ABOVE ↓

22

23

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID:	Subarea:	Date Started:	Date Completed:
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller:		
GPS collected? Yes or No	Drill Method:		Depth Drilled into Bedrock:
Radiological Background:	Borehole diameter:		
PID Background:	Depth to GW:		Sampling Method:
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:		Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

KL 8-21-13

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By P Hartman

Sample ID SL-548-GASD-SB-4.0-5.0 Date/Time 8/26/13 / 14:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzak

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enfos	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK BROWN 7.5YR 3/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Walter Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By C. COX

Sample ID SL549-SA5D-SB-0.0-0.5 Date/Time 11/12/2013 1025

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. COX

Sampler A. UIJAN

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) NA

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown (7YR 5/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Dobbyn **PG Registration #** 7735

Additional Comments None

08/12/13

NA – Not Applicable

Location ID: DG-549	Subarea: 5D	Date Started: 1020 TUES 11/12/13	Date Completed: 11/12/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 12.2'
Company Name: CDM SMITH	Drill Contractor/Driller: SAFS		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: 12/89	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hodgson #7735		Geologist: C. Cox

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	3.6/4	0.0		SL-549-SASD-SB-0.0-0.5	1025		
1		0.0	12/48			CL 11/12/13 ~~Clayey~~ ML 11/12/13	Silt: Brown (7YR 5/3) 90% silt, pg, f-m, 5% clay low plasticity, m stiff, 5% weathered SS pieces throughout, dry, no odor
2		0.0	12/36				
3		0.0	12/60				
4		0.0	12/96	SL-549-SASD-SB-4.0-5.0	1040		reddish brown (5YR 4/4)
5		0.0	10/54			ML	Same as above ^ with ~~stiff~~ 11/12/13 slightly stiffer and moist at ~4.5' bgs no odor.
6	4.0/4.0	0.0	10/48				
7		0.0	10/72				
8		0.0	10/48				
9	3.8/4.0	0.0	10/54				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2 11/12/13

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-549	Subarea: 5D	Date Started: 11/12/13	Date Completed: 11/12/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 12.2'
Company Name: CDM SMITH	Drill Contractor/Driller: SAFS		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background:	Borehole diameter: 2.25"		
PID Background:	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:		Geologist: C. Cox

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	10/54	SL-549-SA5D-SB-11.0-12.0	1105		See above
11		0.0	10/60				
12		0.0	10/96				Refusal @ 12.2 top of Sandstone

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 2 of 2

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By C. Cox

Sample ID SL-549-SA5058-4.0-5.0 Date/Time 11/12/2013 1040

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. Cox

Sampler A. UJUJAM

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) NA

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color Reddish brown (5YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments None

8/12/13

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By C. COX

Sample ID SL-549-SA50-SB-11.0-12.0 Date/Time 11/12/2013 1105

Matrix (circle one): (Soil) Sediment Water

Start Depth 11.0

End Depth 12.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist G Cox

Sampler A. UIUIAN

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color Reddish brown (5YR 4/4)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments None

11/12/13

NA = Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-550-SASW-SB-0.0-0.5 **Date/Time** 9/6/13 @ 8:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kasprzyk

Sampler U Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-550	SD	9/6/13	9/6/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F. Rodriguez	13/14.7/15.2
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: .5 ft
Radiological Background: α=13/γβ=87	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: B KASPOVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/81	SL550-SA5D-SB-0.0-0.5	8:40	ML	SILT - BROWN (10YR 4/3) - 60% SILT, SOFT, NON-PLASTIC, DRY, 40% CLAY NO ODOR.
		0.0	13/60				
1	4.0/4.0	0.0	13/48				
2		0.0	13/54				
3		0.0	13/78				
4		0.0	13/78	SL550-SA5D-SB-4.0-5.0 MS	9:00	ML	AS ABOVE W COLOR CHANGE TO YELLOWISH BROWN 10 YR 5/6
5		0.0	13/66	SL850-SA5D-SB-4.0-5.0	9:10		
6	4.0/4.0	0.0	13/60				
7		0.0	13/72				
8		0.0	13/78				
9	4.0/4.0		66			ML	SILT - LT YELLOWISH BROWN (10 YR 6/4); 80% SILT, FIRM, LOW PLASTIC, SEMI MOIST, 20% CLAY, NO ODOR, TRACE GRAVEL & LIGNITE FLAKES.
10			84				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
DG550	5D	9/6/13	9/6/13
Project: SSFL		**Geologist:** BKAMPZYIC	**Total Depth:** 15'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	4.0/4.0						SILT – LT YELLOWISH BROWN (10YR 6/4); 80% SILT, FIRM, LOW PLASTIC, SEMI MOIST; 20% CLAY; TRACE GRAVEL & LIGNITE FLAKES, NO ODOR
11		0.0	13/72				
12		0.0	13/90				SILT W/ SAND – MOTTLED GRAY (10YR 6/1) & STRONG BROWN (7.5 YR 5/8); 75% SILT SOFT LOW PLASTIC, SEMI MOIST, 25% SAND, F, PG, LOOSE; NO ODOR
13	3.0/3.0	0.0	13/72				
14		0.0	13/78				
15		0.0	13/90				SILTSTONE – LT GRAY (7.5 YR 6/1) W/ IRON OXIDE STAINING, HIGHLY WEATHERED
							REFUSAL ON BEDROCK AT 15.0 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G F

Sample ID SL-550-SASD-SB-4.0-5.0 MS **Date/Time** 9/6/13 @ 9:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6 – 16 oz JARS
6 – ENCORE

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) (0)

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike D Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. C

Sample ID SL-850-SA5D-SB-4.0-5.0 **Date/Time** 9/6/13 @ 9:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-550-SA5D-SB-4.0-5.0 MS

Field Geologist BKASPZYIC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz Jars
2- Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10YR 5/6

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL551-SA5D-SB-0.0-0.5 Date/Time 9/12/13 09:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASZYK

Sampler VCortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
Propellants	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-4oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 7.5 YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

Location ID: DG-551	Subarea: 5D	Date Started: 9/12/13	Date Completed: 9/12/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 18.5, 19.7, 18.5
Company Name: ~~CDM~~ SMITH	Drill Contractor/Driller: STRONGARM		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: 2.0 FT
Radiological Background: 12, AM=13	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: NA		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/83	SL-551-SA5D-SB-0.0-0.5	9:05	CL	CLAY W/ SAND – DK BROWN (7.5YR 3/3) 75% CLAY, SOFT NON-PLASTIC, DRY, 25% SAND, F, PG; NO ODOR
1		0.0	13/84				
2	3.5/4.0	0.0	13/86				~~Clay w/Sand~~
3		0.0	13/84			CL	~~SANDY CLAY~~ – STRONG BROWN (7.5YR 5/6) 75% CLAY SOFT NON PLASTIC, SEMI MOIST, 25% SAND, F, PG; NO ODOR
4		0.0	13/78	SL-551-SA5D-SB-4.0-5.0	9:15		
5		0.0	13/72				
6	4.0/4.0	0.0	13/84				
7		0.0	13/84				
8		0.0	13/90				
9	4.0/4.0		78	SL-551-SA5D-SB-9.0-10.0	9:25		
10			102				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
06551	5D	9/12/13	9/12/13
Project: SSFL		**Geologist:** KASPOR	**Total Depth:** 18.5

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							~~clay w/ Sand~~
4	4.0/4.0	0.0	13/78			CL	~~SAND CLAY~~ - STRONG BROWN (7.5YR 5/6) 75% CLAY, SOFT, NON-PLASTIC SEMI MOIST; 25% SAND, F, PS; NO ODOR
12		0.0	13/84				
13		0.0	13/78				
14	4.0/4.0	0.0	13/78	SL-551-SAED-GB 14.0-15.0	9:35		
15		0.0	13/90			ML	SILT - BROWNISH YELLOW (10YR 6/6) - 90% SILT, FIRM, NON PLASTIC, SEMI MOIST, 10% CLAY; NO ODOR.
16		0.0	13/90				GRADATIONAL ↓ CONTACT
17	2.5/2.5	0.0	13/102				
18		0.0	13/84	SL-551-SAED-GB-17.5-18.5	9:45	WR	Siltstone - Brown Yellow (10YR 6/6), Hard, Highly Weathered & Broken Dry.
19							REFUSAL AT 18.5 FT ON BEDROCK
20							

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-551-GASD-SB-4.0-5.0 Date/Time 9/12/13 @ 09:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASZYK

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz Jar
2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Willie Hoffman **PG Registration #** 7785

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V Cortes

Sample ID 4-551-SA5D-SB-9.0-10.0 Date/Time 9/12/13 09:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jar
2- Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown (7.5YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G

Sample ID SL-551-SASD-SB-14.0-15.0 Date/Time 9/12/13 09:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jar
2 - Encore

NA - Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brownish Yellow (10YR 6/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By N. Cates

Sample ID SL-551-SASD-SB-17.5-18.5 Date/Time 9/12/13 09:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 17.5

End Depth 18.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BIASPLAIC

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Collect	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz Jar
2-Encore

NA Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		(N/A)
Other _____		

Is Staining Present Yes (No)

Color Brownish Yellow (10YR 6/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Stuart Hyper

Sample ID SL-552-SASD-SB-0.0-0.5 Date/Time 9/6/13 13:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Soil/Sediment	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Biota	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS Sleeves
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Yellowish Brown 10 YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Willie Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG552	SD	9/6/13	9/6/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Rodriguez/Strongarm	11.8/12.8
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: ~13 VD-98	Borehole diameter: 2.25 INCH	0-8
PID Background: 0.0	Depth to GW: N/A	Sampling Method:
Radiological Equipment Used:	PG Review & No.:	MacroCore
✓ MicroR ✓ Alpha/Beta ✓ Pancake	Julia Hoffman #7735	Geologist: B/KASPOVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/72	SL552-SA5D-SB-0.0-0.5	13:10	ML	SILT - DK YELLOW BROWN (10YR 5/6); 80% SILT, SOFT, NON-PLASTIC DRY, 20% CLAY, NO ODOR
1	3.0/4.0	0.0	13/90				
2		0.0	13/102				AS ABOVE - SEMI MOIST
3		0.0	13/96				
4		0.0	13/96	SL552-SA5D-SB-4.0-5.0	13:25		AS ABOVE
5	4.0/4.0	0.0	13/90				
6			13/84			ML	SILT W/ SAND - YELLOWISH BROWN (10YR 5/6); 75% SILT, SOFT, NON-PLASTIC SEMI MOIST; 25% SAND, F, NG, LOOSE
7			13/78				
8			13/80				
9			13/72				
10			91				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG-552	Subarea: SD	Date Started: 9/6/13	Date Completed: 9/6/13
Project: SSFL		Geologist: B KALPAKIS	Total Depth: 11.8 FT/BGS

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials	
11	4.0/4.0	0.0	13/84			ML	SILT w/ SAND – YELLOWISH BROWN (10YR 5/6); 75% SILT, SOFT, NON-PLASTIC SEMI MOIST, 25% SAND, F, PG; NO ODOR	11
12	0.8/0.8	0.0	13/90			SP	ABRUPT CONTACT SAND – LT. GRAY (2.5YR 7/2), 100% SAND, F, PG, LOOSE, DRY, INTERBEDDED W/ WEATHERED SAND STONE NO ODOR	12
								13

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V GK

Sample ID SL-552-SA5D-SB-4.0-5.0 **Date/Time** 09/06/13 @ 13:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Dk Yellow Brown 10YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-553-SA5D-SB-0.0-0.5 MS Date/Time 9/12/13 7:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (Direct Push) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kaszyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6 - 5g sleeves
2 - 40z VOA

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 10
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

(Igneous/Metamorphic Gravel N/A

Other _____

Is Staining Present Yes (No)

Color Brown 7.5 YR 4/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-553	Subarea: SD	Date Started: 9-12-13	Date Completed: 9-12-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 5.4, 5.7, 5.1
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 1.7 FT
Radiological Background: ~~x=13~~ / YB/80	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PO Review & No: ~~Mike Hoffman~~ #7735		Geologist: KASPRYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	B/I 100	SL553-SA5D-SB-0.0-0.5MS	7:30	CL	CLAY - BROWN (7.5YR 4/3); 80% CLAY, SOFT, NONPLASTIC, DRY; 10% SILT, 10% GRAVEL, F, WG, SUBROUNDED TO SUBANGULAR MAX SIZE 3/4 INCH; NO ODORS.
1	3.5/4.0	0.0	13/102				
2		0.0	13/86	SL853-SA5D-SB-0.0-0.5	7:35		AS ABOVE WITHOUT GRAVEL
3		0.0	13/90				
4		0.0	13/102			ML	SILT - BROWN (7.5YR 4/3); ~~SAND~~ 100%, SOFT NON PLASTIC, SEMI MOIST, LOOSE NO ODOR
5	1.7/1.7	0.0	78	SL553-SA5D-SB 4.5-5.5	7:45	ML	SILTSTONE - BROWN (7.5YR 4/3) 100% WEATHERED SILTSTONE, DRY
6		0.0	13/90				REFUSAL AT 5.7 FT ON SILTSTONE
7							
8							
9							
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-853-SASD-SB-0.0-05 Date/Time 9/12/13 07:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): ~~Drive~~ 9/12/13 (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-553-SASD-SB-0.0-0.5MS

Field Geologist BKASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Eurofins	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 55 SLEEVES

2 - 40Z JARS

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 10
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/Metamorphic Gravel		N/A
Other _____		

Is Staining Present Yes (No)

Color Brown 7.5YR 4/3

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong
2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-553-SA5D-SB-4.5-5.5 Date/Time 9/12/13 7:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.5

End Depth 5.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. Kasprzyk

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Speciation	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars
2 Encores
1 4-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 7.5 YR 4/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SB-SC-554-SA5D-0.0-0.5 **Date/Time** 9/5/13 @ 13:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Effluent	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 55 SLEEVES
1 4-oz JAR

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
TB-554	SD	9/5/13	9/5/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F Rodriguez	8.0/7.8/7.9
GPS collected? Yes or No (LW) 9/6/13	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: 13 88	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mull Ogram #7735	Geologist: BLACKPYR

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1		0.0	13/91	SL-554 SA5D SB-0.0 0.5	13:15	ML	SILT - DK REDDISH BROWN (10YR 4/4) 80% SILT, FIRM, NON-PLASTIC, DRY; 20% Clay; NO ODORS.
		0.0	13/70				
		0.0	13/72				
2	3.5/4.0	0.0	13/66				
3		0.0	13/78				
4		0.0	13/72	SL-554 SA5D SB-4.0	13:30		ABRUPT CONTACT
5		0.0	13/60	5.0		ML	WEATHERED SILT STONE — Very PALE BROWN (10YR 7/4) DRY
6	4.0/4.0	0.0	13/72				
7		0.0	13/66	SL554 SA5D SB-7.0	13:40		
8		0.0	13/68	8.0			REFUSAL AT 8.0 FT ON BEDROCK
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-554-SA5D-SB-4.0-5.0 **Date/Time** 9/5/13 @ 13:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPER

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Encore	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz JARS

2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) ~~0~~

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK YELLOWISH BROWN (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

~~Dry~~ Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-SS4-SA5D-SB-7.0-8.0 Date/Time 9/5/13 @ 13:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 7.0

End Depth 8.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKosgrzyk

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16-oz Jars

2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color PALE BROWN 10YR 7/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GE

Sample ID SL-555-SA5D-SB-0005 **Date/Time** 9-5-13 @ 8:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist RKaspzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	~~X~~ RK 9/6/13
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown (10YR 4/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-555	Subarea: SD	Date Started: 9/5/13	Date Completed: 9/5/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 11.3/11.4/11.4
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/E Rodriguez		Depth Drilled into Bedrock: ~0
GPS collected? (Yes) or No	Drill Method: DPT		
Radiological Background: γ=13/YB=78	Borehole diameter: 2 1/4 inch		Sampling Method: MACRO CORE
PID Background: 0.0	Depth to GW: NA		
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mulle Hoffman #7735		Geologist: B KAGAYAMA

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/81	SS555-SA5D-SB-0.0-0.5	8:55	ML	SILT – BROWN (10YR 4/3) – 80% SILT, SOFT, NON-PLASTIC, DRY; 20% CLAY, NO ODOR
		0.0	13/68				
1		0.0	13/78				
2	3.5/4.0	0.0	13/66				
3		0.0	13/66			CL	CLAY – STRONG BROWN (7.5YR 5/8); 60% CLAY, HARD, NON-PLASTIC, DRY, 40% SILT; NO ODOR
4		0.0	13/90	SS-555-SA5D-SB-4.0-5.0	9:15		
5		0.0	13/84			CL	SAME AS ABOVE W/ TRACE FN SAND AS ABOVE GRADING TO MOTTLED STRONG BROWN (7.5YR 5/8) W/ BROWN (10YR 5/3) AND YELLOW 10YR 7/8. NO SAND
6	4.0/4.0	0.0	13/72				
7		0.0	13/66				
8		0.0	13/90				
9	3.4/3.4	0.0	13/72				
10			196			CL	CLAY W/ SAND – MOTTLED BROWN (10 YR 5/3) AND STRONG BROWN, 80% CLAY (CONTINUE ON PG 2)

MD 9-5-13

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG-555	Subarea: 5D	Date Started: 9-5-13	Date Completed: 9-5-13
Project: SSFL		Geologist: RKASPRZYK	Total Depth: 11.4

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	3.4 / 3.4	0.0	13/96	SL-555-SA5D-SB-10.5-11.5	9:30	CL	CLAY W/ SAND - MOTTLED ~~STRONG~~ BROWN (10YR 5/6) STRONG BROWN (7.5YR 5/8); 80% CLAY SOFT, NON PLASTIC, DRY; 20% SAND, F, MG DENSE; NO-ODOR. (BS 9/5/13) 11
							REFUSAL @ 11.4 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VIGT

Sample ID SL-555-SA5D-SB-4.0-5.0 **Date/Time** 9/5/13 @ 9:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKasparc

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Soil/Sediment	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** ⊘

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5YR 5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GA

Sample ID SL-555-SASD-SB-10.5-11.5 **Date/Time** 9/5/13 @ 9:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 10.5

End Depth 11.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist M Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Enprotec	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10 YR 5/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By _____

Sample ID SC-556-SASD-SB-0.0-0.5 Date/Time 9/5/13 10:20

Matrix (circle one): Soil Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BOB KASPZYK

Sampler VIDAL CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	~~X~~ VC. 9/5/13
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS SLEEVES

2 4-oz JARS

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color BR (7.5 YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG556	SP	9/5/13	9/5/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 12.0 / 11.8
Company Name: CDM SMITH	Drill Contractor/Driller: STRATAPROBE/Kostas/RR2	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0.25 FT
Radiological Background: Y=13 / YB=81	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & KO: Julie Hoffman #7735	Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/85	SL-556-SA5D-SB-0.0-	10:20	ML	SILT - BROWN (7.5YR 4/4) 100% SILT, SOFT, NON-PLASTIC, LOOSE DRY TRACE FN gravel, NO ODOR
		0.0	13/72				
1		0.0	13/60	0.5			
	3.0 / 4.0						
2		0.0	13/70				
3		0.0	13/84				
4		0.0	13/66	SL-556-SA5D-SB-4.0-	12:20		
5		0.0	13/66	5.0			
	4.0 / 4.0						
6		0.0	13/78				
7		0.0	13/96				
8		0.0	13/64				ABRUPT CONTACT
						SM	SILTY SAND DK Yellow Brown (10YR 4/6); 70 % SAND, F, PG, LOOSE, DRY; 30% SILT, NO ODOR
9	4.0 / 4.0	0.0	13/90				
10							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
DB-556	SD	9/5/13	9/5/13
Project: SSFL		**Geologist:** K KASPOK	**Total Depth:** 11.4

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cm)	Sample Name	Sample Time	USCS	Description of Materials	
11		0.0	13/90	~~SL-556-SA5D-SB-11.0-12.0~~	(12) 1240	~~SM~~	SILTY SAND – DK YELLOW BROWN (10YR 6/4) 70% SAND, F, PG, LOOSE, DRY,	12
12		0.0	13/90			ML	SILTSTONE – Brownish Yellow	12
							REFUSAL AT 12.1 FT ON ROCK	

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL556-SA5D-SB-4.0-5.0 Date/Time 9-5-13 / 12:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/~~9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JARS
2-ENCORE
1-4 oz JAR

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color Brown (7.5YR 4/4)

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-556-SA50-SB-11.0-12.0 Date/Time 9/5/13 12:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 11.0

End Depth 12.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BRADRAC

Sampler V Cortez

Analysis

	Parameter	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz JAR
2 - ENCORE
1 - 40z JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color Dk Yellowish Brown (10yr 6/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 2235

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-557-SA5D-SB-0.0-0.5 **Date/Time** 9-24-13 / 0935

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Excess	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4 oz jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown 7.5YR 4/2

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-557	Subarea: 5D	Date Started: 9-24-13	Date Completed: 9-24-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st NA = 1.1 2nd NA = 1.6
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 13 $\alpha\beta$ = 90	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Non: Mila [illegible] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 / 0.0	18 97 / 12 90	SL-557 SA5D-SB 0.0-0.5	0935	SP-SM	SAND w/SILT, brown (7.5YR 4/2) f grn w/ few ang-med grn, subrounded, quartz, dry, some ang silty sand mod poorly consolidated material, 90% SD 10% SILT, few amount org (roots) — 0.5
1	HA	0.0	13 96			SM	
		0.0	13 84			GW-GM	SILTY SAND w/GRAVEL, lt yel brn (10YR 6/4) mottled w/ brown (10YR 5/3) f grn w/ few to some med grn & tr ang coarse, mod poorly ~~sorted~~ graded quartz and sd stn, Gravel is f-c sized (becoming coarser w/depth) subangular to angular, sd stn mod well- to well cemented, 50% SD, 15% SILT, 35% GRAVEL (increasing gravel & decreasing silt w/depth), dry — 1.0
2							GRAVEL w/SILT & SAND, A.A. except 60% GRAVEL, 30% SD, 10% SILT, dry — 1.6
							Refusal @ 1.6' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GF

Sample ID SL-558-SA5D-SB-0.0-0.5 **Date/Time** 9-24-13 / 0830

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (7.5YR 4/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-558	Subarea: 5D	Date Started: 9-24-13	Date Completed: 9-24-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 5.0 2nd HA = 4.8
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 11 $\alpha\beta$ = 98	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Reviewer & No.: Mike Hoffman #735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/.05	0.0 0.0	11/68 11/78	SL-558 SA5D-SB 0.0-0.5	0830	SM	SILTY SAND brown (7.5YR 4/2), f grn w/ Few ant med & tr ant coarse grn, mod poorly graded subrounded to subangular, quartz, dry, few to some poorly consolidated silty sand material, 70% SD, 30% SILT, Few to some ant org (roots), tr ant gravel - sdsth f sized subangular to angular
1	HA	0.0	11/30				
2		0.0	11/66			SM	SILTY SAND, grayish brown (10YR 5/2) mottled w/ v pale (10YR 7/4), A, A except only tr ant org (roots) & no gravel! — 2.0'
3		0.0	11/72			SM	SILTY SAND, lt gray (10YR 7/2) mottled w/ pale brown (10YR 6/3) f grn w/ Few med & tr coarse grn, Mod poorly graded subangular quartz & some sdsth dry 60% SD 40% SILT, tr ant gravel; Few ant mod poorly consolidated silty sand material increasing in ant @ refusal — 3.0'
4		0.0	11/84	SL-558 SA5D-SB 4.0-5.0	0845		
5		0.0	11/66				— 5.0'

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G 7

Sample ID SL-558-SA5D-SB-4.0-5.0 **Date/Time** 9-24-13 / 0845

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyte
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyte
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves, 1 4oz jar + 2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color lt gray (10YR 7/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID 56559-SA5D-SB-0.0-05 Date/Time 9/5/13 @ 07:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Rob Kasprak

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Specialty	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-SS SLEEVES
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-559	Subarea: 5D	Date Started: 9/5/13	Date Completed: 9/5/13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 6.2/6.8/6.9
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F. Rodriguez		Depth Drilled into Bedrock: 0
GPS collected? Yes or No	Drill Method: DPT		
Radiological Background: γ=13/ αβ=106	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: NA		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Nikki Hoffman #7735		Geologist: B KASPZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1		0.0	13/83	SL-559-SA5D-SB-0.0-0.5	7:40	ML	SILT - BROWN (10YR 4/3); 80% SILT, SOFT NON-PLASTIC, DRY; 20% CLAY, NO ODOR.
2	4.0/4.0	0.0	13/84				
3		0.0	13/66			CL	CLAY - BROWNISH YELLOW (10YR 6/6); 80% CLAY, FIRM, NON PLASTIC, DRY; 20% SAND, F, PG, DENSE, NO ODOR.
4		0.0	13/66				
5	2.9/2.9	0.0	13/90			SC	CLAY SAND - BROWNISH YELLOW (10YR 6/6) 70% SAND, F, PG, LOOSE DRY; 30% CLAY FIRM, NON-PLASTIC; W/ FRAGMENTS OF WEATHERED LIMESTONE (RENTS W/ HCL) NO ODOR
6		0.0	13/86	SL-559-SA5D-SB-6.0-7.0	7:55		
7		0.0					REFUSAL @ 6.9 FT
8							
9							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SS559-SA5D-SB-6.0-7.0 **Date/Time** 9/5/13 @ 7:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.0

End Depth 7.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist R Kasprzyk

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA ~~300.0/9056~~ 6020	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Special	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 1602 JARS
2 - Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown Yellow 10YR 6/6

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By P. Hortness

Sample ID SL-560-SA50-SB-0.0-0.5 Date/Time 11/12/2013 0835

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID _____

Field Geologist C. Cox

Sampler A. VIJIAN

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	~~X~~ PH 11/12/13

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	~~X~~ PH 11/12/13
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color olive brown (2.5Y 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Miles Hoffman **PG Registration #** 7735

Additional Comments None

10/4/13

NA – Not Applicable

Location ID: SD-560	Subarea: SD	Date Started: 11/12/13 TUES 0826	Date Completed: 11/12/2013
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 8.2'
Company Name: CDM SMITH		Drill Contractor/Driller: SAFS	
GPS collected? Yes or No		Drill Method: DPT	Depth Drilled into Bedrock: NA
Radiological Background: 14/76		Borehole diameter: 2.25"	
PID Background: 0.0		Depth to GW: NA	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PO Review & No:	Geologist: C. COX

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cm)	Sample Name	Sample Time	USCS	Description of Materials
0	3/4	0.0	14/96	SL-560-SA5D-SB-0.0-0.5	0835	CL	SANDY CLAY ~~clay with sand~~: olive brown (2.5Y 4/4); 70% clay, 30% silt, sand, pg, f, moist, no odor.
		0.0	14/72				
1		0.0	12/54				
2		0.0	12/90				
3		0.0	12/78				
4		0.0	12/72	SL-560-SA5D-SB-4.0-5.0	0905		silt with sand: pale brown (2.5Y 7/4); 80% silt, low plasticity, Fm 20 sand, pg, f, dry, no odor.
5		0.0	12/66	SL-560-SA5D-SB-4.0-5.0MS		ML	
6		0.0	12/84				
7		0.0	12/48				
8		0.0	12/84	SL-560-SA5D-SB-7.0-8.0	0935		Refusal at sandstone at 8.2', 7.8'

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By PHar BM 11/12/13

Sample ID SL-560-SASD-SB-4.0-5.0MS Date/Time ~~11/12/13~~ 11/12/2013 0920

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID

Field Geologist C. Cox

Sampler A. UIUIAM

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** NA

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Pale brown (2.5Y 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments None

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By P. Hartman

Sample ID SL-S60 (AFS 11/12/13) - SA50 - SB 4.0-5.0 Date/Time 11/12/2013 0905

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) (FD) FB RB

Parent Sample ID SL-S60-SA50-SB-4.0-5.0MS

Field Geologist C. Cox

Sampler A. Ujuan

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	[redacted] X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** NA

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Pale brown (2.5Y 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments None

Cell/2/13

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By P. Hartman

Sample ID SL-560-SA50-SB 7.0-8.0 Date/Time 11/12/2013 0935

Matrix (circle one): (Soil) Sediment Water

Start Depth 7.0

End Depth 8.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID _____

Field Geologist C. COX

Sampler A. UICIAM

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	X
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** NA

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color pale brown (2.5 Y 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NONE

11/12/13

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-561-SA5D-SB-0.0-0.5 **Date/Time** 10-8-13 / 0840

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves + 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color brn (7.5YR 5/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Niles Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-561	Subarea: 5D	Date Started: 10-8-13	Date Completed: Did not have Refusal @ 10.0' 10-8-13
Client: DOE	Project Name/#: ~~GSFL-66959-033376.4903.009.933.02231 SSPH3~~ SM 10-113		Total Depth: 1st NA = 10.0 ~~2nd NA =~~
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 αβ = 87	Borehole diameter: 3" ø		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mulli Hoffman #735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0 0.0	12/80 12/67	SL-561 SA5D-SB 0.0-0.5	0840	SM	SILTY SAND, brn (7.5YR 5/4) f grn w/tr ant med grn, poorly ~~graded~~ subrounded, quart, dry, 80% SD 20% SILT few to some organics (roots), sli to mod well compacted, sli crumbly — 0.5
1	HA	0.0	12/78			SM	
2		0.0	12/78				SILTY SAND, dk reddish gray (5YR 4/2) mottled w/reddish brown (5YR 5/4) and lt reddish brown (5YR 6/3) f w/some med grn, poorly to mod poorly ~~graded~~ sorted, subrounded to subangular, quartz & sdstn, dry 85% SD, 15% SILT, tr ant organics (roots) sli compacted, mod crumbly
3		0.0	12/72			SP-SM	— 2.8
4	1.0/1.0	0.0	12/66	SL-561 SA5D-SB 4.0-5.0	0900	SC	SAND w/SILT brn (7.5YR 4/3) mottled w/(7.5YR 5/3) f-m grn w/tr coarse grn, mod poorly ~~graded~~ sorted sr to sa, quartz & sdstn, dry, few to some amounts of $CaCO_3$ deposits (white (7.5YR 8/1)) on grains suspected to be in root molds & burrows, 90% SD 10% SILT tr ant gravel, f-sized, sa to angular, sdstn — 4.0
5		0.0	12/96				CLAYEY SAND, strong brn (7.5YR 4/6) mottled w/brn (7.5YR 4/4), low plasticity, mod crumble, firm to sli soft SD is f-m grn A.A.; clay is mostly disseminated in sd but also present as sandy clay blebs, some to common $CaCO_3$ deposits on grns suspected to be deposits in root molds & burrows 60% SD 30% CLAY 10% SILT, becoming less clayey w/depth
6	HA	0.0	12/84				
7		0.0	12/96			SM	SILTY SAND brn (7.5YR 5/4) mottled w/lt brn (7.5YR 6/4) and strong brn (7.5YR 5/6) f grn w/tr ant med and coarse grn, quartz & tr ant sdstn, dry, mod poorly ~~graded~~ sorted sr to sa; ~~grns~~ SILT is disseminated in sd, tr ant clay A.A.; 75% SD, 20% SILT, 5% clay mod well compacted, few to some $CaCO_3$ deposits on grains — 6.5
8		0.0	12/84				
9	1.0/1.0	0.0	12/96	SL-561 SA5D-SB 9.0-10.0	1010	SM	SILTY SAND, strong brown (7.5YR 5/6) mottled w/(7.5YR 5/8) and brn (7.5YR 4/4), A.A w/tr to few amount of yel red (5YR 4/6) blebs of sandy clay; sli more compacted than 6.5-8.2 unit above.
10		0.0	12/84				Ceased advancing HA @ 10' bls - No Refusal

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G

Sample ID SL-561-SA5D-SB-4.0-5.0 Date/Time 10-8-13/0900

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color strong brn (7.5YR 4/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √, GK

Sample ID SL-561-SA5D-SB-9.0-10.0 Date/Time 10-8-13/1010

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color strong brown (7.5YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.E

Sample ID SL-562-SA5D-SB-0.0-0.5 **Date/Time** 9-25-13 / 1335

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (7.5YR 4/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-562	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 13.1 2nd HA = 13.1
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? Yes or No	Drill Method: Hand auger		Depth Drilled into Bedrock: NA
Radiological Background: γ=12 $\alpha\beta$=75	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/.05	0.0 0.0	12/105 12/78	SL-562 SA5D-SB 0.0-0.5	1335	SM	SILTY SAND, brown (7.5YR 4/3) f-m gnd w/ tr amt coarse gnd, mod well sorted, subrounded to subangular, quartz & siltstone, dry, 70% SD, 25% SILT, 5% GRAVEL GRAVEL is siltstone, mod poorly cemented, f-m sized few to some org. (roots)
1	HA	0.0	12/78				
2		0.0	12/90			SC	CLAYEY SAND, reddish brn (5YR 4/3) mottled w/ (5YR 5/4) f gnd w/ Few amt med gnd, mod poorly graded, subrounded quartz, dry 60% SD 30% CLAY 10% SILT, mod well to well compacted, hard, low plasticity, Friable, Few amt org (roots) decreasing in amount w/ depth — 2.0
3		0.0	12/72				
4	1.0/1.0	0.0	12/60	SL-562 SA5D-SB 4.0-5.0	1350		
5		0.0	12/78			CL	SANDY CLAY, reddish brn (5YR 4/4) mottled w/ brn (10YR 5/4), low plasticity, hard, Friable, dry, well compacted, few to some amt of calcium carbonate inclusions & bedding planes? SD is disseminated in — 5.0
6	HA	0.0	12/78			CL	clay, 50% CLAY, 30% SD, 20% SILT — 6.0 SANDY CLAY, brn (7.5YR 4/4) mottled w/ strong brn (7.5YR 5/6) low plasticity, firm to hard, friable, laminated, dry to sl moist 65% CLAY 30% SD, 5% SILT
7		0.0	12/72				
8		0.0	12/60				
9		0.0	12/84			CL	SANDY CLAY, strong brown (7.5YR 5/6) mottled w/ (7.5YR 5/8), A.A except 60% CLAY 30% SD 10% SILT and no laminations observed — 8.5
10		0.0	12/60			SC	CLAYEY SAND, yel brn (10YR 5/8) mottled w/ dk yel brn (10YR 4/6) f gnd, few amt med gnd, mod poorly graded, subrounded quartz, dry to sl moist. 60% SD 30% CLAY, 10% SILT — 9.5

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

78e11

Location ID: DG-562	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Project: SSFL		Geologist: David Rojas	Total Depth: 13.1

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	HA						SEE LITHOLOGY ON PG 1
11		0.0	12/78			CLAYEY SC	SAND WITH ~~CLAY~~ SILT, lt yel brn (10YR 6/4) mottled w/ yel brn (10YR 5/4) f-m grn w/ Tr to Few ant coarse grained, well sorted, clay is disseminated in sd dry ~~10~~ 65% SD, 20% CLAY, ~~5~~ 15 silt — 11
12		0.0	12/66				
						SM	SILTY SAND lt yel brn (10YR 6/4) mottled, w/ v pale brn (10YR 7/4) f grn w/ Few to some med-coarse grained, quartz & silty sandstone, mod poorly sorted, subrounded, dry, Tr amount gravel, f sized mod well to well cemented sdstone, 80% SD 20% SILT — 12.5
13		0.0	12/72				— 13.1

Refusal @ 13.1' bls

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.K

Sample ID SL-562-SA5D-SB-4.0-5.0 **Date/Time** 9-25-13/1350

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Specialty	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Sleeves, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color reddish brown (5YR 4/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cost

Sample ID SL-563 - SA5D-SB-0.0-0.5 **Date/Time** 9-25-13 / 12:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves # / 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Light yellow brown (10YR 6/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-563	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 9.5, 2nd NA = 9.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{x}$ = 10 σ = 83	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Sign: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0 0.0	10/75 10/54	SL-563 SA5D-SB 0.0-0.5	1215	SM	SILTY SAND, lt yel brn (10YR 6/4) mottled w/ brown (10YR 5/3) f grn with few ant med grn, subrounded to subangular quartz, dry, few to some org. (rootlets) 80% SD, 15% SILT 5% GRAVEL, Gravel is sdstn F-c sized, sa. decreasing w/ depth, sr to sa
1		0.0	10/60				1.0
2	HA	0.0	10/78			SM	SILTY SAND, v pale brn (10YR 7/4) mottled w/ pale brn (10YR 6/3), AA except 75% SD 25% SILT & tr gravel A.A except mostly f-m sized, mod well to well cemented
3		0.0	10/60				3.0
4	1.0/1.0	0.0	10/66	SL-563 SA5D-SB 4.0-5.0 MS SL-563 SA5D-SB 4.0-5.0	1245 1300	SM	SILTY SAND, lt gray (10YR 7/2) mottled w/ lt brn gray (10YR 6/2), f grn, few ant med grn & coarse grn, mod well poorly sorted, subrounded quartz & sdstn, dry 70% SD, 30% SILT, tr gravel A.A. except sa to angular, Siltstone, mod poorly to poorly cemented, lt gray (10YR 7/1) to white (10YR 8/1)
5		0.0	12/48			SM	SILTY SAND w/ GRAVEL, A.A. except 60% SD 25% SILT 15% GRAVEL Gravel is predominantly f-sized, sa to angular, siltstone, mod poorly to poorly cemented 4.4
6	HA	0.0	12/78			SP SM	SILTY SAND w/ GRAVEL, A.A except pale brn (10YR 6/3) mottled w/ lt gray (10YR 7/2); 55% SD, 25% SILT 20% GRAVEL, GRAVEL is siltstone AA except grayish brown (10YR 5/2) mottled w/ lt gray (10YR 7/1), & f-c grn 6.0
7		0.0	12/96				
8			12/78				
9			12/60			SM	SILTY SAND w/ GRAVEL brown (10YR 5/3) mottled w/ lt yel brn (10YR 6/4) & yel brn (10YR 5/6) f-m grn w/ few to some coarse gravel, mod well sorted, subrounded to subangular quartz, siltstone, & sdstn, dry 60% SD 25% SILT 15% GRAVEL GRAVEL is mostly sdstn, sa, mod well to well cemented, some siltstone A.A. 8.4
			12/84				9.5 Refusal @ 9.5

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-563-SA5D-SB-4.0-5.0MS Date/Time 9-25-13 / 1245

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6 SS Sleeves, 6 Encores, 1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND w/ GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** None

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color lt gray (10YR 7/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G L.

Sample ID SL-863-SA5D-SB-4.0-5.0 Date/Time 9-25-13 / 1300

Matrix (circle one): Soil Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-563-SA5D-SB-4.0-5.0MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enviros	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Frontier	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND w/ GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color lt gray (10YR 7/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-564-SA5D-SB-0.0-0.5 **Date/Time** 10-1-13/1250

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves + 1 Hoz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		(GM)	Silty GRAVEL w/ SAND
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments Sdstn gravel is suspected to be weathered material

NA – Not Applicable

Location ID: DG-564	Subarea: 5D	Date Started: 10-1-13	Date Completed: 10-1-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 9.6 2ND DPT = 9.4
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: α = 11 $\alpha\beta$ = 68	Borehole diameter: 2.25"		
PID Background: 0.0ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mulle Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	11/87 11/60	SL-564 SASD-SB 0.0-0.5	1250	GM	SILTY GRAVEL w/sand yel brn (10YR 5/4) mottled w/ (10YR 5/6) f-m gr, mod poorly graded, subangular to subrounded, angular, sdstn, mod well to well cemented, dry, SD is F-C gr, subrounded to subangular quartz & sdstn, 60% GRAVEL 20% SILT 20% SD
1	2.8/3.5	0.0	11/48				GRADATIONAL CONTACT
2		0.0	11/54			SP SM SM	1.7 SILTY SAND w/ GRAVEL lt yel brn (10YR 6/4) mottled w/ grayish brn (10YR 5/2) and dk grayish brn (10YR 4/2) f-C gr, mod poorly graded, subrounded to subangular quartz & sdstn, dry; 50% SD 30% GRAVEL 20% SILT GRAVEL is mod well cemented
3		0.0	11/66				
4		0.0	11/48	SL-564 SASD-SB 4.0-5.0	1300	SM	Abrupt Contact 3.8 SILTY SAND w/GRAVEL dk grayish brown (10YR 4/2) mottled w/ yel brn 10YR (5/6) 60% SD, 25% GRAVEL 15% SILT f-m gr w/ Few ant coarse gr, subangular to angular, quartz & sdstn, dry; GRAVEL is subangular to angular f-m sized sdstn, mod well cemented becoming less well cemented w/depth
5	3.2/4.0	0.0	11/60				GRADATIONAL CONTACT
6		0.0	11/60			SM	5.5 SILTY SAND w/GRAVEL A.A except yel brn (10YR 5/4) w/ Zones of $CaCO_3$ deposits @ 6.2' & 6.8' bls, sdstn is less well cemented (mod poorly cemented) & predominantly F gr 55% SD 25% SILT 20% GRAVEL
7		0.0	11/72				
8		0.0	11/72			SM	7.4 SILTY SAND w/GRAVEL lt yel brn (10YR 6/4) mottled w/ yel brn (10YR 5/6) & strong brown (7.5YR 5/6) 60% SD 25% SILT 15% GRAVEL, F gr mod well sorted, quartz & sdstn, GRAVEL is F sized, mod poorly cemented, silty sdstn
9		0.0	11/72			SM	9.0 SILTY SAND, lt olive brn (2.5Y 5/3) mottled w/ olive brn (2.5Y 4/3) 65% SD, 25% SILT 10% GRAVEL, compacted, F gr, well sorted, quartz
		0.0	11/90				Refusal @ 9.6' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J. Catz

Sample ID SL-564-SA5D-SB-4.0-5.0 **Date/Time** 10-1-13 1300

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16oz jars, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND w/ GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) NONE

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color dk grayish (10YR 4/2)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-565-SA5D-SB-0.0-0.5MS **Date/Time** 9-24-13/0740

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

6 SS Sleeves & 1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				(GP)	Poorly graded GRAVEL w/SAND
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color v pale brown (10YR 7/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-565	Subarea: 5D	Date Started: 9-24-13	Date Completed: 9-24-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 1.3' 2nd HA = 1.7'
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 10 αβ = 73	Borehole diameter: 2.25		
PID Background: 0.9ppm	Depth to GW: NA		Sampling Method: Side Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Nikki Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	10/69	SL-565 SA5D-SB p.0-0.5	0740	GP	GRAVEL w/SAND v pale brn (10YR 7/3) mottled w/ pale brn (10YR 6/3) and brown (10YR 5/3) f sized w/some to few med sized, silty sdstn, mod poorly cemented, subangular to angular, SD is f-m gr, subrounded to subangular, mod poorly sorted quartz and sdstn, dry ~65% GRAVEL, 30% SD, 5% SILT — 0.5'
1	HA	0.0	10/60	SL-565 SA5D-SB 0.0-0.5	0750	SM	
2							SILTY SAND w/ GRAVEL, same colors as above, A.A. f-m gr A.A. GRAVEL is A.A; 50% SD, 30% SILT, 20% GRAVEL dry — 1.7'

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-865-SA5D-SB-0.0-0.5 **Date/Time** 9-24-13/0750

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-565-SA5D-SB-0.0-0.5MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves + 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL w/SAND
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V pale brown (10YR 7/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GK

Sample ID SL-566-SA5D-SB-0.0-0.5 **Date/Time** 9-24-13/1230

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (7.5YR 4/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-566	Subarea: 5D	Date Started: 9-24-13	Date Completed: 9-24-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st HA = 5.0 2nd HA = 3.5
Company Name: CDM SMITH		Drill Contractor/Driller: NA	
GPS collected? (Yes) or No		Drill Method: Handauger	Depth Drilled into Bedrock: NA
Radiological Background: γ = 13 αβ = 86		Borehole diameter: 2.25"	
PID Background: 0.0		Depth to GW: NA	Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Mike Hollyon #7735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5	0.0	13/80	SL-566 SA50-SB 0.0-0.5	1230	SP	SAND w/silt, brown (7.5YR 4/2) mottled
	0.5	0.0	13/78			SM	w/ lt brn (7.5YR 6/3) f grained w/ few to some med grn, subrounded to subangular, mod poorly graded, NP, quartz, dry, some
1	HA	0.0	13/84				mod poorly to poorly compacted silty sand material 90% SD 10% SILT, Few amount
						SM	organics (roots) f-4
2		0.0	13/66				SILTY SAND, brown (7.5YR 5/4) mottled w/ lt brn (7.5YR 6/4) & reddish yel (7.5YR 6/6) f-m grn subrounded to subangular, mod poorly graded, NP, few amt mod poorly to poorly compacted silty sand material, 75% SD 20% SILT, 5% CLAY to few amt (roots) 2.5
						SC	
3		0.0	13/60				CLAYEY SAND, yel brn (10YR 5/4) mottled w/ brn yel (10YR 6/6) f grn, mod poorly graded, subrounded, NP, dry, some, mod well to well compacted clayey material
4	1.0/1.0	0.0	13/54				55% SD 30% CLAY 15% SILT dry, more common & more compacted The compacted material becomes dk yel brn (10YR 4/4) and slightly lithified w/depth
5		0.0	13/78				Refusal @ 5.0'

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. SE

Sample ID SL-566-SA5D-SB-4.0-5.0 Date/Time 9-24-13/1315

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND ~~Silty~~ SM10 SC3
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brown 10YR 5/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-567-SA5D-SB-0.0-0.5 Date/Time 10-7-13/ 0950

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-567	Subarea: 5D	Date Started: 10-7-13	Date Completed: 10-7-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st DPT = 4.5 2nd DPT = 3.7 3rd DPT = 3.7
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 cB = 85	Borehole diameter: 3"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Note: Miller Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	12/60 12/78	SL-567 SA5D-S3 0.0-0.5	0950	SM	SILTY SAND, yel brn (10YR 5/4), f gw, poorly graded SUBrounded, quartz, mod well to well compacted, dry tr to few abt organics (roots) 70% SD, 30% SILT SM10411
1	HA	0.0	12/66				
2		0.0	12/102			SM	SILTY SAND, brn (10YR 4/3) mottled w/ dk brn (10YR 3/3) and lt yel brn (10YR 6/4) f gw w/ tr amt med & coarse gw, sr, quartz, dry, 80% SD 20% SILT 1.8
3		6.0	12/72			SM	tr amt org (roots), mod well compacted 2.6 SILTY SAND, strong brn (7.5YR 5/6) mottled w/ brn (7.5YR 4/4), f gw, sr, poorly graded quartz, dry, sli compacted to loose, 70% SD 30% SILT
4	1.0/1.0	0.0 0.0	12/72 12/72	SL-567 SA5D-SB 3.5-4.5	1020	SM	4.0 SILTY SAND, dk yel brn (10YR 4/4) mottled w/ yel brn 10YR 5/6, f-m gw w/ tr to few amt coarse gw, sr to sa, quartz & sdstn; dry 80% SD, 15% SILT 5% GRAVEL; Gravel is sdstn, mod well to well cemented, sa to angular, becoming more common w/ depth, sdstn is lt gray (10YR 7/2) 4.5
5							Refusal @ 4.5'

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	φ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Lafaro

Sample ID SL-567-SA5D-SB-3.5-4.5 **Date/Time** 10-7-13 / 1020

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.5

End Depth 4.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS SLEEVES
2 ENCORES
1 4-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None *
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments * 5% GRAVEL is suspected to be weathered sandstone bedrock

ARR

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GK

Sample ID SL-568-SA5D-SB-0.0-0.5 Date/Time 9-23-13/ 0730

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS SLEEVES
1 4-OZ JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		(SW)	Well-graded SAND w/GRAVEL
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present (Yes) No

2. Percentage Fill (%) 25%

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

(Concrete) Wood Glass

~~Igneous/Metamorphic~~ (Sdstn Gravel) N/A

Other _____

Is Staining Present Yes (No)

Color grayish brown (10YR 5/2)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-568	Subarea: 5D	Date Started: 9-23-13	Date Completed: 9-23-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 3.5, 2nd HA = 3.4
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 αβ = 89	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Handauger/Slidehammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Miller Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	12/80 12/60	SL-568 SA5D-SB 0.0-0.5	0730	SW	SAND w/GRAVEL, grayish brn (2.5YR 5/2) mottled w/ dk gry brn (10YR 4/2), f-mgrn w/ some coarse grn, subrounded to subangular, gritty, dry, Gravel is predominantly sdstn but also some concrete rubble, f-c sized, subangular to angular; 70% SD & 25% GRAVEL tr to few amts organics (roots & twigs) decreasing w/ depth
1	HA	0.0	12/54				5% SILT
2		0.0	12/66				Gravel becomes mostly f sized w/ depth and less common (but remains >15%) — 2.0
				SL-568 SA5D-SB 2.5-3.5 MS	0800	SM	SAND, YellBrn (10YR 6/4), fgrn w/ few-some med grn & tr coarse grn, subrounded to subangular, quartz and Sdstone, dry, 60% SD, 30% SILT, 10% GRAVEL
3		0.0	12/66	SL-568 SA5D-SB 2.5-3.5	0810		GRAVEL is predominantly sdstn, f sized w/ tr med & coarse sized sa, tr amt concrete gravel. — 3.5
							Refusal @ 3.5' bls

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-568-SA5D-SB-2.5-3.5 MS **Date/Time** 9-23-13 / 0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

6 SS Sleeves, 6 Encores, 1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 10

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

(Concrete) Wood Glass

~~Igneous/Metamorphic~~ Sdstn Gravel N/A

Other _____

Is Staining Present Yes (No)

Color Ltyel brn (10YR 6/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-868-SA5D-SB-2.5-3.5 **Date/Time** 9-23-13/0810

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-568-SA5D-SB-2.5-3.5 MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves, 2 Encores, 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 10
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
(Concrete)	Wood	Glass
~~Igneous/Metamorphic~~	(Sdstn Gravel)	N/A
Other _____		

Is Staining Present Yes (No)

Color lt yel brn (10YR 6/4)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong
2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C.

Sample ID SL-569-SA5D-SB-0.0-0.5 **Date/Time** 9-25-13 / 10:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X V.C.
	Pesticides	EPA 8081	X 9/25/13

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves, 1 4-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** NONE

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Olive brown (2.5Y 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments GRAVEL is suspected to be native material

NA – Not Applicable

Location ID: DG-569	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st HA = 2.1, 2nd HA = 2.3
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 13 αβ = 86	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Reviewer & No.: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	13/100	SL-569 SA5D-SB 0.0-0.5	1000	SP-SM	SAND w/ SILT & GRAVEL, lt olive brn (2.5Y 5/3) mottled w/ lt yel brn (2.5Y 6/4), f-m grained, mod poorly sorted, graded, 0.5
		0.0	13/60			SM	Subrounded quartz, dry, 75% SD, 15% GRAVEL 10% SILT GRAVEL is F-m sized, sdstn, subangular to angular, well cemented
1	HA	0.0	13/60			SM/SW/SP	SILTY SAND w/ GRAVEL, yel brn (10YR 5/4) mottled w/ brn (10YR 4/3) f grn w/ Fe-ox aut mod grn, poorly sorted, graded quartz, dry, 70% SD, 20% SILT, 10% GRAVEL becoming siltier w/ depth → 60% → 30% GRAVEL is AA except Fe-ox coarse-sized
2		0.0	13/74				2.3
							Refusal @ 2.3' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-570-SA5D-SB-0.0-0.5 **Date/Time** 10-1-13 / 1010

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameter	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt + GRAVEL
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND + GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 25

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/Metamorphic Gravel) ~5%		N/A
Other Sdstn Gravel ~20%		

Is Staining Present Yes (No)

Color lt yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments Sdstn gravel is suspected to be weathered local material

NA – Not Applicable

Location ID: DG-570	Subarea: 5D	Date Started: 10-1-13	Date Completed: 10-1-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st DPT = 8.4
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		2nd DPT = 8.2
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 3rd DPT = 8.7
Radiological Background: γ = 11 αβ = 67	Borehole diameter: 2.25"		NA
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Reviewed & No: [illegible] #7755		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	11/65 11/66	SL-570 SA5D-SB 0.0-0.5	1010	SM	~~SAND & SILT & GRAVEL~~ Silty sand w/ gravel lt yel brn (10YR 6/4), F-m gnd w/ few c gnd, mod poorly ~~graded~~ cemented, subangular to angular, quartz & sdstn, dry. GRAVEL is F-med sized, subangular to angular, sdstn & ignesous; 60% SD 25% GRAVEL 15% SILT, dry, SDSTN gravel is well cemented * in top 0.5'
1	2.5/3.5	0.0	11/48				Silty sand w/ gravel
2		0.0	11/114		1013	SM	~~SAND & SILT & GRAVEL~~, yel brn (10YR 5/4) mottled w/ dk yel brn (10YR 4/4) and strong brown (7.5YR 4/6), F.A except GRAVEL is sdstn & subrounded to subangular w/ few sub angular becoming more angular w/ depth sdstn gravel is becoming less well cemented & sli friable w/ depth, 55% SD 30% GRAVEL, 15% SILT Zone w/ $CaCO_3$ deposit @ 5.5' 1.6
3		0.0	11/48				
4		0.0	11/72	SL-570 SA5D-SB 4.0-5.0	1020		
5	3.5/4.0	0.0	11/78				Poor Gravel w/ Silt + sand GRADUAL TRANSITION 6.0
6		0.0	11/66			GP-GM	~~SILTY GRAVEL w/ SAND~~, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/4), GRAVEL is predominantly dk grayish brown (10YR 4/2), F-m sized ~~w/ few sand~~ mostly F-sized, subangular to angular sdstn, mod poorly cemented, mod friable to friable, dry to sli moist, SD is predom F-m gnd, quartz & sdstone, Zones of $CaCO_3$ deposit @ 7.6' bls & 8.4' bls 60% GRAVEL 30% SD, 10% SILT * v dk grayish brn (10YR 3/2)
7		0.0	11/42				
8	0.7/0.7	0.0 0.0	11/54 11/60				Refusal @ 8.7' bls 8.7

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cifuentes

Sample ID SL-570-SA5D-SB-4.0-5.0 **Date/Time** 10-1-13/1020

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analysis
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameters	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16 oz jars, 2 Encores, 1 4oz jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				GP-GM	Poorly graded SAND with silt +GRAVEL SM1D1513
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND +GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No ?
2. **Percentage Fill (%)** ? 30
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
Other Sdstn Gravel		

Is Staining Present Yes (No)

Color yellowish (10YR5/4)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7235

Additional Comments Sdstn gravel is suspected to be weathered local material

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VC GE

Sample ID SL-571-SA5D-SB-0.0-0.5 Date/Time 9-23-13 / 1025

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	X 9/23/13
Perchlorate Confirmation	EPA 6850/6860	X
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves + 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) NONE

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color lt yel brn (10YR 6/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7235

Additional Comments NA

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-571	5D	9-23-13	9-23-13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: 1ST HA = 1.0 2ND HA 2.2
Company Name: CDM SMITH	Drill Contractor/Driller: NA	
GPS collected? (Yes) or No	Drill Method: Hand auger	Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 αβ = 77	Borehole diameter: 2.25	
PID Background: 0.0 ppm	Depth to GW: NA	Sampling Method: Slide Hammer
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: #7735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/89 12/78	SL-571 SA5D-SB 0.0-0.5	1025	SP SM	SAND w/SILT and GRAVEL, lt yel brn (10YR 6/4) mottled w/ yel brn (10YR 5/4) f-m gnd w/some coarse grained, mod poorly graded subrounded to subangular quart and sdstn, dry, tr to few ante org (roots) 60% SD, 15% SILT 25% GRAVEL, GRAVEL is sdstn, f-med sized w/a coarse, subangular to angular 1
1	HA	0.0	12/72			SP SM	
2		0.0	12/60			Silty Sand SD	SD w/SILT and GRAVEL, lt yel brn (2.5Y 6/4) mottled w/ lt olive brn (2.5Y 5/3), f-m gnd, mod poorly sorted, subrounded, quart & sdstn, 55% SD 20% SILT, 25% GRAVEL, GRAVEL is A.A., dry 2.2

Refusal @ 2.2' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Cortes

Sample ID SL-572-SA5D-SB-0.0-0.5 **Date/Time** 9-23-13 / 0945

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color strong brown (7.5YR 4/6)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-572	Subarea: 5D	Date Started: 9-23-13	Date Completed: 9-23-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 2.5 2ND HA = 2.0
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? Yes or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 18 αβ = 99	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Mill Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.9/1.05	0.0	18/115	SL-572-SA5D-SB 0.0-0.5	0945	SP-SM	SILTY SAND w/GRAVEL, strong brown (7.5YR 4/6) mottled w/ (7.5YR 5/6) f grn w/ few med grn, mod poorly graded SM10ISI3 Subrounded to subangular quartz, dry; 70% SD, 20% SILT 10% GRAVEL, GRAVEL is subangular to angular, sdstn well cemented, mostly f sized w/ tr to occ med sized. tr to few amt organics (roots)
1		0.0	18/48				
			18/72				
2						SM	SILTY SAND w/GRAVEL yel brn (10YR 5/6) mottled w/ dk yel brn (10YR 4/4). f grn, mod poorly graded SM10ISI3 Subrounded quartz, dry 60% SD, 25% SILT, 15% GRAVEL, GRAVEL is f-c sized, subrounded to angular, sdstn Well cemented, tr to occ org (roots) 2 2.5
							Refusal @ 2.5' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Vidal

Sample ID SL-573-SA5D-SB-0.0-0.5 **Date/Time** 9-25-13/ 0745

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	~~X~~
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
Semivolatiles	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	
Inorganics	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
Semivolatiles	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Volatiles	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
Inorganics	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotins	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (10YR 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-573	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st HA = 18.3 ~~2nd HA = 8.0~~
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 16 $\alpha\beta$ = 85	Borehole diameter: 8.25		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Millie Gibson #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	16/100 16/84	SL-573 SA5D-SB 0.0-0.5	0745	SM	SILTY SAND, brown (10YR 5/3) f grn, poorly ~~sorted~~ graded, quartz, dry, 80% SD 20% SILT, few org (roots), few amt of poorly compacted sandy silt material decreasing w/ depth
	HA						
1		0.0	16/84			SM	SILTY SAND, dk yel brn (10YR 4/4) f grn, poorly ~~sorted~~ graded, few amt med grn, subrounded, dry becoming slightly moist and siltier w/ depth, 65% → 55% SD, 35 → 45% SILT tr amt sdstone gravel near base of unit, SDSTN gravel is f-med sized, subrounded to subangular, mod well to well cemented, tr amt org (roots) 1.0
2		0.0	16/72				
3		0.0	16/78			SM	SILTY SAND, ~~dk~~ brn (7.5 10YR 5/4) tr to few amt mottled w/ dk yel brn (10YR 4/4) and lt yel brn (10YR 6/4) f grn w/ tr amt med grn, poorly ~~sorted~~ graded, quartz, dry, tr amt org (roots) tr to few amount sli compacted, friable sandy silt material, tr sdstn gravel @ 5.5' bls - mod well cemented, coarse sized, 70% SD 30% SILT Mottling is rare to absent from 5'-10', tr amt @ 10'-10.8', rare to absent from 10.8-13' 3.0
4	1.0/1.0	0.0	16/96	SL-573 SA5D-SB 4.0-5.0	0800		Becoming silter w/ depth ~~SM~~ 70 → 60% SD 30 → 40% SILT
5		0.0	16/84				
	HA						
6		0.0	16/72				
7		0.0	16/96				
8		0.0	16/78				
9		0.0	16/30				
10		0.0	16/78				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID: DG-573	Subarea: 5D	Date Started: 9-25-13	Date Completed: 9-25-13
Project: SSFL		Geologist: David Rojas	Total Depth: 1st HA = 18.8

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							SEE LITHOLOGY ON Page 1
	HA						
11		0.0	16/84				
12		0.0	16/78				
13		0.0	16/90				Gradual transition
						SM	SILTY SAND brn (7.5YR 5/4) mottled w/ strong brown (7.5YR 5/6) f grn, poorly graded SUBROUNDED, quartz, dry, few to some sandy silt material that is poorly compacted, but is friable, tr amt, mod well compacted silty sand material that is present as subrounded to subangular fine gravel-sized material, becoming more common w/ depth, 55% SD 45% SILT — 13
14		0.0	16/96				
15		0.0	16/78				
16		0.0	16/72				
17		0.0	16/78				
18		0.0	16/96				Abrupt transition
						SM	SILTY SAND, brn yel (10YR 6/6) mottled w/ yel brn (10YR 5/4) f grn, poorly graded SUBROUNDED, quartz, dry, tr amt mod well to well compacted silty sand material A.A. — 18
							60% SD 40% SILT — 18.8
							Refusal @ 18.8' bls

CDM Smith

BORING LOG AND SAMPLING RECORD

Page ___ of ___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C

Sample ID SL-573-SA5D-SB-4.0-5.0 Date/Time 9-25-13 / 0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT ~~DPR~~ Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Soil/Water	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color ~~light brn.~~ 7.5 (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J. Cortez

Sample ID SL-57H-SA5D-SB-0.0-0.5 Date/Time 9-23-13/0920

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Biota	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND w/GRAVEL
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) (No) ~~NA~~

2. **Percentage Fill (%)** ~~None~~ 15%

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic	(Sdstn Gravel)	N/A
Other _____		

Is Staining Present Yes (No)

Color yellow brown (10YR 5/4)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature Julia Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-574	Subarea: 5D	Date Started: 9-23-13	Date Completed: 9-23-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1ST HA = 0.5 2ND HA = 0.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand augers		Depth Drilled into Bedrock: NA
Radiological Background: γ = 15 $\alpha\beta$ = 95	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	15/97	SL-574-SA5D-SB-0.0-0.5	0920	SM	SILTY SAND w/GRAVEL, yellowish (10YR 5/4) mottled w/ (10YR 5/6), f-gm w/ tr to f-gm sa mod gm, tr ont coarse, mod poorly graded, subrounded to subangular grains, dry, ~~50~~ 45% SD, 20% SILT 15% GRAVEL. GRAVEL is f-c sized sa to angular Sdstn, well cemented
	0.0		15/84				
	HA 1RR						

0.5

Refusal @ 0.5' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G K

Sample ID SL-575-SA5D-SB-0.0-0.5 Date/Time 10-7-13 / 0830

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None*
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic	(Gravel)	N/A
Other	Sdstn	

Is Staining Present Yes (No)

Color brn (7.5YR 4/3)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Olgerson **PG Registration #** 7735

Additional Comments Gravel is suspected to be weathered from adjacent outcrops

NA – Not Applicable

Location ID: DG-575	Subarea: 5D	Date Started: 10-7-13	Date Completed: 10-7-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st HA = 3.4, 2nd HA = 4.0
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? Yes or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: Y = 16 αβ = 72	Borehole diameter: 3"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slidehammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [illegible] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	17/113	SL-575 SA5D-SB 0.0-0.5	0830	SM	SILTY SAND, brn (7.5YR 4/3) mottled w/ (7.5YR 5/3), f gw w/ few ant med & coarse gw, poorly graded, subrounded quartz & sdstn, dry, 80% SD, 15% SILT, 5% GRAVEL, Gravel is sub angular to subrounded, sdstn, f-m sized, few ant org (roots & grasses)
		0.0	17/138				
1	HA	0.0	17/96			SM	
2		0.0	17/72				SILTY SAND, reddish brown (5YR 5/4), A.A except some silt nodules, mod poorly compacted, tr to ~~few~~ few ant org (roots)
3		0.0	17/114	SL-575 SA5D-SB 2.5-3.5 3.0-4.0	0900	SM	SILTY SAND, strong brn (7.5YR 5/6) mottled w/ brown (7.5YR 5/4) f gw w/ tr ant m & c gw, poorly graded, subrounded quartz; dry; 85% SD, 15% SILT, tr ant sdstn gravel, sr to sa, f-m sized
		0.0	17/102				
4		0.0	17/102				Refusal @ 4.0' bls

0.5

3.0

4.0

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cruz

Sample ID SL-575-SA5D-SB-~~2.5~~ 3.0-4.0 Date/Time 10-7-13 / 0900

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~2.5~~ 3.0

End Depth ~~3.5~~ 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None*
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
~~Igneous/Metamorphic~~ NRR	(Gravel)	N/A
Other sdstn		

Is Staining Present Yes (No)

Color Strong ~~reddish~~ brn (5YR 5/6)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments sdstn suspected to be weathered material from adj outcrops

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GL

Sample ID SL-576-SA5D-SB-0.0-0.5 Date/Time 9-19-13 / 1310

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate *Confirmation*	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and *Trends, Krone et al.*	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (10YR 4/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-576	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 4.4, 2nd HA = 4.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: 8-15 avg = 93	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Reviewer's No: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5	0.0	15/95	SL-576 SA5D-SB 0.0-0.5	1310	SP-SM	SAND w/SILT ~~+ GRAVEL~~ AND, brown (10YR 4/3) f grn w/tr amt med grn, mod well sorted, subrounded quartz, 85% SD 10% SILT, 5% GRAVEL, dry GRAVEL is f-m Φ sized, mod poorly indurated friable sdstn, Few amt org (roots), Few silt nodules -
	0.5	0.0	15/66			SP-SM	0.5
1	HA	0.0	15/84			SP-SM	
2		0.0	15/90			SP-SM	SAND w/SILT, A.A. except yel brn (10YR 5/4) 90% SD 10% SILT, Tr GRAVEL, Few to some sandy silt nodules - friable
3		0.0	15/72			SP-SM	3.0
4		0.0	15 48	SL-576 SA5D-SB ~~2.5-3.5~~ 3.5-4.5	1330	SM	SILTY SAND, dK yel brown (10YR 4/4) mottled w/yel brown (10YR 5/6), F grn w/ Few med grn, mod well to well sorted, subrounded quartz & tr amt sdstn, dry, Few sandy silt nodules, most Friable, some weakly cemented 85% SD 15% SILT, Tr amt org (roots)
		0.0	15 60				4.5

REFUSAL @ 4.5' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	Φ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V-GE

Sample ID SL-576-SA5D-SB-3.5-4.5 Date/Time 9-19-13/1330

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.5

End Depth 4.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 2 Encores

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NA
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-577-SA5D-SB-0.0-0.5 Date/Time 9-19-13 1040

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves / 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt +GRAVEL Sm10Si3
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt +GRAVEL
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk brn (7.5YR 3/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments GRAVEL is weathered natural material

NA – Not Applicable

Location ID: DG-577	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 0.5 2nd HA = 0.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 14 cpm 86	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Not: [signature] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
						SP-SM	
1	0.5/0.5	0.0 0.0	14/99 14/78	SL-577 SA5D-SB 0.0-0.5	1040	SW SM GW GP	SAND w/SILT & GRAVEL, dk brn (7.5YR 3/2) mottled w/brown (7.5YR 4/3) f-m grn w/Few ant coarse grn, poorly graded, sbang to sa, quartz & sdstn, dry; GRAVEL is sdstn, F-C sized sa to angular, more common w/depth, mod well to well indurated, v pale brn (10YR 7/3) 70% SD, 10% SILT, 20% GRAVEL GRAVEL w/SAND, v pale brn (10YR 7/3), well indurated, sdstn, f-c sized, coarse w/depth; 70% GRAVEL, 30% SD decreasing sand w/depth, dry Refusal @ 0.5' bls

0.4
0.5

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G

Sample ID SL-578-SA5D-SB-0.0-0.5 Date/Time 9-19-13/1235

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color grayish brown (10YR 5/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 2735

Additional Comments NA

NA – Not Applicable

Location ID: DG-578	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 2.2, 2.0
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: 8=18 ~~9=79~~	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: [signature] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5	0.0	18/102	SL-578 SA5D-SB 0.0-0.5	1235	SM	SILTY SAND, grayish brown (10YR 5/2), f grn w/ tr amt med grn, well sorted, subrounded quartz, dry, 85% SD, 15% SILT, tr amt CLAY — 0.6
	.05	0.0	18/72				
1	HA	0.0	18/84			SP SM	SAND w/ SILT ~~and GRAVEL~~ light brown (10YR 5/4) f grn w/ few to some med grn, mod well sorted, subrounded quartz & sandstone, tr gravel - sandstone, F-m sized, mod friable, dry; 85% SD, 10% SILT, 5% GRAVEL — 1.4
2		0.0	18/90		SP-SM1353	SP SM	~~GRAVEL~~ SAND w/ SILT & GRAVEL brown 7.5YR 5/4 mottled w/ strong brown (7.5YR 5/6) f-m grn w/ few to some coarse grn, poorly sorted, subrounded to subangular, quartz & sdstn, GRAVEL is sdstn v pale brn (10YR 7/4) F to c sized, mod well to well cemented, some friable 75% SD 15% GRAVEL 10% SILT, dry — 2.2

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J. Cruz

Sample ID SL-579-SA5D-SB-0.0-0.5 MS Date/Time 9-19-13/ 0830

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) ~~(Hand Auger/Slide Hammer)~~ DRR Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	X SM 9/13
Perchlorate Confirmation	EPA 6850/6860	X
pH	EPA 9045 (Soil)	~~X~~ DRR
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	~~X~~ DRR
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Parameters	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

3 SS Sleeve ~~1 2 4 oz jars~~ DRR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-579	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 1.5 2nd HA = 1.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 13 αβ = 60	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer / ~~HA~~ DPR
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	QC Review & No: Mike Hoffman #7735		Geologist: David R Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	13/74	SL-579 SA5D-SB 0.0-0.5 ft	0830	SP-SM	SAND w/ SILT yel brn (10YR 5/4), F gr w/ few ant med gvl, mod well ~~graded~~, subrounded to sa, quart, dry, 90% SD 10% SILT few to some ant org (roots), tr ant sdstn gravel increasing w/ depth to ~5% Gravel sa to angular, well cemented, quartz, dry
	HA	0.0	13/84	SL-579 SA5D-SB 0.0-0.5 Also	0835		
1		0.0	13/84				1.5
							Refusal @ 1.5' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-879-SA5D-SB-0.0-0.5 Date/Time 9-19-13 / 0835

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-579-SA5D-SB-0.0-0.5MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Fraction/Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	X
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Fraction/Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Julia Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-580-SA5D-SB-0.0-0.5 Date/Time 9-19-13/0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Collection Method (circle one): V. Cortez 9/19/13

Check if Composite ☐ DPT (Slide Hammer) ~~(Hand Auger/Slide Hammer)~~ Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David R Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	X SMAA13
Perchlorate Confirmation	EPA 6850/6860	X
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve + 2 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		GW-SM (circled)	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM (circled)	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

5/10/13

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 5
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic (Gravel) N/A

Other Sandstone gravel

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-580	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 1.0 2nd HA = 1.0
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: 3" Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: Y = 17 Φ = 74	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer / HA
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review/& No.: Matt Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0 0.0	17/102 17/78	SL-580-SA5D-SB 0.0-0.5	0800	SP-SM	SAND w/SILT, dk yel brn (10YR 4/4) f-m grn w/some to few coarse grn, poorly graded sr to sa, quartz & sandstone, 85% SD, 10% SILT 5% GRAVEL, dry, Sdstn gravel is lt yel brn (10YR 6/4) sa to angular, few ant org (roots)
1	HA	0.0	17/90			SP-SM	SAND w/SILT & GRAVEL, yel brn (10YR 5/4) f-m grn w/some coarse grn, poorly graded, sr to sa quartz & sdstn, 70% SD 20% GRAVEL, 10% SILT dry, sdstn gravel is A.A, few ant org (roots)
							Refusal @ 1.0' bls

CDM Smith — **BORING LOG AND SAMPLING RECORD** — Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	Φ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-581-SA5D-SB-0.0-0.5 Date/Time 9-19-13/ 0930

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	X
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 2 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DC-581	Subarea: 5D	Date Started: 9-19-13	Date Completed: 9-19-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 3.7 2nd HA = 3.9
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Handauger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 18 αβ = 94	Borehole diameter: 2.25		
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Reviewed: Yes No Mulli Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	18/106	SL-581 SA5D-SB 0.0-0.5	0930	SP-SM	SAND w/ SILT, yel brn (10YR 5/4) f grn w/ tr amt med grn, well sorted, subrounded, quartz dry, 90% SD, 10% SILT, tr amt clay, few amt org (roots), ~~dry~~ decreasing w/ depth
		0.0	18/96				
	HA						
1		0.0	18/72				
2		0.0	18/54				
				SL-581 SA5A-SB 2.5-3.5	0940	SP-SM	SAND w/ SILT strong brown (7.5YR 4/6) w/ trace mottling w/ strong brown (7.5YR 5/8), f grn w/ tr to few amt med grn, well sorted, subrounded quartz, dry 90% SD 10% SILT tr amt clay tr amt organics (roots) becoming less w/ depth 2.5
3		0.0	18/60				
		0.0	18/90				3.9
							REFUSAL @ 3.9' bls Tr amt of sdstn gravel @ 3.8'-3.9' bls, f-med-sized, quartz sdstn, poorly consolidated friable

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-581-SA5D-SB-2.5-3.5 Date/Time 9-19-13/0940

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Other	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve + 2 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown (7.5YR 4/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicki Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By [illegible]

Sample ID SW-582-SA5D-SB-0.0-0.5 Date/Time 9-30-13/0845

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) ~~Slide Hammer~~ SPR Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tissue	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-582	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 10.8 2nd DPT = 11.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: 3rd DPT = 11.3
Radiological Background: γ = 12 β = 91	Borehole diameter: 2.25"		NA
PID Background: 0.0	Depth to GW: NA		Sampling Method: Slickhammer DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Review & No: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0	12/99	SL-582 SA5D-SB 0.0-0.5	0845	SP-SM	SAND w/SILT, yel brn 10YR 5/4, f gr w, mod well sorted, well sorted subrounded quartz, dry, 90% SD 10% SILT, sli to mod compacted w/silty sand matrix, tr to few ant org (roots)
1		0.0	12/72				
2	3.2/3.5	0.0	12/66			SM	SILTY SAND dk yel brn (10YR 3/4) mottled w/ (10YR 4/4) and yel brn (10YR 5/4), f gr w, well sorted, quartz, mod well compacted becoming sli clayey and more compacted w/depth 70% SD, 25% SILT 5% CLAY dry 2.0
3		0.0	12/60			SC	CLAYEY SAND, yel brn (10YR 5/6) mottled w/ lt yel brn (10YR 6/4) and tr amts red (2.5YR 5/8), f gr w, mod well sorted, quartz, mod well to well compacted, clay is low plasticity, soft, crumbly, dry 65% SD, 20% CLAY 15% SILT, burrows & decayed root molds are filled w/ $CaCO_3$ deposits 3.0
4		0.0	12/72	SL-582 SA5D-SB 4.0-5.0MS	0855		
5		0.0	12/96	SL-582 SA5D-SB 4.0-5.0	0900		
6	4.0/4.0	0.0	12/72				GRADUAL TRANSITION
7		0.0	12/84			SC	CLAYEY SAND, strong brown (7.5YR 4/6) mottled w/ yel red (5YR 4/6), f gr w, mod well to well sorted, quartz, dry to sli moist, 55% SD, 25% CLAY 20% SILT, CLAY & SILT are dispersed in SD, unit is mod well to well compacted, CLAY is low plasticity soft, becoming mod low plasticity w/depth, crumbly becoming less crumbly w/depth, tr to few ant laminations, tr ant burrows & decayed root molds some filled w/ $CaCO_3$ deposits 6.0
8		0.0	12/90				
9	3.8/3.8	0.0	12/90				
10		0.0	12/96				Refusal @ 11.3' bls
10.3		0.0	12/84	SL-582 SA5D-SB 9.0-10.0	0910		11.3

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GA

Sample ID SL-582-SA5D-SB-4.0-5.0MS **Date/Time** 9-30-13/ 0855

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Noah Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

16 oz jars
to ~~SS Sleeves~~, & to Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brown (10YR5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.A

Sample ID SL-882-SA5D-SB-4.0-5.0 **Date/Time** 9-30-13/0900

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-582-SA5D-SB-4.0-5.0MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	

Parameter	Method	Analysis?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16oz jars & 2 Encores

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yellowish brown (10YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7135

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Stef Mypel

Sample ID SL-582-SA5D-SB-10.0-11.0 Date/Time 9-30-13/0910

Matrix (circle one): (Soil) Sediment Water

Start Depth 10.0

End Depth 11.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
		EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
		EPA 300.0/9056	
		EPA 8270	
		EPA 8270	
		EPA 8270 SIM	X
		EPA 8270 SIM	
		EPA 1613	
		EPA 8082	X
		EPA 314.0/331	
		EPA 6850/6860	
		EPA 9045 (Soil)	X
		EPA 9040 (Water)	
		EPA 7196/7199	
		EPA 8151	X
		EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 16oz jars & 2 Encores

SSFL Phase 3 – Field Data Sample Sheet (Sample Des ations)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAM
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GR
				GP	Poorly graded GF
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVI
				GW-GC	Well-graded GRAVE
				GP-GM	Poorly graded GRAVI
				GP-GC	Poorly graded GRAVI
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVE
				GC	Clayey GRAV
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded S
				SP	Poorly graded S
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND
				SW-SC	Well-graded SAND
				SP-SM	Poorly graded SAN
				SP-SC	Poorly graded SAN
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC (circled)	Clayey SAN
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT wit
				CL	Lean inorganic CLAY wit ticity
				OL	Organic SILT with
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with mod high plas
				CH	Fat inorganic CLAY with mod s plas
				OH	Organic SILT or CLAY with mo high pl
HIGHLY ORGANIC SOILS				PT	PEAT soils with high org ents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Strong brown (7.5YR 4/6)

Odor

1. **Odor Strength** (circle o) (None) Sli t ong
2. **Odor Descri tio (circl ne)** Organic Petroleum omi (N/A) Other

Moisture Condition (circ ne) (Dry) Mo t

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GF

Sample ID SL-583-SA5D-SB-0.0-0.5 **Date/Time** 9-23-13/1240

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color yel brn 10YR5/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-583	Subarea: 5D	Date Started: 9-23-13	Date Completed: 9-23-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st HA = 2.4, 2nd HA = 2.5
Company Name: CDM SMITH	Drill Contractor/Driller: NA		
GPS collected? (Yes) or No	Drill Method: Hand Auger		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 $\alpha\beta$ = 74	Borehole diameter: 2.25		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	12/80 12/78	SL-583 SA5D-SB 0.0-0.5	1240	SM	SILTY SAND, yel brn (10YR 5/4) mottled w/ dk yel brn (10YR 4/4), f-grn w/ some med grn & few coarse grn, mod poorly graded, subrounded to subangular quartz & some sandstone; 75% SD, 20% SILT 5% GRAVEL, Gravel is sdstn, F-m sized, sa to angular, well cemented, dry — 1
1	HA	0.0	12/78			SM	
2		0.0	12/78			SM	SILTY SAND w/ GRAVEL dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/6) and brn yel (10YR 6/6), f-m grn w/ some coarse grn, mod poorly graded, subrounded to subangular quartz & sdstn 60% SD, 20% silt 20% GRAVEL, Gravel is f-c sized, sdstn, well cemented, sa to angular; dry — 2
		0.0	12/78				SILTY SAND w/ GRAVEL brn yel (10YR 5/6) f-grn w/ some med-coarse grn, S rounded to subangular quartz & sdstn, dry 60% SD, 20% SILT 20% GRAVEL, Gravel is A.A. — 2.5
							Refusal @ 2.5' bls

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-589-SA5D-SB-0.0-0.5 **Date/Time** 10-2-13 / 1030

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyses
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Parameters	Method	Analyses
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves + 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color DK. YEL. BRN (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-589	Subarea: 5D	Date Started: 10-2-13	Date Completed: 10-2-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 27.0 2ND DPT = 26.8
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{X}$ = 13 σ = 76	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [signature] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 0.0	13/87 13/90	SL-589 SA5D-SB 0.0-0.5	1030	SM	SILTY SAND, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/4) and strong brn (7.5YR 5/6) f gm, poorly graded, quart dry, mod compacted, dry, 70% SD 30% SILT tr ant clay increasing to 10% CLAY w/ depth
1		0.0	13/72				
2	2.8/3.5	0.0	13/66				
3		0.0	13/108				
							GRADUAL TRANSITION 3.4
4		0.0	13/78	SL-589 SA5D-SB 4.0-5.0	1040	SC	CLAYEY SAND, dk brn (10YR 3/3) mottled w/ dk yel brn (10YR 4/4) and strong brn (7.5YR 5/6) f gm, poorly graded, quart, dry, clay is dissimentated in SD. 55% SD 30% CLAY 15% SILT. clay is low plasticity Firm to hard, crumbly
6	3.8/4.0	0.0	13/66				
							GRADUAL TRANSITION 5.4
6		0.0	13/48			CL	SANDY CLAY brn (7.5YR 4/4) mottled w/ strong brown (7.5YR 5/6) & lt yel brn (2.5Y 6/3), F-m gm predominently f gm, quartz, CLAY is, low plasticity hard, Friable, 60% CLAY 30% SD 10% SILT (SD is)
7		0.0	13/48				
8		0.0	13/66				
							GRADUAL TRANSITION 8.6
9	4.0/4.0		102		1050	CL	SANDY CLAY yel brn (10YR 5/8) mottled w/ dk yel brn (10YR 4/4) & brn (7.5YR 4/4), mod low plasticity, moderately crumbly, Firm to sli soft, tr ant mottly w/ yel red (5YR 5/8) From 11-13'
10			78				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 3

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-589	Subarea: 5D	Date Started: 10-2-13	Date Completed:
Project: SSFL		Geologist: David Rojas	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							~~SILTY~~ CLAY ~~SILTY~~ SANDY see pg 1
11	see Pg 1	0.0	13/90				
12		0.0	13/114			SC	GRADUAL TRANSITION ~~SANDY~~ CLAYEY SAND, dk yel brn (10YR 4/6) mottled w/ yel brn (10YR 5/8), fgrn, ~~poorly sorted~~, graded quart, clay is disturbed in sp CLAY is mod low plasticity, mod soft to sli firm, dry to sli. moist, 60% SD 30% CLAY 10% SILT SM10YR3
13	4.0/4.0	0.0	18/66				
14		0.0	18/84	SL-589 SASD-SB 14.0/15.0	1100		
15		0.0	18/66				11.6
16		0.0	18/72			SC	CLAYEY SAND strong brn (7.5YR 5/6) mottled w/ brn (7.5YR 4/4) and yel red (5YR 4/6), A.A.
17	3.5/4.0	0.0	18/84				
18		0.0	18/96				
19		0.0	18/84	SL-589 SA-SD-SB 19.0/20.0	1110		
20		0.0	18/72				
21	4.0/4.0	0.0	13/84			CL	Clay w/ sand SM10YR3 ~~SANDY CLAY~~ strong brn (7.5YR 4/6) mottled w/ dk yel brn (10YR 4/4) & yel red 5YR 4/6, mod low plasticity firm to sli soft, dry to sli moist 30% CLAY 25% SD 15% SILT 20.3

Location ID: DG-589	Subarea: 5D	Date Started: 10-2-13	Date Completed: 10-2-13
Project: SSFL		Geologist: David Rojas	Total Depth: 27.0'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							~~SANDY CLAY~~ SM10/4/13 A.A Clay w/ sand
22		0.0	13/42				
23	See pg 2	0.0	13/54				
24		0.0	13/78				
25	3.0/3.0	0.0	13/78				
26		0.0	13/96				26.0
27		0.0	13/66			SP	SAND, brn yel (10YR 4/6) mottled w/ pale brn (10YR 4/3) F-m gr, mod poorly ~~sorted~~ graded sr to sa, granule, dry SM10/4/13
							Refusal @ 27.0' bls

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID:	Subarea:	Date Started:	Date Completed:
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller:		
GPS collected? Yes or No	Drill Method:		Depth Drilled into Bedrock:
Radiological Background:	Borehole diameter:		
PID Background:	Depth to GW:		Sampling Method:
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:		Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By [signature]

Sample ID SC-SB9-SASD-SB-4.0-5.0 **Date/Time** 10.2.13 / 1040

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist DAVID ROJAS

Sampler VIDAL CORTES

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	X

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16-OZ JARS & 2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) Ø

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK BRN. (10 YR 3/3)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nate Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-590-SA5D-SB-0.0-0.5 **Date/Time** 9/6/13 @ 1150

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BRADLEY

Sampler VCortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	~~X~~
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Ecotox	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediments	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-SS Sleeve
1-40z VAA

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Yellow Brown (10YR 5/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG590	SD	9/6/13	9/6/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 12.0 / 11.8 / 11.7
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/Rodriguez	
GPS collected? (Yes) or No LGCW 9/6/13	Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: α = 13 / β = 84.6	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: NA	Sampling Method: Macro Core
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No: Mike Gibson #7735	Geologist: BRADLEY/K

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1	3.5/4.0	0.0	13/95	SL590-SA5D-SB-0.0- 0.5	11:50	ML	SILT - DK YELLOWISH BROWN (10YR 5/6) 80% SILT, SOFT, NON-PLASTIC, DRY, 20% CLAY NO ODOR
		0.0	13/60				
		0.0	66				
2		0.0	78			CL	CLAY - DK YELLOWISH BRN (10YR 5/6) 90% CLAY, HARD, NON-PLASTIC, DRY, 10% Gravel, FN, Rounded PG, INTER BEDDED SAND STONE, FN, PG, CT. RED HIGHLY WEATHERED
3		0.0	66				
4		0.0	13/72	SL590-SA5D-SB-4.0- 5.0MS	12:00		
5		0.0	13/90	SL890-SA5D-SB-4.0- 5.0	12:14		
6	3.5/4.0	0.0	13/90				
7		0.0	13/90				GRADITIONAL CONTACT
8		0.0	13/72			CL	CLAY - BROWNISH YELLOW (10YR 6/6) 100% CLAY, HARD NON PLASTIC DRY
9	4.0/4.0	0.0	13/60				
10		0.0	13/66				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
DG 590	SD	9/6/13	9/6/13
Project: SSFL		**Geologist:**	**Total Depth:** 12.0

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cm)	Sample Name	Sample Time	USCS	Description of Materials
						CL	CLAY - BROWNISH YELLOW (10YR 6/6) 100% CLAY, HARD NON PLASTIC DRY
11		0.0	13/12	DG590 SB50-11.0-12.0	12:20	ML	SANDY SILT - V PALE BROWN (10YR 7/4). 70% SILT, SOFT, DRY; SAND 30%, F, MD, LOOSE; NO ODOR
12		0.0	13/90				REFUSAL AT 12 FT

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 2 of 2

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-590-SA50-SB-4.0-5.0 MS **Date/Time** 9/6/13 @ 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYIC

Sampler VCortez

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Specialty	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

3-16 of 2 Jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK YELLOW BRN (10YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-890-~~SSD~~ SASD -SB-4.0-5.0 (KW 9/6/13) **Date/Time** 9/6/13 @ 1210

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID SL890-~~SSD~~ SASD -SB-4.0-5.0 MS (KW 9/6/13)

Field Geologist B Knapczyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	X
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil/Water	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Solid	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color DK Yellowish Brown 10YR 5/6

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By [signature]

Sample ID SL-590-SASD-SB-11.0-12.0 Date/Time 9/6/13 12:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 11.0

End Depth 12.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist [illegible]

Sampler ✓ Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	X
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Pale Brown (10YR 7/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.E

Sample ID SC-591-SASD-SB-0.0-05 Date/Time 9/12/13 1295

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kaspzyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil/Water	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 – 55 Gleeve

1 – 4oz Jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 10 yr 5/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DB 591	5D	9/12/13	9/12/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 7.1, 7.4, 7.4
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: 3.4 FT
Radiological Background: 9:13/16-90	Borehole diameter: 2.25	
PID Background: 0.0 ppm	Depth to GW: N/A	Sampling Method: Macro Core
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: RACHEVIC

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/103	SL591-SA5D-SB-0.0-0.5	1235	CL	~~CLAY SILT~~ 9/12/13
1	4.0	0.0	12/72			ML CL	CLAY - BROWN 10YR 5/3, 80% CLAY, HARD, NON-PLASTIC, DRY 20% SILT, NO ODOR
2	4.0	0.0	13/84				
3		0.0	13/84				
4		0.0	13/84				SILTSTONE - V PALE BROWN 10YR 7/4 FISSILE, HIGHLY WEATHERED, DRY
5		0.0	14/84			MU	
6		0.0	12/72				
7		0.0	13/90	SL591-SA5D-SB-6.5-7.5	1240		REFUSAL AT 7.4 FT ON BEDROCK

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.S.

Sample ID SC-591-SASD-SB-65-7.5 **Date/Time** 9/12/13 12:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.5

End Depth 7.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kaesbah

Sampler J Cortez

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1-1602 Jan

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 7/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SC-592-SA5D-SB-0.0-0.5 Date/Time 9-12-13 @ 12:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG592	5D	9/12/13	9/12/13

Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489	Total Depth: 11.4, 11.2, 11.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 1 FT
Radiological Background: γ = 13 kBq 1	Borehole diameter: 2.25 INCH	
PID Background: 2.0	Depth to GW: NA	Sampling Method: Macro Core
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Mulla Hoffman #7735	Geologist: KASPER/K

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13/63	SL592-SA-5D-SB-0.0-0.5	12:00	CL	CLAY – DK BROWN (10YR 3/3) 80% CLAY, SOFT NON PLASTIC, SEMI MOIST, 20 SILT, NO ODORS.
1		0.0	13/54				
2	4.0/4.0	0.0	13/54				
3		0.0	13/78				
4		0.0	13/54	SL592-SA5D-SA-4.0-5.0	12:05	CL	SAND/CLAY – YELLOWISH BROWN 10YR 5/6; FIRM, NON PLASTIC CLAY 70%; 30% SAND, F-MG, SEMI MOIST NO ODOR
5		0.0	13 54				
6	4.0/4.0	0.0	13/60				– TRACE CLAYSTONE
7		0.0	14/72				
8		0.0	13/66			CL	AS ABOVE W/ COLOR CHANGE TO BROWN 10YR 5/3
9	4		66				
10			66				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	Φ: diameter

Location ID: DG 592	Subarea: SD	Date Started: 9/11/13	Date Completed: 9/12/13
Project: SSFL		Geologist: [illegible]	Total Depth: 11.4

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	4.0 / 4.0			DG592-SASD-SB10.5-11.5	12:10	CL	SANDY CLAY - BROWN (10YR 5/3), CLAY 60%, SOFT, NON PLASTIC SEMI MOIST; 40% SAND, F, PG, NO ODOR
11		00	13/84			ML	SILTSTONE - V PALE BROWN (10YR 8/4) DRY. HIGHLY WEATHERED
		00	13/72				
		~~0.0~~	~~13/72~~				REFUSAL AT 11.4 FT ON ROCK
12							

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.CK

Sample ID 4592-SA5D-4.0-5.0 Date/Time 9/12/13 12:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V CONTCG

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Radiochemistry	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Yellowish Brown 10YR 5/6

Odor

1. Odor Strength (circle one)

None Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cf

Sample ID SL592-SA5D-SB-10.5-16.5 Date/Time 9/12/13 12:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 10.5

End Depth 16.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist A Kasprzyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
Glycols	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
Other	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Biological	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color ✓ Pale Brown 8/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Skyler Mupel

Sample ID SL-593-SA5D-SB-0.0-0.5 Date/Time 10-7-13 / 1240

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve # / 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color ypl brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-593	Subarea: 5D	Date Started: 10-7-13	Date Completed: 10-7-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st NA = 4.5' 2nd NA = 4.0
Company Name: CDM SMITH		Drill Contractor/Driller: NA	
GPS collected? (Yes) or No		Drill Method: Handauger	Depth Drilled into Bedrock: NA
Radiological Background: γ = 16 αβ = 88		Borehole diameter: 3"	
PID Background: 0.0 ppm		Depth to GW: NA	Sampling Method: Slide Hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Julie Hoffman #7735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0 / 0.0	16/91 / 16/98	SL-593 SA5D-SB 0.0-0.5	1240	SM	SILTY SAND, yel brn (10YR 5/4), f grn, poorly graded, subrd quartz, dry, tr amt org (roots); 70% SD, 30% SILT mod well compacted, silt is disseminated in SD SM101413
1	NA	0.0	16/90			SM	SILTY SAND, yel brn (10YR 5/6) mottled w/ brn yel (10YR 6/6), f grn, poorly graded, subrd quartz, dry; 65% SD 35% SILT, tr amt org (roots) sli to mod compacted Silt is disseminated in SD SM101413
2		0.0	16/102				
3		0.0	16/96			SM	SILTY SAND, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/6) and lt gel brn (10YR 6/4), f-m grn mod poorly graded, subrd quartz & sdstn; dry SM101413 75% SD 25% SILT
						SC	CLAYEY SAND, lt olive brn (2.5Y 5/3) mottled w/ lt yel brn (2.5Y 6/4) and olive brn (2.5Y 4/4) f grn w/ tr amt med grn, poorly graded, subrd quartz, dry, CLAY is disseminated in SD Clay is low plasticity and present as lenses SM101413 65% SD, 25% CLAY 10% SILT firm to hard, crumbly,
4		0.0	16/60	SL-593 SA5D-SB 4.0-5.0 DRG	1300	SM	SILTY SAND, same as 2.4-3.2 except f w/ tr amt mod well cemented sdstn gravel from 4.3-4.5 bgs f-m sized, pale brn (2.5Y 7/4) mottled w/ yellow (2.5Y 7/6) & brn yel (10YR 6/8) becoming better cemented and more common w/ depth
5	NA	0.0	16/72	3.5-4.5			Refusal @ 4.5

0.8 2.4 3.2 3.8 4.3 X DRG

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Sky Mupel

Sample ID SL-593-SA5D-SB-~~4.0~~ 3.5-4.5 Date/Time 10-7-13/ 1300

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~4.0~~ 3.5

End Depth ~~5.0~~ 4.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Olive brn (2.5Y 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-594-SA5D-SB-0.0-0.5 **Date/Time** 10-2-13 / 0940

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** None

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Willis Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-594	Subarea: 5D	Date Started: 10-2-13	Date Completed: 10-2-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT-8.0 2nd DPT = 7.7 3rd DPT = 7.7
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: χ = 12 AB = 74	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Nikki Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0 0.0	12/95 12/78	SL-594 SA5D-SB 0.0-0.5	0940	SM	SILTY SAND yel brn (10YR 5/4) F gr, poorly graded, quartz dry, mod well compacted, tr ort org (roots) 70% SD 30% SILT tr ort clay, becomes only sli compacted w/ depth
1	2.2/3.5	0.0	12/72				
2		0.0	12/84				
3		0.0	12/90			SC	CLAYEY SAND brn (7.5YR 4/4) F gr, poorly graded, quartz dry, sli to mod compacted, Clay is disseminated in SD 70% SD 20% CLAY 10% SILT
4		0.0	12/78	SL-594 SA5D-SB 4.0-5.0	0950		
5	4.0/4.0	0.0	12/66			CL	Clay w/ sand → strong brn (7.5YR 4/6) mottled w/ (7.5YR 5/6) & (10YR 5/4) yel brn SANDY CLAY low plasticity, Firm to hard mod crumbly, dry to sli moist, becomes sandier w/ depth 55% CLAY 20% SD 25% SILT → 55% CLAY 40% SD 5% SILT
6		0.0	12/66/78			SP-SC	Abrupt Contact SAND, brn yel (10YR 5/6) mottled w/ yel brn (10YR 5/4) F gr, poorly graded, quartz, dry to sli moist, 90% SD 10% CLAY, Clay is present as lenses @ 6.5' & 7.2' bls, Clay is mod low plasticity but same color as 4.8-6.0' bls
7		0.0	12/66/78	SL-594 SA5D-SB 7.0-8.0	0955		
8		0.0	12/60				Refusal @ 8.0' bls

graded SP 10/14/13 — 3.0 — graded SC 10/14/13 — 4.8 — 6.0

CDM Smith — **BORING LOG AND SAMPLING RECORD** — Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.E

Sample ID SL-594-SA5D-SB-4.0-5.0 Date/Time 10-2-13/0950

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brn (7.5YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nila Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.S.T

Sample ID SL-594-SA5D-SB-7.0-8.0 Date/Time 10-2-13/0955

Matrix (circle one): (Soil) Sediment Water

Start Depth 7.0

End Depth 8.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

SP SM 0413

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): None

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other: _____		

Is Staining Present Yes (No)

Color brn yel (10YR 6/6)

Odor

1. Odor Strength (circle one): (None) Slight Strong

2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other: _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mila Bellefroon **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VLS

Sample ID SL-595-SA5D-SB-0.0-0.5 Date/Time 9-30-13/0950

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nathan Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-595	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 17.6 2nd DPT = 17.6 3rd DPT 17.5
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{X}$ = 12 σ = 79	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Nikki Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5 / 0.5	0.0 0.0	12/85 12/66	SL-595 SA5D-SB 0.0-0.5	0950	SM	SILTY SAND, yel brn (10YR 5/4) mottled w/ lt yel brn (10YR 6/4) F grn, mod well to well sorted, subrd, dry, mod well to well compacted, tr to Few dist organics (roots) some mod decayed and filled w/ $CaCO_3$ deposits, tr to Few ant laminations becoming more prevalent w/ depth, 70% SD, 20% SILT, 10% CLAY
1	2.8 / 3.5	0.0	12/60				
2		0.0	12/72			SC	CLAYEY SAND, brn (7.5YR 5/4) mottled w/ (7.5YR 4/3) F grn, well sorted, subrd, dry, well compacted, Clay is dispersed in SD, low plasticity, firm to mod hard 55% SD, 35% CLAY 10% SILT, tr ant org (roots) mod well laminated, Few root & burrow molds Filled w/ $CaCO_3$ deposits 1.6
3		0.0	12/78			CL	GRADUAL TRANSITION 3.0
4		0.0	12/90	SL-595 SA5D-SB 4.0-5.0	1000		CLAY w/ SAND, dk brn (7.5YR 3/4) mottled w/ strong brn (7.5YR 4/6) and brn (7.5YR 5/4), hard, low plasticity, crumbly tr to Few ant rootlets molds & burrows filled w/ $CaCO_3$ deposits 75% CLAY, 15% SD, 10% SILT, dry, slightly laminated less laminated and siltier w/ depth
5	4.0 / 4.0	0.0	12/60				
6		0.0	12/78			CL	GRADUAL TRANSITION 6.0
7		0.0	12/66				CLAY ~~w/ SAND~~, strong brown (7.5YR 4/6) mottled w/ brown (7.5YR 4/4) and lt brn (7.5YR 6/3), some mottles w/ strong brown (7.5YR 5/8) w/ depth, A.A except less laminated & siltier 75% CLAY, 15% SILT 10% SD
8		0.0	12/72				
9	4.0 / 4.0	0.0	12/60	SL-595 SA5D-SB 9.0-10.0	1010	CL	GRADUAL TRANSITION 9.0
10		0.0	12/90				CLAY ~~w/ SAND~~ dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/8), hard to firm, mod low plasticity, moderately crumbly, 80% CLAY, 15% SILT, 5% SD, dry becoming slightly moist w/ depth

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-595	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Project: SSFL		Geologist: David Rojas	Total Depth: 17.7

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							CLAY A.A see Pg 1
11	See Pg 1	0.0	12/78				
12		0.0	12/72				
13		0.0	12/66				
14	3.6/4.0	0.0	12/72	SL-595 SA5D-SB 14.0-15.0	1020		
15		0.0	12/84				
16		0.0	12/72				
17	1.6/1.7	0.0	12/60	SL-595 SA5D-SB 17.0-18.0	1030	SC	CLAYEY SAND, yel brn (10YR 5/4) mottled w/ pale brn (10YR 6/3), f grn, well sorted, fract clay is disminated in SD, clay is mod low plasticity, mod soft to firm, sli crumbly, dry to sli moist. — 16.3
17.0-18.0		0.0	12/66	~~ORR~~			— 17.7
18							REFUSAL @ 17.7'

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.R.S

Sample ID SL-595-SA5D-SB-4.0-5.0 **Date/Time** 9-30-13/1000

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk brn (7.5YR 3/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.K

Sample ID SL-595-SA5D-SB-9.0-10.0 Date/Time 9-30-13 / 1010

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.B

Sample ID SL-595-SA5D-SB-14.0-15.0 Date/Time 9-30-13/1020

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J.C.V.

Sample ID SL-595-SA5D-SB-17.0-18.0 Date/Time 9-30-13/1030

Matrix (circle one): (Soil) Sediment Water

Start Depth 17.0

End Depth 18.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Y. Cortez

Sample ID SW-596-SA50-SB-00-0.5 **Date/Time** 9-30-13/1235

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brn (7.5YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-596	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 12.4 2nd DPT = 12.5 3rd DPT = 12.5
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 α/β = 83	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [signature] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0	0.5/0.5	0.0	12/102 12/60	SL-596 SA5D-SB 0.0-0.5	1235	SC	CLAYEY SAND, brn (7.5YR 4/4) mottled w/ strong brown 7.5YR 4/6, F gr, well sorted, quartz, dry, clay is disseminated in sd. low plasticity, crumbly, Firm to sli soft 60% SD 30% CLAY 10% SILT, tr to few org (roots)
1	3.0/3.5	0.0	12/66			CL	SANDY CLAY, dk brn (7.5YR 3/4) mottled w/ brn 7.5YR 4/4 and strong brn (7.5YR 4/6), low plasticity, Firm to hard, dry, tr to Fa ant org (roots), Few to some root molds & burrows filled w/ $CaCO_3$ deposits sli to mod laminated, mod well to well compacted
2		0.0	12/66				
3		0.0	12/60				
4		0.0	12/72				Abrupt Contact
4		0.0		SL-596 SA5D-SB 4.0-5.0	1245	CL	CLAY, strong brown (7.5YR 4/6) mottled w/ strong brown (7.5YR 4/6), del brn (10YR 5/6) and brn yel (10YR 6/8) low plasticity, Firm to hard, crumbly, sli to mod silty 70% CLAY 20% SILT 10% SD, sli to mod laminated, becoming more laminated and less silty w/ depth, tr ant org (roots) mod well compacted
5	4.0/4.0	0.0	12/66				
6		0.0	12/90				
7		0.0	12/72				
8		0.0	12/90				
9	4.0/4.0	0.0	12/60				GRADUAL CONTACT
9		0.0	12/72			CL	CLAY, yel brn (10YR 5/4) mottled w/ (10YR 5/8) and dk grayish brown (2.5Y 4/2), Firm, mod low plasticity, moderately crumbly, dry to sli moist, tr ant org (roots) 80% CLAY, 15% SILT, 5% SD, mod well compacted

No Sample

0.5

4.0

9.0

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DC-596	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Project: SSFL		Geologist: David Rojas	Total Depth: 12.5

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							CLAY - See Pg 1
11	See Pg 1	0.0	12/78				CLAY WITH SAND
							~~SAND~~ Abrupt Contact 11.5
				SL-596 SA5D-SB 11.5-12.5	1255	CL	~~SANDY CLAY~~, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/4) and lt yel brn (10YR 6/4), hard, low plasticity, well compacted, SD is disseminated in clay, ~~65~~ 75% CLAY, 30% SD, ~~5~~ 10% SILT, dry
12		0.0	12/72				
		0.0	12/72				12.5
							Refusal @ 12.5' bs

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-596-SA5D-SB-4.0-5.0 Date/Time 9-30-13 / 1245

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Target	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Target	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Suspect	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 ~~8~~ oz jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Brown 7.5YR (4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-596-SA5D-SB-11.5-12.5 **Date/Time** 9-30-13/ 1255

Matrix (circle one): (Soil) Sediment Water

Start Depth 11.5

End Depth 12.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 ~~402~~ 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity w/SAND
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-597-SA5D-SB-0.0-0.5 **Date/Time** 9-30-13/ 1340

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Lab Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Lab Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brn (7.5YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-597	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 17.6 2nd DPT = 18.0 ~~3rd DPT~~
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: γ=12 $\alpha\beta$=75	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/63	SL-597 SASD-SB 0.0-0.5	1340	SC	CLAYEY SAND brn (7.5YR 4/4) mottled w/ strong brn (7.5YR 4/6) F grn, well sorted, round, dry, clay is dissemnated in sd, low plasticity, crumbly, firm to sli soft
		0.0	12/60				
1	3.5/3.5	0.0	12/60			CL	60% SD, 25% CLAY, 15% SILT GRADUAL CONTACT 1.0
2		0.0	12/54			CL	SANDY CLAY, yel brn (10YR 5/4) mottled w/ (10YR 5/6) & (10YR 5/8), low plasticity, mod well to well ~~consolidated~~ compacted, sli to mod laminated SD is dissemnated in clay, 60% CLAY, 30% SD 10% SILT, becomes siltier w/ depth, dry
3		0.0	12/66			CL	~~SILTY~~ CLAY, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/4), low plasticity, firm to hard, well compacted, sli to moderately laminated, 60% CLAY 30% SILT, 10% SD, dry ABRUPT CONTACT 2.7
4		0.0	12/78	SL-597 SASD-SB 4.0-5.0	1356		
5	3.7/4.0	0.6	12/66				
6		0.0	12/78				
7		0.0	12/84				
8		0.0	12/72				
9			84	SL-597 SASD-SB 9.0-10.0	1400	CL	~~SANDY~~ W/SAND CLAY yel brn (10YR 5/4) mottled w/ (10YR 5/6) and (10YR 5/8), hard, low plasticity, well compacted sli laminated, dry to sli moist 70% CLAY 20% SD 10% SILT 8.5
10			90				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-597	Subarea: 5D	Date Started: 9-30-13	Date Completed: 9-30-13
Project: SSFL		Geologist: David Rojas	Total Depth: 18.0

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11		0.0	12/78			CL	CLAY, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/6), hard, mod low plasticity mod crumbly dry to sli moist, 80% CLAY 15% SILT, 5% SD tr amt mottles w/ brn yellow (10YR 6/8)
12		0.0	12/72				12
13	4.0/4.0	0.0	12/60			CL	SANDY CLAY, lt yel brn (10YR 6/4) mottled w/ brn yel (10YR 6/6) & tr amt strong brown (7.5YR 5/8) low plasticity, firm, crumbly, dry to sli moist 65% CLAY, 30% SD, 5% SILT, becoming silty w/ depth
14		0.0	12/84	SL-597 SA5D-SB 14.0-15.0	1410	CL	13.6 CLAY w/ SAND, yel brn (10YR 5/4) mottled w/ (10YR 5/6) and lt yel brn (10YR 6/4), low plasticity, mod firm to sli soft, crumbly, dry, mod well laminated becoming more laminated w/ depth to 16.5 then sli laminated from 16.5 to 18.0 ~~80~~ 70% CLAY, 10% SILT, 20% SD
15		0.0	12/90				
16		0.0	12/108				
17		0.0	12/72	SL-597 SA5D-SB 17.0-18.0	1410 1415		
18		0.0	12/72				18.0 Refusal @ 18.0' bls

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. C/E

Sample ID SL-597-SA5D-SB-4.0-5.0 **Date/Time** 9-30-13 / 1350

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-597-SA5D-SB-9.0-10.0 **Date/Time** 9-30-13 / 1400

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist DAVID ROJAS

Sampler VIDAL CORTES

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.T

Sample ID SL-597-SA5D-SB-14.0-15.0 Date/Time 9-30-13/1410

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nikki Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.GA

Sample ID SL-597-SA5D-8B-~~16.5~~ 17.0 - 18.0 Date/Time 9-30-13/ ~~1400~~ 1415

Matrix (circle one): (Soil) Sediment Water

Start Depth ~~16.5~~ 17.0

End Depth ~~17.5~~ 18.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analysis
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gf

Sample ID SL-598-SA5D-SB-0.0-0.5 **Date/Time** 10-1-13/ 0835

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analysis
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				(SP-SM)	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color H brown 7.5YR 5/4

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-598	Subarea: 5D	Date Started: 10-1-13	Date Completed: 10-1-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 18.8 2nd DPT = 18.7
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm	
GPS collected? (Yes) or No		Drill Method: DPT	Depth Drilled into Bedrock: NA
Radiological Background: β = 12 $\alpha\beta$ = 75		Borehole diameter: 2.25"	
PID Background: 0.0 ppm		Depth to GW: NA	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Will Hoffman #7735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/81	SL-598 SA5D-SB 0.0-0.5	0835	SP-SM	SAND w/silt, brown (7.5YR 5/4) f grn, mod poorly to poorly graded, quartz, dry; 85% SD 10% SILT 5% CLAY trace few ant org (roots), few to some compacted material — 0.5
		0.0	12/66				
1	3.0/3.5	0.0	12/36			SM	SILTY SAND, brn (7.5YR 5/4) f grn w/tr ant med grn, mod poorly graded, subrounded to subangular, quartz, dry, mod well compacted, sli laminated, rootlet voids & burrows filled w/ $CaCO_3$ deposits. 60% SD 25% SILT 15% CLAY
2		0.0	12/66				
3		0.0	12/72			SC	CLAYEY SAND, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/6) f grn, mod poorly to poorly graded, quartz, dry; 60% SD, 30% CLAY, 10% SILT, mod well to well compacted, sli laminated, root channels & burrows filled w/ $CaCO_3$ deposits becoming more laminated w/ depth — 2.5
4		0.0	12/90	SL-598 SA5D-SB 4.0-5.0	0845		
5	4.0/4.0	0.0	12/60				
6		0.0	12/54				GRADUAL TRANSITION
						CL	SANDY CLAY, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/6), strong brn (7.5YR 5/8) and tr ant yel red (5YR 5/8) and black (5YR 2.5/1), low plasticity, firm to hard, crumbly, dry becoming sli moist w/ depth 60% CLAY, 30% SD 10% SILT — 6.0
7		0.0	12/78				
8		0.0	12/60				GRADUAL TRANSITION
						CL	CLAY, brown (10YR 4/3) mottled w/ strong brn (7.5YR 4/6) mod low plasticity, mod crumbly, firm to hard, dry to sli moist, 80% CLAY 10% SILT 10% SD becoming less sandy w/ depth, tr ant mottling w/ black w/ depth — 8.5
9		0.0	12/48				
				2-598 SA5D-SB 9.0-10.0	0855		
10		0.0	12/66				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-59B	Subarea: 5D	Date Started: 10-1-13	Date Completed: 10-1-13
Project: SSFL		Geologist: David Rojas	Total Depth: 18.8

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							CLAY A.A See Pg 1
11	See Pg 1	0.0	12/90				
12		0.0	12/60				GRADUAL TRANSITION
13		0.0	12/60			CL	CLAY yel brn (10YR 5/6) mottled w/ (10YR 5/4) and brownish yel (10YR 6/6), mod low plastic becoming more plastic w/depth, sli to mod crumbly, sli moist 90% CLAY, 10% SILT, tr ant F-gru SD, Firm to sli soft, some mottly w/ strong brown (7.5YR 5/8) w/depth.
14	4.0/4.0	0.0	12/84	SL-59B SA5D-SB 14.0-15.0	0905		
15		0.0	12/78				
16		0.0	12/66				CLAY w/SAND, A.A. except ~70% CLAY 15% SD 15% SILT
17	2.8/2.8	0.0	12/90				
18		0.0	12/98	SL-59B SA5D-SB 18.0-19.0	0915		
		0.0	12/48				Refusal @ 18.8' bls

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √. GL

Sample ID SL-598-SA5D-SB-4.0-5.0 Date/Time 10-1-13 / 0845

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 Hoz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk yel brn (10YR 4/4)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. SK

Sample ID SL-59B-SA5D-SB-9.0-10.0 Date/Time 10-1-13 / 0855

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color brown (10YR 4/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Timothy O'Hagan **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G K

Sample ID SL-598-SA5D-SB-14.0-15.0 **Date/Time** 10-1-13/0905

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel brn (10YR 5/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-598-SA5D-SB-18.0-19.0 Date/Time 10-1-13 / 0915

Matrix (circle one): (Soil) Sediment Water

Start Depth 18.0

End Depth 19.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity w/SAND
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color yel brn (10YR 5/6)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-599-SA50-SB-00-0.5 **Date/Time** 9/9/13 @ 7:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BKASPZYK

Sampler V CORTES

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Chemistry	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Biology	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-SS Sleeve
1-4oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK brown 10YR 3/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-599	SD	9/9/13	9/9/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: STRONGARM/R. PANIAGUA	23FT/23FT
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: λ=13 / VB=67	Borehole diameter: 2.25 INCH	0
PID Background:	Depth to GW: NA	Sampling Method:
Radiological Equipment Used:	PG Review & No.:	MACRO CORE
✓ MicroR ✓ Alpha/Beta ✓ Pancake	Mike Hoffman #7735	Geologist: S KASHYAP

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1	3.0/4.0	00	13/66	SL-599-SA5D-SB-00-0.5	7:45	ML	SILT W SAND – DK BROWN (10YR 3/3) – 80% FIRM NONPLASTIC, DRY; 20% SAND, SILT FINE, PG; NO ODOR
2		00	13/78				
3		00	13/72				
4		00	13/66	SL-599-SA5D-SB-4.0-5.0	7:55		GRADATIONAL CONTACT
5	4.0/4.0	00	13/66			CL	CLAY – STRONG BROWN 7.5YR (5/6); 70% CLAY, HARD, NON PLASTIC, SEMI MOIST, 30% SILT, NO ODOR TRACE LIGNIGHT.
6		0.0	13/72				
7		0.0	13/90				
8		00	13/102			CL	AS ABOVE
9	4.0/4.0	00	13/60	SL-599-SA5D-SB-9.0-10.0	8:05		
10			13/72				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DB599	SD	9/9/13	9/9/13
Project: SSFL		**Geologist:** R. Kasprzyk	**Total Depth:** 23 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	4.0 / 4.0	0.0	13/78			CL	CLAY – STRONG BROWN (7.5 YR 5/6); 70% CLAY, HARD NON PLASTIC, SEMI MOIST; 30% SILT; NO ODOR TRACE LIGNITE.
12		0.0	13/84				
13		0.0	13/84			CL	AS ABOVE
	4.0						
14	4.0	0.0	13/90	SL-599-SASD-SB-14.0-15.0	8:15		
15		0.0	13/72				
16		0.0	13/90			CL	AS ABOVE
17			13/84				
18	4.0 / 4.0		13/84				
19			13/96	SL-599-SASD-SB-19.8-20.0	8:25		
20			13/78			CL	CLAY W/SAND – STRONG BROWN (7.5 YR 5/6); 60% CLAY, HARD, NON PLASTIC, SEMI MOIST; 20% SILT, 20% ~~Gravel~~ SAND w/ white Calcium Carbonate
	3.0 / 3.0		/84				TRACE FINE GRAVEL

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID:	Subarea:	Date Started:	Date Completed:
DG599	5D	9/9/13	9/9/13
Project: SSFL		Geologist: BKASA/ZK/L	Total Depth: 23 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
22	3.0/3.0	0.0	13/90	SL-599-SA-50-SB-220-23.0	8:35	CL	CLAY W/ SAND - STRONG BROWN (7.5YR 5/6); 60% Clay, HARD, non plastic SEMI MOIST; 20% SILT; 20% SAND, FN, PG; Trace gravel w/ white Calcium Carbonate
23	0.0	0.0	13/72				REFUSAL AT 23 FT
24							
25							
26							
27							

CDM Smith

BORING LOG AND SAMPLING RECORD

Location ID:	Subarea:	Date Started:	Date Completed:
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller:		
GPS collected? Yes or No	Drill Method:		Depth Drilled into Bedrock:
Radiological Background:	Borehole diameter:		
PID Background:	Depth to GW:		Sampling Method:
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.:		Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

KM 9/9/13

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-599-SASB-SB-4.0-5.0 **Date/Time** 9/9/13 @ 7:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist BLASZYK

Sampler VCORTES

Analysis

	Parameters	Method	Analyze?
Soil/Sediment	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil/Sediment	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown (7.5 YR 5/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments M-H

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-599-SASD-SB-9.0-10.0 Date/Time 9/9/13 @ 8:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPERYC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16 oz VAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown (7.5 YR 5/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-599-SA5D-EB-14.0-15.0 **Date/Time** 9/9/13 @ 8:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYLC

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enpores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 - 16 oz VAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown (7.5 YR 5/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Julia Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL599-GA5D-SB-19.0-20.0 **Date/Time** 9/9/13 @ 8:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 19.0

End Depth 20.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Krzysztyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16 oz Jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color Strong Brown (7.5YR 5/6)

Odor

1. Odor Strength (circle one)

None Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VLA

Sample ID SC-599-SASD-SB-220-23.0 **Date/Time** 8/9/13 @ 8:35

Matrix (circle one): (Soil) Sediment Water

Start Depth 22.0

End Depth 23.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B KACZYK

Sampler V CONTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Specialty	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-160z VAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color Strong brown (7.5YR 5/6)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong
2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cr

Sample ID SL-600-SA5D-SB-0.0-0.5MS Date/Time 10-2-13 / 1325

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Constituent	Method	Check
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Constituent	Method	Check
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

3 SS Sleeves + 1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color dk red brn (5YR 4/2)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-SL600	Subarea: 5D	Date Started: 10-2-13	Date Completed: 10-2-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 19.4 2nd DPT =
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 αβ = 68	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Reviewer & No.: Mike [illegible] #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/80	SL-SL600 SA5D-SB 0.0-0.5	1325	SP-SM	SAND w/SILT, dk red brn (5YR 4/2), f gm w/ Few med gm, poorly graded, subrounded to subangular, quartz, dry, 90% SD 10% SILT, tr to Few amt org (roots)
		0.0	12/72				
				AND			
1		0.0	12/78	SL-900 SA5D-SB 0.0-0.5	1330	SM	SILTY SAND, dk brn (7.5YR 3/4) mottled w/ brown (7.5YR 4/3) f gm, poorly graded, sr to sa, quartz, tr to amt clay, dispersed in SD. 75% SD 20% SILT 5% clay tr amt org (roots)
	2.4/3.5						
2		0.0	12/66				
3		0.0	12/78				
						SC	CLAYEY SAND, dk brn (7.5YR 3/4) mottled w/ strong brown (7.5YR 4/6) f gm w/ Few to some med gm poorly graded, subrounded to subangular quartz, clay is disseminated in SD, few mottles w/ red (5YR 5/6) w/ depth. Clay is mod low plasticity, mod crumbly, becoming more common w/ depth 60% SD 30% CLAY 10% SILT → 55% SD 35% CLAY 10% SILT
4		0.0	12/66	SL-600 SA5D-SB 4.0-5.0	1335	CL	
5		0.0	12/72				
	3.8/4.0						4.0
6		0.0	12/54				Clayey Sand dry to sli moist, firm, SD is f gm w/ tr amt med gm, subrounded to subangular, quartz 60% CLAY 25% SD 15% SILT
7		0.0	12/84				
8		0.0	12/54				Clayey sand
						CL	SANDY CLAY, A.A except also mottled w/ strong brown (7.5YR 5/6) and red (2.5YR 4/6)
9	4.0/4.0	0.0	12/72	SL-600 SA5D-SB 9.0-10.0	1345		8.0
10		0.0	12/66				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-600	Subarea: 5D	Date Started: 10-2-13	Date Completed: 10-2-13
Project: SSFL		Geologist: David Rojas	Total Depth: 19.4

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
						CL	~~SANDY CLAY~~, A.A. see pg 1 Clay w/ Sand
11	see Pg 1	0.0	12/72				
12		0.0	12/60				
13		0.0	12/54				
14	4.0/4.0	0.0	12/84	SL-600 SA5D-SB 14.0-15.0	1355		
15		0.0	12/54				
						CL	CLAY w/SAND, yel red (5YR 4/6) mottled w/ red brn (5YR 4/3), mod low plasticity to sli high plasticity, mod Firm to sli soft, mod Silty, SD is F qtz, SR to SA, quartz, CL is becoming less plastic w/ depth & Firm to hard 70% CLAY 20% SD 10% SILT 15.5
16		0.0	12/78				
17		0.0	12/72				
18			12/102				
19			12/72	SL-600 SA5D-SB 18.5-19.5	1405		
			12/72			CL	CLAY, same colors AA, CLAY is low plasticity Firm to hard, some to common $CaCO_3$ material and subtn gravel, F-sized
							Refusal at 19.4 bls.

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G K

Sample ID SL-900-SA5D-SB-0.0-0.5 **Date/Time** 10-2-13 / 1330

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-600-SA5D-SB-0.0-0.5MS

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color dk red brn (5 YR 4/2)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-600-SA5D-SB-4.0-5.0 **Date/Time** 10-2-13/1335

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	SANDY Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** NONE
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color yel red (5YR 4/6)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-600-SA5D-SB-9.0-10.0 **Date/Time** 10-2-13/1345

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	SANDY Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel red (5YR 4/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By D Rojas

Sample ID SL-600-SASD-SB-14.0-15.0 **Date/Time** 10.2.13 / 1355

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist DAVID ROJAS

Sampler VIDAL CORTES

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	✓
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	✓
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) None

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel red (5YR 4/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nelli Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By DRojas

Sample ID SL-600-SASD-SB-18.5-19.5 Date/Time 10.2.13 / 1405

Matrix (circle one): (Soil) Sediment Water

Start Depth 18.5

End Depth 19.5

Depth Units (circle one): Inches (Feet)

Check if Composite: ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist DAVID ROJAS

Sampler VIDAL CORTES

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	✓
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	✓
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Notes
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 9-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color yel red (5YR 4/6) SM 12/14/19

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Julie Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SC-601-SA5D-SB-0.0-0.5 Date/Time 9/9/13 13:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B. KASPZAK

Sampler V. CORTEZ

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS SLEEVE

~~2 16 oz Jars~~ V. Cortez 9/9/13

~~8 Encores~~

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Brown 10YR 4/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-601	SD	9/9/13	9/9/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: (FT) 21.5, 21.0
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: 0.5FT
Radiological Background: Y=13 αB=84	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Init: Mike Hoffman #7735	Geologist: AKASPRZAK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/81	SL-601-SA5D-SB-0.0-0.5	13:10	ML	SILT W/ SAND - BROWN (10YR 4/3); 80% SILT, SOFT, NON-PLASTIC, DRY 20% SAND, F, PG, LOOSE, NO ODOR
		0.0	13/66				
1		0.0	13/79				
2	4.0/4.0	00	13/66				
3		0.0	13/78			CL	CLAY W/ SAND - DK BROWN (10YR 3/2) HARD, NON-PLASTIC, 80% CLAY; 20% SAND, F, PG, DRY, NO ODOR T
4		0.0	13/90	SL-601-SA5D-SB-4.0-5.0	13:20		
5		0.0	13/102				CLAY - STRONG BROWN (7.5YR 5/8) 80% CLAY, HARD, NON-PLASTIC, DRY 10% SILT; 10% WEATHERED LIMESTONE; NO ODORS; TRACE LIGNITE
	4.0/4.0						
6		00	13/102				
7		00	13/108				
8		0.0	13/96			CL	AS ABOVE W/ ONLY TRACE WEATHERED LIMESTONE
9	4.0/4.0	0.0	13/96	SL-601-SA5D-SB-9.0-10.0	13:30		
10		0.0	13/90				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG 601	Subarea: SD	Date Started: 9/9/13	Date Completed: 9/9/13
Project: SSFL		Geologist: KASPRYK	Total Depth: 21.5 FT

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11	4.0/4.0	0.0	13/78			CL	CLAY – STRONG BROWN (7.5YR 5/6) 90% CLAY, HARD, NON PLASTIC, DRY; 10% SILT, TRACE LIMESTONE, NO ODOR
12	—	0.0	13/96			CL	AS ABOVE
13		00	13/90				
14	4.0/4.0	0.0	13/100	SL-601 SA5D-GB-14.0-15.0	1340		
15		00	13/90				
16	—	0.0	13/96			CL	AS ABOVE
17		0.0	13/94				
18	4.0/4.0	0.0	13/90				
19		0.0	13/114				
20	—	00	13/96	SL-601-SA5D-GB-20.5-21.5	1345	SP	SAND – V PALE BROWN (10YR 7/4); 90% SAND F-M, PG, LOOSE, DRY; 10% GRAVEL, F, PG, ROUND, LOOSE, NO ODOR WEATHERED SAND STONE IN LAST 0.5 FT
21			90/96				

21.5

CDM Smith

BORING LOG AND SAMPLING RECORD

REFUSAL AT 21.5 ON SANDSTONE

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-601-SA5D-SB-4.0-5.0 Date/Time 9/9/13 13:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. KASPZYK

Sampler V. CORTEZ

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	✓
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enviro	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Special	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 16-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By KC

Sample ID SL-601-SASD-SB-90-10.0 **Date/Time** 9/9/13 13:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. KASPAR

Sampler Y. CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	✓
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enclaves	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 16-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5 YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-601-SA5D-SB-14.0-15.0 Date/Time 9/9/13 13:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	✓
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explos.	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Various	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 - 160z Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color Strong brown 7.5 YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hodgson **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By _____

Sample ID SL-601-SA50-SB-20.5-21.5 Date/Time 9/9/13 - 13:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 20.5

End Depth 21.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B. KASPZYK

Sampler V. CORTES

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	✓
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Biocides	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Tributyltin	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 16-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color Pale Brown (10YR 7/4)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Shy Myers

Sample ID SL-602-SA5D-SB-0.0-0.5 Date/Time 10-8-13/1220

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No) 10 DRR

Color ~~DRR~~ ~~Strong~~ brown (7.5YR 5/8) DRR

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Location ID: DG-602	Subarea: 5D	Date Started: 10-8-13	Date Completed: DID NOT REACH REFUSAL 10-8-13
Client: DOE	Project Name/#: Santa Susana Field Laboratory/94489		Total Depth: 1st HA = 10' 2nd HA =
Company Name: CDM SMITH		Drill Contractor/Driller: NA	
GPS collected? (Yes) or No		Drill Method: Handauger	Depth Drilled into Bedrock: NA
Radiological Background: γ =	αβ =	Borehole diameter: 3"	
PID Background: 0.0 ppm		Depth to GW: NA	Sampling Method: Slide hammer
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Julie Hoffman #7735	Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (μR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/97	SL-602 SA5D-SB 0.0-0.5	1220	SM	SILTY SAND brn (10YR 5/3) f-gm, poorly graded sm101413 subrounded to subangular, quartz, dry, silt is disseminated in sd, mod well compacted, some organics (roots) 80% SD 20% SILT 0.5'
1	HA	0.0	12/66			SM	SILTY SAND, dk yel brn (10YR 4/4) mottled w/ brn (10YR 5/3) and yel brn (10YR 5/4), f-gm w/ few ant med-gm sr to sa, quartz, sli to mod compacted, dry, few to some organics (roots); 75% SD 25% SILT. Becomes siltier w/ depth to ant clayey sand increasing w/ depth clay is brn (7.5YR 4/2), low to mod low plasticity, crumbly
2		0.0	12/90				
3		0.0	12/72				
4		0.0	12/72	SL-602 SA5D-SB 4.0-5.0	1250	SC	CLAYEY SAND, brn (7.5YR 4/3) mottled w/ (7.5YR 5/4) and strong brown (7.5YR 5/6), f-gm, poorly sorted, graded, quartz, dry, clay is disseminated in sd and present as sandy clay blebs, clay is low to moderate plasticity, mod crumbly, firm to hard 3.4'
5		0.0	12/84			CL	65% SD, 20% CLAY 15% SILT becoming more clayey w/ depth 4.6' few ant org (roots) 2" root @ 4' bls
6		0.0	12/78				SANDY CLAY strong brn (7.5YR 5/6) mottled w/ lt brn (7.5YR 6/4) and yel red (5YR 4/6); 50% CLAY, 30% SD 20% SILT, blebs of silty sand brn yel (10YR 6/6); clay is low plasticity, hard to firm, sli to mod crumbly, sd is dispersed in clay and present as blebs; some to common $CaCO_3$ deposits in root molds, burrows, & laminations to ant org (roots)
7		0.0	12/96				7.8'
8		0.0	12/84			CL	clay w/ sand sm101413 SANDY CLAY, yel red (5YR 4/6) mottled w/ red brn (5YR 4/4) & (5YR 5/4) and strong brn (7.5YR 5/6) low plasticity, firm to hard, crumbly, sd is disseminated in clay and present as clayey silty sand blebs; 55% CLAY, 25% SD 20% SILT, SD is f-gm, quartz, poorly graded sm101413; dry
9		0.0	12/78	SL-602 SA5D-SB 9.0-10.0	1350		
10		0.0	12/102				Ceased Handaugering @ 10' bls - NOT REFUSAL

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:			
amt: amount	gr: grained	pg: poorly graded	t: trace
c: coarse	lt: light	rnd: rounded	v: very
dk: dark	m: medium	sa: subangular	wg: well graded
f: fine	mod: moderate	sr: subrounded	ϕ: diameter

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Shy Myal

Sample ID SL-602-SA50-SB-4.0-5.0 Date/Time 10-8-13/1250

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyzed
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyzed
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color brn (7.5YR 4/3)

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong
2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Shy Mypeel

Sample ID SL-602-SA5D-SB-9.0-10.0 Date/Time 10-8-13/1350

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	
	EPA 6020	
	EPA 7471 (Soil)	
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	X
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameters	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

1 SS Sleeve & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	SANDY lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** None
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color yel red (5YR 4/6)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-603-SA5D-SB-0.0-0.5 **Date/Time** 9/10/13 @ 10:10

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KASPZYK

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Enviros	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 SS Sleeve

1 - 4oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color DK BROWNISH YELLOW 10 YR 3/4

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-603	Subarea: SD	Date Started: 9/10/13	Date Completed: 9/10/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 14.0, 13.7, 13.7
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/F Rodriguez		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: -0-
Radiological Background: 1-03/1-75	Borehole diameter: 2.25 INCH		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: MACRO CORE
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: #7735		Geologist: KASPAR

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	~~13/88~~ 9/10/13				
		0.0	13/60	SL-603-SA5D-SB-0.0-0.5	1040	CL	CLAY - DK BROWNISH YELLOW (10YR 3/4) 70% CLAY, HARD, NON-PLASTIC, DRY; 25% SILT; 5% $CaCO_3$ STRINGERS, NO ODOR
1	2.3/4.0	0.0	13/66				
2		0.0	13/90				
3		0.0	13/90				
4		0.0	13/66				GRADATIONAL CONTACT
				SL-603-SA5D-SB-4.0-5.0	10:20	CL	CLAY - STRONG BROWN (7.5YR 5/6); 95% CLAY, FIRM, NON PLASTIC, SEMI MOIST, 5% $CaCO_3$ STRINGERS, NO ODORS
5		0.0	13/60				
6	4.0/4.0	0.0	13/72				
7		0.0	13/54				
8		0.0	13/96				
9	4.0/4.0	0.0	13/78	SL-603-SA5D-SB-9.0-10.0	10:30		
10		0.0	13/72				



CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG603	Subarea: 50	Date Started: 9/10/13	Date Completed: 9/10/13
Project: SSFL		Geologist: [redacted]	Total Depth: 14.0

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
11		0.0	13/60			CL	CLAY – STRONG BROWN (7.5YR 5/8) 90% CLAY, SOFT, NON PLASTIC, SEMI MOIST, 10% SILT W/ CACO3 STRINGERS; TRACE LIMESTONE FRAGMENTS (WEATHERED) NO ODORS
12		0.0	13/72				
13		0.0	13/78	SC603-SA50-SB-13.0-14.0	10:40	CL	CLAY – LT. BROWNISH GRAY (10YR 6/2) Hard, non plastic, semi moist, 80% Clay; with LIMESTONE FRAGMENTS
14		0.0	13/72				REFUSAL AT 14.0 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G

Sample ID SL-603-SASD-SB-4.0-5.0 Date/Time 9/10/13 @ 10:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): ~~DPT~~ Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B KASPZYK

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Inorganics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organics	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-9-03 JAE

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GA

Sample ID SL-603-~~SA~~SD-SB-9.0-10.0 **Date/Time** 9/10/13 at 10:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Inorganics	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Organics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Radiologics	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-9 or Van

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) (0)

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5YR5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] (KW) 9/10/13 **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. S

Sample ID SL-603-SA-SD-SB-13.0-14.0 Date/Time 9/10/13 @ 10:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 13.0

End Depth 14.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Knapp

Sampler N Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Groups	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-9 on Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes No

Color Lt brownish gray 10yr6/2

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-604-SA5D-SB-0.005 Date/Time 9/10/13 @ 8:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist R. KASPAR

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 - SS Sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brownish Yellow 10YR 3/4

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG 604	SD	9/10/13	9/10/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Stratagrum/F Rodriguez	17.4, 17.4, 17.2
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock: 0.4 FT
Radiological Background: γ=14 / αβ=79	Borehole diameter: 2.25 INCH	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Thompson #7735	Geologist: [illegible]

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	13/72	SL-604-SA5D-SB-0.0-0.5	8:55	CL	CLAY - DK Brownish Yellow (10YR 3/4) 70% CLAY, HARD, NON PLASTIC, DRY; 25% SILT; 5% CaCO3 STRINGERS NO ODOR
1		0.0	13/78				
2	2.0/4.0	0.0	13/90				
3		0.0	13/102			CL	CLAY, STRONG BROWN (7.5 YR 5/8) 95% CLAY, FIRM, NON PLASTIC, SEMI MOIST, 5% CaCO3 STRINGERS - NO ODOR
4		0.0	13/84	SL-604-SA5D-SB-4.0-5.0	9:05	CL	AS ABOVE
5		0.0	13/72				
6	4.0/4.0	0.0	13/[illegible]				
7		0.0	13/84				
8		0.0	13/72			CL	AS ABOVE
9			72	SL604-SA5D-SB-9.0-10.0	9:15		
10			90				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG-604	SD	9/10/13	9/10/13
Project: SSFL		**Geologist:** KASPZYK	**Total Depth:** 17.4

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							GRADATIONAL CONTACT
						CL	CLAY W/ SAND – STRONG BROWN 7.5YR 5/8, 75% CLAY, SOFT, NON PLASTIC SEMI MOIST, 25% SAND, F, PG, TRACE LIMESTONE
11		0.0	13/78				
12		0.0	13/84				
13		0.0	13/78				
14	4.0/4.0	0.0	13/96				
							ABRUPT CONTACT
15		0.0	13/90				SAND – V PALE BROWN (10YR 7/4); 100% SAND, F, PG, SEMI MOIST, NO ODOR
16		0.0	13/66			SP	
	1.4			SC-604-SA5D-SB-16.5-17.5	9:25		
17		0.0	13/72				
		0.0				ML	SILT STONE – V PALE BROWN (10YR 7/4), WEATHERED
							REFUSAL AT 17.4 FT ON BEDROCK

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GE

Sample ID SC-604-SA5D-SB-4.0-5.0 Date/Time 9/10/13 9:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite: ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
Soil	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Groundwater	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 – 902 SAN

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Straw brown 7.5 YR 5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. GK

Sample ID SC-604-SASD-SB-9.0-10.0 **Date/Time** 9/10/13 9:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
Chemistry	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-902 JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color strong brown 7.5 YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √ CE

Sample ID SL-604-SASD-SB-16.5-17.5 **Date/Time** 9/10/13 @ 9:25

Matrix (circle one): (Soil) Sediment Water

Start Depth 16.5

End Depth 17.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist Blagoevich

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil/Sed	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-902 Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				(SP)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color V PALE Brown 10YR 7/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SC-605-SA5D-SB-0.0-0.5 **Date/Time** 9/10/13 @ 7:45

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kashyk

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	K
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

9-07 ~~JAA~~ VC 9/10/13
1- 4# sleeve

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brownish Yellow 10YR 3/4

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG 605	Subarea: SD	Date Started: 9/10/13	Date Completed: 9/10/13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 15.6, 15.4, 14.7
Company Name: CDM SMITH		Drill Contractor/Driller: Strayhorn	
GPS collected? Yes or No		Drill Method: DPT	Depth Drilled into Bedrock: 0
Radiological Background: X=13/Y=77		Borehole diameter: 2.25 inch	
PID Background: 0.0		Depth to GW: NM	Sampling Method: Macro Core
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Miller Brown #7735	Geologist: KASPRZAK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1	3.0	0.0	13/93	SL605-SA5D-SB-0D-0.5	7:55	CL	CLAY- DK BROWNISH YELLOW (10YR 3/4) 70% CLAY, HARD, NON-PLASTIC, DRY; 25% SILT; 5% CALCIUM CARBONATE STRINGERS. NO ODOR
		0.0	13/66				
		0.0	13/90				
2	4.0	0.0	13/78				
3		0.0	13/72				
4		0.0	13/72	SL-605-SA5D-SB-4.0-5.0 MS	7:55	CL	CLAY- STRONG BROWN (7.5 YR 5/8) 9/10/13 95% CLAY, FIRM, NON-PLASTIC, DRY, 5% CALCIUM CARBONATE STRINGERS NO ODOR
5	4.0	0.0	13/60	SL-905-SA5D-SB-4.0-5.0	8:00		
6	4.0	0.0	13/72				
7		0.0	13/84				
8		0.0	13/84			CL	CLAY- STRONG BROWN (7.5 YR 5/8) 85% CLAY, FIRM, NON PLASTIC, SEMI MOIST, 10% SAND, F, VG, 5% CaCO3 STRINGERS
9		0.0	13/84	SL-605-SA5D-SB-9.0-10.0	8:05		
10		0.0	13/84				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG 605	SD	9/10/13	9/10/13
Project: SSFL		**Geologist: KASPRZYK**	**Total Depth: 15.6**

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	4.0					CL	CLAY - STRONG BROWN (7.5YR 5/8) 85% CLAY FINES, NON PLASTIC, SEMI MOIST; 10% SAND, F PG; 5% $CaCO_3$ STRINGERS
11	4.0	0.0	13/84				
12		0.0	13/90				
13		0.0	12/90				
14		0.0	13/96	SL-605-SA50-SB-14.5-15.5	8:15		
15		0.0	13/78			CL	AS ABOVE W/ UP TO 20% WEATHERED LIMESTONE
		0.6	12/84				REFUSAL AT 15.6 FT

9/10/13 (KW)

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G E

Sample ID SL-605-SASD-SB-4.0-5.0 MS Date/Time 9/10/13 @ 7:55

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist VS Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotin	Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	Methyl Mercury	EPA 1630	

1-9 OL JAN
1-16 OL JAN

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				(CL)	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5 YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Melissa Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL905-SA5D-SB-4.0-5.0 Date/Time 9/10/13 @ 8:00

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-605-SA5D-SB-4.0-5.0 MS

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Perchlorate	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-907 JAN

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5 YR 5/8

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Nila Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cuta

Sample ID 4-605-SA5D-SB-9.0-100 Date/Time 9/10/13 8:05

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPZYK

Sampler VCortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organotins	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** (0)
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5YR 5/8

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ (PG) 9/10/13 **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. G E

Sample ID SL-605-SA5D-SB-14.5-15.5 Date/Time 9/10/13 @ 8:15

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.5

End Depth 15.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKASPRZAK

Sampler U COVICH

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
EPA 8260	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
EPA 8015	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
EPA 300.0/9056	Nitrates	EPA 300.0/9056	
EPA 8330	Energetics	EPA 8330	
EPA 9012	Cyanide	EPA 9012	
EPA 8315	Formaldehyde	EPA 8315	
EPA 1625	NDMA	EPA 1625	
Krone et al.	Organotin	NOAA Status and Trends, Krone et al.	
EPA 1630	Methyl Mercury	EPA 1630	

1 9-oz JAR

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5 5/6

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

N/A Other _____

Moisture Condition (circle one)

Dry Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-606-GA5D-SB-00.05 **Date/Time** 9/10/13 @ 12:20

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B KAGEYIC

Sampler V Cortez

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	✓
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	✓
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Organics	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 - SS Sleeve
1 - 4oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color DK Brown 10YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-606	SD	9/10/13	9/10/13

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth:
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm / F. Rodriguez	13.7, 13.9, 13.8
GPS collected? Yes or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: 13/18 / 13/81	Borehole diameter: 2.25 inch	0
PID Background: 0.0	Depth to GW: NA	Sampling Method:
Radiological Equipment Used:	PG Review & No:	MACRO CORE
✓ MicroR ✓ Alpha/Beta ✓ Pancake	Julie Hoffman #7735	Geologist: KASPRZYK

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1	3.2	0.0	13/89	SL-606-SA5D-SB-0.0-0.5	12:20	CL	CLAY – DK Brown (10 YR 3/3); 70% CLAY, HARD, NON PLASTIC, DRY, 25% SILT; 5% CaCO3 STRINGERS, NO ODOR
		0.0	15/60				
		0.0	13/78				
2	4.0	0.0	13/60				
3		0.0	13/90				
4		0.0	13/96	SL-606-SA5D-SB-4.0-5.0	12:30	CL	CLAY – STRONG BROWN (7.5 YR 5/8) 90% Clay, SOFT, NON PLASTIC, SEMI MOIST; 10% SAND, F, PG; TRACE CaCO3 STRINGERS,
5	4.0	0.0	13/96				
6	4.0	0.0	13/96				
7		0.0	13/72				
8		0.0	13/78				
9	4.0	0.0	13/72	SL-606-SA5D-SB-9.0-10.0	12:40	CL	AS ABOVE W/ MORE SAND CLAY WITH SAND – STRONG BROWN (7.5 YR 5/8); 75% CLAY, SOFT, NON PLASTIC SEMI MOIST; 25% SAND, F, PG, Trace CaCO3 Stringers / NO Odor
10	4.0	0.0	13/84				

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-606	Subarea: SD	Date Started: 9/10/13	Date Completed: 9/10/13
Project: SSFL		Geologist: [illegible] ZYL	Total Depth: 13.7

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							W/ SAND
						CL	CLAY – MOTTLED STRONG BROWN (7.5YR 5/8) & BROWN 7.5YR 5/2. 75% Clay, Soft, Non-Plastic, semi moist; 25% SAND, F, PG; Trace $CaCO_3$ stringers and fragments of Weathered limestone
	4.0						
11	4.0	00	13/72				
12		00	13/66				
	1.7						
13	1.7	00	13/78	SL-606 SA5D SB-13.0	1250		
		0.0	13/90	14.0			
							REFUSAL AT 13.7 FT

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SC-6660-SASD-SB-4.0-5.0 Date/Time 9/10/13 @ 12:30

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist BKasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5 YR 5/8

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J. Gt

Sample ID SL-606-SA5D-SB-9.0-10-0 Date/Time 9/10/13 @ 12:40

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9-oz Jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brown 7.5YR 5/8

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-606-SA50-SB-130-14.0 **Date/Time** 9/10/13 1250

Matrix (circle one): (Soil) Sediment Water

Start Depth (KW) 9/10/13 13.0

End Depth (KW) 9/10/13 14.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist B Kasprzyk

Sampler V Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	
		EPA 6020	
		EPA 7471 (Soil)	
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	X
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Soil/Water	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1 9-oz Jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong brown 7.5 YR 5/6

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-607-SA5D-SB-0.0-0.5 Date/Time 10-1-13 / 1355

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analyze
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SS Sleeves & 1 4oz jar

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) ~~0~~ TRACE

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/Metamorphic Gravel)		N/A
Other _____		

Is Staining Present Yes (No)

Color DK. YL. BRN. (10 YR 4/4)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-607	Subarea: 5D	Date Started: 10-1-13	Date Completed: 10-1-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1st DPT = 10.7, 2nd DPT = 10.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: γ = 12 α/β = 96	Borehole diameter: 2.25		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Date: Mike Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	0.0	12/89	SL-607 SA5D-SB 0.0-0.5	1355	SP-SM	SAND w/ SILT ~~+ GRAVEL~~, dk yel brn (10YR 4/4) mottled w/ yel brn (10YR 5/4) f-m gr, mod poorly ~~graded~~ Subrounded to subangular, quartz, dry, Gravel is ~~igneous~~ subrounded SM1015I3
		0.0	12/60				
1		0.0	12/90			SM	70% SD, 10% SILT, tr ant gravel, trace (roots) 0.5
	2.1/3.5						SILTY SAND strong brown (7.5YR 4/6) mottled w/ brn (7.5YR 4/3) and yel red (5YR 5/6), f-m gr, mod well sorted subrounded to subangular, dry, 70% SD 30% SILT 1.8
2		0.0	12/72			SC	
							CLAYEY SAND, brn (7.5YR 4/4) mottled w/ (10YR 5/8) yel brn and brownish yellow (10YR 6/6) f gr, mod well to well sorted, quartz, Clay is dispersed in sd, Clay is mod soft to sli firm, 60% SD, 25% CLAY 15% SILT, dry
3		0.0	12/102				mod low plasticity
							GRADUAL TRANSITION
4		0.0	12/84			SC	CLAYEY SAND, strong brown (7.5YR 4/6) mottled w/ dk brown (7.5YR 3/4) and red gel (7.5YR 6/8), tr ant red (2.5YR 5/8) f gr w/ tr to few ant med gr, quartz, Subrounded to subangular, quartz, dry to sli moist, Clay is dispersed in sd, soft to sli firm, mod low plasticity 60% SD 30% CLAY 10% SILT tr ant f gravel from 5.8-6.5 3.8
				SL-607 SA5D-SB 4.0-5.0	1405		
5	4.0/4.0	0.0	12/54				
6		0.6	12/84				
7		0.0	12/66			SC	CLAYEY SAND, dk yel brn (10YR 4/4) mottled w/ 10YR 4/6 yel brn (10YR 5/8), f-m gr w/ Few to some coarse gr, mod poorly ~~graded~~ sr to sa, quartz + silty sdstn, dry to sli moist Clay is dispersed in sd, mod low plasticity 60% SD 35% CLAY 5% SILT some calc CaCO3 deposits 6.5
8		0.0	12/78			SP-SM	SAND w/ SILT yel brn (10YR 5/8) f gr, well sorted, subrounded quartz, dry to sli moist, 90% SD 10% SILT SM1015I3 7.6
							~~8.4~~
9	2.7/2.7	0.0	12/66			SC	CLAYEY SAND, Same as 6.5-7.6 9.4
10		0.0	12/78				Refusal @ 10.7 10.7
10.7		0.0	12/60				

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By √. Cortez

Sample ID SL-607-SA5D-SB-4.0-5.0 **Date/Time** 10.1.13 1405

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist DAVID ROJAS

Sampler VIDAL CORTES

Analysis

Analyte Group	Method	Analyze
Metals	EPA 6010	✓
	EPA 6020	✓
	EPA 7471 (Soil)	✓
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	✓
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	✓
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	✓
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Analyte Group	Method	Analyze
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	✓
TPH-EFH	EPA 8015	✓
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 16-oz JARS & 2 ENCORES

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) 0

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color Strong Brn. (7.5YR 4/6)

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments _____

N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-608-SA5D-SB-0.0-0.5 Date/Time 10-3-13 / 1340

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

2 SSS leaves & 1 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No

2. **Percentage Fill (%)** 5%

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
(Igneous/Metamorphic Gravel)		N/A
Other _____		

Is Staining Present Yes (No)

Color Brn. (10YR 5/3)

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hibbard **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-608	Subarea: 5D	Date Started: 10-3-13	Date Completed: 10-3-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 1ST DPT = 10.7 2ND DPT 10.6 3RD DPT = 10.7
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: $\bar{x}$=13 σ=72	Borehole diameter: 2.25"		
PID Background: 0.0 ppm	Depth to GW: NA		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Michael Hoffman #7735		Geologist: David Rojas

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	0.5/0.5	3/70 13/84	0.0 0.0	SL-608 SA5D-SB 0.0-0.5	1340	SM	SILTY SAND, brn (10YR 5/3), F gr w/ some mod to tr amt coarse gr, mod poorly ~~sorted~~ graded, subrounded, quartz
						SC	70% SD 20% SILT 5% GRAVEL; SILT is decomposed w/sd, GRAVEL is sr to sa igneous, tr to few amt org (roots) 0.5
1		13/72	0.0				
	2.8/3.5						CLAYEY SAND, brn (7.5YR 4/4) mottled w (7.5YR 5/4) F gr w/ tr amt med gr, poorly ~~sorted~~ graded, subrounded to subangular quartz, Clay is decomposed w/SD SM/CL/SC
2		13/60	0.0				60% SD, 30% CLAY 10% SILT Clay is low plasticity crumbly, hard, few amt mottles w/ strong brn 7.5YR 5/8 increasing w/depth, dry tr amt org (roots) 3.0
3		13/84	0.0				
						CL	SANDY CLAY, strong brn (7.5YR 5/6) mottled w/ brn (7.5YR 4/4) low plasticity, hard to ~~firm~~ mod firm, become mod firm w/depth, dry, tr to few amt of $CaCO_3$ deposits in paleo root molds & burrows 60% CLAY 30% SAND 10% SILT, SD is F-m gr sr to sa, quartz
4		13/72	0.0	SL-608 SA5D-SB 4.0-5.0	1350		
5	3.8/4.0	13/42	0.0				
6	~~3.8~~	13/36	0.0				
7	~~3.8~~	13/48	0.0				
8	~~3.8~~	13/60	0.0				GRADUAL TRANSITION
						CL	SANDY CLAY A.A. except also mottled w/ yellowish red (5YR 5/8) and dk red brn (5YR 2.5/2) and clay is F um to sli soft and mod low ~~plasticity~~ 8.0
9	2.0/2.0	13/84	0.0			SC	plasticity 60% CLAY 30% SD 10% SILT few $CaCO_3$ deposits 8.8
							CLAYEY SAND, lt olive brn (2.5Y 5/3) mottled w/ brn (7.5YR 4/4) and strong brn (7.5YR 5/8), F-m gr mod poorly ~~sorted~~ graded sr to sa quartz & sdstn, dry to sli moist, few to some dur $CaCO_3$ deposits in root molds & burrows 65% SD 25% CLAY 10% SILT
10		13/72	0.0				10.3
10.7		13/84	0.0			SP-SM	10.3-10.7 SAND w/ SILT lt yel brn (10YR 6/4) mottled w/ yel brn (10YR 5/6) & brn (10YR 5/3) F gr, poorly ~~sorted~~ graded, sr to sa, quartz, dry 90% SD 10% SILT SM/ML/SP
							Refusal @ 10.7' bls 10.7

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-608-SA5D-SB-4.0-5.0 Date/Time 10-3-13/ 1350

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist David Rojas

Sampler Vidal Cortes

Analysis

Parameter	Method	Analysis
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analysis
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	X
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	SANDY Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): 0
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color SR. BRN. (7.5 YR 5/6)

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A. VIVIAN

Sample ID SL-609-SA5D-SB-0.0-0.5 Date/Time 11/15/2013 1250

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID NA

Field Geologist C. Cox

Sampler A. Vivian

Analysis

Parameter	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	X
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	
Pesticides	EPA 8081	

Parameter	Method	Analyze?
VOCs	EPA 8260	
1,4 Dioxane	EPA 8260 SIM	
TPH-GRO	EPA 8015	
TPH-EFH	EPA 8015	X
Glycols	EPA 8015	
Alcohols	EPA 8015	
Terphenyls	EPA 8015	
Nitrates	EPA 300.0/9056	
Energetics	EPA 8330	
Cyanide	EPA 9012	
Formaldehyde	EPA 8315	
NDMA	EPA 1625	
Organotin	NOAA Status and Trends, Krone et al.	
Methyl Mercury	EPA 1630	

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** (Yes) No
2. **Percentage Fill (%)** 100
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel		N/A
(Other) SSFormation		

Is Staining Present Yes (No)

Color light yellowish brown (2.5Y 6/4)

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hollom **PG Registration #** 7735

Additional Comments None

Location ID:	Subarea:	Date Started:	Date Completed:
DG-609	SD	11/15/2013 Friday 1230	11/15/2013

Client: DOE	Project Name/#: Santa Susana Field Lab/99489	Total Depth: ~~1.5'~~ 1.2', 1.1', 1.5'
Company Name: CDM SMITH	Drill Contractor/Driller: SAFS	
GPS collected? Yes or No	Drill Method: DPT, Handauger	Depth Drilled into Bedrock: NA
Radiological Background: 12/93	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: NA	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: C. Cook

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1	0.7/1.2	0.0	12/72	SL-609-SASD-SB-0.0-0.5	1250	SM	SILTY SAND: light yellowish brown (2.5Y 6/4), 75% sand, pg, f-m, mostly f, 25% silt, ~~non~~ low plastic, trace igneous clasts, trace SS formation, dry, no odor (FILL) cc 11/15/13
2		0.0	12/72				Refusal at SS formation 1.1', 1.5'
3							
4							
5							

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Cs

Sample ID SL-501-SA8-SB-0.0-0.5MS Date/Time 7-15-13 ~~1010~~ 1110

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6-SS sleeves

~~3-4oz jars~~ jf

1-9oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-501	8	7-15-13	7-15-13

Client: DOE	Project Name/#: ~~SSFL-65258-63370,4203,002.229.02234,GSPH6~~ SM 1a41a	Total Depth: 13.3
Company Name: CDM SMITH	Drill Contractor/Driller:	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 14>90	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PO Review & No.: Mike Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	14>85	SL-501 SA-B SB 0.0-0.5	1115	ML	silt, dry, loose red brown 10R 3/6 - trace root mottles
1		0.0	11>60				1' silt, dry, loose 10R 3/6 red brown
2		0.0	11>72			ML	2' silt, becoming moist, ~~dense~~ loose - no organics stain/odor 10R 3/6 - caliche mottles
3		0.0	11>64			ML	3' silt as above, loose, non plastic 10R 3/6 - caliche mottling
4		0.0	11>78	SL-501 SA-B SB 4.0-5.0	1130	ML	4' silt, trace moist loose nonplastic color transition 4.5-5.0 to 5R 4/6 yellow red no stain/odor
5			10>42			ML	5' silt, compacted, dense, moist @ 5R 4/6 yellow red
6			10>78			ML	6' silt w/ sand SM 7.25.13 back to 10R 3/6 red brown - strong FeOx stain throughout
7			10>120			ML	7' sandy silt, 15% v.f.g. sa to sr silica sand 10R 3/6
8			10>90			ML	8' sandy silt 10R 3/6, dense non plastic moist no stain/odor
9			11>66	SL-501 SA-B SB 9.0-10.0	1145	ML	9' sandy silt 10R 3/6 moist dense non-plastic 10R 3/6

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG-501	8	7-15-13	7-15-13

Project: SSFL | Geologist: J. Faubion | Total Depth: 13.3

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
							9.5 color transition from 10R 3/6 to light brown 10YR 8/B
10		0.0	11>64			ML	~~Sandy~~ silt, caliche mottling persists 10' 10YR 8/B moist 10-12% v.f.g. - root relics
11		0.0	11>84	SL-501 SA&SB 11.5-12.5		ML	~~Sandy~~ silt, 12-15% v.f.g. sa to sr 11' silica sand - FeOx stain throughout light brown 10YR 8/3
12		0.0	11>60	SL-501 SA&SB 12.0-13.0	1200	ML	Sandy silt, sand % picking up 17-20% 12' 10YR 8/B moist, non plastic
13	13.3 TD	0.0	11>84			ML	sandy silt as above, FeOx stained 20% v.f.g. sa to sr silica sand in silt 10YR 8/B

13.3 T.D. refusal Run #1
12.5 refusal Run #2
13.2 refusal Run #3

OK -jf

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VL CAT

Sample ID SL-B01-SA8-SB-0.0-0.5 Date/Time 7-15-13 1115

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-501-SA8-SB-0.0-0.5 MS

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	~~X~~ jf
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 ~~1~~ - S.S. sleeves

1 ~~1~~ - 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) Ø

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. Odor Strength (circle one)
   (None) Slight Strong
2. Odor Description (circle one)
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature Miller Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.

Sample ID SL-SOI-SAB-SB-4.0-5.0 Date/Time 7-15-13 1130

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fashion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 5R 4/6 yellowish red

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gk

Sample ID SL-501-SA8-SB-9.0-10.0 Date/Time 7-15-13 1145

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Coffis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars

2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No) 10YR 8/3 light brown

Color ~~10YR 3/1~~ ~~10R 3/6~~ ~~brown~~ brownish brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Julie Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C

Sample ID SC-501-SA8-SB-12.0-13.0 Date/Time 7-15-13 1200

Matrix (circle one): (Soil) Sediment Water

Start Depth 12.0

End Depth 13.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fashion

Sampler V. Curtis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16oz jars

2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-SOZ-SA8-SB 0.0-0.5 Date/Time ~~7-13-13~~ 7/15/13 0840

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one) 7/15/13: DPT (Slide Hammer) Hand Auger/~~Slide Hammer~~ Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 5.5. sleeves

1 - 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other: _____

Is Staining Present Yes (No)

Color 5YR 4/6 yellow-red

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments NA

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-502	Subarea: 8	Date Started: 7-15-13	Date Completed: 7-15-13
Client: DOE	Project Name/#: ~~SSFL-65258-63376,1203,002.223.02231,SGPH3~~ 7LB		Total Depth: 8.7'
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm F. Rodriguez	
GPS collected? (Yes) or No		Drill Method: Hand Auger	Depth Drilled into Bedrock: NA
Radiological Background: 14284		Borehole diameter: 2.23"	
PID Background: 0.0		Depth to GW: NA	Sampling Method: HA
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Julie Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
	.5	0.0	14284	SL-502 SA8-SB 0.0-0.5	0940	ML	0.0-0.5 silt, dry, compacted 5YR 4/6 yellowred - strong oxidation, FeOx pervasive no stain/odor
1		0.0	~~14264~~ 14264			ML	1' silt, dry, compacted 5YR 4/6 yellowred - 5/7% organics (decaying leaves, roots)
2		0.0	14272			ML	2' silt, as above, organics dropping out no stain/odor 5YR 4/6 yellowred - trace caliche stringers
3		0.0	14260			ML	3' silt, becoming moist, 5YR 4/6 yellowred
4		0.0	14260	SL-502 SA-8-SB 4.0-5.0	0930	ML	4' as above, silt, loose, moist - organics absent, trace clay 5YR 4/6 yellowred
5		0.0	14248			ML/CL	5' clayey silt, moist, loose 5YR 4/6 - 10/12% clay intrastitual in silt/yellowred - color transition 5.6' to 10R 3/6 red brown
6		0.0	14242			ML/CL	6' clayey silt, moist, loose 10R 3/6 red brown - no stain/odor
7		0.0	14248			ML/CL	7' clayey silt as above 10R 3/6 red brown - trace v.f.g. sa silica sand
8		0.0	14266			SM/ML	sandy silt w/trace clay 10R 3/6 red brown - v.f.g. sa silica sand
	RD 8.7	0.0	14268	SL-502 SA8-SB 7.5-8.5	1015	SM/ML	- 8.7' refusal sandy silt w/trace clay 10R 3/6 red brown

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	HA: Hand Auger
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Coltis

Sample ID SL-502-SA8-SB-4.0-5.0 Date/Time 7-15-13 0930

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Coltis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars if S.S. sleeves

1 - 4 oz jar

2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** Ø
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 5YR 4/6 yellowred

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Trula O'Hanson **PG Registration #** 7735

Additional Comments N A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.A

Sample ID SL-502-SA8-SB-7.5-8.5 Date/Time 7-15-13 1015

Matrix (circle one): (Soil) Sediment Water

Start Depth 7.5

End Depth 8.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Coltis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 ~~4 8oz jars~~ S.S. sleeves

1-4oz jar

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND — JF
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity — JF
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

ML

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color ~~5YR 4/6 yellowish red~~ JF
10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Nicole Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VGT

Sample ID SL-503-SA8-SB-0.0-0.5 Date/Time 7-15-13 1455

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fawbion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10R 3/6 red brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ PG Registration # 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
OG-503	8	7-15-13	7-15-13

Client: DOE	Project Name/#: ~~SSFL-65268-63378.1203.002.223.02331.GSPH3~~ SM 1a413	Total Depth: 4.2
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/Hedgpeth	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 12766	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PC Review & No.: Nikki Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm) 12240	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12260	SL-503 SAB-SB 0.0-0.5	1455	ML	~~SM~~ ~~sandy~~ silt, v.f.g. sa to sr sand 10-12% 10R 3/6 red brown, dry, loose
1			12272			ML	silt, moist, loose 10YR 8/3 light brown 1.5, picking up v.f.g. sa to sr sand
2		0.0	12266			ML	sandy silt, moist, loose 10YR 8/3 - clay lens 2.2-2.3', sandy silt below
3		0.0	12254	SL-503 SAB-SB 3.0-4.0	1505	ML	sandy silt, 10YR 8/3 sand 12% v.f.g. sa to sr silica sand - transition to silty sand 3.8-4.2
4		0.0	12248			SM	- 4.2 refusal in silty sand - decomposed sandstone bedrock 10YR 8/3
							- 3.7 refusal run #2
							- 3.5 refusal run #3

JF 5

OK JF

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VLS

Sample ID SL-503-SA8-SB-3.0-4.0 Date/Time 7-15-13 1505

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				CH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman PG Registration # 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G

Sample ID SL-504-SA8-SB-0.0-0.5 Date/Time 7-16-13 1145

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

V.C 7/16/13 Collection Method (circle one): (DPT) (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X JF
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5. sleeves

1-4 oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 R 6/3 brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-504	Subarea: 8	Date Started: 7-16-13	Date Completed: 7-16-13
Client: DOE	Project Name/#: ~~SSFL-65258-63376.1203.002.223.02231.SSPHS~~ SSPHS 13410		Total Depth: 3.5
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm F. Rodriguez	
GPS collected? (Yes) or No		Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 11785		Borehole diameter: 2.25	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Nulle Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	11774				
	1.5		11778	SL-504 SA8-SB	1145	ML	silt, dry, loose - 10R 6/3 brown
1		0.0	11778	0.0-0.5		ML	silt, dry, loose - 10R 6/3 brown
						ML/SM	1.5 transition silt to silty sand
2		0.0	12266			SM	silty sand, v.f.g. sa to sr silica sand 60% dry, loose 10YR 8/3 light brown
3		0.0	12246	SL-504 SA8-SB	1200	SM	silty sand dry to moist loose, 10YR 8/3 75% v.f.g. sa to sr silica sand
	3.5 T.D.	0.0	12248	~~3.0-4.0~~ 2.5-3.5 MS	jf	SM	silty sand, silt dropping out 85-90% v.f.g. sa to sr silica sand 10YR 8/3 light brown
				SL-804 SA8-SB 2.5-3.5	1210		- 3.5' refusal run #1 - 3.8' " run #2 - 3.6' " run #3 - 3.3' " run #4 - 3.6' " run #5 - 3.4' " run #6 - 3.2 " run #7 - 3.4 " run #8 ~~MS/MSD sample~~ 1210 jf

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.F

Sample ID SL-504-SA8-SB 2.5-3.5 MS Date/Time 7-16-13 1200

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5'

End Depth 3.5'

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) (FD) JF FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	X
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-9oz jar
6-16 oz jars
15-encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**

None Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By VHT

Sample ID SL-804-SA8-SB-2.5-3.5 ~~MS~~ Date/Time 7-16-13 1210

Matrix (circle one): (Soil) Sediment Water

Start Depth 2.5

End Depth 3.5'

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-504-SA8-SB 2.5-3.5 MS

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	X
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars
2 - Encore } 5 Encore total
3 - Encore
1 - 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Colts

Sample ID SL-505-SA8-SB 0.0-0.5 Date/Time 7-16-13 0855

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Colts

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves

1 - 4 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present (Yes) No

2. Percentage Fill (%) 100

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel FS,LT		N/A
Other _____		

Is Staining Present Yes (No)

Color 10YR 6/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-505	8	7-16-13	7-16-13

Client: DOE	Project Name/#: ~~SSFL-00208-00070,1200,002.223.02201.SSPH8~~ SM 10418	Total Depth: 10.8'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm R. Rodriguez	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: NA
Radiological Background: 11273	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No: Julie Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	11293				
.5		0.0	12254	SL-505 SA8-SB 0.0-0.5	0955	ML	silt, dry, 10YR 6/3 brown, trace root hairs + mottling
1		0.0	12260			GM	gravel-sand-silt - mixed fill + native
2		0.0	12266			GM	gravel-sand-silt / approx = amounts Fill
3		0.0	12>108			GM	Fill - mixed sand-gravel silt no stain/odor
							3.6 fill / native contact
4		0.0	~~11248~~ 12248	SL-505 SA8-SB 4.0-5.0	0930	ML	sandy silt, dry, cohesive, 10YR 6/8 brown yellow brown yellow
5		0.0	12248			CL	clay with silt (silty clay) moist, cohesive 5YR 4/6 yellow red)
6		0.0	12272			ML	silt with clay (clayey silt) moist compact, clays dropping out 6.6, 5YR 4/6 yellow red
7		0.0	12266			ML	sandy silt, moist, 5YR 4/6 yellow red
8		0.0	12284			SM	silty sand moist, 60% v.f.g. sa to sr silica sand 5YR 4/6 yellow red
9		0.0	12254			SM	silty sand, moist, 75% v. Fg. sa to sr silica sand 5YR 4/6 yellow red

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
DG-505	8	7-16-13	7-16-13
Project: SSFL		**Geologist:** J. Faubion	**Total Depth:** 10.8'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10		0.0	12266			SM	silty sand, 80% u.f.g. silica sand, sa to sr, 5YR 4/6 yellowish red
	10.8 TD		12266				- refusal 10.8' sandstone -10.5 refusal run #2 -10.8 refusal run #3

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cobb

Sample ID SL-505-SA8-SB-4.0-5.0 Date/Time 7-16-13 0930

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler J. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 6/8 brown yellow

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C

Sample ID SL-506-SA8-SB 0.0-0.5 Date/Time 7-18-13 0735

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves

2-4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-506	8	7-18-13	7-18-13

Client: DOE	Project Name/#: ~~SSFL-00268-63376:1203.002.223.02231.SGPH3~~ SM latha	Total Depth: 5.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm L. Rodriguez	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 12>63	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Nula Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
0		0.0	12>92	SL-506 SA8-SB 0.0-0.5	0735	ML	silt, 10R 3/6 red brown, compact stiff, dry - .5-1.0 fill gravel over impacted soil dry
.5	.5	0.0	12>84				
1			12>84			GM	silty gravel - roots, root hairs - relic organics sandstone clasts (angular) to 6mm ~~(FH-2)~~
2		0.0	12>60			ML	silt, 5YR 4/6 yellow red, dry, loose - grading through silt → silty sand 2.5-3.3
						SM	3.3 transition silt to silty sand
3		0.0	12>48				10R 3/6 red brown, dry - stiff Feox stain + caliche mottling pervasive
4		0.0	12>24	SL-506 SA8-SB 4.0-5.0	0750	SM	silty sand, 10R 3/6 - caliche mottling Feox stain - 70% v.fg. sa to Br silica sand
5		0.0	12>72			SM	silty sand 10R 3/6 - decomposed sandstone
5.3 TD			12>60			SM	5.3 TD + refusal - weathered sandstone

- 5.3 refusal #1
- 5.2 refusal #2
- 5.0 " #3

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.GA

Sample ID SL-506-SA8-SB-4.0-5.0 Date/Time 7-18-13 0750

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	~~X~~ JF
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	~~X~~ JF
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	X
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

5-En core

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong
2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7035

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V, GT

Sample ID SL-507-SA8-SB 0.0-0.5 Date/Time 7-16-13 1255

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5. sleeves

1-4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 5YR 4/6 red brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-507	Subarea: 8	Date Started: 7-16-13	Date Completed: 7-16-13
Client: DOE	Project Name/#: ~~SGFL-05250-03370.1203.002.223.02231.SSFH3~~ Sim 1414		Total Depth: 4.5'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm F. Rodriguez		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: NA
Radiological Background: 13 ≥ 100	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW:		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Mike Hoffman #7735		Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13≥86	SL-507			
	.5	0.0	12≥76	SA-8SB 0.0-0.5	1255	ML	silt, loose, dry 5YR 4/6 red brown - no stain/odor - moderate caliche mottles/root hairs
1			12≥66				
			~~12≥78~~ SF				
2		0.0	11≥96			ML	~~Sandy silt~~ Silt w/ Sand Sim 3/3 1/3 loose, dry, v.f.g. sa to sr sand 20% 10YR 8/3 light brown
3		0.0	11≥66	SL-507 SA-8SB 3.0-4.0	1310	SM	silty sand, 70% v.f.g. sa to sr silica sand 10YR 8/3 light brown
4		0.0	11≥30			SP-SM Sim 2/3 1/3	silty sand, silt dropping out, 85-90% v.f.g. silica sand 10YR 8/3 light brown - becoming moist at refusal - 4.5
		0.0	11≥54			SM	← 4.5 refusal run #1
							- 3.9 refusal " #2
							- 4.0 " #3

CDM Smith

BORING LOG AND SAMPLING RECORD

Page 1 of ___

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By N.SZ

Sample ID SL-507-SA8-SB-3.0-4.0 Date/Time 7-16-13 1310

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16oz jars

2 - Encore

1 ~~2~~ - 4oz jar

SM 7/6/13

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By 1.9.E

Sample ID SL-508-SA8-SB 0.0-0.5 Date/Time 7-16-13 1330

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0'

End Depth 0.5'

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves

2 - 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-508	Subarea: 8	Date Started: 7-16-13	Date Completed: 7-16-13
Client: DOE	Project Name/#: ~~SSFL-05268-68370.1203.002.223.02201.SSPHS~~ SM 1041a		Total Depth: 2.3
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm/Rodriguez		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: N/A
Radiological Background: 13 >86	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: [signature] #7735		Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12 >96	SL-508 SA-8-SB 0.0-0.5	1330	ML	silt, dry, compact 10YR 8/3 light brown - no stain/odor
	.5	0.0	12 >84				
1		0.0	12 66				
						ML/SM	sandy silt, dry, loose 10YR 8/3 light brown 2.1 - becoming silty sand 10YR 8/3 80% vf-g sand
2		0.0	11 66				- 2.3' refusal in sandstone
	TD 2.3						- 2.7 in run #2

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Ort

Sample ID SL-509-SA8-SB 0.0-0.5 Date/Time 7-18-13 0850

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 5.5. sleeves

2 - 4oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10R 3/6 red brown

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-509	8	7-18-13	7-18-13

Client: DOE	Project Name/#: ~~SSFL-05250-05370.1203.002.220.02231.SSPHS~~ (SM) (GAEA)	Total Depth: 4.7'
Company Name: CDM SMITH	Drill Contractor/Driller: Strayer Drilling	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 12286	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No: Mulli Hoffmon #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12285	SL-509 SA8 SB 0.0-0.5	0850	ML	silt, 10 R 3/6 red brown, dry, loose - no stain/odor
.5		0.0	12254				
1		0.0	12256			ML	1' silt, 10R 3/6 red brown, dense - dry
2		0.0	12254			ML	sandy silt 5R 4/6 yellow red, mod caliche mottling - moist
3		0.0	12248			ML	sandy silt, 5R 4/6 yellow red caliche droppings out
						SM	3.6 transition to silty sand
4		0.0	12266	SL-509 SA8 SB 4.0-5.0	0910	SM	silty sand, 10 YR 8/3 light brown.
		0.0	12254			SP	- poorly graded sand, decomposed bedrock Box stain 4.4-4.7
	4.7 TD						4.7' refusal sandstone 4.5 " #2 5.0 refusal #3

Mulli

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C.

Sample ID SL-509-SA8-SB-4.0-5.0 Date/Time 7-18-13 0900

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	X
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

1 X -4 oz jars

SM1613

5-EN core

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-510-SA8-SB 0.0-0.5 Date/Time 7-16-13 0830

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fawbion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encore	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5. sleeves

1-4 oz. jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 6/8 brown-yellow

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-510	Subarea: 8	Date Started: 7-16-13	Date Completed: 7-16-13
Client: DOE	Project Name/#: ~~SSFL-05268-08076.4208.002.220.02201.GSPH3~~ SM 10412		Total Depth: 0.6'
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm E. Rodriguez	
GPS collected? (Yes) or No		Drill Method: HA	Depth Drilled Into Bedrock: N/A
Radiological Background: 14281		Borehole diameter: 2.25"	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: Hand Auger
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: [signature] 7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
1		0.0	12273			GW/GM	-well graded gravel with silt-sandstone clasts up 10mm - angular to subround,
		0.0	12278				- 0.6 refusal - sandstone outcrop 5 YR 6/8 brown-yellow

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	HA: Hand Auger
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-511-SA8-SB-0.0-0.5 Date/Time 7-15-13 1415

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Coffis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5. sleeves

1-4 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** 0
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-511	8	7-15-13	7-15-13

Client: DOE	Project Name/#: ~~SSFL-65258,63376,1203,002,223,02281,SGPH9~~ SM 10-11a	Total Depth: 6.8'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm F. Rodriguez	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 13>87	Borehole diameter: 2.25"	
PID Background: 0.0 ~~13>84~~	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PO Review & No.: Julie Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	13>84 13>90	SL-511 SAB-SB 0.0-0.5	1415	ML	silt, dry, loose - trace v.f.g. silica sand - 10 R 3/6 red brown no stain/odor
1		0.0	12>42				
2		0.0	12>60			ML	silt, dry, loose - sand absent, no stain odor 10R 3/6 red brown no stain/odor
3		0.0	12>48			ML	silt, dry, loose 10 R 3/6 no stain/odor
4		0.0	12>36			ML	silt, dry, loose 10R 3/6 no stain/odor
5		0.0	12>60			ML	- color transition 4.6', 10R 3/6 to 10 YR 8/3 light brown - picking up 5% v.f.g. sand - sandy silt, moist
6		0.0	12>54	SL-511 SAB-SB 6.0-7.0	1430	ML	~~Sandy~~ silt, 10% v.f.g. sa to sr sand in silt - 10 YR 8/3, moist to 6.8' TD
7		0.0	12>84				- 6.8' refusal run #1 10YR 8/3 light brown
							- 7.0 refusal run #2

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.L

Sample ID SL-511-SA8-SB-6.0-7.0 Date/Time 7-15-13 1430

Matrix (circle one): (Soil) Sediment Water

Start Depth 6.0

End Depth 7.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				CH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) 0
3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Wolfson **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gtz

Sample ID SL-512-SA8-SB 0.0-0.5 Date/Time 7-17-13 0800

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves

1 - 4 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other

Moisture Condition (circle one)
(Dry) Moist Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-512	8	7-17-13	7-17-13

Client: DOE	Project Name/#: ~~66FL-66258-63376.4203.002.223.03231.SSPH3~~ SM 12418	Total Depth: 2'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongson F. Rodriguez	
GPS collected? (Yes) or No	Drill Method: HA	Depth Drilled into Bedrock: N/A
Radiological Background: 162 102	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW:	Sampling Method: HA
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Miller Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5	.5	0.0	~~197~~ 162 ~~155~~	SL-512 SA8-SB 0.0-0.5	0800	ML	silt, 10R 3/6 red brown, dry, loose no stain/odor - root hairs, mottles
1		0.0	162 160			ML	silt, 10R 3/6 red brown, dry, loose no stain/odor
2	TD	0.0	162 166			ML	sandy silt, 5R 4/6 yellow brown 20% v.f.g. sand/gr silica sand

refusal 2'.
" 1.8' run #2

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	HA: Hand augur
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	φ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gt

Sample ID SL-513-SA8-SB0.0-0.5 Date/Time 7-17-13 1345

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	~~X~~ V.C. 7/17/13
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves
2 - 4 oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				CH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 3/3 dark brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-513	8	7-17-13	7-17-13

Client: DOE	Project Name/#: ~~SSFL-65258-63376.4203.002.223.02234.SSPH8~~ SM 12413	Total Depth: 8.9'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm F. Rodriguez	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: 12277	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW:	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: T. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12273				
		0.0	11284	SL-513 SA-8 SB-0.0-0.5	1345	ML	.5 silt, 10YR 3/3 dark brown dry, cohesive, compacted
1		0.0	7248			ML	1'-silt, 10YR 3/3 as above
2		0.0	7236			ML	2' silt, 10R 3/6 red brown, moist compact
3		0.0	7246			ML	3' silt, 10R 3/6 red brown, moist compact
						ML	-3.4 transition to silty sand
4		0.0	7254	SL-513 SA-8 SB 4.0-5.0	1400	SM	4' silty sand, 10YR 3/3 dark brown V. F.g. sr/sa silica sand in silt
						SM	-4.2 ~~hard~~ transition to clayey silt
5		0.0	10254			ML	clayey silt 10YR 3/3 dark brown
						ML	to 5.5 - silty sand 10YR 8/3 5.5-6.0
6		0.0	10266			SM	6' silty sand, 10YR 8/3 light brown - clay absent, loose, moist
7		0.0	10254			SM	7' silty sand, 10YR 8/3 light brown ~~dry~~ moist mod. dense
8		0.0	10272	SL-513 SA 8 SB 8.0-9.0	1415	SM	8' silty sand 10YR 8/3 light brown moist dense-compact
						SW	8.4-8.9 grading to ~~poorly~~ graded sand poorly 10YR 8/3
TD		0.0	10284				- 8.9 refusal
							- 8.6 refusal run #2
							- 8.6 " run #3

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C.

Sample ID SL-513-SA8-SB-4.0-5.0 Date/Time 7-17-13 1400

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars

2-Encore

1 & - 4oz jars

SM 7/17/13

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Julia Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortez

Sample ID SL-513-SA8-SB-8.0-9.0 Date/Time 7-17-13 1415

Matrix (circle one): (Soil) Sediment Water

Start Depth 8.0

End Depth 9.0

Depth Units (circle one): Inches (Feet)

Check If Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	X
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16 oz jars

12 SF - 4 oz jars SF

5 - EnCore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH > 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH > 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Gk

Sample ID SL-514-SA6-SB 0.0-0.5 Date/Time 7-17-13 0855

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) JF Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X JF
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-514	Subarea: 8	Date Started: 7-17-13	Date Completed: 7-17-13
Client: DOE	Project Name/#: ~~SSFL-65268.03370.4208.002.223.02231.3SPH0~~ SM 1941a		Total Depth: 8.7'
Company Name: CDM SMITH	Drill Contractor/Driller: Strong Firm Rodger		
GPS collected? (Yes) or No	Drill Method: HA		Depth Drilled into Bedrock: N/A
Radiological Background: 13>98	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW:		Sampling Method: HA
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Julie Hoffman #7735		Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	12>84	SL-514 SA8-SB 0.0-0.5	0855	ML	silt, dry, loose 10R 3/6 red brown roots/organics -.5' thin wire mesh (plastic) - soil stabilization
1		0.0	13>54			ML	1' silt, dry, loose 10R 3/6 red brown - no stain/odor - becoming moist
2		0.0	13>60			ML	2' sandy silt, dense, moist mod. cohesive 10YR 6/3 brown - no stain/odor - 12/15% v.f.g. sr/sa silica sand - organics absent
3		0.0	12>96			ML	3' ~~Silty Sand~~ ~~Sandy Silt~~ Sm 7.5/13 15-17% v.f.g. silica sand in silt w/ trace clay (1-2%) 10R 6/8 brown yellow
4		0.0	13>60	SL-514 SA8-SB 4.0-5.0	0955	SM	4' silty sand, 10YR 8/3 light brown loose, moist - trace interstitial clay - weak caliche mottling (3-5%) JF
5		0.0	13>72			SM	5' silty sand, 10YR 8/3 light brown loose, moist - clay absent - trace caliche mottling v.f.g. silica sand 85%, silt 15% 5.3 contact bedrock
6		0.0	13>90			SC	6' clayey sand w/ silt 10YR 8/3 light brown, moist, loose - no stain/odor
7		0.0	13>108	SL-514 SA8-SB 7.5-8.5	1015	SC	7' clayey sand w/ silt 10YR 8/3 light brown moist, loose - no stain/odor
8		0.0	13>90			SC	8' clayey sand w/ silt 10YR 8/3 light brown moist, loose - decomposed ss bedrock
8.7 TD		0.0	13>60			SC	8.7' refusal in clayey sand - strong FeOx stain in some frags. 10YR 8/3 8.8' refusal - run #2

CDM Smith

BORING LOG AND SAMPLING RECORD Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr: no recovery
c: coarse	lt: light	rnd: rounded	v: very	HA = Hand auger
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs: below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-514-SA8-SB-4.0-5.0 Date/Time 7-17-13 0955

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check If Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

Parameters	Method	Analyze?
Metals	EPA 6010	X
	EPA 6020	X
	EPA 7471 (Soil)	X
	EPA 7470 (Water)	
Fluoride	EPA 300.0/9056	
SVOCs	EPA 8270	
TIC	EPA 8270	
PAHs	EPA 8270 SIM	X
1,4 Dioxane	EPA 8270 SIM	
Dioxins	EPA 1613	X
PCBs/PCTs	EPA 8082	
Perchlorate	EPA 314.0/331	
Perchlorate Confirmation	EPA 6850/6860	
pH	EPA 9045 (Soil)	X
	EPA 9040 (Water)	
Hexavalent Chromium	EPA 7196/7199	
Herbicides	EPA 8151	X
Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends; Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves
1 - 4oz jar
2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		(SM)	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10 YR 8/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Wolfgram **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J.Fab

Sample ID SL-514-SA8-SB-7.5-8.5 Date/Time 7-17-13 1015

Matrix (circle one): (Soil) Sediment Water

Start Depth 7.5

End Depth 8.8

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT Slide Hammer (Hand Auger/Slide Hammer) Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	X
	Pesticides	EPA 8081	X

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves
1-4oz jar
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH ≤ 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH ≤ 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				(SC)	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes No

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one)
   None Slight Strong
2. Odor Description (circle one)
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature _____ PG Registration # 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Gz.

Sample ID SL-515-SA8-SB 0.0-0.5 Date/Time 7-17-13 1050

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Curtis

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5. sleeves

1-4 oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 3/3 dark brown

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-515	Subarea: 8	Date Started: 7-17-13	Date Completed: 7-17-13
Client: DOE	Project Name/#: ~~SGFL-65250-68876.4203.002.223.02231.CGPHS~~ SM 12410		Total Depth: 14'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm F. Rodriguez		Depth Drilled into Bedrock: N/A
GPS collected? (Yes) or No	Drill Method: DPT		
Radiological Background: 11786	Borehole diameter: 2.25"		Sampling Method: DPT
PID Background: 0.0	Depth to GW: N/A		
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	RG Review & No.: Mike Hoffman #7735		Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	12781	SL-515 SA8-SB 0.0-0.5	1050	ML	.5 silt 10YR 3/3 dark brown, dense compacted - trace caliche mottling
1		0.0	12778				
		0.0	12754			GM	1' dry silty gravel, dry, loose 10YR 6/3 brown (roadmix gravels + silt to 1.5' No Fill
2		0.6	12790			ML	silt, dense compacted moist 10YR 3/3 dark brown
3		0.0	12790			ML	silt, as about 10YR 3/3
							- 3.5 color transition 10YR 3/3 to 10R 3/6 red brown
4		0.0	12108	SL-515 SA-8-SB 4.0-5.0	1105	ML	silt, 10R 3/6 red brown dense compacted relic root mottles, trace caliche - grading to clayey silt 4.5
5		0.0	12102			ML	clayey silt, root mottles prevalent 10R 3/6 red brown
6		0.0	12108			ML	clayey silt, root mottles 10R 3/6 red brown, moist, dense, compact
7		0.0	12790			SC	clayey sand, root mottling absent 10YR 6/8 brown yellow - dense compact, moist
8		0.0	12270			CL	silty clay 10YR 6/8 brown yellow compact, moist, dense
9		0.0	12154	SL-515 SA8-SB 9.0-10.0	1120	CL	silty clay 10YR 6/8 brown/yellow compact, moist, dense

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-515	Subarea: 8	Date Started: 7-17-13	Date Completed: 7-17-13
Project: SSFL		Geologist: J. Fashion	Total Depth: 14'

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10		0.0	12260			CL	silty clay 10YR 6/8 yellow brown moist, dense, compact
11		0.0	12254			CL	silty clay as above 10YR 6/8 yellow brown, moist, dense
12		0.0	12272			CL	silty clay 10YR 6/8 yellow brown - moist dense compact
							12.5 grading to sandy clay
13		0.0	12266			CL	sandy clay - 10YR 6/8
							13.2 clays dropping out
						SW	well graded sand 10YR 8/3
14	TD	0.0	12260	SL-515 SA8-SB 14.0-15.0	1135	SW	well graded sand v. fg sa/sr sand 10YR 8/3 light brown
							14' refusal #1
							15.3 refusal #2
							15.7 REFUSAL #3

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Coates

Sample ID SL-515-SA8-SB 4.0-5.0 Date/Time 7-17-13 1105

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Coates

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	X JF
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars

2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature Mike Hoffman I **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By J.Fa

Sample ID SL-515-SA8-SB 9.0-10.0 Date/Time 7-17-13 1120

Matrix (circle one): (Soil) Sediment Water

Start Depth 9.0

End Depth 10.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 6/8 brown yellow

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature Mike Hoffman PG Registration # 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-515-SA8-SB 14.0-15.0 Date/Time 7-17-13 1135

Matrix (circle one): (Soil) Sediment Water

Start Depth 14.0

End Depth 15.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	X
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars

2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes No

Color 10YR 8/3

Odor

1. Odor Strength (circle one)
   (None) Slight Strong
2. Odor Description (circle one)
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Gt

Sample ID SL-516-SA8-SB0.0-0.5 Date/Time 7-19-13 0800

Matrix (circle one): Soil | Sediment | Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches | (Feet)

Check if Composite ☐

Collection Method (circle one): DPT | (Slide Hammer) | Hand Auger/Slide Hammer | Trenching | Sediment

QC Type (circle one): (N) | FD | FB | RB

Parent Sample ID N/A

Field Geologist J. Fagbion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-9.5. sleeves

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		(ML)	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 8/3

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-516	Subarea: 8	Date Started: 7-19-13	Date Completed: 7-19-13
Client: DOE	Project Name/#: ~~98FL-65259.63378.4209.002.223.02234.66PH3~~ SM Jania		Total Depth: .5 '
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm / T. Rodriguez		
GPS collected? (Yes) or No	Drill Method: HA		Depth Drilled into Bedrock: N/A
Radiological Background: 13278	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: HA
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Mike Hoffman #7735		Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5 .7		0.0 0.0	14289 14278	SL-516 SA-8 SB 0.0 -0.5	0800	ML	Silty Sand Sand 5% Silt 5% Sm 10YR 8/3 yellow brown 20/80 10% .5 refusal #1 refusal # 2.7

JF

CDM Smith

BORING LOG AND SAMPLING RECORD

Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

XXX
SB1314060

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.Cs

Sample ID SL-517-SA8 SB 0.0-0.5 Date/Time 7-19-13 0930

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - S.S. sleeves
2 - 4 oz jars

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 YR 3/3 dark brown

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): (Dry) Moist Wet

PG Signature _____ **PG Registration #** _____

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DC-519(577)	Subarea: 8	Date Started: 7-19-13	Date Completed: 7-19-13
Client: DOE	Project Name/#: ~~SOFL-65288-03376,4203,002,223.02231.3SPH0~~ SM 18412		Total Depth: 4.2'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm Rodgers		
GPS collected? Yes or No	Drill Method: DPT		Depth Drilled into Bedrock: N/A
Radiological Background: 13281	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735		Geologist:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	13282				
.5		0.0	14254	SL-517 SA 8 SB 0.0-0.5	0930	ML	.5 silt, dry, loose 10YR 3/3 dark brown - 100% silt, root hairs
1		0.0	15254				1' silt, dry, loose 10YR 3/3 dark brown 100% silt - root hairs / organics
2		0.0	15284			ML	silt, ~~dry~~, f moist loose 10YR 3/3 dark brown - 100% silt
						ML	2.5 grading to silty sand 0/60/40/0
3		0.0	15290			SM	silty sand, 10 R 3/6 red brown moist, strong caliche mottling
				SL-517 SA 8 SB 3.0-4.0	0940	SM	3.6 sharp transition to p.g. sand, v.f.g
4		0.0	15254			SP	100% sand 10YR 8/3 light brown
			15272			SP	4.0 10YR 8/3 SP sand - ~~80~~ v. granular decomp. sandstone
							-4.2 refusal
							-4.2 refusal #2
							-4.3 refusal #3

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

6 x/x/x/x % gravel/sand/silt/clay %

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G.F

Sample ID SL-517-SA8-SB 3.0-4.0 Date/Time 7-19-13 0940

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.0

End Depth 4.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars
1-4oz jar
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**
   (None) Slight Strong

2. **Odor Description (circle one)**
   Organic Petroleum Chemical
   (N/A) Other _____

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C

Sample ID SL-518-SA8-SB 0.0-0.5 Date/Time 7-19-13 0820

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	~~X~~ V.C 7/19/13
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves, 1-2-4oz jars

~~1-4oz jar #~~ JF,

~~2-8oz~~ 1P

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other: _____		

Is Staining Present Yes (No)

Color 10 YR 8/3 light brown

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other: _____

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-518	Subarea: 8	Date Started: 7-19-13	Date Completed: 7-19-13
Client: DOE	Project Name/#: ~~SSFL-65258-03370.1200.002.229.02201.00PH0~~ SM Santa Susana		Total Depth: 5.0
Company Name: CDM SMITH		Drill Contractor/Driller: Strosnider Drilling	
GPS collected? (Yes) or No		Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 13767		Borehole diameter: 2.25"	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: Mike Stoffregen #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	15248				
	.6			0820	0820 SA 8 SB 0.5	SP	silty sand, v.fg. sa to sr silica sand 10YR 8/3 light brown 80/20 sand/silt
1		0.0	14766			GM	1'- silty gravel (gravel-sand-silt) No Fill 10R 3/6, dry, loose - angular clasts to 6 mm (sandstone) - transitions to ML 1.8'
						GM/ML	
2		0.0	14760			ML	2' silt, 5YR 6/8 brown yellow caliche mottling, dry - compact 0/0/100/0
3		0.0	14760			ML	2.8' grading to sandy silt
						SM	3.2 grading to silty sand 5YR 6/8 brown-yellow moist, compact 0/70/30/0
4		0.0	14710	SC-518 SA 8 SB 4.0-5.0	0900	SM	4.0 silty sand 10YR 6/8 brown yellow - caliche mottling 0/85/15/0 %
						SP	4.4 fg. v.FA. silica sand 100% 10YR 6/3 brown
5	- TP	0.0	14742			SP	5.0 refusal #1
							4.3 refusal #2

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr: no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs: below ground surface

x/x/x/x = gravel/sand/silt/clay
0/0

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.G

Sample ID SL-518-SA8-SB 4.0-5.0 Date/Time 7-19-13 0900

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fanbion

Sampler V. Colts

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	X
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars
1-4oz jar
2-Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)
2. Percentage Fill (%) N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 6/3 brown

Odor

1. Odor Strength (circle one)
   (None) Slight Strong
2. Odor Description (circle one)
   Organic Petroleum Chemical
   (N/A) Other

Moisture Condition (circle one)
Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.C.F

Sample ID SL-519-SA8-SB0.0-0.5 Date/Time 7-18-13 1330

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fawbion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 5.5. sleeves

1 - 4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean Inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic Inorganic SILT with moderate to high plasticity
				CH	Fat Inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 3/3 dark brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-519	8	7-18-13	7-18-13

Client: DOE	Project Name/#: ~~GSFL-05260-00070.1209.002.220.00201.SSPH3~~ SM 1341a	Total Depth: 4, 5
Company Name: CDM SMITH	Drill Contractor/Driller: Strosnider Drilling	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 12>73	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: Julie Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12>89				.5'
.5		0.0	12>84	SL-519 SAB-SB 0.0-0.5	1330	ML	silt, 10YR 3/3 dark brown, moist loose - 100% silt
1			13>48				1' silt 10YR 3/3 compact - trace caliche 100%/6
2		0.0	13>42			ML	2.0 silt 10YR 3/3 dark brown, moist compact - light caliche mottling 100% silt
3		0.0	13>60			ML	10YR 3/3 silt - moist
				SL519 SAB-SB 3.5-4.5	1340	SP	3.0' sharp contact silt & p.g. sand below sand, p.g., 10YR 8/3 light brown
4		0.0	13>66			SP	sand, p.g., 10YR 8/3 light brown (decomposed sandstone) 100% v.f.g. silica sand
		0.0	13>78			SP	- 4.5 refusal
							- 4.4' refusal #2
							- 4.6' " #3

CDM Smith

BORING LOG AND SAMPLING RECORD

Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (uR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V.GA

Sample ID SL-519-SA8-SB 3.5-4.5 Date/Time 7-18-13 1340

Matrix (circle one): (Soil) Sediment Water

Start Depth 3.5

End Depth 4.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-16oz jars

2-Encore

~~1-4oz jar~~ JF

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present: Yes (No)
2. Percentage Fill (%): N/A
3. Fill Description (circle all that apply)

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other: _____		

Is Staining Present: Yes (No)

Color: 10YR 8/3 light brown

Odor

1. Odor Strength (circle one): (None) Slight Strong
2. Odor Description (circle one): Organic Petroleum Chemical (N/A) Other: _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature: [signature] PG Registration #: 7735

Additional Comments: N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Staff Mypel

Sample ID SL-520-SA8SB 0.0-0.5 Date/Time 7-18-13 1300

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Energetics	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP (circled)	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10YR 8/3 light brown

Odor

1. Odor Strength (circle one)

(None) Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID:	Subarea:	Date Started:	Date Completed:
DG-520	8	7-18-13	7-18-13

Client: DOE	Project Name/#: ~~SSFL-65258-68378.1205.002.280.00234.GSP118~~ SM Jarilla	Total Depth: 2.0'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm - F. Rodriguez	
GPS collected? (Yes) or No	Drill Method: DPT	Depth Drilled into Bedrock:
Radiological Background: 13 ≷ 90	Borehole diameter: 2.25"	
PID Background: 0.0	Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: [✓] MicroR [✓] Alpha/Beta [✓] Pancake	PG Review & No.: [signature] #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	13≷88	SL-526	1300	SP	Sand, poorly graded, dry, loose 10YR 8/3 light brown
		0.0	12≷76	SA-83B			-.5 refusal
				0.0-0.5			
1		0.0	12≷78			SP	Sand, p.g. dry, loose 10YR 8/3
2		0.0	12≷66			SP	Sand, pog. loose, dry - decomp bedrock 10YR 8/3
							-2.0 refusal

refusal #1 - 0.5
" #2 - 2.0
#3 1.9

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 1

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page ___ of ___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By V. Cortes

Sample ID SL-521-SA8-SB 0.0-0.5 **Date/Time** 7-19-13 0730

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler V. Cortes

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5,5. sleeves
1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. Is Fill Material Present Yes (No)

2. Percentage Fill (%) N/A

3. Fill Description (circle all that apply)

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 5YR 4/6 yellow red

Odor

1. Odor Strength (circle one)

None Slight Strong

2. Odor Description (circle one)

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID:	Subarea:	Date Started:	Date Completed:
DG-521	8	7-19-13	7-19-13

Client: DOE	Project Name/#: ~~SGFL-65859-63376,4969.002.023.00204.SGPH2~~ SM Trailer	Total Depth: 2'
Company Name: CDM SMITH	Drill Contractor/Driller: Strongfarm Rodriguez	
GPS collected? Yes or No	Drill Method: HA	Depth Drilled Into Bedrock: NA
Radiological Background: 14273	Borehole diameter:	
PID Background: 0.0	Depth to GW: NA	Sampling Method: HA
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No.: Mike Hoffman #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	14287	SL-521 SM70513	0730	ML	.5 ~~sandy~~ silt, 5R 4/6 yellow red, dry, loose ~~90% to 95%~~ - high organics (roots) 10/90/0 %
			15288	SAG-SB 0.0-0.5			
1		0.0	14268	SM70513 1		ML	~~Sandy Silt~~ Silt w/ Sand 10R 3/6 red brown 15/85/0% - root hairs, dry, loose silt
2	TD	0.0	14284			SP	2' p.g. sand - v.f.g. silica sand, sa to sr 10YR 8/3 light brown - decomposed bedrock 100/0/0
							2.0 refusal #1
							2.2 refusal #2

OIL JF

CDM Smith — **BORING LOG AND SAMPLING RECORD** — Page 1 of 1

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	HA = Hand auger
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

x/x/x % = sand/silt/clay

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

Page___of___

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By T. Bennett

Sample ID SL-522-SA8-SB 0.0-0.5 Date/Time 7-26-13 1250

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler T. Bennett

Analysis

	Parameters	Method	Analyze?
Solids	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Solids	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-S.S. sleeves

1-4oz jar

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 10 YR 3/3

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments _____

NA – Not Applicable

Location ID: DG-522	Subarea: 8	Date Started: 7-26-13	Date Completed: 7-26-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 19.8
Company Name: CDM SMITH	Drill Contractor/Driller: Strongarm F. Rodriguez		
GPS collected? (Yes) or No	Drill Method: DPT		Depth Drilled into Bedrock: N/A
Radiological Background: 11246	Borehole diameter: 2.25"		
PID Background: 0.0	Depth to GW: N/A		Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & No: Mike Hoffman #7775		Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	11210	SL-522		ML	SILT, 10YR 3/3 dk. brown, dry 100% ML
		0.0	11284	SA8-SB	1250		1' compact, no plas., No stain/odor
1		0.0	11296	0.0-0.5			1' FILL, angular gravel/dry sand 50/50%
2		0.0	11266			ML	2' SILT, 10R 3/6 red brown, moist dense, no plas, 100% ML
3		0.0	11248			ML	3' SILT, as above
4		0.0	11272	SL-522 SA8-SB 4.0-5.0	1320	ML	4' SILT, 10R 3/6 red brown, moist compact, no plas. 100% silt
5		0.0	11266			ML	5' SILT, 10R 3/6, moist, compact - mod. caliche mottling, no plas. 100% ML
6		0.0	11254			ML	6' SILT - as above 100% - stg. caliche mottling
7		0.0	11272			ML	7' SILT - as above 100% - stg. caliche mottling
8		0.0	11210			ML	8' SILT, - as above, caliche mottling dropping out 100% ML
9		0.0	11266			8.8	color Δ 10R 3/6 → 10YR 8/3 light brown 9' SILT, 10YR 8/3 light brown, moist, compact, no plas. 100% ML - mottling absent

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of 2

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-522	Subarea: 8	Date Started: 7-26-13	Date Completed: 7-26-13
Project: SSFL		Geologist: J. Faubion	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10		0.0	11242			ML	SILT, 10YR 8/3, moist, compact no plas., 100% ML - mottling absent
11		0.0	11242			ML	- as above
12		0.0	11284			ML	- as above
13		0.0	10254			ML	- as above
14		0.0	10254			ML	SILT, moist abus ML 100% no plas, organics absent - no mottling
15		0.0	10284			ML	SILT 10YR 8/3 as above
16		0.0	10266			ML	SILT - as above 100% ML
						ML/SP	-16.6 transition ML/SP
17		0.0	11248			SP	P.G. v. fg. silica sand 10 YR 8/3 light brown, loose, moist 100% SP
18		0.0	11254			SP	- as above
19		0.0	11248			SP	P.G. v. f. g sr to sa silica sand 10YR 8/3 - loose, moist, no plas
	1.9ft		11270				-19.8 refusal #1, -20.4 refusal #2 / 20.3 #3 100

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By T. Bennett

Sample ID SL-522-SA8-SB 4.0-5.0 Date/Time 7-26-13 1320

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler T. Bennett

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Other	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars

2 - Encore

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other _____		

Is Staining Present Yes (No)

Color 10 R 3/6 red brown

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other _____

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature _____ **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By Bennett

Sample ID SL-522-SA8-SB 0.0 0.5-DTSC Date/Time 7-24-13 1120

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): DPT (Slide Hammer) Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler P. Hartman

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	
	PCBs/PCTs	EPA 8082	
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Explosives	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

1-16 oz jar 7/24/13

1-8 oz jar

(DTSC split sample)

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND JF
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** _____

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel N/A

Other _____

Is Staining Present Yes No

Color 10 YR 8/3 light brown

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

(Dry) Moist Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments DTSC Split Sample

NA – Not Applicable

Location ID: DG-522	Subarea: 6	Date Started: 7-24-13	Date Completed: 7-24-13
Client: DOE	Project Name/#: ~~-ESPL-05258-03376.1203.002.223.02231.33PHS~~ SM Jama		Total Depth: .5
Company Name: CDM SMITH		Drill Contractor/Driller: Strongfirm	
GPS collected? Yes or No		Drill Method: SH	Depth Drilled Into Bedrock: N/A
Radiological Background: 12257		Borehole diameter: 2.25	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: SH
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		PG Review & No.: [signature] #7735	Geologist: J. Faubion

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
.5		0.0	12285 12248	SL-522 SAB-SB 0.0-0.5	1120	SM	S.P. sand, 10YR 8/3 light brown, w/ silt about 10 R 3/6 red brown gravel/sand/silt mix

CDM Smith **BORING LOG AND SAMPLING RECORD** Page 1 of ___

ABBREVIATIONS:				
amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By T. Bennett

Sample ID SL-523-SA8-5B 4.0-5.0 MS Date/Time 7-25-13 0820

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Fashion

Sampler T. Bennett

Analysis

	Parameters	Method	Analyze?
	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Encores	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	X
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

6-16 oz jars

6 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes (No)

Color 5YR 4/6 yellow-red

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Santa Susana Field Laboratory/94489

Location ID: DG-523	Subarea: 8	Date Started: 7-25-13	Date Completed: 7-25-13
Client: DOE	Project Name/#: ~~SGFL-65258-63376.4203.002.223.02231.33PI18~~ Sm Canada		Total Depth: 11'
Company Name: CDM SMITH		Drill Contractor/Driller: Strongarm Rodriguez	
GPS collected? (Yes) or No		Drill Method: DPT	Depth Drilled into Bedrock: N/A
Radiological Background: 12269		Borehole diameter: 2.25"	
PID Background: 0.0		Depth to GW: N/A	Sampling Method: DPT
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake		~~PG Review & No.~~ Millie Hoffman #7735	Geologist: JF

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12297				
			11296				
1		0.0	11266			ML	silt, 5YR 4/6 yellowred, moist, compact ~~0 0 0 100~~ JF 0 10 100 0
2		0.0	11254			ML	silt 5YR 4/6 - moist ~~0 10 0 100~~ - moist, compact
3		0.0	11272			ML	silt 5YR 4/6 - moist 0 0 100 0 ~~0 0 0 0 100~~ - no caliche mottling noted
4		0.0	11256	SL-523 SA8-SB 4.0-5.0MS	0820	ML	silt w/clay 5YR 4/6 0 10 80 10 - 4.5 color Δ 5YR 4/6 to 10YR 6/8 brown yellow
5		0.0	12272	~~SL-523~~ SA8-SB 4.0-5.0	0850	ML	silt w/clay ~~5YR 4/6~~ JF 10YR 6/8 0 10 80 10
6		0.0	12266			ML	silt, clay dropping out 10YR 6/8 moist, compact 0 10 80 10
7		0.0	12260			ML	silt w/clay (clayey silt) 0 10 90 10 - color Δ 10YR 6/8 to 10YR 3/3 dk brown
8		0.0	12262			CL	clay w/silt, 10YR 3/3 dk brown - moist, compact 0 0 15 85
9		0.0	11252			CL	clay w/silt 10YR 6/8 - moist, compact 0 10 15 85

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID:	Subarea:	Date Started:	Date Completed:
Project: SSFL		Geologist:	Total Depth:

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10		0.0	11/102			SP	P.G. sand, bleached, trace interstitial clay - caliche mottling 0/100/0/0 10YR 6/8
11		0.0	11/120			SP	P.G. sand, loose, vf-f. silica sand 11' refusal @ 1 10YR/6/8 0/100/0/0
							11.2 " @ 2
							11.6 " @ 3

CDM Smith

BORING LOG AND SAMPLING RECORD

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By T Bennett

Sample ID SL-823-SA8-SB 4.0-5.0 Date/Time 7-25-13 0850

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): N (FD) FB RB

Parent Sample ID SL-523-SA8-SB 4.0-5.0

Field Geologist J. Fasbird

Sampler T. Bennett

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Low Level	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	X
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Trace	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars

2 - En Core

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)

2. **Percentage Fill (%)** N/A

3. **Fill Description (circle all that apply)**

Asphalt Metal Plastic

Concrete Wood Glass

Igneous/Metamorphic Gravel (N/A)

Other _____

Is Staining Present Yes No

Color 5YR 4/6 yellow-red

Odor

1. **Odor Strength (circle one)**

(None) Slight Strong

2. **Odor Description (circle one)**

Organic Petroleum Chemical

(N/A) Other _____

Moisture Condition (circle one)

Dry (Moist) Wet

PG Signature Mike Hoffman **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By [signature]

Sample ID DG-524-SA8-SB 4.0-5.0 Date/Time 7-25-13 1000

Matrix (circle one): (Soil) Sediment Water

Start Depth 4.0

End Depth 5.0

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID N/A

Field Geologist J. Faubion

Sampler T. Bennett

Analysis

	Parameters	Method	Analyze?
Solids	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
	SVOCs	EPA 8270	X
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
Liquids	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	X
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	X
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
Sediment	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2 - 16 oz jars

2 - Encore

NA – Not Applicable

SSFL Phase 3 – Field Data Sample Sheet (Sample Descriptions)

Soil Classification (circle one)

MAJOR DIVISION			GROUP SYMBOL	LETTER SYMBOL	GROUP NAME
COARSE GRAINED SOILS CONTAINS MORE THAN 50% FINES	GRAVEL AND GRAVELLY SOILS MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVEL WITH < 5% FINES		GW	Well-graded GRAVEL
				GP	Poorly graded GRAVEL
		GRAVEL WITH BETWEEN 5% AND 15% FINES		GW-GM	Well-graded GRAVEL with silt
				GW-GC	Well-graded GRAVEL with clay
				GP-GM	Poorly graded GRAVEL with silt
				GP-GC	Poorly graded GRAVEL with clay
		GRAVEL WITH ≥ 15% FINES		GM	Silty GRAVEL
				GC	Clayey GRAVEL
	SAND AND SANDY SOILS MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE	SAND WITH < 5% FINES		SW	Well-graded SAND
				SP	Poorly graded SAND
		SAND WITH BETWEEN 5% AND 15% FINES		SW-SM	Well-graded SAND with silt
				SW-SC	Well-graded SAND with clay
				SP-SM	Poorly graded SAND with silt
				SP-SC	Poorly graded SAND with clay
		SAND WITH ≥ 15% FINES		SM	Silty SAND
				SC	Clayey SAND
FINE GRAINED SOILS CONTAINS MORE THAN 50% FINES	SILT AND CLAY	LIQUID LIMIT LESS THAN 50		ML	Inorganic SILT with low plasticity
				CL	Lean inorganic CLAY with low plasticity
				OL	Organic SILT with low plasticity
		LIQUID LIMIT GREATER THAN 50		MH	Elastic inorganic SILT with moderate to high plasticity
				CH	Fat inorganic CLAY with moderate to high plasticity
				OH	Organic SILT or CLAY with moderate to high plasticity
HIGHLY ORGANIC SOILS				PT	PEAT soils with high organic contents

Fill Material

1. **Is Fill Material Present** Yes (No)
2. **Percentage Fill (%)** N/A
3. **Fill Description (circle all that apply)**

Asphalt	Metal	Plastic
Concrete	Wood	Glass
Igneous/Metamorphic Gravel	(N/A)	
Other		

Is Staining Present Yes (No)

Color 10YR 6/8 brown yellow

Odor

1. **Odor Strength (circle one)**: (None) Slight Strong
2. **Odor Description (circle one)**: Organic Petroleum Chemical (N/A) Other

Moisture Condition (circle one): Dry (Moist) Wet

PG Signature [signature] **PG Registration #** 7735

Additional Comments N/A

NA – Not Applicable

Location ID: DG-524	Subarea: 8	Date Started: 7-25-13	Date Completed: 7-25-13
Client: DOE	Project Name/#: Santa Susana Field Lab/99489		Total Depth: 15.5'
Company Name: CDM SMITH	Drill Contractor/Driller: Stratagerm F. Rodriguez		Depth Drilled into Bedrock: N/A
GPS collected? Yes or No	Drill Method: DPT		Sampling Method: DPT
Radiological Background: 12250	Borehole diameter: 2.25"		Geologist: J. Faubion
PID Background: 0.0	Depth to GW: N/A		
Radiological Equipment Used: ✓ MicroR ✓ Alpha/Beta ✓ Pancake	PG Review & Nam: Julie Hoffman #7735		

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
		0.0	12250				
			12276				
1			12272			ML	silt, 10R 3/6 red brown, dry, loose no stain/odor 100% silt, trace organics
2			12276			ML	silt 10R 3/6 red brown dry, loose, 100% silt
3			12248			ML	silt, 10R 3/6 red brown, low plas., 100% ML — color Δ 10R 3/6 to 10YR 6/8 brown yellow
4			12254	SL-524 SA-8-SB 4.0-5.0	1000	ML	clayey silt, 10YR 6/8 brown yellow mod plas, moist, dense 0/0/70/30
5			12254			ML	clayey silt, 10YR 6/8 brown yellow - mod plas, moist, dense 0/0/60/40
6			12242			CL	clay w/silt 10YR 6/8 brown yellow, - mod plas, moist, dense 0/0/30/70
7			12260			CL	clay w/silt as above 0/0/30/70 — color Δ 10YR 6/8 to 5YR 4/6
8			12272			CL	yellow-red clay w/silt 5YR 4/6, clay % picking up, moist, dense, mod. plas 0/0/20/80
9			272			CL	clay w/silt 5YR 4/6 moist, mod plas., dense - as above 0/0/20/80

CDM Smith

BORING LOG AND SAMPLING RECORD

ABBREVIATIONS:

amt: amount	gr: grained	pg: poorly graded	t: trace	nr:no recovery
c: coarse	lt: light	rnd: rounded	v: very	
dk: dark	m: medium	sa: subangular	wg: well graded	
f: fine	mod: moderate	sr: subrounded	ϕ: diameter	bgs:below ground surface

Location ID: DG-524	Subarea: 8	Date Started: 7-25-13	Date Completed: 7-25-13
Project: SSFL		Geologist: J. Faubion	Total Depth: 15.5

Depth (feet) bgs	Recovery (feet)	PID (ppm)	Radiological (µR/cpm)	Sample Name	Sample Time	USCS	Description of Materials
10			11266			CL	clay w/silt 5YR 4/6 moist, mod plas., dense 0/0/40/60 - clay dropping out
11			11260			ML	silt w/clay 5YR 4/6, moist, mod plastic, 0/0/60/40
12			11266			ML	silt w/clay 5YR 4/6, moist, mod. plastic 0/0/60/40 -as above
13			11278			SM	silty sand, v.f.g. silica sand, in silt color change to 10YR 6/8 - moist, loose - no stain/odor
14			11260			SM	silty sand
						SP	S.P. sand, loose, moist 0/70/30/10
							- lens interbedded clay in SP sand 14.5-14.8
15			11264			SP	S.P. v.f.g. saltgr silica sand
						SM	(decomp. ss) 0/10/10/0
15.5 TP			11276				- 15.5 refusal #1
							- 15.2 " #2
							- 15.2 " #3

CDM Smith

BORING LOG AND SAMPLING RECORD

Page__of__

SSFL Phase 3 – Field Sample Data Sheet

CDM Smith

FSDS Checked By A Bennett

Sample ID SL-525-SA8-SB-0.0-0.5 Date/Time 7-25-13 1305

Matrix (circle one): (Soil) Sediment Water

Start Depth 0.0

End Depth 0.5

Depth Units (circle one): Inches (Feet)

Check if Composite ☐

Collection Method (circle one): (DPT) Slide Hammer Hand Auger/Slide Hammer Trenching Sediment

QC Type (circle one): (N) FD FB RB

Parent Sample ID _____

Field Geologist J. Faubion

Sampler A. Bennett

Analysis

	Parameters	Method	Analyze?
Metals	Metals	EPA 6010	X
		EPA 6020	X
		EPA 7471 (Soil)	X
		EPA 7470 (Water)	
	Fluoride	EPA 300.0/9056	
SVOCs	SVOCs	EPA 8270	
	TIC	EPA 8270	
	PAHs	EPA 8270 SIM	X
	1,4 Dioxane	EPA 8270 SIM	
	Dioxins	EPA 1613	X
	PCBs/PCTs	EPA 8082	X
	Perchlorate	EPA 314.0/331	
	Perchlorate Confirmation	EPA 6850/6860	
	pH	EPA 9045 (Soil)	X
		EPA 9040 (Water)	
	Hexavalent Chromium	EPA 7196/7199	
	Herbicides	EPA 8151	
	Pesticides	EPA 8081	

	Parameters	Method	Analyze?
VOCs	VOCs	EPA 8260	
	1,4 Dioxane	EPA 8260 SIM	
	TPH-GRO	EPA 8015	
	TPH-EFH	EPA 8015	X
	Glycols	EPA 8015	
	Alcohols	EPA 8015	
	Terphenyls	EPA 8015	
	Nitrates	EPA 300.0/9056	
	Energetics	EPA 8330	
	Cyanide	EPA 9012	
	Formaldehyde	EPA 8315	
	NDMA	EPA 1625	
	Organotin	NOAA Status and Trends, Krone et al.	
	Methyl Mercury	EPA 1630	

2-5.5, sleeves

1-4oz jar

NA – Not Applicable