NEPA COMPLIANCE SURVEY #249

				Project Infe	ormation			
Project '	Title:	Down Hole	Seismic	Source	68-SX-11		Date:	10-26-2009
DOE	ode:						Contractor Code:	8067.742
Project I	.ead:	Mike Curtis						
 What are impacts' What is What is What ma 	e the en ? the lega the dura ajor equi	verview vironmental I location? tion of the project? ipment will be used rig, drilling rig,	will be powered by the 8 surrounding Environmental Imp Location - Tool will wells Duration - 3 month	y a self-containe wells. pact - There wil Il be installed in ths	ed, electric driven, Il be no environme 68-68-Sx-11. Pro	, surface, hydra ental impact on l aduction will be I	ource set in well 68-68-S ulic unit. Production data the surface or subsurface logged at the 8 surrounce Vater truck to top up the	a will be logged at ee.

The table below is to be completed by the Project Lead and reviewed by the Environmental Specialist and the DOE NEPA Compliance Officer. NOTE: If Change of Scope occurs, Project Lead must submit a new NEPA Compliance Survey and contact the Technical Assurance Department.

		mpac ticipat		If YES, then complete below
Water Quality	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed project present potential for impacts on water resources or water quality?		Ø		
Does the project affect surface water quantity or quality under both normal operations and accident conditions?				
Does the proposed project affect groundwater quantity or quality under both normal operations and accident conditions?				
Will the project area include "Waters of the State?"		×		
Will the project area require a Corps of Engineers permit?				

NEPA COMPLIANCE SURVEY

		mpact		If YES, then complete below.
Geology & Soils	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed project present potential for impacts related to geology or soils?				
Does the proposed project alter, excavate or otherwise disturb land area consistent with other land use and habitat area?		×		
Is the proposed project likely to impact local seismicity?		×		Energy imparted into the subsurface is very localized and extremely weak so it will not impact the local seismicity
If the project involved disturbance of surface soils, are erosion and storm water control measures addressed?				Best management practices will be followed to prevent erosion.
Air Quality	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed action present potential for impacts on ambient air quality under both normal and accident conditions?		\boxtimes		The hydraulic unit is electrically powered
Are potential emissions (gases and/or airborne particulates including dust) outside of the normal scope for oil field operations?		⊠		
Does the project present risk to human health and the environment from exposure to radiation and hazardous chemicals in emissions?				Al compressed gas cylinders will be secured to a permanent structure to prevent spills. MSDS must be available at location and TAD
Is the project subject to New Source Performance Standards?		×		
Is the project subject to National Emissions Standards for Hazardous Air Pollutants?		⊠		
Is the project subject to emissions limitations in an Air Quality Control Region?		\boxtimes		

2

NEPA COMPLIANCE SURVEY

	Impa Antic	cts ipate	17	If YES, then complete below.
Wildlife and Habitat	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed action present potential for impacts on wildlife or habitat?				
Does the project impact state or federally listed threatened and endangered species?		×		
Human Health Effects	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed project present potential for effects on human health? e.g.: Hanta virus, radiological exposure, or chemical exposure (must provide MSDS)				There may be a small tank of compressed nitrogen gas which will be stored, secured and utilized an accordance with best management practices.
Transportation	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Does the proposed project involve transportation of radiological sources or hazardous materials (including explosives)?		Ø		
Waste Management and Waste Minimization	Yes	No	NA	If the anticipated impact might be unacceptable, recommend mitigation measures:
Are pollution prevention and waste minimization practices needed in the proposed project?				There may be a small tank of compressed nitrogen gas which will be stored, secured and utilized an accordance with best management practices.
Does project plan establish procedures in compliance with local, state and/or federal laws and guidelines affecting the generation, transportation, treatment, storage or disposal of hazardous and other wastes?				A JSA will be completed at the start of each workday. SOPs will be followed and reviewed for compliance with State and local regulations

NEPA COMPLIANCE SURVEY

	Impacts Anticipated?				If YES, then complete bel			
c	ultural Impac	at	Yes	No	NA	unacceptable, re	ted impact might be ecommend mitigation easures:	
Is there potential for impact on cultural (historic) resources?				×		Archeologist reviewe	ed with no negative impact	
Cor	nmunity Imp	act	Yes	No	NA	unacceptable, re	ted impact might be ecommend mitigation easures:	
Will the proposed proje auditory, visual, or other		significantly adve	erse 🗆					
Will the proposed proje community's use of pu	_			×				
Will the proposed proje community's access to				×				
NOTE: Topography	Map and Wet		uired to be a and specific				or Risk Assessment	
Are permits required?	If YES, list b	elow:				Yes	No 🗵	
	Section be	low to be reviewe	d by Environ	mental Sp	ecialis	t and DOE NCO.		
Adequate Mitigation M	easures Prov	rided?			Ade	quate Mitigation M	leasures Provided?	
	Yes	No			Yes	No		
Water Quality Impacts		□ Tr	ansportation Imp	oacts	×			
Air Quality Impacts	×		Waste Management Impacts					
"Wildlife and Habitat Impacts	⊠		cultural Impacts					
Geology and Soils Impacts		□ C	ommunity Impac	nmunity Impact				
Human Health Impacts		□ c	Categorical Exclusion		\boxtimes			
			Approvals					
Conditions: which are B5.12 W squeeze	to be drilled in Vorkover (oper cementing) of to the existing	n geological formation ations to restore pro an existing oil, gas,	ons that have o duction, such or geothermal	existing op as deeper well to res	erating v ning, plu store pro	wells gging back, pulling a	, and geothermal well, and resetting lines, and over operations will be uld adversely affect	
Contractor ESS&H	12.	34			Date 11-2-09			
Comments and Conditions:		(.						
as NEPA within the	Compliance C specified clas	Officer (as authorized	d under DOE of er regulatory r	Order 451. equiremen	(A), Ih	nave determined that	ing the proposed action, the proposed action fits nd the proposed action	
DOE NEPA CX 5 Compliance Officer	B 3.7	4 B5.12		21.6		Date ///	6/09	



Artificial Lift


VSH2[™] Nitrogen-Over-Hydraulic Pumping Unit

Weatherford's VSH2 nitrogen-over-hydraulic reciprocating rod pump is designed specifically for fields with heavy crude oil and wells with rod fall problems. Nitrogen-over-hydraulic technology lifts greater loads and, in most cases, uses less energy than conventional pumping units. The VSH2 pumping unit can accommodate polished rod loads up to 40,000 lb (18,144 kg) and has pump depths to 11,000 ft (3,353 m). Strokes per minute (SPM) can be changed with a simple turn of a knob.

Managing surface pumping assets is a key step in optimizing production from mature reservoirs. Weatherford's flexible reciprocating rod-lift systems feature the latest technology in pumping unit, rod pump, and sucker rod designs. The industry's only comprehensive, solutions-driven suite of artificial lift systems, products, and services ensures systems integration and full-service capabilities for optimal lift performance and return on investment.

Applications

- Lifting of heavy crude oil in pumpto-surface applications
- · Correction of rod fall problems
- · Testing of new and re-entry wells
- Short-term repairs
- Wells requiring large-bore pumps







VSH2™ Nitrogen-Over-Hydraulic Pumping Unit

Features, Advantages and Benefits

- Energy consumption, in most cases, is less than that of conventional pumping units. Nitrogen supplies approximately two-thirds of the lifting power, decreasing the horsepower requirement.
- · With only three moving parts (excluding the prime mover), the VSH2 unit offers low maintenance and high reliability. Maintenance consists of just one filter per year and the normal visual inspections required of any piece of equipment.
- The lightweight, compact, and uncomplicated design of the VSH2 unit minimizes site preparation, transportation, and setup costs.
- Easy, variable speed control provides greater flexibility in operating the equipment and adjusting to well conditions.
- Design provides versatility for pumping a wide range of wells.

Specifications

Performance Data


Unit model	60	120	150			
Maximum stroke	60	120	150			
(in./mm)	1,524	3,048	3,810			
Minimum stroke	24	52	72			
(in./mm)	610	1,321	1,829			
Maximum speed¹ (SPM)	9	8	7			
Maximum rod loads ²	35,000	40,	000			
(lb/kg)	15,876 18,144					
Cylinder size		4				
(in./mm)	101.6					

PPRL loads can vary, depending on speed (SPM).

Specifications

Overall Dimensions

Uni	it model	60	120	150		
A Width (ft/m)		5.1 1.5				
B Length (ft/m)		8.5 2.6				
C Shipping height (ft/m)		4.8				
С	Working height, 90° (ft/m)	5.2 6.2 1.6 1.9		4900		
С	Working height, vertical (ft/m)	6.9 9.6 2.1 2.9		1000		
D	Height, cylinder (fl/m)	13.1 4.0	21.3 6.5	23.1 7.0		
E	Height, pedestal (ft/m)	12.0 18.0 3.7 5.5		21.2 6.5		
F	Shipping width, mast (in./mm)	26.0 660				
G	Width, mast (in./mm)	18.5 470				



68-SX-11

