



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Multifamily Ventilation – Best Practice?

**Dianne Griffiths**  
**April 29, 2013**



# Presentation Outline

---

- Basic Objectives
- Exhaust Systems
- Make-up Air Systems



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Two Primary Ventilation Objectives

---


- 1) Providing Fresh Air - *Whole-House*
- 2) Removing Pollutants - *Local Exhaust*

Our goal is to find the simplest solution that satisfies both objectives while minimizing cost and energy impacts.

Common Solution: Align local exhaust with fresh air requirements  
(*Ex: 25 Bath + 25 Kitchen*)

# Exhaust-Driven Fresh Air Design

- Exhaust slightly depressurizes the units
- Outside air enters through leaks, cracks, or planned inlets
- Widely used in the North



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Multifamily Ventilation Best Practice

---

- Step 1: Understand ventilation requirements
- **Step 2: Select the simplest design that can achieve both air quality and energy objectives**
- Step 3: Build a tight building
- Step 4: Pay attention to installation quality
- Step 5: Check to make sure ventilation works
- Step 6: Educate users




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872






# Exhaust: Central and Unitized

## Central Exhaust



## Unitized Exhaust



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Standard Central Exhaust Practice

---

- Roof or mushroom fans
- Vertical shaft with horizontal take-offs
- Sidewall or ceiling grilles at each floor
- Continuous operation




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Mechanical Designers' Intent

- **Balancing damper** → transferring responsibility to balancing contractor
- Many grilles, many floors, relatively low flow targets, plus wind and weather on balancing day = balancing is difficult




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



Consortium for Advanced Residential Buildings



# Automatic Balancing Dampers



Balance in two ways:


- Provide restriction in size of opening (increase static pressure)
- Dynamically self-adjust to changes in the system (automatic balancing)



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Duct Leakage



Register connections can be the largest set of leaks



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Best Practice

---

- Include performance specifications for duct tightness in construction documents
- Call out specific details to be sealed: all joints, takeoffs, connections, registers, etc., etc.



Then test for leakage:

- Good =  
10 CFM50/register
- Better =  
5 CFM50/register



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Duct Sealing Methods

---



Aeroseal® aerosol duct sealant sticks to holes in ductwork and seals them



**Steven Winter Associates, Inc.**  
Improving the Built Environment Since 1972




Consortium for Advanced Residential Buildings





Working elevators and power on the roof are helpful.

- Prepare a plan.
- Check weather report!





# Mastic Spray

---



Rotating spray head  
applies mastic directly  
to leaks identified by  
camera

-Simple concept  
-Very effective on  
straight shafts



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# In-Unit Exhaust Systems

---



Small fans, relatively low flow (50-100 CFM), low power consumption, easier to balance floor to floor




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# In-Unit Ventilation Quality Control

---

- Duct sealing
- Avoid kinks, long duct runs; use rigid duct



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Exhaust System Design Parameters

---

## Central Systems

- Constant Air Regulating (CAR) dampers to balance flows
- **Airtight ductwork**, including fan and grille connections
- **Tightly compartmentalized units**

## Unitized Systems

- ENERGY STAR fans with variable speed where appropriate
- Short straight duct runs
- **Tightly sealed ducts**
- **Tightly compartmentalized units**



# Exhaust-Driven Make-up Air Strategies

---

## Current Research Focus

Where is the make-up air coming from?

- Leaks
- Trickle vents
- Make-up air supplied to corridor
- Vent or fan within PTAC



# Trickle Vents - Designed Inlets

---

- Intentional openings in building envelope that allow a trickle of air into buildings in response to pressure differential
- Trickle Vents often built into window frames



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Trickle Vents – Installed Performance

---

- Flow from trickle vents measured with hot wire anemometer in a building under actual operating conditions.
- Also measured inside/outside pressure difference across exterior window.




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Trickle Vent Airflow vs. Pressure Difference

Air flow at typical building operating pressures is expected to be about 5-10 CFM per trickle vent – a “trickle”



AAMA = American Architectural Manufacturers Association




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



Consortium for Advanced Residential Buildings


# Comparison of trickle vents in two buildings



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Airflow patterns in a tight unit with trickle vents




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972





# Airflow patterns with trickle vents



Steven Winter Associates, Inc.  
 Improving the Built Environment Since 1972



# This Year's Research Plan

---

1. Evaluate performance of more systems in more buildings
  - Corridor supply systems
  - Trickle vents
  - PTAC outside air vents
2. Measure pressure variation within buildings and apartments over time
  - 2 weeks in winter and 2 weeks in summer





Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Earlier Testing

- Airflow through gaps in apartment door




**Steven Winter Associates, Inc.**  
Improving the Built Environment Since 1972



# Latest Test Rig

---



Powered Flow Hood  
Energy Conservatory's FlowBlaster™





Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



# Other Make-up Air Inlets

---



**Steven Winter Associates, Inc.**  
Improving the Built Environment Since 1972




Consortium for Advanced Residential Buildings



# Variability in Driving Forces

---



Typical for Winter – But what about summer, windy days, ...




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



Consortium for Advanced Residential Buildings

# Pressure Monitoring

---




Steven Winter Associates, Inc.  
Improving the Built Environment Since 1872



# Pressure Monitoring

---



**Steven Winter Associates, Inc.**  
Improving the Built Environment Since 1972



# Best Practice Summary

---

- Step 1: Understand ventilation requirements
- **Step 2: Select the simplest design that can achieve both air quality and energy objectives**
- Step 2: Build a tight building
- Step 3: Pay attention to installation quality
- Step 4: Check to make sure ventilation works
- Step 5: Educate users



Steven Winter Associates, Inc.  
Improving the Built Environment Since 1972



Consortium for Advanced Residential Buildings

# Thank You

