

Exterior Insulation & Overclad Retrofits

Residential Energy Efficiency Stakeholder Meeting

March 2, 2012 – Austin, TX



Exterior Insulation

- Incredible practical experience:
 - New construction – nearly a century
 - Retrofit applications – many decades



1980s ON – a “weird” builder



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

1990s ON – a “good” builder



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

2000s ON – a “typical” builder



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

2000s ON – another “typical” builder



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

2000s MA – a “High-R” assembly



Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

1990s – “modest” retrofit



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

2000s – “High-R” retrofit



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

1980s – faced semi-rigid fiberglass



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX


2000s – masonry “High-R” retrofit



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

2000s – masonry rockwool retrofit



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX


Gaps?

- Practice
 - Lots of practical experience
- Theory
 - Misconceptions
 - Missing context
- Codes & Standards
 - Playing catchup



Perceived Benefits

- Increase overall thermal performance
- Minimize thermal bridges
- Improve air tightness
- Improve rainwater management
- Eliminate potential for air leakage condensation



Perceived Problems

- Moisture
 - Rainwater management
 - Vapor diffusion condensation
- Structural
 - Wind load (lateral & perpendicular)
 - Gravity load
- Fire
 - Lack of code accepted assemblies



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Work to Close Moisture Gaps

- BSC
- Private Industry (mfrs, builders, etc.)




Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Rainwater Management Details

- 62 details provide guidance on ext. insulation retrofits
 - Windows
 - Roofs
 - Balconies
 - Decks



Energy Efficiency & Renewable Energy

ROOF TO WOOD FRAME WALL - B

SCALE: 1-1/2" = 1'-0"


Field Testing & Demonstration



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Field Testing & Demonstration



Round1: Interior Wetting & Rain



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round1: Interior Wetting & Rain



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round1: Interior Wetting & Rain




Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round1: Interior Wetting & Rain (no XPS)




Round2: Exterior Wetting & Rain



Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round2: Exterior Wetting & Rain



Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round2: Exterior Wetting & Rain



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round2: Exterior Wetting & Rain



Round2: Exterior Wetting & Rain



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round2: Exterior Wetting & Rain



Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Round2: Exterior Wetting & Rain



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Remaining Moisture Gaps

- Hygric Redistribution:
is this effect significant enough to be
 - Useful?
 - Problematic?



Energy Efficiency &
Renewable Energy


Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Work to Close Structural Gaps

- BSC
- FSC and NYSERDA /SFA
- NAHB
- others



Lateral Wind Loads



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Lateral Wind Loads



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Perpendicular Wind Loads



- American Wood Council 2005 NDS

Fastener Type	Unthreaded Shank Diameter (in)	Withdrawal Capacity (W) per inch of thread penetration
#8 Wood Screws	0.164	82 lbs
#10 Wood Screws	0.190	96 lbs
#12 Wood Screws	0.216	109 lbs
1/4" Lag Screws	0.250	173 lbs


	#8 Wood Screw		#10 Wood Screw		#12 Wood Screw		1/4" Lag Screw	
	Furring Spacing (in)		Furring Spacing (in)		Furring Spacing (in)		Furring Spacing (in)	
Vertical Fastener Spacing	16"	24"	16"	24"	16"	24"	16"	24"
8"	148	99	172	115	195	130	301	200
12"	99	66	115	76	130	87	200	134
16"	74	49	86	57	98	65	150	100
24"	49	33	57	38	65	43	100	67




Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Gravity Loads (i.e. cladding loads)




- Begin with AWC TR-12
 - Dowel fastener connects 2 pcs of wood (with an empty space between them)



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX


Work by others (D. Deress et. al., WJE)




These researchers used 1/4" dia. Headlok screws and loaded the system to failure (1000-2000 lb/screw !)

Gravity Loads (i.e. cladding loads)

- Strut & tie model?
 - the space between the pieces of wood isn't empty, it's filled with insulation



Short-term Gravity Load Response



Energy Efficiency &
Renewable Energy


Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Short-term Gravity Load Response




Short-term Gravity Load Response

Total Load (lbs)		Load / ft2 (lbs)	Load/fastener (lbs)
120	Fiber Cement	3.8	8.6
370	Hard Coat Stucco	11.6	26.4
500		15.6	35.7
750	Adhered Stone	23.4	53.6
1000		31.3	71.4



Energy Efficiency & Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX



Short-term Gravity Load Response

- For 4" thick insulation w/ #10 screws
 - Material type has a small impact
 - Higher compressive strength insulation = less delta
- Current consensus allow 0.015" (1/64") deflection
- Too small relative to other movements (e.g. moisture)?

$$\Delta D = \frac{D_1(M_F - M_1)}{30(100)/S_T - 30 + M_1} \quad (13-3)$$

		Predicted change in dimension (in/1000)						
S _T (%)		7	Starting Moisture Content (%wt)					
D ₁ (in)		3.5	20	18	16	14	12	10
Ending MC (%wt)	20		0	17	34	51	68	86
	18		-17	0	17	34	51	69
	16		-33	-17	0	17	34	51
	14		-50	-34	-17	0	17	34
	12		-67	-50	-34	-17	0	17
	10		-84	-67	-51	-34	-17	0
	8		-100	-84	-68	-51	-34	-17
6		-117	-101	-84	-68	-51	-34	



Energy Efficiency & Renewable Energy

Short-term Gravity Load Response

- System capacities for 0.015" (1/64") deflection
 - EPS & XPS ~ 10 psf or 23 lb/fastener
 - Polyiso & MF ~ 13 psf or 29 lb/fastener
- Comparison to NYSERDA work
 - 5% yield from TR-12 w/ #10 screws & 4" space – 27 lb




Long-term Gravity Load Response



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX



Long-term Gravity Load Response

- Long term deflections
 - Extremely small (close to experimental error)
 - Can barely see creep under low (5 psf) load
 - Very little movement under high (20 psf) load
 - Influenced by lab temperature & humidity conditions?

- What initial deflection is acceptable?
- What long term deflection is acceptable?
- These must be considered separately



Remaining Structural Gaps

- Compare wider range of system tests to calcs
 - 5% TR-12
- What deflections are allowable?
 - Initial
 - Long-term
- Changing environmental conditions
 - e.g. moisture, temperature, etc.
 - How do these impact gravity load deflections?
 - Deflections vs other dimension changes?



Work to Close Fire Gaps

- Private Industry (mfrs)
 - e.g. Dow Thermax CI
- Little work has been done to close this gap
 - Not necessarily a performance problem rather a regulatory problem
 - Change in any element in an assembly requires a new test
 - \$20-50k / test



Exterior Insulation & Cladding Retrofits

Thank You




Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX


Test Hut Ext. Insul. w/ OSB

Panel 7: Exterior Insulation 2X6
(no poly/insulated sheathing)



Test Hut Ext. Insul. w/o OSB

Panel 10: Exterior Insulation 2X6
(no poly / no OSB / insulated sheathing)



Test Hut Ext. Insul. w/o OSB



Energy Efficiency &
Renewable Energy

Residential Energy Efficiency Stakeholder Meeting
March 2, 2012 | Austin, TX

Test Hut Ext. Insul. w/o OSB

