

ETA-TP004

Revision 3

Effective March 1, 1997

Electric Vehicle Constant Speed Range Tests

Prepared by

Electric Transportation Applications

Prepared by: _____ Date: _____

Jude M. Clark

Approved by: _____ Date: _____

Donald B. Karner

TABLE OF CONTENTS

1.0	Objectives	3
2.0	Purpose	3
3.0	Documentation	3
4.0	Initial Conditions and Prerequisites	4
5.0	Testing Activity Requirements	7
5.1	Range at 45 mph Steady Speed	7
5.2	Range at 60 mph Steady Speed	9
5.3	Range at Maximum Speed	10
5.4	Calibration of the Speedometer	11
5.5	Time on 3% Grade at 55 mph	12
6.0	Glossary	14
7.0	References	16

Appendices

Appendix A - 45 mph Constant Speed Range Test Data Sheet	17
Appendix B - 60 mph Constant Speed Range Test Data Sheet	19
Appendix C - Maximum Achievable Speed Range Test Data Sheet	21
Appendix D - Calibration of Vehicle Speedometer Test Data Sheet	23
Appendix E - Vehicle Metrology Setup Sheet	24
Appendix F - 3% Grade Test Data Sheet	25

1.0 Objective

The objective of this procedure is to identify proper methods for the control of constant speed range testing, as identified in SAE-J227a (canceled). These methods are not meant to supersede those of the testing facility, those specifically addressed by SAE Test Standards, nor of any regulatory agency who may have or exercise control over the covered activities.

2.0 Purpose

The purpose of this procedure is to identify acceptable methods for the implementation of a constant speed range test, similar to that identified in SAE J227a (canceled). The SAE J227a Recommended Practice, although canceled, established uniform procedures for testing electric battery-powered vehicles as a total system rather than a collection of its individual subsystems. This procedure shall collect and retain test data as specified in the EV America Technical Requirements.

3.0 Documentation

Documentation addressed by this procedure shall be consistent, easy to understand, easy to read and readily reproducible. This documentation shall contain enough information to "stand alone"; that is, be self-contained to the extent that all individuals qualified to review it could be reasonably expected to reach a common conclusion, without the need to review additional documentation. Review and approval of test documentation shall be in accordance with ETA-AC004, "Review of Test Results." Storage and retention of records during and following testing activities shall be completed as described in Procedure ETA-AC001, "Control, Close-out and Storage of Documentation."

4.0 Initial Conditions and Prerequisites

Prior to conduct of any portion of the testing, the following initial conditions and prerequisites shall be met. Satisfactory completion of these items shall be verified as complete and recorded on the Vehicle Road Load Test Data Sheet.

- 4.1 Personnel conducting testing under this procedure shall be familiar with the requirements of this procedure, and when applicable the appropriate SAE Test Instructions, Administrative Control Procedures, and be certified by the Program Manager, Test Manager or specific Test Engineer prior to commencing any testing activities.
- 4.2 All documentation required to complete the testing shall be completed, approved and issued (past it's effective date) prior to commencing the testing it addresses.
- 4.3 Road Testing
 - 4.3.1 Road tests shall be performed on a road or test track which is level to within 1%.

NOTE

Vehicles should be capable of standing for extended periods in extreme temperatures without danger of damage or failure of the vehicle or it's systems. This includes ambient air temperatures of 0-120°F , paved surface temperatures of greater than 150°F, and occupant compartment temperatures in excess of 170°F.

- 4.3.2 Battery temperatures at the beginning of the test shall be between 60°F and 120°F (16°C to 49°C).
 - 4.3.3 Ambient temperature during road testing shall be within the range of 40°F to 100°F (5°C to 38°C).
 - 4.3.4 The recorded average wind speed at the test site during the test shall not exceed 10 mph (16 km/h).
- 4.4 Vehicle shall be tested in its normal configuration with normal appendages (mirrors, bumpers, hubcaps, etc.). Certain items (hub caps, etc.) may be removed where necessary for safety on the dynamometer.
- 4.5 Vehicles shall be tested at curb weight plus 332 pounds. Consideration should be given to how adding instrumentation will affect the test weight and balance of the vehicle.
- 4.6 Tires provided with the vehicle shall be the standard tire offered by the Electric Vehicle manufacturer, and shall be inflated to the manufacturer's (placard) recommended cold inflation pressures. This pressure shall not exceed the maximum allowable pressure imprinted upon the tire's sidewall.
- 4.7 Normal manufacturer's recommended lubricants shall be employed.

- 4.8 Accessories shall not be used during testing activities.
- 4.9 Full charge conditions for the main propulsion batteries shall be established using the manufacturer's recommended charging procedure and equipment in accordance with ETA-TP008, "Battery Charging."
- 4.10 The following data shall be collected during conduct of the various tests specified by this procedure. Overall error in recording or indicating instruments shall not exceed $\pm 2\%$ of the maximum value of the variable being measured. Periodic calibration shall be performed and documented to ensure compliance with this requirement.
 - 4.10.1 Battery voltage versus time;
 - 4.10.2 Battery current versus time;
 - 4.10.3 Vehicle speed versus time;
 - 4.10.4 Distance versus time;
 - 4.10.5 Battery temperature versus time;
 - 4.10.6 Battery watts versus time;
- 4.11 Environmental conditions during the testing shall be recorded and include, at a minimum, the following:
 - 4.11.1 Range of ambient temperature during the test;
 - 4.11.2 Range of wind velocity during the test;
 - 4.11.3 Range of wind direction during the test.
- 4.12 Verify that Procedures ETA-AC006, "Vehicle Verification," and ETA-TP011, "Receipt Inspection," have been completed.
- 4.13 A description of the test route, road surface type and condition (SAE J688), and lengths and grades of test route, shall be recorded.
- 4.14 The date and starting and ending times shall be recorded.
- 4.15 The starting and ending vehicle odometer readings shall be recorded.
- 4.16 All instrumentation used in the test shall be listed on Appendix E, attached to the test data sheets/results, and shall include the following information:
 - 4.16.1 Manufacturer
 - 4.16.2 Model Number
 - 4.16.3 Serial Number
 - 4.16.4 Last Calibration date
 - 4.16.5 Next Calibration date
- 4.17 Any deviation from the test procedure and the reason for the deviation, shall be recorded in accordance with ETA-AC002.
- 4.18 The speed-time measuring device and other necessary equipment shall be installed so that they do not hinder vehicle operation or alter the operating

characteristics of the vehicle. Mounting will nominally be at the rear of the vehicle.

- 4.19 All documentation required to complete the testing shall be completed, approved and issued prior to commencing the testing it addresses.
- 4.20 During data reduction, the actual distance traveled and the corresponding DC Kilowatt-hour consumption shall be determined. These values are the 100% SOC mileage and kWh meter reading. These two values shall be used throughout the remainder of testing, and shall be the basis for determining SOC's less than 100%.
- 4.21 In addition to the formal completion of all sections of this procedure, Section 5.1 may be completed at additional times as requested by the ETA Program Manager or ETA Test Manager. [Additional tests may be completed to determine changes to the range capability of a vehicle, or if a vehicle's permanently installed instrumentation is suspected of mis-operation.

5.0 Testing Activities Requirements

NOTE

All steps shall be completed in the order written. Deviations from any step or requirement shall have the approval of the Program Manager or Test Manager in accordance with Procedure ETA-AC002, "Control of Test Conduct."

5.1 Range at 45 mph Constant Speed

The purpose of this section is to (1) Determine the maximum range the vehicle can achieve with the batteries fully charged (100% SOC), the vehicle loaded at curb weight plus 332 pounds, and operated at a constant 45 mph; and (2) Determine the correlation between the State of Charge indicator and the mileage driven (which will be used to establish partial SOC conditions in other protocols). Vehicles shall have a minimum range between charges of at least 50 miles when loaded with two 166-pound occupants (or equivalent) and operated at a constant 45 mph.

This testing shall be completed subject to the initial conditions and prerequisites stated in Section 4 of this procedure.

- 5.1.1 Instrument the vehicle to obtain, at a minimum, the data identified in Section 4.10. Calibrate the fifth wheel, as necessary.
- 5.1.2 Verify the traction battery is at fully charged (100% SOC).
- 5.1.3 Record time and the vehicle's odometer reading on Appendix A.
- 5.1.4 Adjust the vehicle's cold tire pressures to match the manufacturer's placard value, or the maximum cold inflation pressure imprinted upon the tire's sidewall, whichever is less.
- 5.1.5 From a standing start, accelerate the vehicle under its own power to a speed of 45 mph \pm 1 mph (72 km/h \pm 1.6 km/h). Speed and time may be recorded via a Data Acquisition System (DAS).
- 5.1.6 Each time the vehicle passes the lap marker, record the SOC meter reading and the odometer reading. Each reading shall be recorded in the smallest increment displayed by its respective indicator.
- 5.1.7 Maintain this speed without interruption until an average vehicle lap speed of at least 43 mph (69 km/h) cannot be maintained. If testing is being accomplished at FaAA, continue testing until the vehicle will not maintain 40 mph on the east bound straight-away. Record the final speed, odometer reading and time on Appendix A. (This may be recorded via a DAS.)

- 5.1.8 Pull the vehicle off to the side of the test track. Record the time, mileage, SOC meter and odometer reading on Appendix A. (Time may be recorded via a DAS.)
- 5.1.9 The mileage achieved during this test shall be recorded as the official range mileage for the vehicle being tested.

5.2 Range at 60 mph Constant Speed

The purpose of this section is to determine the maximum range the vehicle can achieve with the batteries fully charged (100% SOC), the vehicle loaded at curb weight plus 332 pounds, and operated at a constant 60 mph. This testing shall be completed subject to the initial conditions and prerequisites stated in Section 4 of this procedure.

- 5.2.1 Instrument the vehicle to obtain, at a minimum, the data identified in Section 4.10. Calibrate the fifth wheel, as necessary.
- 5.2.2 Verify the traction battery is at fully charged (100% SOC).
- 5.2.3 Record odometer reading and time on Appendix B.
- 5.2.4 Adjust the vehicle's cold tire pressures to match the manufacturer's placard value, or the maximum cold inflation pressure imprinted upon the tire's sidewall, whichever is less.
- 5.2.5 From a standing start, accelerate the vehicle under its own power to a speed of 60 mph \pm 1 mph (96 km/h \pm 1.6 km/h). Speed and time may be recorded via a Data Acquisition System (DAS.)
- 5.2.6 Each time the vehicle passes the lap marker, record the SOC meter reading and the odometer reading. Each reading shall be recorded in the smallest increment displayed by its respective indicator.
- 5.2.7 Maintain this speed without interruption until an average vehicle lap speed of at least 57 mph (91 km/h) cannot be maintained. If testing is being accomplished at FaAA, continue testing until the vehicle will not maintain 53 mph on the east bound straight-away. Record the final speed, odometer reading and time on Appendix B. (This may be recorded via a DAS.)
- 5.2.8 Pull the vehicle off to the side of the test track. Record the time, mileage, SOC meter and odometer reading on Appendix B. (Time may be recorded via a DAS.)

5.3 Range at Maximum Achievable Speed

The purpose of this section is to determine the maximum range the vehicle can achieve after the vehicle has been standing, not on charge, uncovered, on a simulated parking lot (blacktop, asphalt, etc.) for at least eight hours. The minimum high ambient temperature achieved during this period shall be 100°F. The batteries shall have been fully charged (100% SOC) prior to the standing period. The vehicle shall be loaded at curb weight plus 332 pounds, and operated at the vehicle's maximum achievable speed, or 80 mph, whichever is less. This testing shall be completed subject to the initial conditions and prerequisites stated in Section 4 of this procedure, as amended by this section.

- 5.3.1 The vehicle does not require instrumentation for this test. Odometer readings shall be sufficient to determine range.
- 5.3.2 Verify the traction battery is at fully charged (100% SOC).
- 5.3.3 Record odometer reading and time on Appendix C.
- 5.3.4 Adjust the vehicle's cold tire pressures to match the manufacturer's placard value, or the DOT sidewall pressure, whichever is less.
- 5.3.5 Identify the maximum speed the vehicle achieved when tested to ETA-TP002. Record the lesser of this value or 80 mph on Appendix C.

NOTE

The vehicle shall be operated at the lower of the two speeds in Step 5.3.5. Transitory operation above 80 mph due to track attitude is allowed.

- 5.3.6 From a standing start, accelerate the vehicle under its own power at wide open throttle to the maximum speed determined in Step 5.3.5 (above). Speed and time may be recorded via a Data Acquisition System (DAS.)
- 5.3.7 Each time the vehicle passes the lap marker, record the SOC meter reading and the odometer reading. Each reading shall be recorded in the smallest increment displayed by its respective indicator.
- 5.3.8 Maintain this speed without interruption until a minimum vehicle speed of at least 40 mph cannot be maintained. Record the final speed, odometer reading and time on Appendix C. (This may be recorded via a DAS.)
- 5.3.9 Pull the vehicle off to the side of the test track. Record the time, miles traveled, and odometer reading on Appendix C. (This may be recorded via a DAS.)

5.4 Calibration of the Vehicle Speedometer

This section should be completed concurrent with completion of ETA-TP011, "Receipt Inspection," as well as in conjunction with Sections 5.1 and 5.2 of this procedure. It may also be implemented any time the speedometer is suspected of misoperation. If the calibration is being completed independent of range testing, do not complete steps 5.4.1, 5.4.2 or 5.4.3.

- 5.4.1 When accelerating the vehicle to a predetermined speed of 45 mph, 60 mph or maximum vehicle speed, record the vehicle speedometer reading compared to the installed Data Acquisition System (DAS) speed reading, in 10 mph increments, up to and including the final speed achieved. [To promote safety, this may be done verbally by speaking to a tape recorder, and then later transcribed into Appendix D.]
- 5.4.2 The error between the speedometer and the DAS readout shall be calculated and the results posted in the vehicle for the driver to use.
- 5.4.3 If the driver notices a difference between the indicated value and the calculated correction factor, this test should be run again.
- 5.4.4 If the vehicle is being operated for the sole purpose of calibrating the speedometer, calibration should be as follows:
 - 5.4.4.1 Ensure the vehicle is instrumented with a DAS.
 - 5.4.4.2 With the vehicle stopped, record the speedometer reading.
 - 5.4.4.3 Accelerate the vehicle to 5 mph; record the speedometer reading and the DAS heads-up display speed readout.
 - 5.4.4.4 Increase vehicle speed in 5 mph increments, recording the speedometer and heads-up display speed read-out at each speed. Continue this until the vehicle has achieved 60 mph.
 - 5.4.4.5 Increase the vehicle speed to 70 mph (or maximum achievable speed, whichever is less) and record the speedometer reading and the DAS heads-up display speed read-out.
 - 5.4.4.5 Increase the vehicle speed to 80 mph (or maximum achievable speed, whichever is less) and record the speedometer reading and the DAS heads-up display speed read-out.
 - 5.4.4.6 Develop a calibration reference table, Appendix D, for the speedometer.
 - 5.4.4.7 Mount the calibration reference table in the subject vehicle adjacent to the speedometer.

5.5 Range/Time At Constant Speed on 3% Grade

This test determines the range and time a vehicle can achieve while maintaining a constant speed of 55 mph when operating on a dynamometer set to simulate a constant 3% grade. This test uses values obtained during completion of ETA-TP001, "Road Load Measurement and Dynamometer Simulation Using Coastdown Techniques." Refer to those test results when completing this section of this procedure. The following are the performance goals and requirements:

- The vehicle shall be operated at a constant 55 mph during the test
- The ambient temperature during the test shall be $77^{\circ}\text{F} \pm 9^{\circ}\text{F}$.
- The vehicle shall have soaked in this temperature for at least 12 hours, but not more than 36 hours.
- The test shall be run on a dynamometer capable of maintaining a constant load for the duration of the test.
- The test shall continue until one of the following occurs:
 - a) The vehicle cannot maintain 52 mph (95% of the target speed);
 - b) The traction battery pack minimum operating voltage is reached;
 - c) The point at which the vehicle manufacturer's owners manual directs stopping of the vehicle has been reached (tell-tale illuminates, specific SOC indication, temperature limit, etc.).
- The vehicle shall be cooled using the methodologies established and allowed by SAE J1634, MAY93. This includes the use of cooling fans with a maximum capacity of 4500 scfm.

Testing shall be accomplished as follows:

- 5.5.1 Obtain the "A" and "C" coefficients determined from coastdown testing done per ETA-TP001. Record on Appendix F.
- 5.5.2 Obtain the vehicle weight of the vehicle determined during ETA-TP011, "Receipt Inspection." Record on Appendix F.
- 5.5.3 Calculate new vehicle weight based on the vehicle being on a 3% positive grade (vehicle headed "up hill"). Record on the Data Sheet (Appendix F).
- 5.5.4 Using the new vehicle weight, adjust the A and C coefficients in the Road Load Equations determined by SAE J1263 JUN91, in ETA-TP001. Record on Appendix F.
- 5.5.5 Install or verified installed the instrumentation pack.
- 5.5.6 Place the vehicle on the dynamometer.
- 5.5.7 Ensure the vehicle is not charging and not connected to the charger.

- 5.5.8 Run the dynamometer at a constant vehicle speed of 35 mph for at least 10 minutes, or until tire temperatures are stabilized. [Stable tire temperatures and vehicle component temperatures are crucial to coastdown curve “fit.”]
- 5.5.9 Place the vehicle on the dynamometer, and conduct road load coastdown curve fit per ETA-TP003. Record the values on Appendix F.
- 5.5.10 Ensure the vehicle is still fully charged. Charge as required.
- 5.5.11 Place the cooling fans in place, as required.
- 5.5.12 Ensure all vehicle auxiliary loads are turned off.
- 5.5.13 Record the following values on Appendix F:
 - 5.5.13.1 Tire temperatures (average temperature of each tire)
 - 5.5.13.2 Beginning odometer reading (in miles)
 - 5.5.13.3 Initial kWh meter reading
 - 5.5.13.4 Initial ambient temperature
 - 5.5.13.5 Initial battery temperature
 - 5.5.13.6 Initial battery voltage
 - 5.5.13.7 Initial battery SOC meter reading
- 5.5.14 Start the Dynamometer 3% Constant Grade Load Cycle Program.
- 5.5.15 Smoothly accelerate the vehicle to achieve a speed of 55 ± 1 mph.
- 5.5.16 Maintain the vehicle at this speed until one of the following occurs:
 - 5.5.16.1 The vehicle cannot maintain 52 mph (95% of the target speed);
 - 5.5.16.2 The battery pack minimum operating voltage has been reached;
 - 5.5.16.3 The point at which the vehicle manufacturer’s owners manual directs stopping of the vehicle has been reached (tell-tale illuminates, specific SOC indication, temperature limit, etc.).
- 5.5.17 Record the following information on Appendix F:
 - 5.5.17.1 Tire temperatures (average temperature of each tire)
 - 5.5.17.2 Final odometer reading (in miles)
 - 5.5.17.3 Time at end of test
 - 5.5.17.4 Final kWh meter reading
 - 5.5.17.5 Final ambient temperature
 - 5.5.17.6 Final battery temperature
 - 5.5.17.7 Final battery SOC meter reading
 - 5.5.17.8 Tell-tales illuminated
- 5.5.18 De-energize / disengage the dynamometer.
- 5.5.19 Place the vehicle on charge.

6.0 GLOSSARY

- 6.1 Battery kilowatt-hour (kWh) Capacity - The capacity of a battery in ampere-hours determined as a function of the total distance traveled by the vehicle during performance of the 45 mph Constant Speed Range Test portion of ETA-TP004.
- 6.2 Curb Weight - The total weight of the vehicle including batteries, lubricants, and other expendable supplies but excluding the driver, passengers, and other payloads.
- 6.3 Effective Date - The date, after which a procedure has been reviewed and approved, that the procedure can be utilized in the field for official testing.
- 6.4 Fifth Wheel - A calibrated mechanical instrument used to measure a vehicle's speed and distance independent of the vehicles on-board systems.
- 6.5 Gross Vehicle Weight Rating (GVWR) - The maximum design loaded weight of the vehicle specified by the manufacturer.
- 6.6 Initial Conditions - Conditions that shall exist prior to an event occurring.
- 6.7 Initial State of Charge (SOC) - Initial State of Charge is the SOC at the beginning of a test. It does not have to be 100%.
- 6.8 Prerequisites - Requirements that must be met or resolved prior to an event occurring.
- 6.9 Program Manager - As used in this procedure, the individual within Electric Transportation Applications responsible for oversight of the EV America Performance Test Program. [Subcontract organizations may have similarly titled individuals, but they are not addressed by this procedure.]
- 6.10 Shall - This word is used to indicate an item which requires adherence without deviation. Shall statements identify binding requirements. A go, no-go criterion.
- 6.11 Should - This word is used to identify an item which requires adherence if at all possible. Should statements identify preferred conditions.
- 6.12 State of Charge (SOC) - For this testing, the SOC of a battery is defined as the expected residual battery capacity, expressed in amperes-hours or watt-hours or miles, as a percentage of the total available. The 100% SOC basis (available ampere-hours, kilowatt hours or miles) is determined by the actual discharge capability of the main propulsion battery when discharged to the requirements of the 45 mph Constant Speed Range Test portion of procedure ETA-TP004.
- 6.13 Test Director - The individual within Electric Transportation Applications responsible for all testing activities associated with the EV America Performance Test Program.

6.0 GLOSSARY (continued)

- 6.14 Test Director's Log - A daily diary kept by the Test Director, Program Manager, Test Manager or Test Engineer to document major activities and decisions that occur during the conduct of a Performance Test Evaluation Program. This log is normally a running commentary, utilizing timed and dated entries to document the days activities. This log is edited to develop the Daily Test Log published with the final report for each vehicle.
- 6.15 Test Engineer - The individual(s) assigned responsibility for the conduct of any given test. [Each contractor/subcontractor should have at least one individual filling this position. If so, they shall be responsible for adhering to the requirements of this procedure.]
- 6.16 Test Manager - The individual within Electric Transportation Applications responsible for the implementation of the test program for any given vehicle(s) being evaluated to the requirements of the EV America Performance Test Program. [Subcontract organizations may have similarly titled individuals, but they are not addressed by this procedure.]

7.0 REFERENCES

- 7.1 EV America Technical Requirements
- 7.2 ETA-AC001, Revision 2 - "Control, Close-out and Storage of Documentation"
- 7.3 ETA-AC002, Revision 2 - "Control of Test Conduct"
- 7.4 ETA-AC004, Revision 2 - "Review of Test Results"
- 7.5 ETA-AC006, Revision 2 - "Vehicle Receipt"
- 7.6 ETA-AC007, Revision 1 - "Control of Measuring and Test Equipment"
- 7.7 ETA-TP001, Revision 2 - Road Load Measurement and Dynamometer Simulation Using Coastdown Techniques"
- 7.8 ETA-TP002, Revision 2 - "Implementation of SAE Standard J1666 May 93, Electric Vehicle Acceleration, Gradeability and Deceleration Test Procedure"
- 7.9 ETA-TP005, Revision 2 - "Electric Vehicle Rough Road Course"
- 7.10 ETA-TP008, Revision 2- "Battery Charging"
- 7.11 ETA-TP011, Revision 1 - "Receipt Verification"
- 7.12 SAE Standard J227a

Electric Transportation Applications

**APPENDIX-A
45 mph Constant Speed Range Test
Data Sheet (Page 1 of 2)**

Vehicle Number: _____

Project No.:	Test Date(s):
Root File No.:	
Test Driver:	(Initials) (Date)
Test Engineer:	(Initials) (Date)

Vehicle Setup

VEHICLE WEIGHTS AS TESTED WITH DRIVER & INSTRUMENTATION (Curb weight plus 332 pounds)			
Left Front: <small>(lbs or kg)</small>	Right Front: <small>(lbs or kg)</small>	Total Front: <small>(lbs or kg)</small>	Percent Front: %
Left Rear: <small>(lbs or kg)</small>	Right Rear: <small>(lbs or kg)</small>	Total Rear: <small>(lbs or kg)</small>	Percent Rear: %
		Total Weight: <small>(lbs or kg)</small>	
INSTALLED TIRES (Placard or sidewall whichever is less)			
Preparation Area Temperature: <small>(°F or °C)</small>			
Left Front		Right Front	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	
Left Rear		Right Rear	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	

Track/Weather Conditions

Test Track Location:	Track Grade: %
Ambient Temperature (initial): <small>(40-100°F or 5-38°C)</small>	Ambient Temperature (final): <small>(40-100°F or 5-38°C)</small>
Track Temperature (initial): <small>(°F or °C)</small>	Track Temperature (final): <small>(°F or °C)</small>
Wind Velocity (initial): <small>(<10 mph or 16 km/h)</small>	Wind Velocity (final): <small>(<10 mph or 16 km/h)</small>
Wind Direction (initial): °	Wind Direction (completion): °

Electric Transportation Applications

APPENDIX-A
45 mph Constant Speed Range Test
Data Sheet (Page 2 of 2)

Test Data Sheet

Sequence No:	File No.:	Direction of Travel:
Time (initial):		Time (final):
Odometer (initial): <small>(miles or kilometers)</small>		Odometer (final): <small>(miles or kilometers)</small>
Status of Charge (initial): <small>(SOC,kWh,Ah)</small>		Status of Charge (final): <small>(SOC,kWh,Ah)</small>
Battery Temp (initial): <small>(°F or °C)</small>		Battery Temp (final): <small>(°F or °C)</small>
Comments (initials/date):		
Completed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Reviewed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Approved By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>

Electric Transportation Applications

APPENDIX-B
60 mph Constant Speed Range Test
Data Sheet (Page 1 of 2)

Vehicle Number: _____

Project No.:	Test Date(s):
Root File No.:	
Test Driver: <small>(Initials) (Date)</small>	
Test Engineer: <small>(Initials) (Date)</small>	

Vehicle Setup

VEHICLE WEIGHTS AS TESTED WITH DRIVER & INSTRUMENTATION (Curb weight plus 332 pounds)			
Left Front: <small>(lbs or kg)</small>	Right Front: <small>(lbs or kg)</small>	Total Front: <small>(lbs or kg)</small>	Percent Front: %
Left Rear: <small>(lbs or kg)</small>	Right Rear: <small>(lbs or kg)</small>	Total Rear: <small>(lbs or kg)</small>	Percent Rear: %
		Total Weight: <small>(lbs or kg)</small>	
INSTALLED TIRES (Placard or sidewall whichever is less)			
Preparation Area Temperature: <small>(°F or °C)</small>			
Left Front		Right Front	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	
Left Rear		Right Rear	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	

Track/Weather Conditions

Test Track Location:	Track Grade: %
Ambient Temperature (initial): <small>(40-100°F or 5-38°C)</small>	Ambient Temperature (final): <small>(40-100°F or 5-38°C)</small>
Track Temperature (initial): <small>(°F or °C)</small>	Track Temperature (final): <small>(°F or °C)</small>
Wind Velocity (initial): <small>(<10 mph or 16 km/h)</small>	Wind Velocity (final): <small>(<10 mph or 16 km/h)</small>
Wind Direction (initial): °	Wind Direction (completion): °

Electric Transportation Applications

**APPENDIX-B
60 mph Constant Speed Range Test
Data Sheet (Page 2 of 2)**

Test Data Sheet

Sequence No:	File No.:	Direction of Travel:
Time (initial):	Time (final):	
Odometer (initial):	Odometer (final):	
<small>(miles or kilometers)</small>	<small>(miles or kilometers)</small>	
Status of Charge (initial):	Status of Charge (final):	
<small>(SOC,kWh,Ah)</small>	<small>(SOC,kWh,Ah)</small>	
Battery Temp (initial):	Battery Temp (final):	
<small>(°F or °C)</small>	<small>(°F or °C)</small>	
Comments (initials/date):		
Completed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Reviewed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Approved By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>

Electric Transportation Applications

**APPENDIX-C
Maximum Achievable Speed Range
Test Data Sheet (Page 1 of 2)**

Vehicle Number: _____

Project No.:	Test Date(s):
Root File No.:	
Test Driver: <small>(Initials) (Date)</small>	
Test Engineer: <small>(Initials) (Date)</small>	

Vehicle Setup

VEHICLE WEIGHTS AS TESTED WITH DRIVER & INSTRUMENTATION (Curb weight plus 332 pounds)			
Left Front: <small>(lbs or kg)</small>	Right Front: <small>(lbs or kg)</small>	Total Front: <small>(lbs or kg)</small>	Percent Front: %
Left Rear: <small>(lbs or kg)</small>	Right Rear: <small>(lbs or kg)</small>	Total Rear: <small>(lbs or kg)</small>	Percent Rear: %
		Total Weight: <small>(lbs or kg)</small>	
INSTALLED TIRES (Placard or sidewall whichever is less)			
Preparation Area Temperature: <small>(°F or °C)</small>			
Left Front		Right Front	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	
Left Rear		Right Rear	
Pressure: <small>(psi or kPa)</small>		Pressure: <small>(psi or kPa)</small>	

Track/Weather Conditions

Test Track Location:	Track Grade: %
Ambient Temperature (initial): <small>(40-100°F or 5-38°C)</small>	Ambient Temperature (final): <small>(40-100°F or 5-38°C)</small>
Track Temperature (initial): <small>(°F or °C)</small>	Track Temperature (final): <small>(°F or °C)</small>
Wind Velocity (initial): <small>(<10 mph or 16 km/h)</small>	Wind Velocity (final): <small>(<10 mph or 16 km/h)</small>
Wind Direction (initial): °	Wind Direction (completion): °

Electric Transportation Applications

**APPENDIX-C
Maximum Achievable Speed Range
Test Data Sheet (Page 2 of 2)**

Test Data Sheet

Sequence No:		File No.:		Direction of Travel:	
Time (initial):			Time (final):		
Odometer (initial): <small>(miles or kilometers)</small>			Odometer (final): <small>(miles or kilometers)</small>		
Status of Charge (initial): <small>(SOC,KWH,AH)</small>			Status of Charge (final): <small>(SOC,KWH,AH)</small>		
Battery Temp (initial): <small>(°F or °C)</small>			Battery Temp (final): <small>(°F or °C)</small>		
Comments (initials/date):					
Completed By: _____					
<small>(Printed Name)</small>		<small>(Signature)</small>		<small>(Date)</small>	
Reviewed By: _____					
<small>(Printed Name)</small>		<small>(Signature)</small>		<small>(Date)</small>	
Approved By: _____					
<small>(Printed Name)</small>		<small>(Signature)</small>		<small>(Date)</small>	

Electric Transportation Applications

**APPENDIX-D
Calibration of Vehicle Speedometer
Test Data Sheet (Page 1 of 1)**

Vehicle Number: _____

Sequence No:	File No.:	Direction of Travel:
Time (initial):		Time (final):
Odometer (initial): <small>(miles or kilometers)</small>		Odometer (final): <small>(miles or kilometers)</small>
Status of Charge (initial): <small>(SOC,KWH,AH)</small>		Status of Charge (final): <small>(SOC,KWH,AH)</small>
DAS Heads-up Display:		Vehicle Speedometer:
0 MPH		
5 MPH		
10 MPH		
15 MPH		
20 MPH		
25 MPH		
30 MPH		
35 MPH		
40 MPH		
45 MPH		
50 MPH		
55 MPH		
60 MPH		
70 MPH		
80 MPH		
MPH		
MPH		
Comments (initials/date):		
Completed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Reviewed By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>
Approved By:		
<small>(Printed Name)</small>	<small>(Signature)</small>	<small>(Date)</small>

Electric Transportation Applications

**APPENDIX-E
Vehicle Metrology Setup Sheets
(Page 1 of 1)**

Vehicle Number: _____

Instrument/Device:	Calibration Due Date:	Initials / Date:
Fifth Wheel S/N:		
Fifth Wheel Calibrator S/N:		
Daytronics S/N:		
Daytronics Set-up Sheet S/N		
kWh Meter S/N:		
Shunt S/N:		
Tire Pressure Gauge S/N:		
Misc:		
Misc:		
Misc:		
Misc:		
Comments (initials/date):		
Completed By:		
(Printed Name)	(Signature)	(Date)
Reviewed By (QA):		
(Printed Name)	(Signature)	(Date)
Approved By:		
(Printed Name)	(Signature)	(Date)

Electric Transportation Applications

APPENDIX-F
3% Grade Constant Speed Test
Data Sheet (Page 1 of 5)

Vehicle Number: _____

Project No.:	Test Date(s):
Root File No.:	
Test Driver: <small>(Initials) (Date)</small>	
Test Engineer: <small>(Initials) (Date)</small>	

Vehicle Setup

VEHICLE WEIGHTS AS TESTED WITH DRIVER & INSTRUMENTATION (Curb weight plus 332 pounds)			
Left Front: <small>(lbs or kg)</small>	Right Front: <small>(lbs or kg)</small>	Total Front: <small>(lbs or kg)</small>	Percent Front: %
Left Rear: <small>(lbs or kg)</small>	Right Rear: <small>(lbs or kg)</small>	Total Rear: <small>(lbs or kg)</small>	Percent Rear: %
		Total Weight: <small>(lbs or kg)</small>	
COLD SHAVED TIRE PRESSURE (50 psig ±0.5 psig)			
Left Front: <small>(psig or kPa)</small>	Right Front <small>(psig or kPa)</small>		
Left Rear <small>(psig or kPa)</small>	Right Rear <small>psig or kPa (</small>		

Determination of Dynamometer and Tire Parasitic Losses

Inertial Weight Setting:				
TIRE WARM-UP TEMPERATURES				
Left Front: <small>(°F or °C)</small>	Right Front: <small>(°F or °C)</small>			
Left Rear: <small>(°F or °C)</small>	Right Rear: <small>(°F or °C)</small>			
Parasitic Loss -V _____				
	Base	_____	_____	_____
C1				
C2				
C3				
C4				
Tire Temperatures [°F]				
	Base	_____	_____	_____
Left				
Right				

Electric Transportation Applications

APPENDIX-F
3% Grade Constant Speed Test
Data Sheet (Page 2 of 5)

Repeatability:

Parasitic Loss -V _____				
	Base	_____	_____	_____
C1				
C2				
C3				
C4				
Tire Temperatures [°F]				
	Base	_____	_____	_____
Left				
Right				
Parasitic Loss -V _____				
	Base	_____	_____	_____
C1				
C2				
C3				
C4				
Tire Temperatures [°F]				
	Base	_____	_____	_____
Left				
Right				
Parasitic Loss -V _____				
	Base	_____	_____	_____
C1				
C2				
C3				
C4				
Tire Temperatures [°F]				
	Base	_____	_____	_____
Left				
Right				

Electric Transportation Applications

APPENDIX- F
3% Grade Constant Speed Test
Data Sheet (Page 4 of 5)

Vehicle Number: _____

Inertial Weight Setting: <small>(lb.)</small>		Maximum Allowable Vibration:	
TIRE PRESSURES (50 psig ±0.5 psig)			
Left Front: <small>(psig or kPa)</small>		Right Front <small>(psig or kPa)</small>	
Left Rear <small>(psig or kPa)</small>		Right Rear <small>(psig or kPa)</small>	
TIRE TEMPERATURES			
Left Front: <small>(°F or °C)</small>		Right Front: <small>(°F or °C)</small>	
Left Rear: <small>(°F or °C)</small>		Right Rear: <small>(°F or °C)</small>	
Traction Battery State of Charge:			
Minimum Allowable Traction Battery Voltage:			
Test Room Ambient Temperature: <small>(°F or °C)</small>			
EXCURSIONS FROM TEST CYCLE (see next page)			
Odometer Reading:		Time Waited:	
TIRE TEMPERATURES			
Left Front: <small>(°F or °C)</small>		Right Front: <small>(°F or °C)</small>	
Left Rear: <small>(°F or °C)</small>		Right Rear: <small>(°F or °C)</small>	
Time of Day:		Test Time:	
Odometer Reading:		Total Distance:	
FINAL TIRE TEMPERATURES			
Left Front: <small>(°F or °C)</small>		Right Front: <small>(°F or °C)</small>	
Left Rear: <small>(°F or °C)</small>		Right Rear: <small>(°F or °C)</small>	

Excursions from Drive Cycle:

Time:	Speed:	Distance:	Comments:	Initials:

