

Fully Integrated High Speed Megawatt Class Motor and High-Speed MW Motor for Gas Compression Systems

DE-EE0007254

Clemson University and TECO Westinghouse Motor Co.

May 1st, 2016 to November 30th, 2018

J. Curtiss Fox, Ph.D.
Director of Research Facilities
Energy Innovation Center
Clemson University

U.S. DOE Advanced Manufacturing Office Program Review Meeting
Washington, D.C.
June 13-14, 2017

Project Objective

- The primary objective of this project is to develop an integrated motor and drive system for high speed applications
- To increase overall system efficiency, volumetric power density and costs a fully integrated system that utilizes a high speed induction motor and wide band-gap semiconductors is proposed

Fully Integrated System Specifications	
VSD Input Voltage	4.16 – 35 kV set by transformer
Targeted WBG devices	Full SiC MOSFET
WBG device switching frequency	5 kHz – 10 kHz
Apparent switching frequency	30 kHz – 60 kHz
Motor fundamental frequency	500 Hz – 600 Hz
Motor shaft speed	15,000 rpm
Motor output power	1 MW
Overall volumetric power density	< 6.31 m ³ /MW
Overall full load efficiency	> 93%
Overall drive output THD _v (2 nd -50 th)	< 2% without a sine filter
Input displacement power factor	> 0.99

Technical Innovation

- Existing electrified high speed systems are not as efficient as they could be and are often comprised of several different OEMs
 - Systems with a high speed gearbox suffer from the additional losses of the gearbox
 - Previous high speed motor applications have utilized de-rated low frequency converters with poor efficiencies at high frequencies
- The integrated system developed during this project will:
 - Increase overall system efficiency removing the gearbox and use a wide bandgap semiconductor high frequency converter
 - Build upon decades of experience in design and fabrication of induction machines to provide a robust and reliable solution
 - Develop US manufacturing of turn-key high speed motor and drive systems for high energy compressor applications

Technical Innovation

- Traditional materials and design methodologies cannot be applied to meet the motor requirements
 - Steel laminations with low core loss at high frequency
 - Litz wire stator coils to reduce eddy currents
 - Rotor dynamics and manufacturing processes to support high rotational stresses
 - Efficient thermal management to enable compact design
- Electromagnetic, thermal and fluid simulations with finite element analysis
 - Model refinement and validation with benchtop testing of components and materials
 - Utilization of Clemson HPC for 3D motor modeling

Technical Innovation


- Integration of wide band-gap semiconductors into a modular multi-level drive topology
 - Retrofit a very common half-bridge module (ECONO-Dual package) to aid in short term adoption of wide band-gap semiconductors
 - Power requirements (1700 V, 400 A) stretch the present commercial availability of SiC MOSFET modules
 - Either developments in packaging or gate drivers required to meet protection and performance metrics with today's technology
 - Future redesign of the power modules will be made possible by validating additional MOSFET modules with alternative packaging

Technical Approach


- Materials testing, manufacturing process development and model validation are being used to reduce project risks
- Special manufacturing processes have been developed and verified
- Innovative Litz wire modeling techniques are being developed and validated to enable further research




Bench top model validation of a Litz wire coil embedded in a slot



3D FEA Simulated input voltage with PWM




3D FEA Model



3D FEA Simulated Phase A Current

Technical Approach


- Commercially available SiC MOSFET modules did not meet the performance criterion for integration
- Alternative paths have been developed to meet project objectives and ensure competitive pricing in the future
- Improvements to components have increased the efficiency of the system (transformer efficiency up to 98.6%)



DC laminated bus redesigned to reduce inductance by 40%



Benchtop testing setup for a single power module at 164 kVA



Full load SiC-based power cell testing with a single power module

Transition (beyond DOE assistance)

- Contacts with potential stakeholders started in the first quarter of the project
 - Stakeholders include both end users and compressor OEMs
 - Questionnaires communicated with potential stakeholders
 - Power and voltage specifications, performance, reliability and certification requirements, evaluation criterion with respect to cost and efficiency, etc.
- The certification process of the system has begun
 - Request for Field Certification with CSA for the system
 - Drive UL listing to build on existing UL certifications
- Development of manufacturing processes and methods
 - Efficient ways to create Litz wire motor stators
 - High strength braising processes for high speed rotors

Measure of Success

- Electrifying the chemical and petroleum refining industries will greatly increase the efficiency of the two largest energy consuming industries in the USA
- Commercializing a line of high speed motors and high frequency variable speed drives would:
 - Remove the speed increasing gearbox in electrified low speed applications to increase the efficiency by $> 1.5 - 2.5\%$
 - Apply to new applications a direct drive variable speed solution that is 93% efficient to the shaft of the compressor
 - Provide a system that beats a cost target of \$1/Watt and increases power density by greater than 200% over the present state of the art

Project Management & Budget

- Project Duration: 30 months
 - May 1st, 2016 – November 30th, 2018
- The project consists of 7 main tasks
 - There is one milestone for each task per quarter
 - Project Go/No-Go points are scheduled on a yearly basis for each task
- The invoicing for the project was delayed but did not impact overall progress
 - Some costs will be shifted to BP2 to account for this

Total Project Budget	
DOE Investment	\$ 5,093,046
Cost Share	\$ 1,769,942
Project Total	\$ 6,862,299

Results and Accomplishments

- Budget Period 1 tasks near completion:
 - The motor design is feasible and will achieve a full load efficiency of greater than 96.5 %
 - SiC MOSFET modules are now able to switch at ~ 8 kV/us with SC protection in ~ 1.5 us and ~ 3.6 kA
 - SiC based drive efficiency is calculated greater than 97%
 - Total system efficiency is calculated greater than 93%
- Budget Period 2 tasks include:
 - Manufacturing of the high speed motor and drive
 - Test plan development, including applicable standards
 - Assembly and commissioning of the dynamometer
 - Continuing to engage stakeholders in the R&D process