



# EV Smart Charge Management and High Power Fast Charging:


*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*

Tony Markel and Andrew Meintz  
November 27, 2018

State Energy Advisory Board at NREL

# EV Grid Integration @ NREL

- Facility Smart Charge Management: NREL employee workplace charging integration with building load for demand charge mitigation.
- DCFC Systems Integration: DC fast charging system integration with onsite storage, generation, L2 charging, and building load.
- Distribution System Vehicle-Grid Impacts: PHIL capability to emulate multiple nodes on a feeder at medium voltage to residential (L1/L2) and/or commercial (XFC) low voltage systems at up to 2 MW real load
- Wireless Charging and Transportation Systems: Energy use and design analysis for adding frequent intra-day charging to a shuttle services
- EVSE Cyber Security: Virtualized environment representing power and operational networks of a small distribution utility enables protect, detect, and isolate strategies for grid integrated infrastructure






# Energy Systems Integration Facility (ESIF)

- 182,500 sq. ft.
- 2x 1-MVA bi-directional grid simulator
- Low Voltage Distribution Bus
- Medium Voltage Outdoor Test Area
- Full Power Hardware in the Loop (PHIL) testing
- Petascale High Performance Computing (HPC)




## Research Electrical Distribution Bus (REDB)


AC (600 V)	DC ( $\pm 500$ V)
• 250 A	• 250 A
• 1600 A	• 1600 A



## Example microgrid




# Experiments Evaluating High Penetration EV Integration in Residential Networks



MVOTA: Medium Voltage Outdoor Testing Area  
SPL: Smart Power Laboratory  
ESL: Energy Storage Laboratory  
REDB: Research Electrical Distribution Bus

— Communication line  
— Power line  
— REDB

# Scenarios for High Voltage DC Distribution to XFC



PHIL enables evaluation of

- Grid **interface control** for reactive and real power
- Grid **system dynamics** with simulated feeders
- **Microgrid controller** interaction with multiple DER controllers
- **System conversion** and roundtrip **energy storage efficiency** under various operating conditions
- **Vehicle-to-vehicle** control **interactions** for site wide energy control

# Key Messages

- Integrated EV infrastructure scenarios present challenges for both power and communications implementation
- Minimizing cost and complexity while enhancing functionality drives research agenda
- Future mobility systems rely on secure connectivity and coordination

# EV Smart Charge Management

---

*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*

# Challenges of Smart Charge Management in Workplaces

- Value of forecasting
  - Precise forecasts of loads and local generation combined with charge management offer electricity cost savings
- Better estimation of PEV users' energy requests and departure times
  - The information provided by users is not always reliable
  - Good estimation of user's energy request and departure time provides better performance of charge management






# Putting EV Smart Management to Work

## NREL Parking Garage EVSE Status Display

6/19/2018, 4:43:34 PM



Monthly Peak	Campus Net Load	Total EVSE Power	Curtailed EVSE Load
4.576 [MW]	2.585 [MW]	0.063 [kW]	No load management

- The campus net load went from 1.6 MW to 4 MW in 6 minutes (fast moving storm)
- The curtailed EV load during the management is about 28 kW, which is about \$470 based on NREL's demand charge rage (\$16.79/kW).
- If same event happened during morning, more than 90kW could have been curtailed, saving >\$1500.

# Bi-directional Power Flow and Emergency Power Back-up

---

*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*

# Bi-directional System Component Characterization

- Sharp Energy Storage System: 43 kWh, 30 kW IPC interface
  - Via Motors Van - Coritech EVSE: 23 kWh, 14.4 kW V2G-V2H
  - Nissan Leaf - Nichicon EV Power Station: 6 kW V2H
  - Smith EV Truck - Coritech EVSE: 80 kWh, 60 kW
  - Transpower School Bus - Milbank EVSE: 90 kWh, 22.6 kW
  - Mini-E – Milbank EVSE: 30 kWh, 14.4 kW
- 
- PV System (emulated: 22 kW and real: 18 kW)
  - Residential and commercial loads (125 kW AC)
  - 30 kW grid simulator and RTDS system



Source NREL, Andrew Meintz

**Nissan Leaf Nichicon V2H**



Source NREL, Mithat Kisacikoglu

**Via Motors Van**



Source NREL, Andrew Meintz

**Smith EV Truck**



Source NREL, Andrew Meintz

**Sharp Stationary Storage**


# Export Power Using PEVs

- Via Motors Van with Coritech EVSE
  - 14.4-kW on-board bidirectional charger
  - Series hybrid PHEV with 23-kWh battery
  - V2H and V2G capable, SEP 2.0 grid link, Homeplug GREEN PHY
  - Single phase 120V/240V up to 60 A off-grid power generation


- Nichicon EV Power Station
  - 6-kW off-board charging capability
  - 120 V / 240 V, total 50 A@120 V V2H power capability
  - Runs with Chademo-compatible PEVs (Leaf, Mitsubishi i-MiEV)
  - Switching from grid-connected to grid-isolated operation

## Research scope

- Analysis of powering real home loads with Nissan Leaf and Via Van w/o grid.
- Evaluating the emergency power capability of EV (Leaf) and PHEV (Via-Van).
- Integrating emulated/real solar PV systems with V2H to extend the emergency power duration.
- Investigating microgrid operation of vehicles to power several houses.




Source NREL, Mithat Kisackoglu



Leaf-Nichicon power export

# Emergency Power Backup




	HVAC	Water Heater	Dryer	Stove	Refrigerator	Washer	Dishwasher	Lights	Television
On Time (Min)	56.6	37.17	65.52	1.12	122.12	45.50	55.50	24.35	20.58
Energy (Wh)	1136.91	3519.60	3014.62	23.16	254.10	204.54	675.98	213.61	37.24
Avg. Power (W)	1205.20	5681.87	2760.78	1244.40	124.85	269.72	730.79	526.36	108.56
Peak Power (W)	4849.15	5776.56	6156.19	1293.11	351.61	1244.24	1033.68	550.13	112.16



PV Generation



Home Loads





# Truck Electrification Testing at ESIF



Utility Truck Offering Ability to Power Local Transformers



Exploring Grid Value Proposition with EV School Bus

# Smart Charge Management (RECHARGE)

---

*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*


# Smart PEV Charging for a Reliable and Resilient Grid (RECHARGE)

RECHARGE will consider the **impact to the grid of PEV charging at scale** under a variety of future scenarios, including

- adoption of different vehicle types,
- proliferation of extreme fast charging (xFC),
- expanded adoption of distributed energy resources (DER) throughout the system,
- and multiple smart charge management approaches

This project will address the following questions for smart charging of PEVs at Scale:

1. How would grid planning and operation need to change to minimize the impacts of **uncontrolled charging** at scale and at what cost?
2. Which control strategies for smart charging provide the most value in **avoiding grid adaptation** for PEVs?
3. What are the **critical strategies and technologies** required to enable high-value smart charging control?








# Peña Station NEXT



# Preliminary EV Load Scenarios

- Building occupancy data used as proxy for vehicle population (weekday)
- NREL's EVI-Pro and Columbus travel pattern data used to create typical EV energy demands by infrastructure type
- All scenarios assume:
  - **50% of LDVs as EVs** (about 10k EVs on campus throughout typical weekday)
  - **PSN residents** utilize PSN residential EVSE (but not PSN workplace/public EVSE)
  - **PSN commuters** utilize PSN workplace/public EVSE (but not PSN residential EVSE)
- EV loads will be integrated into UrbanOpt building loads to investigate impact on PSN microgrid






# Exploring Flexibility

For next iteration... take “Free Workplace Charging at PSN” from previous slide and explore load flexibility of workplace charging.


Three simulations:

1. Min delay – EVs begin charging immediately upon arriving at work
2. Min power – EVs are charged at minimum rate over park event
3. Max delay – EVs are plugged in immediately but do not begin charging until necessary


All simulations contain the same energy content per charging session, but explore flexibility within window of charging opportunity (only enabled at workplaces).




# Aligning EV Load with PV Generation May Offer System Value



- Case 1: residen



- Case 3: Emphasize workplace everywhere
  - Less storage for evening demand



# Summary Findings

- The introduction of electric vehicle loads to districts with high solar penetration levels can improve performance, 50% fleet electrification,
  - Reduced curtailment by 80%
  - Reduced local grid voltage violations by 65%
- Integration of grid, building, and vehicle modeling tools supported by high performance computing enabled robust design space exploration

# Ultra-High Power Fast Charging or Extreme Fast Charging (XFC):

---

*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*

# A Glimpse of the Future Station



Source: <https://chargedevs.com/newswire/fastned-and-abb-unveils-new-generation-of-350-kw-charging-stations/>



Source: Tritium



# High Power Fast Charging Installations



Electrify America Chicopee MA  
7 CCS ports, 1 CHAdeMO  
Michael Scarpino, Volpe





*This photo was taken on July 18 at the Barrett Pavilion shopping center in Kennesaw, Georgia and uploaded to the popular EV charging infrastructure website PlugShare.com*

# Potential XFC Loads

Hypothetical XFC station with 6-ports @ 350kW per  
(source: Idaho National Laboratory)

Lack of home charging availability for MUD residents and TNC drivers may drive needs for extreme fast charging

XFC station load has potential to be highly transient and large in magnitude  
(below plot shows load aggregated at various time scales)






# Multiport 1+ MW Charging System for MD and HD

Megawatt (MW)-scale charging systems that can quickly charge large capacity (~800 kWh) battery packs in less than ~30 minutes at an attractive charging cost (\$/kWh). Many challenges must be met to realize such an integrated system, including

- Understanding and **optimizing power demand and management** requirements, configuring local infrastructure requirements,
- Developing **distribution voltage-level hardware** for the point of grid connection, designing grid interface converters,
- Understanding and overcoming **power electronics semiconductor** and architecture limitations,
- Developing safe and **robust hardware connections**
- Design model-based **real-time battery charge control** algorithms accounting for chemistry dynamics and thermal constraints while minimizing peak power
- Developing **robust thermal management systems**, and
- Assessing and developing **vehicle-side power delivery** architectures.




# XFC Challenges and Gaps: Buildings, Onsite Resources, and the Grid

What technology solutions will support integration of convenient XFC charging into the grid at a cost comparable to L1/L2 charging that is reliable and resilient?

- Site optimization of XFC with onsite
  - Distributed energy resources (DER) such as energy storage or photovoltaics (PV)
  - Commercial buildings, and/or other large flexible loads
- Resilient energy supply through onsite generation that utilizes alternative fuels with the potential to operate in a microgrid.
- XFC site control technologies for distribution system operation that mitigate capacity expansion, line upgrades, and voltage management

# XFC Challenges and Gaps: Site Optimization and Resilience



**Load and generation estimation** is required for optimal energy storage integration


- **HPFC load** will vary depending on charging infrastructure and travel patterns
- Onsite **renewable generation** will be dependent on regional conditions
- **Building load** will be dependent on occupancy, building design, and is subject to seasonal weather variation

Control integration is required for energy system and microgrid management

- **Interoperability** of communication and control across multiple sectors
- Resolving **multi-objective optimization** across the building, transportation, and grid interface that is open yet cybersecure



# XFC Challenges and Gaps: Distribution system operation



The **value of reactive and real power** control for the XFC site will need to be understood

- What will be the **impact on voltage regulation hardware** from XFC installation
- Value of system efficiency and avoidance of line upgrades with **reactive XFC support**
- Capacity deferral opportunities through real power control at XFC sites to **avoid concurrent peak load** on the feeder

How does the addition of XFC affect stability of the distribution system control


- Impacts of load that is fast ramping, highly variable, and a constant power device
- Integration requirements for **onsite generation** to support microgrids and support system resiliency

# Wireless Charging Scenarios

---

*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*


# Electric Roadways



<https://www.youtube.com/watch?v=gqfih5swB8Q>

Search: nrel e-roadway animation

# Addition of E-Roadway to Grid Loads (Spring)




# Description of MD WPT at NREL's Campus

## ✓ Wirelessly Charged NREL's Shuttle

- Full electric on-demand
- 16 passenger
- 62.1 kWh battery capacity
- 100 miles range
- 7600 curb weight, including VA
- 6.6 kW on-board charger

## ✓ Momentum Dynamics WPT system

- 36"x36" symmetrical square pads
- 25 kW maximum power transfer
- 20 (19-21) kHz nominal operating frequency






# Expanding Infrastructure Analysis to Consider Security and Resilience

---



*Integrating EVs with Buildings, Onsite  
Energy Resources, and the Grid*

# Consequence-Driven Cybersecurity for High-Power Charging Infrastructure

- Conduct a full threat assessment of XFC and high-power WPT (i.e., >200 kW) charging infrastructure ecosystems, utilizing PEV, charging infrastructure, and electric grid R&D and cybersecurity expertise at three national laboratories
- Lab Partners:
  - INL, NREL, ORNL
- Industry:
  - Electrify America, ABB, Tritium
- Outcomes:
  - Vulnerability testing methods and simulated environments to evaluate mitigation strategies



# ATHENA: Modeling Transportation Hubs





# Thank You!

[www.nrel.gov](http://www.nrel.gov)

Tony Markel, Sr. Engineer

[Tony.Markel@NREL.gov](mailto:Tony.Markel@NREL.gov)

NREL is a national laboratory of the U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy, operated by the Alliance for Sustainable Energy, LLC.

