

#### 3-D PRINTING OF NUCLEAR FUEL ASSEMBLY NOZZLES AND END SPACER GRIDS

AMM Technical Review Meeting Webinar December 17-18, 2019

Presented By: George Pabis gpabis@novatechusa.com

Funded By: DOE SBIR Phase II Grant, DE-SC0015902

THIS PRESENTATION INCLUDES NOVATECH PROPRIETARY INFORMATION



220 Jefferson Ridge Pkwy 💋 Lynchburg, VA 24501 💋 NovaTechUSA.com 💋 Tel: (434) 239-1979



### **Acknowledgement and Disclaimer**

**Acknowledgment:** This material is based upon work supported by the U.S. Department of Energy, Office of Science under Award Number DE-SC0015902.

**Disclaimer:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.





#### Agenda

- NovaTech Overview
- Project Team
- Objectives
- Project Plan
- Project Status
- Publications
- Future Tasks
- Q&A





#### Who is NovaTech?

- Founded in 1994
- Located in Lynchburg, VA
- Quality Assurance Program Compliant with:
  - ASME NQA-1
  - 10CFR50 Appendix B
- Business Segments
  - Aerospace
  - Defense
  - Nuclear
  - Industrial





**Project Team** 

- George Pabis Principal Investigator (PI)
- Anne Austin Engineering Manager
- Lauren Gramlich Senior Engineer
- Lew Walton Consulting Engineer
- John Malloy Consulting Engineer
- Sean Routon Consulting Engineer





**Project Objectives** 

- Additively Manufacture (AM) a monolithic Pressurized Water Reactor (PWR) Bottom Nozzle that will be ready for implementation on lead assemblies at the conclusion of Phase II.
  - Reduce part count
    - combine the bottom nozzle, filter plates, and the bottom end grid into one part.
  - Improve performance
    - debris capture, pressure drop, and fuel handling
  - Utilize geometries that were previously not manufacturable
    - torturous path designs and internal fuel rod locking features.



#### Bottom Nozzle Engineering Requirements Document

#### Summary of Key Engineering Requirements (NT-TDR-16-016 Rev 0):

| 1. Normal Operations      | <ul> <li>Bottom Nozzle shall fit existing envelope</li> <li>Shipping and handling loads</li> <li>Shall operate in all reactor thermal &amp; hydraulic conditions</li> <li>SCRAM loads</li> </ul> |
|---------------------------|--|
| 2. Performance            | <ul> <li>Pressure Drop of existing Bottom Nozzle shall be used as baseline</li> <li>FME filtering shall meet or exceed current capabilities</li> <li>Maintain Fuel geometry</li> </ul>           |
| 3. Interfaces             | <ul> <li>Reactor Alignment Pins</li> <li>Guide Tubes</li> <li>Fuel Rods</li> <li>Incore Detector</li> <li>Adjacent Fuel</li> <li>Shipping and Handling Equipment</li> </ul>                      |
| 4. Cost/Part count        | Bottom Nozzles shall be designed with the fewest parts possible  |
| 5. Manufacturing          | Compatible with existing fuel assembly fabrication techniques  |
| 6. Bottom Nozzle Material | Bottom Nozzle material shall be Low-cobalt Inconel 718 (with heat<br>treat) or Stainless Steel.  |





#### Phase I – Accomplishments

- Additive Manufactured (AM) eight bottom nozzle
   5X5 prototypes out of Inconel-718
- Age hardened (no HIP) and inspected Inconel-718 parts
- Designed and fabricated a prototype fuel rod lower end cap
- Successfully tested the fuel rod locking mechanism
- Performed tensile tests, flow tests, and debris filtering tests





# Phase I – AM Build Example







#### Phase I – Tensile Testing

#### **Tensile Testing**

- Yield Strength
- Ultimate Strength
- Elongation
- Conclusion: Material properties of AM Inconel-718 meet minimum material requirements.







#### Phase I – Flow Loop Testing



FLOW LOOP TEST DATA





## Phase I – Debris Filter Testing

- Tested all filter designs twice for debris resistance
- Small holes and torturous paths are the most effective filters
- AM fabricated designs are highly effective at debris filtering







# Phase I – Fuel Rod Locking Tests

- Designed to replace the lower end grid
  - Removes lower end grid and a fuel rod failure initiation point
- Integral to the bottom nozzle grillage
- Allows for longer fuel rod
  - Room for more fuel or plenum volume
- Locks fuel rod axially
- Provides anti-rotation feature
- Reconstitutable
- Designed for single setup machining
  - Lathe turning + wobble broaching
- Successfully tested to 30 lb pull force





#### Phase II – Objectives

- Predictive CFD Modeling
- HFIR (High Flux Isotope Reactor) Irradiation Testing
- Fuel Rod Vibration Testing
  - Small scale flow loop at NovaTech
- Design Full Nozzle
  - Merged debris filtering with fuel rod locking
  - Incorporated Guide Tube and ICD Tubes
  - Incorporated Core Pin Holes
  - Added lead-in features for handling
- Full Scale Flow Loop Testing
  - Built a full scale flow loop at NovaTech





#### Phase II – CFD Benchmarking









# Phase II – HFIR Irradiation Testing

- 24 specimens
- Inconel-718
- 60x10<sup>19</sup> n/cm<sup>2</sup>
  - ~6 dpa
- 2020



Parts layout for NOVA01 capsule





- Testing Performed in the small flow loop at NovaTech
  - 5X5 Test Bundle representing a standard 17X17 bundle Baseline.
  - Production-grade fuel rod components with copper tungsten ballast
  - Production-grade guide tube in center of bundle
  - Production-grade grid segments
  - Axial flow up to ~150 gpm
  - Cross flow up to ~2 fps focused at grid mid-span
  - Fuel rod vibrations measured with strain gages and Keyence laser displacement sensors





[Redacted]

**Patent Pending** 





# Phase II – Full Scale Flow Testing

- Full Scale flow loop fabricated
  - Up to ~2000 gpm flow
- Capable of flow testing a full scale fuel bundle
  - Life and wear testing
  - Pressure drop testing







# Phase II – Project Risks

- Time
  - Funding ends at the end of January 2020
  - As presented, many tasks left to complete
- Implementation on a production fuel assembly
  - NovaTech is not a fuel vendor
  - Fuel users (utilities) are not willing to buy an individual fuel assembly component and modify a purchased fuel assembly
    - Liability issues
  - Need fuel vendors (Framatome and/or Westinghouse) to work with NovaTech to get an AM Bottom Nozzle on a production fuel assembly
    - Liability issues
    - Intellectual Property (IP) issues





# **Publications/Presentations**

- Phase I Final Report
  - "Preliminary Research into the Viability of Additive Manufacturing of Nuclear Fuel Assembly Components"
  - DOE-NOVATECH-15902-1
  - Submitted to: Office of Science, U.S. DOE
- NRC Presentation at the Public Meeting on Additive Manufacturing for Reactor Materials & Components
  - November 28, 2017
- AMM Program Review
  - INL, October 4, 2017
  - ORNL, December 5, 2018
- Meeting with DOE Program Manager, Tansel Selekler
  - July 17, 2018





# **Publications/Presentations (Cont.)**

- AMM Newsletter article
  - March 2016
  - September 2019
- Fuel Vendor Presentations
  - Framatome
  - Westinghouse
- Customer Presentations
  - Dominion
- Provisional Patent
  - In process





#### **Next Activities**

- HFIR Irradiation Testing
  - Late 2020
  - Waiting for HFIR availability
- Fuel Rod Vibration Testing
  - Ongoing
  - 5X5 Assembly in Small Flow Loop
- Full Size Bottom Nozzle Fabrication
  - Getting quotes now
- Full Scale Testing
  - January 2020
- Final DOE Report
  - January 2020
- Phase IIB Funding Proposal?







