

Solar Uncertainty Management and Mitigation for Exceptional Reliability in Grid Operations (SUMMER-GO)

Bri-Mathias Hodge, Ph.D.

May 5, 2021 SETO Solar Forecasting Workshop

SUMMER-GO

SUMMER-GO: Solar Uncertainty Management and Mitigation for Exceptional Reliability in Grid Operations

SUMMER-GO will bring probabilistic solar forecasts into ERCOT's real-time operation environment through automated reserve and dispatch tools that increase economic efficiency and improve system reliability.

- Develop accurate, calibrated, and sharp probabilistic solar power forecasts for both hourly and 5-minute resolution
- Develop and validate risk-parity economic dispatch for *5-minute dispatch period*
- Develop and validate adaptive reserves algorithm to *reduce flexibility and regulation reserves* and *deploy in ERCOT'S iTest system*
- Produce situational awareness tool to present timely information for *better decision making*

erco



Forecasting Time Horizon



Why Use Probabilistic Forecasts?

	Pros	Cons
Point Forecast ("Deterministic")	Simple, easy to understand	 Always wrong to some degree Erodes operator confidence in the forecast
Probabilistic Forecast	 Demonstrates uncertainty in the forecast Builds operator confidence in the forecast over time 	 Not intuitive, takes some practice to understand

Calibration: Does 20th percentile get hit 20% of the time?



Resolution: does the method generate case-dependent forecasts?

Research on Probabilistic Forecast Benchmarks

How do we properly assess improvement in probabilistic forecast methods? What are the most common and/or useful probabilistic solar forecast benchmarks?

Illustrated characteristics and recommended implementations of benchmark probabilistic methods

- 5 methods implemented at hourlyresolution for day-ahead forecast
- 5 methods implemented at 5-minute resolution for hour-ahead forecast
- Code shared with Project Area 1 Team and open-sourced on Github
- SolarArbiter implemented persistence ensemble as a standard benchmark



Advanced Probabilistic Forecast Methods

Developed new Bayesian model averaging (BMA) method to post-process NWP ensembles

BMA regularly outperforms ensemble MOS

- Better Continuous Ranked Probability Scores (proper probabilistic metric)
- Better tail behavior
- Ensemble MOS's single parametric distribution can fail to capture disagreements in the ensemble

Ensemble model output statistics (MOS) uses normal kernel based on a weighted sum of members and ensemble variance



Advances to ERCOT's Operational Solar Forecasts

Temporal Resolution

- *Previously:* Hourly resolution
- *Now:* 5-minute resolution for first 2 hours, then hourly
- Currently testing in iTest system
- Will be operational on May 27nd
- ERCOT estimates \$6-7 million savings from using new forecast in regulation reserve calculations

Reg Up Cost Savings = \$4.0 million



Reg Down Cost Savings = \$2.7 million



Mohthly Reg-down Cost Chane (Pre-SCR811) Mohthly Reg-down Cost Chane (Post-SCR811)

Advances to ERCOT's Operational Solar Forecasts

Probabilistic Format

- *Previously*: Point forecast (50th) and 20th percentile
- Now: All 99 percentiles available
- Maxar already providing operationally based on much larger NWP ensemble
- Upgrade to ERCOT's EMS to ingest new format expected end of year/early next



NREL | 7

Behind-the-Meter Forecast Case Study

Conducting case study of probabilistic behind-the-meter (BTM) solar power forecasting for San Diego Gas and Electric (SDG&E) service territory

Chose California because BTM penetration in Texas within "noise" of net load

Zip-code scale bottom-up approach:

- 15-min zip-code average sampled power for 2-year period from Genscape
- California net-meter interconnected list is used to determine daily specifications by zip code
- Generating zip-code average power forecasts by translating Maxar weather forecasts through PVWatts



Forecast Applications: Non-Spinning Reserves

Use probabilistic forecasts to improve scheduling of non-spinning reserve requirements (NSRR) from year-ahead to hour-ahead



Overall framework of the developed method for NSRR estimation

- ✓ Follow ERCOT NSRR estimation procedure
- ✓ Take forecasting error into account
- ✓ Add four-step flexibility

Dynamic Non-Spinning Reserve Results



MethodNoteHourly
averageERCOTThe current ERCOT method2353.871HAHourly updated reserve under low solar1414.751HAHSHourly updated reserve under high solar539.82

Hourly average NSRR [MW]

- The hourly NSRR is reduced by 39.89% and 77.07% based on 1 hourahead forecasts under low and high solar penetration, respectively, compared to 1-year-ahead scheduling
- Negative values mean no NSRR is required during these time periods
 - Negative values replaced with 0 in post-processing

Current Work: Dynamic Reserves under Extremes

Extending previous work inspired by extreme conditions in Texas in Feb. 2021



Under extreme conditions

- Vulnerabilities: Determine the factors that are most discriminatory between minor and major power outage events.
- **Outages**: Identify generators with high probability of failure.
- Forecasting: Accurate load/wind/solar forecasting is needed for reliable system operations.

Operational Simulations with High Solar Penetrations

- Developed very high solar penetration model system based on ACTIVSg2000 synthetic system of Texas
- Added 110 new solar plants (20 GW) of solar power based on ERCOT's Interconnection Queue
- Instantaneous solar penetrations up to 45%
- Testing day-ahead and real-time operational algorithms using probabilistic forecasts of system-total solar power



Mapping Probabilistic Forecasts into System Operation Forecasts

- Map probabilistic solar forecasts to probabilistic forecasts of corrective actions
 - E.g., reserve deployment
- Enhances operator's situational awareness about future system states
- Could prompt preventive actions, like reserve substitution or curtailment



ACE Forecast



Current Work: Unit Commitment with Solar Ramps

- Focusing on risks relevant to day-ahead decision making: Ramping capacity for steep diurnal solar ramps
- Hourly resolution day-ahead unit commitment can result in insufficient intrahourly ramping capacity
- Using probabilistic solar forecast scenarios to model the risk of needing to take future recourse actions at the hour-ahead timescale



SolarView Visualization Tool



Thank You

www.nrel.gov

Publication Number

NREL is a national laboratory of the U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy, operated by the Alliance for Sustainable Energy, LLC.

