



Particle Heat Exchangers: Development and Testing of a 20 kW_t Moving Packed-Bed Particle-to-sCO₂ Heat Exchanger

Kevin J. Albrecht, Hendrick Laubscher, Christopher Bowen, Dereje Amogne, David Moon, Ashley Byman, Neville Jordison, and Clifford Ho

U.S. Department of Energy Gen3 Summit, Particle Heat Exchangers

CPS# 34152 and 37371



August 26, 2021



Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.


SAND2021-10313 C

Moving Packed-Bed Heat Exchanger Introduction




- Particle CSP is being developed to enable high efficiency sCO_2 power cycles
- The particle/ sCO_2 heat exchanger is a critical enabling technology for these systems

Moving Packed-Bed Heat Exchanger for Particle CSP



- Overall heat transfer coefficient needs to approach 600 W/m²-K for particle heat exchangers to meet 2020 cost targets with current manufacturing (>\$5000/m²)
- With reduction in manufacturing cost, overall heat transfer coefficients between 400-500 W/m²-K could be acceptable

20 kW_t Stainless Steel Heat Exchanger Design



Metric	Value	Units
Thermal Duty	20	kW
Design Temperature	550	°C
Design Pressure (MAWP)	20.0	MPa
Operating Pressure	17.0	MPa
Particle Inlet Temperature	500	°C
Particle Outlet Temperature	340	°C
Particle Flow Rate	0.112	kg/s
sCO ₂ Inlet Temperature	290	°C
sCO ₂ Outlet Temperature	450	°C
sCO ₂ Flow Rate	0.103	kg/s
sCO ₂ Pressure Drop	<40	kPa


Prototype heat exchanger was developed to evaluate novel design features in G3P3:

- Narrow plate spacing (~3 mm)
- Increase approach temperature
- Bonded/brazed construction
- Integral porting
- Flow distribution inside of plate
- Welding headers across bond lines

Difference in G3P3 heat exchanger:


- Nickel alloy construction
- Multiple inlets/outlets
- Higher temperature/pressure operation

Heat Exchanger Test Facility



Process Flow Diagram

Physical System Layout





- Integrated particle/sCO₂ flow loop design was developed to locate entire system in a dedicated indoor test cell at NSTTF

Heat Exchanger Manufacturing and Installation




- Heat exchanger core was manufactured at VPE and shipped to Sandia for installation in the system and testing

Postprocessed Overall Heat Transfer Coefficient



- Heat exchanger performance measured over a wide range of operating conditions
- Overall heat transfer coefficients up to $400 \text{ W/m}^2\text{-K}$ were measured at high flow rate

20 kW_t Nickel Heat Exchanger Project



Design revisions:

- Design temperature: 800 °C
- Design pressure: 25 MPa
- Nickel alloy construction (IN617)
- Overall HTC: >450 W/m²-K
 - <3 mm particle channel width
 - sCO₂ microchannel enhancement
- Pressure Drop: <30 kPa
- Reduction in material per surface area

Conclusions



- Integrated particle/sCO₂ heat exchanger test facility was developed targeting short lead time and low cost
- Novel design features for a moving packed-bed particle/sCO₂ heat exchanger were evaluated in a small-scale heat exchanger prototype
- Performance has demonstrated design point heat transfer coefficients above 300 W/m²-K and off design conditions approaching 400 W/m²-K
- System is currently being upgraded for Gen3 conditions and manufacturing a prototype high nickel alloy design targeting 500 W/m²-K

Sandia can provide testing services for industry and university led research projects on particle/sCO₂ heat exchangers up to 40 kW_t

Acknowledgements



Sandia would like to acknowledge the contributions of industry partners VPE and Solex

This work was funded in part or whole by the U.S. Department of Energy Solar Energy Technologies Office under Award Numbers 34211, 34152, and 37371.

Technology Managers: Matthew Bauer and Vijay Rajgopal



Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.