

# DOE/NASA Advances in Liquid Hydrogen Storage Workshop

Virtual, Wednesday August 18<sup>th</sup>, 2021

## LH<sub>2</sub> Storage and Handling Demonstrations Using Active Refrigeration

**Adam Swanger**

**Sr. Cryogenics Research Engineer**

NASA Kennedy Space Center, Cryogenics Test Laboratory, KSC, FL 32899 USA

[adam.m.swanger@nasa.gov](mailto:adam.m.swanger@nasa.gov)

# Contents

- LH<sub>2</sub> Background at NASA-KSC
- Integrated Refrigeration and Storage (IRAS)
- Densification
- Ground Operations Demonstration Unit for Liquid Hydrogen (GODU-LH2) Project
  - Objectives
  - System Description
- GODU-LH2 Test Results
- Conclusions
- Questions



# Background

- In the 1950's and 1960's DoD and NASA requirements drove the development of large scale LH<sub>2</sub> systems
- Kennedy Space Center has not substantially changed its LH<sub>2</sub> hardware or processes since that time
- Inefficiencies lead to the **loss of almost 50%** of liquid hydrogen purchased during the shuttle program
- Some technology development work done with densified propellants but never incorporated by NASA



Image Credit : [1]





Image Credit : [2]




Image Credit : [3]

# Integrated Refrigeration and Storage (IRAS)

- Interface a cryogenic refrigerator to a liquid hydrogen storage tank via an internal heat exchanger
- Remove energy directly from the liquid to control bulk fluid
- Enables **Full Control Storage**, including Zero Boil-Off, Densification, and Liquefaction
- NASA and DoE funded small scale LH<sub>2</sub> IRAS proof of concept demonstration from 2002-2006
- NASA funded IRAS Heat Exchanger characterization tests in 2008-2009



# Densification Benefits



Properties of para-hydrogen from RefProp Version 8

- Additional payload to orbit of 4.9% to 17.5% for liquid, up to 26% for slush
- Enables advanced capabilities such as reusability (SpaceX Falcon 9)



- Additional energy storage capacity and enthalpy margin



# GODU-LH2 Project

- Ground Operations Demonstration Unit for Liquid Hydrogen (GODU-LH2) project ran from 2012 to 2016
- IRAS tech development and scale-up

## Project Goal

Demonstrate cost efficient cryogenic operations using IRAS, on a relevant scale that can be projected onto future Spaceport architectures


## Primary Technical Objectives

1. Demonstrate large scale zero loss storage and transfer of  $\text{LH}_2$
2. Demonstrate hydrogen densification inside the storage tank
3. Demonstrate in situ hydrogen liquefaction






# IRAS Tank



- Originally constructed in 1991 for Titan-Centaur program
- 33,000 gallons (125, m<sup>3</sup>) of NBP LH<sub>2</sub> storage
- Modified into an IRAS tank by incorporating an internal HX, stiffening rings, temperature rakes, and man-way feed-through





# Site Build-Up



September 14<sup>th</sup>, 2012




# Site Build-Up



October 30<sup>th</sup>, 2014




# Site Build-Up






# GODU-LH2 Functional Diagram



# “Bird’s-eye View” of GODU-LH2 Site







# Test Matrix and Timeline

- Completed Test Readiness Review on February 12, 2015
- First tanker offload occurred May 21, 2015
- Refrigerator contamination from October 2015 until March 2016
- Compressed testing from March 2016 until October 2016

Test	Start Date	End Date
Chilldown	4/9/2015	5/21/2015
Tanker 1 Offload	5/21/2015	5/29/2015
Tanker 2 Offload	5/3/2016	5/6/2016
Tanker 3 Offload	8/3/2016	8/12/2016
33% Boil Off	5/29/2015	6/19/2015
66% Boil Off	5/6/2016	5/31/2016
100% Boil Off	8/14/2016	8/24/2016
33% ZBO (Press Control)	4/25/2016	5/3/2016
66% ZBO (Press Control)	6/12/2016	6/21/2016
100% ZBO (Press Control)	8/25/2016	9/6/2016
33% ZBO (Temp Control)	6/23/2015	7/13/2015
66% ZBO (Temp Control)	6/21/2016	6/29/2016
100% ZBO (Temp Control)	9/6/2016	9/12/2016
33% ZBO (Duty Cycle)	8/4/2015	8/11/2015
66% ZBO (Duty Cycle)	6/5/2016	6/13/2016
100% ZBO (Duty Cycle)	8/12/2016	8/16/2016
33% Densification	3/24/2016	4/21/2016
66% Densification	6/29/2016	7/23/2016
100% Densification	9/12/2016	10/5/2016
0% Liquefaction	4/9/2015	5/21/2015
33% Liquefaction	9/23/2015	10/8/2015
66% Liquefaction	7/22/2016	8/2/2016



# Inner Tank Instrumentation



## Accuracies


Diodes:  $\pm 0.5$  K from 450 K to 25 K, and  $\pm 0.1$  K from 25 K to 1.5 K

Pressure Transducers:  $\pm 6.89$  kPa (1% of full scale)



# Zero-Loss Tank Chilledown Test Results


- Initial Conditions
  - 99.95% GH<sub>2</sub> at 300 K and 40 psia.
- Lock up tank and turn on refrigerator at T-0.
- Add GH<sub>2</sub> as tank pressure decreases
- Final Conditions
  - Tank near isothermal at 20.8K - 22.4 K and 14.7 psia
  - Saturated vapor with condensation on HX tubing
- Multiple lessons learned would decrease total timeline in the future



**Conclusion: IRAS enables zero-loss chilledown of a large cryogenic vessel**

# Zero-Loss Tanker Offload Test Results

- Based on STS Program data, 13% of purchased  $\text{LH}_2$  is lost due to transport and offload inefficiency
- Heat from transport and line chilldown can be removed by refrigerator, allowing no loss offload
- Zero-loss tanker offloads were achieved at 33%, 67%, and 100% fill levels



**Conclusion: IRAS enables zero-loss tanker offloads at all fill levels**




# Boil-off Heat Leak Test Results

- Boil off testing to quantify heat leak was conducted at 3 fill levels
- Vented thru control valve and mass flow meter
- Pre-test analysis estimated 300 W

$$\dot{Q} = \dot{m} * \{h_{fg} + (h_{\text{ullage}} - h_{\text{sat,vapor}})\} \text{ [W]}$$


Level	MF3	PT2	TT19	Q <sub>L</sub>	Q <sub>V</sub>	Q
%	(slm)	(psia)	(K)	(W)	(W)	(W)
33	255	15.2	49.5	170	120	290
67	295	16.6	41.3	196	100	296
100	351	15.9	34.5	234	81	315



**Conclusion: Tank heat leak was quantified at three fill levels and agreed closely with pretest estimates**

# ZBO Pressure Control Test Results

- GODU-LH2 software controlled refrigerator to achieve and maintain IRAS tank pressure set-point.
- No  $\text{LN}_2$  pre-cooling used
- Approach set points from above and below
- Pressure stability  $\pm 0.5\%$  for all three fill levels
- Near isothermal temperature profile following saturation line




**Conclusion: IRAS using tank pressure control achieves ZBO and provides complete control over the state of the fluid**



# ZBO Temperature Control Test Results


- Linde software controlled refrigerator to achieve and maintain constant helium supply temperature.
- No  $\text{LN}_2$  pre-cooling used
- Helium supply temperature response fast and accurate
- But  $\text{LH}_2$  takes long time period to reach equilibrium state



**Conclusion: IRAS using supply temperature control achieves ZBO but takes a long time to reach  $\text{LH}_2$  equilibrium state**

# ZBO Duty Cycle Test Results

- ZBO achieved in batch processes by turning on and off the refrigerator as required
- Testing was both accidental and purposeful
- Minimum electrical cost but depends on multiple start/stop cycles of cryogenic equipment
- Duty cycle varied from 1.13 (33%) to 1.16 (67%) to 3.6 (100%) on/off with no LN<sub>2</sub> precooling




**Conclusion: IRAS using duty cycling of the refrigerator achieves ZBO with minimal energy but provides no control of LH<sub>2</sub> state**



# Liquefaction Test Results


- $\text{GH}_2$  was controlled using a mass flow controller until the tank pressure remained constant.
- NOT optimized for liquefaction.  $\text{GH}_2$  was fed in at ambient temperature.
- Using  $\text{LN}_2$  pre-cooling, roughly 78 gal of  $\text{LH}_2$  was produced during the test.



**Conclusion: Hydrogen liquefaction was achieved using IRAS, though the current system was not optimized for yield**

# Densification Test Results


- System performance exceeded expectations! Min temp was expected to be  $\approx 15$  K
- Fridge ran with  $\text{LN}_2$  precooling, and densified 13,000 gallons of  $\text{LH}_2$  for 14 days.
- $\text{LH}_2$  cooled below the triple point. Minimum temp recorded was 12.6 K ( $-437^\circ\text{F}$ )
- Estimated that **3,700 lb** of hydrogen ice was formed during the course of testing; or about **5,100 gal**



**Conclusion: IRAS enables propellant densification down to the freezing point**




# Solid Hydrogen Production



46% LH<sub>2</sub> Fill Level Test

# Solid Hydrogen Production



67% LH<sub>2</sub> Fill Level Test



# Conclusions

- The GODU-LH2 system successfully met all test objectives at the 33%, 46%, 67%, and 100% tank fill levels
- Complete control over the state of the fluid has been demonstrated using Integrated Refrigeration and Storage (IRAS)
  - First large-scale demonstration of **Full Control Storage** of LH<sub>2</sub>
  - Almost any desired point within the liquid phase envelop can essentially be “dialed in” and maintained indefinitely
- System can also be used to **produce densified/slush hydrogen in large quantities**

# Current Status of the System

- Refrigeration system consolidated into a single 40' shipping container
- IRAS tank and fridge currently installed at Test Stand 300 at NASA-MSFC in Alabama for an upcoming densification loading test





Thank you for your attention!

Questions?



# Image References

1. Krenn, A., et. al., 2015, The safe removal of frozen air from the annulus of an LH2 storage tank, *Advances in Cryogenic Engineering, AIP Conference Proceedings*, doi:10.1088/1757-899X/101/1/012031
2. [http://www.apolloarchive.com/apollo\\_gallery.html](http://www.apolloarchive.com/apollo_gallery.html)
3. [https://www.nasa.gov/mission\\_pages/shuttle/flyout/launchpadflyout.html](https://www.nasa.gov/mission_pages/shuttle/flyout/launchpadflyout.html)
4. <https://www.teslarati.com/spacex-nears-third-falcon-heavy-launch/>

# Technical References

1. *Kennedy Engineering Academy #144: Final Results of the Ground Operations Demonstration Unit for Liquid Hydrogen (GODU-LH2) Project*, Kennedy Space Center, FL, March 28<sup>th</sup>, 2017 (<https://ntrs.nasa.gov/citations/20170002713>)
2. *IRAS Maximizes Cryogenic Process Efficiency*—Notardonato, Fesmire, & Swanger, *Cold Facts* magazine, Vol 33, Number 3, June 2017 ([https://cryogenicsociety.org/35879/news/iras\\_maximizes\\_cryogenic\\_process\\_efficiency/](https://cryogenicsociety.org/35879/news/iras_maximizes_cryogenic_process_efficiency/))
3. *New Technology at NASA Offers Full Control Of Cryogenic Liquids*—*Cold Facts* magazine, Vol 35, Number 1, February 2019 ([https://cryogenicsociety.org/36886/news/new\\_technology\\_at\\_nasa\\_offers\\_full\\_control\\_of\\_cryogenic\\_liquids/](https://cryogenicsociety.org/36886/news/new_technology_at_nasa_offers_full_control_of_cryogenic_liquids/))
4. *ASME Section VIII Recertification of a 33,000 Gallon Vacuum-Jacketed LH2 Storage Vessel for Densified Hydrogen Testing at NASA Kennedy Space Center*, Swanger A. M., Notardonato W. U., and Jumper K. M., Proceeding of the ASME Pressure Vessels and Piping Conference, Massachusetts, Boston, PVP2015-45625, (2015)
5. *Modification of a Liquid Hydrogen Tank for Integrated Refrigeration and Storage*, Swanger A. M., Jumper, K. M., Fesmire J. E., and Notardonato W. U., *Advances in Cryogenic Engineering*, IOP Conf. Series: Materials Science and Engineering 101 (2015) 012080 doi:10.1088/1757-899X/101/1/012080
6. *Integrated Refrigeration and Storage for Advanced Liquid Hydrogen Operations*, Swanger A. M., Notardonato W. U., Johnson W. L., and Tomsik T. M., *Cryocooler 19: Proceedings of the 2016 International Cryocooler Conference*, San Diego, California, 513-522 (2016)
7. *Large scale production of densified hydrogen to the triple point and below*, Swanger A. M., Notardonato W. U., Fesmire J. E., Jumper K. M., Johnson W. L., and Tomsik T. M., *Advances in Cryogenic Engineering*, IOP Conf. Series: Materials Science and Engineering 101 (2017)
8. *Zero boil-off for large scale liquid hydrogen tank using integrated refrigeration and storage*, Notardonato W. U., Swanger A. M., Fesmire J. E., Jumper K. M., Johnson W. L., and Tomsik T. M., *Advances in Cryogenic Engineering*, IOP Conf. Series: Materials Science and Engineering 101, (2017)
9. *Final test results for the ground operations demonstration unit for liquid hydrogen*, Notardonato W. U., Swanger A. M., Fesmire J. E., Jumper K. M., Johnson W. L., and Tomsik T.M., *Cryogenics*, Volume 88, (2017), Pages 147-155, ISSN 0011-2275, <https://doi.org/10.1016/j.cryogenics.2017.10.008>.