Addendum No. 4 to Master Field Sampling Plan for Chemical Data Gap Investigation Phase 3 Soil Chemical Sampling at Area IV Santa Susana Field Laboratory Ventura County, California

Subarea 5A

Prepared for:

Department of Energy Energy Technology and Engineering Center P.O. Box 10300 Canoga Park, California 91309

Prepared by:

CDM Federal Programs Corporation (CDM Smith) 555 17th Street, Suite 1200 Denver, Colorado 80202

Prepared under:

US Department of Energy EM Consolidated Business Center Contract DE-AM09-05SR22404 CDM Smith Task Order DE-AT30-08CC60021/ET17

August 2012

Addendum No. 4 to Master Field Sampling Plan for Chemical Data Gap Investigation Phase 3 Soil Chemical Sampling at Area IV Santa Susana Field Laboratory Ventura County, California

Subarea 5A

Contract DE-AM09-05SR22404 CDM Smith Task Order DE-AT30-08CC60021/ET17

"I certify that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted.

Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete."

In Polleek

Prepared by: _

Margaret Bloisa, P.G. CDM Smith Geologist

CALIFORNI

Approved by:

John Wondolleck

CDM Smith Project Manager

August 30, 2011

Date

Table of Contents

Introduction	1
Purpose of FSP Addendum	2
Sample Analytes	3
Field Locating Soil Sample Locations	3
Surface Soil Sampling	3
Subsurface Soil Sampling	4
Trenching and Test Pit Sampling	4
Sampling of Locations with Sustained Instrument Readings, Odor, or Staining	5
Decontamination of Sampling Equipment	5
Instrument Calibration and Maintenance	5
Laboratory Sample Preparation (Homogenization	5
Schedule	6
References	6
Figure 1 – Area IV and Northern Buffer Zone Subarea Designation Table 1 – Additional Information for Selected Sample Locations	
Attachment 1 – Subarea 5A Phase 3 Data Gap Analysis Technical Memorandum, Santa Susana Field Laboratory, Ventura County, California (MWH Americas, Inc.)	ì

Tables within Attachment 1 Relevant to the Field Sampling Plan Addendum

Table 1 - Subarea 5A Phase 3 Proposed Soil Matrix Locations

Figures within Attachment 1 Relevant to the Field Sampling Plan Addendum

Figure 1 – Subarea 5A North Phase 3 Proposed Soil Matrix Sampling Locations and Previous Data Summary

Figure 2 – Subarea 5A South Phase 3 Proposed Soil Matrix Sampling Locations and Previous Data Summary

Introduction

This document supports implementation of the soil sampling program described in the *Master Field Sampling Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California* (Master FSP, CDM Smith 2012a). The Master FSP addresses soil sampling within Area IV of the Santa Susana Field Laboratory (SSFL) as required under the *Administrative Order on Consent for Remedial Action* (Docket Number HSA-CO 10/11-037) (AOC) signed by the California Department of Toxic Substances Control (DTSC) and the Department of Energy (DOE). The Master FSP includes field Standard Operating Procedures (SOPs) describing the details of sampling activities and sample management at SSFL. For all samples collected at locations within Subarea 5A, the Master FSP and the SSFL SOPs dictate the procedures pertaining to:

- locating and verifying sampling points
- surface soil sampling techniques
- subsurface soil sampling techniques using a direct push technology (DPT) rig and a hand auger and slide hammer for those locations not accessible by the DPT rig
- sampling of trenches and test pits
- sample handling and shipping
- analytical, quality control, and data review
- instrument calibration and maintenance

The AOC between DTSC and DOE was signed on December 6, 2010. The AOC is a legally binding order that describes the characterization of Area IV and Northern Buffer Zone soils/sediments and further defines DOE's obligations in relation to radiologic and chemical cleanup of soils within these areas. It stipulates that during Phase 1 of the chemical investigation activities, DOE was to analyze a soil sample for chemical constituents at locations where EPA collected a sample for radiological analysis. Phase 1 co-located sampling with EPA in Subarea 5A was completed in April 2011. Phase 2, which was random co-located sampling with EPA in the Northern Buffer Zone was also completed in April 2012.

Phase 3 of the AOC is the data gap investigation, which includes an assessment of data adequacy using the data collected under the Resource Conservation and Recovery Act (RCRA) Facility Investigation (RFI) program, the results of co-located soil samples collected during Phase 1 of the AOC, and multiple lines of evidence as described in the Work Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California (CDM 2012b) (Phase 3 Work Plan). The purpose of the data gap investigation is to identify

additional soil chemical data needed to support the Soil Remedial Action Implementation Plan for Area IV. The sampling that will be performed under this FSP Addendum is based on the results of the data gap investigation.

The Phase 3 sampling within Subarea 5A is governed by the Phase 3 Work Plan and its elements including the Master FSP, Phase 3 Quality Assurance Project Plan (CDM Smith 2012c) (QAPP), Worker Health and Safety Plan (CDM Smith 2012d), and the Phase 3 SSFL SOPs (attachments to the Master FSP and QAPP). These documents are incorporated into this FSP Addendum by reference.

Purpose of FSP Addendum

This FSP Addendum addresses Phase 3 sampling in Subarea 5A. Figure 1 of the Subarea 5A FSP Addendum illustrates the location of Subarea 5A within Area IV of SSFL. The rationale for sample location and chemical analytes is provided in the document Subarea 5A Phase 3 Data Gap Analysis Technical Memorandum, Santa Susana Field Laboratory, Ventura County, California (MWH 2012¹) (Subarea 5A Data Gap TM). The Subarea 5A Data Gap TM is included as an attachment to this FSP Addendum. It illustrates the proposed sample locations and includes a table providing the sampling rationale for each location. Figure 1 of the Subarea 5A Data Gap TM (MWH 2012) provides soil sample locations in the northern portion of Subarea 5A that were identified through the data gap investigation and Figure 2 shows the soil sample locations in the southern portion of Subarea 5A. Table 1 of the Subarea 5A Data Gap TM provides the sampling rationale. Table 1 of the Subarea 5A FSP Addendum, included at the request of DTSC, provides additional information beyond the rationale in Table 1 of the Subarea 5A Data GAP TM for sample locations that target four different conditions that will be encountered in the field. This information will be useful during sample staking and collection.

For Subarea 5A, surface, subsurface, and trench/test pit soil samples will be collected. For surface soil samples, only the top 6-inches of soil (surface soil) will be collected. The majority of sample locations will involve collection of subsurface samples. A direct push technology (DPT) rig will be used to sample subsurface soil at all locations except those inaccessible due to terrain constraints. Areas inaccessible to the DPT rig will be sampled using a hand auger and slide hammer as described in the Phase 3 SSFL SOPs.

CDM Smith will be responsible for all aspects of the field sampling program under Phase 3 of the AOC. This includes locating in the field the sample locations selected during the data gap investigation and that were initially generated and displayed electronically using Geographic Information System (GIS) coordinates. The GIS coordinates are downloaded into a Geographic Position System (GPS) unit for

-

¹ MWH prepared this Technical Memorandum under contract with The Boeing Company, which is under direct contract with DOE. Through this contractual relationship and under the regulatory oversight of DTSC, MWH has represented DOE in conducting the Chemical Data Gap Analysis and in the preparation of this Technical Memorandum.

physically locating the samples in the field. SSFL SOP 1 provides the process for verifying that the sample locations initially identified by GIS review reflect the targeted feature described in Table 1 and are consistent with the GPS coordinates generated in the field. If necessary the sample location will be adjusted in the field so the targeted feature is sampled. Adjusted and all final sample location coordinates will be provided back to the GIS managers so that the GIS database can be updated.

CDM Smith will be responsible for the physical collection of all samples per the procedures and controls specified in the Master FSP. CDM Smith personnel will be responsible for the sample container preparation, sample handling and documentation, sample shipment, laboratory coordination, chemical analyses of the samples, and chemical data review. Soil samples collected by CDM Smith will be analyzed for chemical analytes identified in Table 1 of the *Subarea 5A Data Gap TM* (MWH 2012). Analytical methods and quality control criteria to be used are stipulated in Table 8-3 (Quality Control Objectives for Analytical Methods) of the QAPP (CDM Smith 2012c) and Table 6-1 (Analytical Methods, Containers, Preservatives, and Holding Times) of the Master FSP (CDM Smith 2012a).

Table 1 of the *Subarea 5A Data Gap TM* also identifies proposed target depths for sample collection. Samples will also be collected from depth intervals (until refusal) that exhibit evidence of staining, odor, debris, or photoionization detector (PID) readings above background.

This FSP Addendum only addresses the collection of surface soil and subsurface soil to the bedrock interface. The sampling of soil gas or other media will be addressed in a future sampling plan.

Sample Analytes

Table 1 of the *Subarea 5A Data Gap TM* (MWH 2012) provides the chemical analyses (analytes) for each sample proposed for collection under this FSP Addendum and the respective rationale for sample location and chemical analyses. The chemical analyses by location were identified through the data gap investigation process.

Field Locating Soil Sample Locations

CDM Smith will be responsible for determining the precise position of soil sample locations in the field in accordance with SSFL SOP 1. At the same time, each sample location will also be cleared for buried utilities, and assessing the presence of cultural and biological resources for their protection.

Surface Soil Sampling

Surface soil samples will be collected at each location as proposed in Table 1. Surface soil samples will be collected in accordance with SSFL SOP 2. A slide hammer with stainless steel sleeve will be used to collect the soil sample to be analyzed for semi-

volatile organic compounds and polychlorinated biphenyls. Volatile organic compounds and total petroleum hydrocarbon samples will be collected using Encore samplers. Soil for all other sample analytes will be place in one or more glass jars.

Subsurface Soil Sampling

Subsurface soil samples will be primarily collected through the use of a DPT rig. SSFL SOP 4 describes the DPT sampling procedures. Sampling will be conducted through the use of 5-foot long acetate sleeves placed within the DPT sampling tool. All cores will be screened using a PID instrument for volatiles and via a Micro R gamma detection instrument and a dual phosphor alpha/beta detection instrument (SSFL SOPs 6 and 7, respectively). Soil samples will be collected at the depths specified in Table 1 of the *Subarea 5A Data Gap TM* (MWH 2012) and/or at locations where instrument readings, soil staining, or evidence of debris is observed.

To determine depth of contamination at locations where prior data indicates contamination at the surface but depth has not been defined, the core will be divided into one-foot long samples and prepared for shipment to the laboratory. The laboratory will be requested to analyze the shallowest interval first (e.g., 1 to 2 foot interval) and provide results in an expedited turnaround time. If chemicals are detected above the interim screening levels, the lab will be instructed to analyze the next interval (e.g., 2 to 3 foot interval) and provide results under expedited analytical turnaround time. This process may be repeated depending on results. To address holding time concerns, the lab may be instructed to extract each interval and hold the extract until the prior interval results are available. Table 1 identifies the locations where the depth analysis process is proposed.

There are proposed sampling locations that the DPT rig will not be able to access. At those locations, subsurface samples will be collected using a hand auger to access the sample depth and a slide hammer sampler with stainless steel sleeve to collect the actual sample. SSFL SOP 3 describes the hand auger sampling procedure.

The soil logging of all samples, surface and subsurface, will be conducted following SSFL SOP 9.

Trenching and Test Pit Sampling

The investigation of Subarea 5A will include the characterization of debris and fill areas through backhoe trenching. Figures 1 and 2 of the *Subarea 5A Data Gap TM* identify the trench locations. The primary purpose of the trenches will be to visually characterize fill material and to sample subsurface soil within the trench.

Prior to any trenching, geophysical surveys of the trenching locations will be conducted to identify potential buried debris and to assist in targeting trench locations. The geophysical surveys will include ground penetrating radar, electromagnetic surveys, and soil density surveys. Procedures for the geophysical surveys are described in SSFL SOP 14. The firm selected to perform the surveys will

prepare a detailed plan of their procedures for DTSC review prior to conducting the surveys.

Where sampling can be performed safely, soil samples will be collected from the side wall of the trench/pit to 5 feet below ground surface (bgs) using an impact sampler with extended rod. Soil samples deeper than 5 feet below ground surface (or when samples cannot be collected safely at 5 feet bgs) will be collected directly from the backhoe bucket using the impact sampler. SSFL SOP 5 describes the test pit sampling procedure.

Sampling of Locations with Sustained Instrument Readings, Odor, or Staining

For any locations where PID instrument readings remain above measured background readings, there is an odor, or the soil appears to be stained with hydrocarbons, samples will be collected at the sample depth interval and analyzed for VOCs, 1,4-dioxane, and total petroleum hydrocarbons-gasoline range organics (TPH-GRO) using Encore samplers, in addition to the target analytes specified in Table 1 of the *Subarea 5A Data Gap TM*. Any sustained instrument readings above background (PID, Micro R gamma detection and dual phosphor alpha/beta detection instruments) will be immediately reported to DOE by the CDM Smith Field Team Leader and DOE will contact Boeing with this information in accordance with the Worker Health and Safety Plan requirements. The monitoring instruments will be operated per SSFL SOPs 6 (volatile organics) and 7 (radiation).

Decontamination of Sampling Equipment

Equipment that comes in contact with sample material will be decontaminated per SSFL SOP 12. Investigation derived waste will be handled per SSFL SOP 13.

Sample Handling, Recording, and Shipment

SSFL SOPs 10 and 11 describe the sample custody, handling, information recording, preservation, and shipping procedures. Photographic documentation of sampling activities will be performed per SSFL SOP 15.

Instrument Calibration and Maintenance

All instruments used to screen samples for volatile organics and radioactivity will be calibrated and maintained per SSFL SOP 16.

Laboratory Sample Preparation (Homogenization)

Soil samples intended for chemical analyses of non-volatile and non-semivolatile constituents (e.g. metals, PCBs, and dioxins) will be homogenized by the analytical laboratory in the laboratory in accordance with SSFL SOP 17.

Schedule

Soil sampling activities under this FSP Addendum will most likely start the first week of September, 2012, following DTSC approval of this 5A Subarea FSP Addendum, with the locating and staking of proposed sample locations and utilities clearance. Surface soil sampling will start mid October 2012, and subsurface soil borings (handauger and DPT) will start on October 29, 2012. It is anticipated that 40 surface samples, 32 shallow hand auger samples, and 32 DPT boring samples will be collected each week. As a budget saving measure, geophysical surveys, test pits, and trenching for Subareas 5C, 5B, and 5A will be performed at one time. Therefore test pits and trenching will not occur until after completion of the surface, DPT, and hand auger sampling proposed in this Subarea 5A addendum. A plan for conducting the geophysical surveys will be provided to DTSC in September. Each trench/test pit will take one day to dig, describe, sample, and backfill.

References

- CDM Smith. 2012a. Master Field Sampling Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- CDM Smith. 2012b. Work Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- CDM Smith. 2012c. Quality Assurance Project Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- CDM Smith. 2012d. Worker Health and Safety Plan for Chemical Data Gap Investigation, Phase 3 Soil Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- MWH 2012. Subarea 5A Phase 3 Data Gap Analysis Technical Memorandum Santa Susana Field Laboratory, Ventura County, California. August.




Table 1
Additional Information for Selected Sample Locations

-	1	ation for Selected Sample Locations
	5A_DG-777	
	5A_DG-799	
	5A_DG-800	
	5A_DG-801	
	5A_DG-802	Samples are proposed within potential dredge piles and hummocky areas
	5A_DG-804	suspected to contain dredge pile materials. First, excavate trenches through
Potential Dredge Piles/Hummocky Areas	5A_DG-807	the areas identified and log sediments, native soil, and the contact between
Potential Dieuge Flies/Hullillocky Aleas	5A_DG-808	fill and native material. Collect samples in the sidewall to target the
	5A_DG-810	fill/sediments, top of native soil, and soil just above bedrock.
	5A_DG-812	ling sediments, top of native soil, and soil just above bedrock.
	5A_DG-817	
	5A_DG-818	
	5A_DG-820	
	5A_DG-821	
	5A_DG-506	
	5A_DG-509	
	5A_DG-512	
	5A_DG-542	Constitution of the test of th
	5A_DG-547	Excavate test pits to investigate linear geophysical anomalies as potential
Took Bits at Coombusies! Amouselies	5A_DG-548	pipelines identified by EPA. Inspect test pits for signs of backfill, impacts
Test Pits at Geophysical Anomalies	5A_DG-587	(staining, debris, etc.), piping, or other subsurface infrastructures. Collect
	5A_DG-635	samples at top of native and just above bedrock to evaluate depth of
	5A_DG-636	uncertainty of feature and potential recharge to groundwater.
	5A_DG-730	
	5A_DG-740	
	5A_DG-757	
	5A_DG-828	
	5A_DG-829	
	5A_DG-830	
	5A_DG-831	Samples are proposed across drainage in a transect. Recollect sample within
Dunings Transacts	5A_DG-832	the drainage pathway and advance boring to bedrock; collect samples at 5-
Drainage Transects	5A_DG-833	foot and 10-foot stepouts on each bank laterally from the drainage and also
	5A_DG-834	advance to bedrock.
	5A_DG-835	
	5A_DG-836	
	5A_DG-837	
		Detects will refer of consider leaves the second consideration of the second considera
	FA DO 055	Prior to collection of samples, locate the position or trace of the surface water
Ephemeral Drainages	5A_DG-852	drainage pathway and map with GPS. Look for rilling, topographic low, or
-	5A_DG-853	other surface features indicative of a surface water pathway. Collect sample
		within the center of the drainage pathway.
	5A_DG-522	
	5A_DG-535	Conduct geophysical surveying to locate position of removed fuel oil
	5A_DG-550	USTs (UT-18, UT-19, and UT-22) and position of former trenches within
Tank and floor trench samples	5A_DG-551	Building footprints (Buildings 4042 and 4032). Previous sampling
	5A_DG-564	conducted at the fuel oil USTs UT-18 and UT-19 do not appear to have
	5A_DG-619	targeted the correct location based on review of facility diagrams.

NOTE: If a previous sample location is referenced and/or being re-sampled, look for the original staked location in addition to re-locating using GPS coordinates. If the stake is missing look for a cut in asphalt/concrete, a depression in the soil, or other physical evidence of the actual boring location.

Attachment 1 Subarea 5B Phase 3 Data Gap Analysis Technical Memorandum, Santa Susana Field Laboratory, Ventura County, (MWH 2012)

SUBAREA 5A PHASE 3 DATA GAP ANALYSIS TECHNICAL MEMORANDUM SANTA SUSANA FIELD LABORATORY VENTURA COUNTY, CALIFORNIA

Prepared For:

THE UNITED STATES DEPARTMENT OF ENERGY

Prepared By:

MWH Americas, Inc. 618 Michillinda Ave, Suite 200 Arcadia, CA 91007

August 2012

"I certify that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete."

August 2012

Alex Fischl, P.M.P.

Data Gap Manager

Mark Sherwin, P.G. 7874 **Senior Technical Lead**

CH 6532

David Collins, P.E. CH 6532 **Project Manager**



TABLE OF CONTENTS

Section	<u>Page No.</u>
1.0	INTRODUCTION1
2.0	DATA GAP ANALYSIS PROCESS 1
2.1	COMPARISON OF PREVIOUS SAMPLING DATA TO SCREENING CRITERIA 2
2.2	EVALUATION OF MIGRATION PATHWAYS4
2.3	HISTORIC AND SITE SURVEY INFORMATION REVIEWS
2.4	DATA GP ANALYSIS PROCESS SUMMARY6
3.0	SUBAREA 5A DATA GAP ANALYSIS
4.0	REFERENCES
	TABLES
<u>Table</u>	e No.
1	Subarea 5A Phase 3 Proposed Soil Matrix Sample Locations
2	Subarea 5A Phase 3 Proposed Soil Vapor Sample Locations
3	Subarea 5A Phase 3 Proposed Sample Locations for Future Collection
4	Subarea 5A Data Gap Checklist
	FIGURES
<u>Figur</u>	e No.
1	Subarea 5A North Phase 3 Proposed Soil Matrix Sampling Locations
2	Subarea 5A South Phase 3 Proposed Soil Matrix Sampling Locations
3	Subarea 5A Phase 3 Proposed Soil Vapor Sampling Locations
4	Subarea 5A Proposed Locations of Geophysical Surveys



ACRONYMS AND ABBREVIATIONS

AOC Administrative Order on Consent

DOE Department of Energy
DQO Data Quality Objective

DTSC Department of Toxic Substances Control

EPA Environmental Protection Agency
GIS geographic information system

HGL Hydrogeologic, Inc.

HSA historical site assessment ISL interim screening level

MFSP Master Field Sampling Plan

MWH MWH Americas, Inc.

NDMA n-Nitrosodimethylamine

NBZ Northern Buffer Zone

PAH polyaromatic hydrocarbon

PCB polycyclic biphenyls

PDU Process Development Unit

RCRA Resource Conservation and Recovery Act

RFI RCRA Facility Investigation
SSFL Santa Susana Field Laboratory
TIC tentatively identified compound

TM technical memorandum

VOC Volatile Organic Compound



1.0 INTRODUCTION

This technical memorandum (TM) has been prepared to describe the chemical data gap analysis performed by MWH Americas, Inc. (MWH) for the U.S. Department of Energy (DOE) for Subarea 5A within Area IV and the Northern Buffer Zone (NBZ) at the Santa Susana Field Laboratory (SSFL). The chemical data gap analysis was performed in compliance with the Administrative Order on Consent (AOC) for Remedial Action (AOC; Docket No. HSA-CO 10/11 - 037), and serves as the basis for the Phase 3 data gap investigation being performed in Subarea 5A within Area IV by DOE and implemented by CDM Smith, a contractor to DOE. This Data Gap TM is included as an appendix to the Master Field Sampling Plan (MFSP) Addendum for Subarea 5A prepared by CDM Smith for review and approval by the California Environmental Protection Agency Department of Toxic Substances Control (DTSC).

The focus of this Data Gap TM is Subarea 5A. Information is provided to describe the overall background and approach for the chemical data gap analysis and investigation, followed by a description of specific application of the data gap analysis approach or unique circumstances within Subarea 5A.

2.0 DATA GAP ANALYSIS PROCESS

The AOC requires a chemical data gap investigation to identify locations within Area IV, the NBZ, or contiguous areas where additional chemical investigation is necessary. Per the AOC (Section 2.5.3.2):

"In determining the scope, DOE and DTSC shall evaluate the results from the Phase 1 Co-Located sampling effort, the results from the Phase 2 Co-Located sampling effort¹, the results of the U.S. EPA's radiological survey and characterization efforts, the data and information presented in the previous RFI reports and RFI work plans, and any available historical Site data. This scoping effort shall be used to determine the locations at the Site where insufficient chemical data exists and additional chemical investigation is necessary."

This Data Gap TM describes the data evaluation process that has been used to identify chemical data gaps. Data gaps exist where more information is needed for DTSC and DOE to make remedial planning decisions, (i.e., whether soil contamination exists, and if so, to what extent). The data gap analysis approach was developed using the U.S. Environmental Protection Agency's (EPA's) seven-step Data Quality Objective (DQO) process that presents a systematic approach to identify chemical sampling needs, address existing data gaps, and obtain environmental data and information required for future remedial planning. The Phase 3 chemical

¹ According to the AOC, the Phase 2 random sampling is to be conducted with EPA. EPA has completed random sampling within the NBZ. The data gap analysis will use the results from Phase 2 sampling within the NBZ to assess additional sampling for that area.



-

data gap investigation DQOs are the framework for the analysis described in this TM and are presented in Section 4.0 of the MFSP (CDM Smith, 2012b).

The Phase 3 data gap analysis described in this TM will be an iterative process. At this time in the data gap analysis process, data are compared with the interim screening levels (ISLs) developed for evaluation of available data (see Master Phase 3 Work Plan Table 2-1, CDM Smith, 2012a). The ISLs were developed jointly by DTSC and DOE, and reflect the 2005 background soil concentrations for metals and dioxins, and analytical reporting limits for chemicals not having a background value. In the future, background values will be updated based on the ongoing DTSC soil chemical background study and evaluation of the precision and accuracy requirements for reporting limits. Ultimately, all available previous data, including EPA radionuclide data, will be evaluated based on the final soil cleanup values (Look-up Table values) per the AOC. Therefore, a final data gap analysis will be required incorporating data collected as described in this TM and the Master Phase 3 Work Plan (CDM Smith, 2012a), prior chemical data, and EPA radionuclide results.

The data gap analysis described in this TM is based on available results from EPA's radiological investigation activities (e.g., gamma surveys, geophysical surveys, aerial photograph interpretations), prior Resource Conservation and Recovery Act (RCRA) Facility Investigation (RFI results), the Phase 1 co-located sample results, and historical information on activities within Area IV. Since recent radiological data have not been completely published by EPA, this data gap analysis used available EPA summaries of these results for planning purposes.

The data gap analysis identifies where additional information is needed for remedial planning by:

- Comparing existing soil sampling results to ISL criteria to identify additional sample locations needed to define the extent of contamination (based on criteria exceedance) and/or gradients in chemical concentrations away from a potential source;
- Evaluating migration pathways to ensure that samples are collected where contamination may have migrated via natural or anthropogenic processes; and
- Evaluating historical documents and site survey information to identify potential release areas that may not have been adequately characterized.

Each of these evaluation steps are described below.

2.1 COMPARISON OF PREVIOUS SAMPLING DATA TO SCREENING CRITERIA

To determine future chemical sampling needs (to be implemented under the Master Phase 3 Work Plan and MFSP), validated soil chemistry results are compared with ISL criteria. The



ISLs reflect either existing 2005 soil background concentrations for metals and dioxins² or analytical reporting limits for chemicals that do not have 2005 background concentrations. Table 2-1 in the Master Phase 3 Work Plan (CDM, 2012a) lists the ISL values currently being used for the data gap analysis.

This data comparison is conducted to answer several questions:

- Are the data adequate to define the extent of soil contamination? (i.e., What is the areal extent? How deep does contamination go?)
- Where are additional data needed to address areal and depth extent?
- What types of chemical data are needed at each location?

The soil chemical results within the analytical database are "filterable," meaning each individual soil chemical result can be selectively evaluated or results can be collectively reviewed for each prior sample point. The analytical database incorporates data files for soil chemical data collected under the RFI and co-located sampling programs. A geographic information system (GIS) is used to spatially display the sampling results. To display the data, the sampling results are compared with the ISL values for all chemicals analyzed at each sample location using a computer algorithm. The algorithm calculates the ratio of the soil concentration to the ISL value. The GIS is then used to display the maximum comparison value (i.e., 'ratio') at a sampling location, so that the highest result relative to the ISL is displayed. The GIS uses a color-coded system to display the soil concentration relative to the ISL value. For example, soil concentrations that are at or below the ISL value are displayed as a blue symbol. Locations where the soil concentration exceeds the ISL are displayed as yellow, orange, magenta, or red, depending on the degree of exceedance of the ISL value. Maps displaying the sampling results as color-coded symbols are included in this Data Gap TM (Figures 1, 2, and 3) to help display this evaluation step in the context of proposed sampling locations.

The data gap evaluation includes review of sampling results for combined chemicals, individual chemical groups (e.g. volatile organic compounds [VOCs], polyaromatic hydrocarbons [PAHs], polycyclic biphenyls [PCBs], etc.), and individual chemicals (e.g., barium, perchlorate). Sampling results in the database are 'filtered' to determine which chemicals are above ISLs, their depth of occurrence, and which chemicals are co-located. This allows for effective evaluation and selection of step-out sample locations and analytical suites for assessing the extent and/or distribution of chemicals that exceed their respective ISLs. In some cases where detected chemical concentrations slightly exceed ISL values, Phase 3 step-out sampling is not proposed in this Data Gap TM, but will be subject to an additional data gap review once the final AOC Look-

² DTSC is in the process of completing a new soil background study that includes additional chemicals not analyzed in the 2005 study. When the new background values are finalized they will replace the existing background values and will be used for subsequent data gap analyses.



-

Up Table values are made available. Similarly, sampling to address elevated reporting limits in historical data is not proposed in all areas of Subarea 5B in this Data Gap TM. In areas where other data gaps have been identified, sampling for elevated reporting limits is also proposed as needed. In other areas, data gap evaluation for elevated reporting limits in historical data will be addressed after final Look-Up Table values are established and in the context of recent sampling results.

The GIS display of the ISL-compared sampling results is used to evaluate potential sampling locations. In areas where detected concentrations exceed ISLs, previous sampling data are evaluated to determine if the lateral or vertical extent of the exceedance is limited by other sampling results below ISLs or other features at the site (e.g., bedrock). If not, then additional sampling is proposed in that area. Conversely, in some areas existing sampling results are adequate to support remedial planning or cleanup decisions. A review of the distribution of results along with other lines of evidence (described below) is used to identify where additional sampling is needed.

Some locations with significant exceedances of ISL values have been identified by DOE and DTSC as soil "clearly contaminated areas." These are areas most likely requiring remediation based on the existing elevated sampling results, and are displayed in GIS and on maps in this TM with pink shading. The data gap analysis for these areas considers whether sufficient information is available to determine the lateral and vertical extent of contamination. In many cases, more data are needed to determine a volume of soil to be removed for use in remedial planning, and additional sampling is proposed in these areas.

2.2 EVALUATION OF MIGRATION PATHWAYS

Migration pathways are the means by which chemicals can move in the environment, including surface water transport, downward movement to subsurface soil, or air/wind dispersion. Migration pathways are evaluated to answer several questions:

- Where could potentially contaminated soil migrate via surface water flow?
- Where could contaminants migrate in subsurface soils? Could groundwater be affected by the soil contamination?
- Were chemicals potentially released into the air, dispersed by wind and deposited in surrounding areas at concentrations exceeding ISLs?

The topographic and surface water flow data in the GIS is used to identify surface water pathways from potential contamination sources. Prior data for those pathways will be evaluated as to the adequacy for addressing contaminant migration. If additional data are needed to define



the extent of chemicals moved by surface water, downward migration in the subsurface, or to assess air dispersion, sampling locations are proposed for the migration pathways.

This data gap analysis identifies previous soil sampling locations or features where there may be outstanding groundwater investigation program data needs. At these features, the data gap analysis is evaluating the adequacy of existing soil sampling results to assess potential migration of contaminants to groundwater, and proposing additional soil sampling to the top of bedrock if gaps are identified.

2.3 HISTORIC AND SITE SURVEY INFORMATION REVIEWS

The data gap analysis also addresses potential sources of contamination not covered by prior sampling events. Historical survey and site operational information for Area IV is represented in GIS and viewed in context of previous sampling results. Historical and site survey information will be used to answer two questions:

- Are there any potential chemical use/release features that have not been sampled?
- If a potential chemical use area has already been sampled (but not for all chemicals potentially used), are additional samples/analyses needed to complete characterization?

A checklist has been developed that is reviewed along with the chemical data to ensure that features not covered by RFI or Phase 1 co-located sampling are addressed. The checklist includes the results of the historical site assessment (HSA) conducted by Sapere (2005), site operational and aerial photographic information recently compiled for the RFI, and the recent HSA completed by EPA (Hydrogeologic, Inc. [HGL], 2012). The "lines of evidence" reviewed as part of the checklist are published in the Master Phase 3 Work Plan Table 2-2, and provided herein (Table 4) for how they were applied in Subarea 5A.

Site information includes various site features or survey information that is displayed in GIS using a common coordinate system (similar to latitude and longitude). Tanks, buildings, leach fields, geophysical survey results, historical aerial photos, storage areas, debris/disposal areas, identified chemical use areas, and surface water flow paths are examples of site information/features used to identify potential data gaps and proposed sampling locations. Site information is shown as layers in GIS that can be displayed individually or combined with sampling results. The site information features, compiled from historical documents, aerial photo review, and site surveys are evaluated using existing data to assess the completeness of characterization. If gaps are identified (e.g., a storage area not previously sampled), sampling is proposed with the analytical suites developed based on surrounding site operational uses and existing sample result exceedances.



In addition to site historical use or survey information, soil borings and trench logs are reviewed to identify relevant soil conditions (e.g., debris, staining, bedrock depth) since unique soil characteristics may also guide proposed sampling intervals. For example, sampling may be proposed both within and below stained horizons, or in another case, both within fill materials and below fill materials in underlying native soils. In both of these cases, sampling is needed below a potential contamination zone to identify how far contamination has migrated downward.

Data gaps associated with some historical operational use features are not addressed in this Data Gap TM but will be included in future documents. Historical operational use features not addressed in this plan include the Area IV sewer system, the natural gas pipelines within Area IV, and features within existing Area IV buildings. Data gaps associated with the sewer system and natural gas pipelines are being evaluated for these systems as a whole, and will be addressed in a separate Data Gap TM. Where applicable, sampling is proposed in this TM where sewer pipelines leave former or existing buildings since these are considered site-specific sampling features. Data gaps associated with existing buildings are being evaluated as part of this process, but sampling requirements within or below existing buildings will be detailed in forthcoming demolition plans since that work will proceed under a different schedule and process.

2.4 DATA GAP ANALYSIS PROCESS SUMMARY

A systematic process that incorporates the evaluation components discussed in Sections 2.1 through 2.3 is being used during data gap analysis to ensure available information from multiple sources is considered during data gap review. Thus, combining data gap recommendations from the three evaluation components (data screening evaluations, migration pathway evaluations, and historical document/site survey reviews), sampling is proposed for the evaluated subarea.

The outcome of the data gap analysis process is the identification of soil sampling requirements for Phase 3, including rationale for Phase 3 samples, their locations, depths, and proposed analytical suites. Both soil and soil vapor sampling for chemicals in Phase 3 are proposed in this TM ('soil' sampling is often referred to as 'soil matrix' sampling to distinguish it from soil vapor sampling). Soil matrix and soil vapor media provide different types of chemical data for remedial planning purposes. Soil vapor sampling is preferred to assess the potential release of solvents, which contain VOCs. Since VOCs are highly volatile, they are best evaluated in soil vapor samples, not soil matrix. Therefore, soil vapor sampling is proposed in this TM to evaluate locations where solvents may have been used, stored, or released, or to step-out around previous detections of VOCs above ISLs. Soil vapor sampling is also proposed to provide VOC data over larger areas to evaluate potential solvent release locations when historical operations are uncertain (e.g., large storage areas), or to assess vapor transport from an underlying groundwater plume.



The analytical parameters proposed for step-out or step-down sampling locations are based both on what the prior data indicate are chemicals of potential concern for the location, in conjunction with data needs identified based on review of migration pathways and other lines of evidence. Proposed sample spacing is based on the types of operations and releases, the magnitude and gradients of nearby sampling results, and site conditions (e.g., depth of soil, proximity of bedrock outcrops). Generally, samples are located with a 25 to 100 foot spacing laterally, and at 0.5-, 5-, and 10-foot depth intervals vertically. In many cases the deepest samples will be placed on 'hold' by the laboratory, and analyzed if elevated results are detected in the shallower samples. In special cases, sampling is proposed at shallower depths (e.g., 2 feet) to assess potentially more limited downward migration of large organic molecules like PCBs, dioxins, or PAHs.

The data gap analysis also identifies additional investigation techniques for some areas to aid in selection of sampling locations. The additional investigation techniques can include trenching or test pit excavation to observe soil conditions prior to sampling, or geophysical surveying of areas to identify targeted features, such as pipelines, underground storage tanks, or fill areas. In some cases, field reconnaissance or mapping is needed to refine proposed sampling locations, such as along drainages. The sampling rationales included in this Data Gap TM specify these additional investigative techniques where applicable.

The data gap analysis can identify future sampling locations outside of the subarea being evaluated. These future locations are displayed with pink '+' symbols on Figures 1 and 2. In some cases, the samples are located outside of Area IV and will require additional surveys and coordination prior to sampling. In other cases, the proposed samples are within another subarea, and will be included in the corresponding Data Gap TM.

The information presented in this Data Gap TM, along with supporting GIS and analytical information, is reviewed with DTSC during the data gap process and with interested stakeholders at the end of the data gap process. Input received from DTSC during review and from the public during meetings is incorporated into the proposed sampling included in this Data Gap TM.

3.0 SUBAREA 5A DATA GAP ANALYSIS

The data gap analysis for Subarea 5A was performed following the process outlined above and using the DQOs presented in Section 4 of the MFSP (CDM Smith, 2012b). The proposed sampling for this subarea is presented in Tables 1 (Soil Matrix), 2 (Soil Vapor), and 3 (Future), and Figures 1 (5A North), 2 (5A South), 3 (Soil Vapor), and 4 (Geophysical Survey Areas). Table 4 presents the lines of evidence evaluation summary for this subarea, with checkmarks indicating what information resulted in proposed data gap samples.



As part of the Subarea 5A data gap analysis, some areas were identified where the DQOs were uniquely applied, or where specific sampling approaches have been recommended. These are briefly described below. More detailed, sample-specific rationales for these (and all) areas are provided in Tables 1 through 3.

- Adjacent to the Process Development Unit (PDU) Clearly Contaminated Area, sampling is proposed to define its lateral extent, as well as to assess additional features in the area such as above-ground tank or possible stained soil locations. Samples are not proposed inside the clearly contaminated area since the depth of contamination is sufficiently defined and depth to bedrock generally shallow. Because potential underground storage tanks have been identified in the PDU area with unknown or uncertain locations, this entire operational area is identified for additional geophysical surveying as shown in Figure 4.
- Near the PDU Coal Storage Clearly Contaminated Areas 1 and 2, samples are proposed to define their lateral extent targeting along the edge of where the coal was stored since the parking lot was paved and the surrounding soils received runoff. Additional representative sampling is also proposed within the storage area itself.
- At representative geophysical anomaly locations, investigation using test pits are proposed to evaluate potential subsurface features associated with each anomaly and to inspect soil conditions prior to collecting a soil sample (e.g., 5A_DG-509, 5A_DG-512, 5A_DG-635, 5A_DG-636, and 5A_DG-730).
- Within historical unlined drainages in Subarea 5A, sampling locations are proposed based on aerial photograph review. These unlined drainage ditches occur along G Street, 12th Street, and 17th Street (at the western boundary of Subarea 5A). Samples will be collected down to bedrock to evaluate potential vertical migration into the bedrock and groundwater.
- At other water collection and conveyance features in the northern portion of Subarea 5A, sampling is proposed at representative locations along the conveyance system, and at junctions and discharge points. This man-made stormwater collection system includes an extensive network of catch basins, collection trenches, and associated underground stormwater piping. Samples will be collected beneath the feature, with the deepest sample collected above bedrock to assess vertical migration into groundwater and horizontal migration along bedrock (e.g., 5A_DG-520, -531, -552, -558, and -582). Proposed sample analysis at these locations includes corrosion inhibitor chemicals since these features may have received liquid waste from facilities that used or stored cooling water. As described in the Subarea 5B Data Gap TM, potential corrosion inhibitor chemicals include hexavalent chromium, arsenic, hydrazine, and morpholine. Since hydrazine breaks down rapidly in the environment, sample analysis for the breakdown



products n-Nitrosodimethylamine (NDMA) and formaldehyde are included in the analysis plan. Morpholine is not a typical laboratory analyte and will be identified if present as a tentatively identified compound (TIC). To assess potential solvent release to this conveyance system, soil vapor sampling for VOCs is also proposed at representative locations.

- East of the 17th Street Pond and Drainage Clearly Contaminated Area, lateral step-out sampling is proposed to define the extent of contamination northeast of the former pond area. Samples are proposed along a northeast trend in the clearly contaminated area, generally following the extent of cleared vegetation and possible disturbed soils observed in a 1959 historical aerial photograph, which is also co-incident with the sewer pipeline in this area (e.g., 5A_DG-792, -793, and -789).
- Within and adjacent to the Eastern Hummocky Clearly Contaminated Area, sampling locations are proposed to define its lateral and vertical extent. As part of this data gap analysis, field mapping was performed to locate mounded soil piles. The field mapping focused in the vicinity of the Eastern Hummocky Clearly Contaminated Area and along roads, but also included a general reconnaissance throughout the southern 5A Subarea. Several soil mounds were identified in proximity of this clearly contaminated area, and are targeted for data gap sampling. At these proposed sampling locations, exploratory trenching of the soil mounds will be conducted prior to sampling to characterize soil beneath the sediments and evaluate vertical migration of contaminants (e.g., 5A_DG-808, -810, -812). Future sampling is also proposed south of the contamination area to assess downslope migration of contaminants into Area III (e.g., 5A_DG-803, -805, and -806).
- Sampling to address potential impacts to groundwater is proposed at several locations (listed below and shown on Figure 3). Proposed sampling at these locations includes vertical sampling to top of bedrock (including VOC analysis in the deepest samples collected) and soil vapor sampling. In addition, further evaluation by the groundwater team is recommended for mobile chemicals detected in soil in the vicinity of these features, including VOCs, perchlorate, hexavalent chromium, nitrate, and NDMA. Since some of these mobile chemicals are being evaluated as part of the DTSC background study, characterization of these constituents may be completed after background is established. The identified potential groundwater input features/locations identified in Subarea 5A are:
 - o Building 4024 Sub-grade Reactor Test Cell Complex
 - o Building 4024 Hot Waste Storage Tanks
 - o Building 4024 Liquid Waste Tanks and Retention Basin
 - o Building 4005 Radioactive Liquid Waste Holdup Tank Vault



- o Building 4005 Sump
- o Building 4005 Cooling Tower Sump
- o Building 4073 KEWB Reactor
- o Building 4093 Leach Field

4.0 REFERENCES

- CDM Smith. 2012a. Work Plan for Chemical Data Gap Investigation, Phase 3 Chemical Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- CDM Smith. 2012b. Master Field Sampling Plan for Chemical Data Gap Investigation Sampling at Area IV, Santa Susana Field Laboratory, Ventura County, California. April.
- Hydrogeologic, Inc. (HGL) 2012. Draft Final Historic Site Assessment Santa Susana Field Laboratory Site Area IV Radiological Study, Ventura County, California.





Table 1 Subarea 5A Phase 3 Proposed Sample Locations (1 of 39)

	1	1	<u> </u>		1							An	alvtic	cal Method								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)		(EPA Method 8015B) TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A DG-501	SETF	Drainage Northwest of	Soil Boring	0.5	X	X	X	X						X					X	X	*	Location targets low spot in drainage before entering culvert inlet (dioxins, metals, and PAHs detected above ISLs in existing samples within drainage). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with the deepest sample
511_5 0 001	5211	Building 4024	Son Boring	5	X	X	X	X						X					X	X		just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Same as 5A_DG-537 (note, sample located south of pole-mounted transformer identified in HMSA RFI Report; prior sampling of transformer was ND for PCBs).
5A_DG-502	SETF	Northwest of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	*	identified in Thylor Kill Report, prior sampling of dansformer was 110 for 1 cbs).
				10	Н	Н	Н	Н						Н					Н	Н		
54 DG 502	CETTE	Open Storage West of Building	C ID :	0.5	X	X	X	X						X					X	X		Stepout from SL-237-SA5A (PAHs detected above ISLs at 10') and characterizes open storage area with most storage along fence. Bedrock anticipated ~15'. Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock.
5A_DG-503	SETF	4024	Soil Boring	5	X	X	Н	X						X					X	X	•	Analyze 10' sample for PAHs only (hold other analyses pending shallower results).
				10	X	Н	Н	Н						Н					Н	Н		Stepdown from SL-237-SA5A for deeper sample (PAHs detected above ISLs at
		Onen Storese West of Duilding		0.5	X	X	X	X						X					X	X		10') and characterizes open storage area with most storage along fence. Bedrock
5A_DG-504	SETF	Open Storage West of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	*	anticipated ~15'. Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock. Analyze all depths for PAHs only; hold other analyses pending
				10	X	Н	Н	Н						Н					Н	Н		shallower results.
5A DG-505	SETF	Open Storage West of Building	Soil Boring	0.5 5	X	X	X H	X						X					X	X	/	Same as 5A_DG-503.
		4024		10	X	Н	Н	Н						Н					Н	Н		
			Soil Boring /	0.5	X	X	X	X						X					X	X		Same as 5A_DG-503.
5A_DG-506	SETF	West of Building 4024	Test Pit	5 10	X H	X H	X H	X H						X H			1	1	X H	X H	\	
				0.5	Х	п X	Х	Х						X					п Х	Х		Stepout from SL-237-SA5A (PAHs detected above ISLs at 10') and characterizes
5A_DG-507	SETF	Open Storage West of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	✓	open storage area with most storage along fence. Bedrock anticipated ~15'. Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock.
		4024		10	X	Н	Н	Н						Н					Н	Н		Analyze 10' sample for PAHs only (hold other analyses pending shallower results); hold deeper samples pending shallower results.
				0.5	X	X	X	X						X					X	X		Location targets fill from unknown origin west of B4024 observed at SL-245-
				5	X	X	X	X						X					X	X		SA5A to 30' (fill extent shown on 1961 B4024 facility drawing and likely placed during original construction activities); positioned near outside storage. Bedrock
5A_DG-508	SETF	West of Building 4024	Soil Boring	10	X	X	X	X						X					X	X	/	anticipated ~30'. Collect samples at 5' intervals to 20', then every 10' to bedrock
3H_DO-300	SEIL	West of Building 4024	Son Donnig	15	X	X	X	X						X					X	X		with the deepest sample just above bedrock; analyze all depths to characterize fill.
				20	X	X	X	X						X					X	X		
				30	X	X	X	X						X					X	X		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (2 of 39)

Г			<u> </u>									A	alvetica!	Method								
												Ana	atytical	Method								-
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls IEPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X						X					X	X		Location targets potential staining observed in aerial photo (1999) identified by EPA, terrain conductivity anomaly, localized depression with cracked asphalt,
				5	X	X	X	X						X					X	X		linear patched asphalt observed on site walk, and fill from unknown origin west of
			Soil Boring /	10	X	X	X	X						X					X	X		B4024 observed at SL-245-SA5A to 30' (fill extent shown on 1961 facility drawing and likely placed during original construction activities of B4024). Bedrock
5A_DG-509	SETF	West of Building 4024	Test Pit	15	X	X	X	X						X					X	X	1	anticipated ~30'. Collect samples at 5' intervals to 20', then every 10' to bedrock with the deepest sample just above bedrock; analyze all depths to characterize fill.
				20	X	X	X	X						X					X	X		Conduct adjacent test pit for linear terrain conductivity anomaly and adjust 5' sample to target feature (or sample pit as appropriate).
				30	X	X	X	X						X					X	X		
				0.5	X	X	X	X						X					X	X		Location targets terrain conductivity anomaly, linear patched asphalt observed on
				5	X	X	X	X						X					X	X		site walk (possibly related to anomaly), and fill from unknown origin west of B4024 observed at SL-245-SA5A to 30' (fill extent shown on 1961 B4024 facility
5A_DG-510	SETF	West of Building 4024	Soil Boring	10	X	X	X	X						X					X	X		drawing and likely placed during original construction activities). Bedrock
3A_DG-310	SEII	West of Building 4024	Son Bornig	15	X	X	X	X						X					X	X	'	anticipated ~30'. Collect samples at 5' intervals to 20', then every 10' to bedrock with the deepest sample just above bedrock; analyze all depths to characterize fill.
				20	X	X	X	X						X					X	X		
				30	X	X	X	X						X					X	X		
				0.5	X	X	X	X						X					X	X		Location targets fill from unknown origin west of B4024 observed at SL-245-SA5A to 30' (fill extent shown on 1961 B4024 facility drawing and likely placed
			-	5 10	X	X	X	X X						X					X	X		during original construction activities); positioned near ramp into B4024 adjacent
5A_DG-511	SETF	West of Building 4024	Soil Boring	15	X	X	X	X						X					X	X	✓	to the reactor vault complex. Bedrock anticipated ~30'. Collect samples at 5'
				20	X	X	X	X						X					X	X		intervals to 20', then every 10' to bedrock with the deepest sample just above bedrock; analyze all depths to characterize fill.
			-	30	X	X	X	X						X					X	X		
				0.5	X	Х	X	X						X					X	Х		Location targets terrain conductivity anomaly and characterizes operational area. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with the
5A_DG-512	SETF	Southwest of Building 4024	Soil Boring / Test Pit	5	X	X	X	X						X					X	X	✓	deepest sample just above bedrock; hold deeper samples pending shallower results. Conduct adjacent test pit for linear terrain conductivity anomaly and adjust 5'
				10	Н	Н	Н	Н						Н					Н	Н		sample to target feature (or sample pit as appropriate).
				0.5	X	X	X	X						X					X	X		Location targets asphalt swale that directs surface flow west of B4024 to the
5A_DG-513	SETF	Drainage Southwest of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	✓	culvert west of the transformer pad. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock; analyze all depths.
		Building 1021		10	X	X	X	X						X					X	X		r . J
5A_DG-514A	SETF	Transformer 4927	Soil Boring	0.5		X														X		Transformers in Area IV with previous ND results are being resampled with
		(Southwest of B4024) Transformer 4927		0.5		H X		-							1					H X		discrete samples. Collect samples at four discrete locations and analyze 0.5' samples for PCBs; hold deeper samples pending shallower results.
5A_DG-514B	SETF	(Southwest of B4024)	Soil Boring	3		H														H	,	samples for 1 CDs, note deeper samples pending snanower results.
5A_DG-514C	SETF	Transformer 4927	Soil Boring	0.5		X														X	*	
		(Southwest of B4024) Transformer 4927		0.5		H X								+						H X		
5A_DG-514D	SETF	(Southwest of B4024)	Soil Boring	3		Н														Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (3 of 39)

												Ana	alytical Mo	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	FPH EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X						X		Į O			X	X		Location targets AST with unknown contents (AT-HS-5) identified in the Sitewide Tank Inventory (CH2M Hill, 2011); positioned adjacent to undefined feature
5A_DG-518	SETF	Southwest of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	✓	observed in 1978 photograph (HDMSm000000249). Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with the deepest sample just above
				10	Н	Н	Н	Н						Н					Н	Н		bedrock; hold deeper sample pending shallower results.
		Drainage Along B Street South		0.5	X	X	X	X						X			X	X	X	X		Location targets the drainage along the northern edge of B Street downslope from the transformer prior to flow leaving 5A North. Bedrock anticipated <5'. Collect
5A_DG-519	SETF	of Building 4024	Soil Boring	5	X	X	X	X						X			X	X	X	X	*	at 5' intervals to bedrock with the deepest sample just above bedrock; analyze all depths.
		Drainage Along B Street South		0.5	X	X	X	X						X					Х	X		Location targets the drainage along the northern edge of B Street immediately prior to flowing into the culvert diverting flow south under B Street. Bedrock
5A_DG-520	SETF	of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	*	anticipated <5'. Collect at 5' intervals to bedrock with the deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets cooling tower and sump located south of B4024, cooling tower analytical suite (formaldehyde and Cr[VI]) included. Bedrock anticipated ~10'.
5A_DG-521	SETF	Cooling Tower 4928 (South of Building 4024)	Soil Boring	5	X	X	Н	X	X					X	X	X			X	X	✓	Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock; hold deeper samples pending shallower results.
				10	Н	Н	Н	Н	Н					Н	Н	Н			Н	Н		L. C.
				0.5	X	X	X	X						X					X	X		Location targets removed fuel oil UST (UT-18) located south of B4024. Tank bottom depth expected ~8' with bedrock anticipated at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to
5A_DG-522	SETF	South of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	*	characterize fill of unknown origin and potential release from tank. Conduct geophysical survey prior to sampling to determine location of removed UST.
				10	X	X	X	X						X					X	X		Location targets the storm drain discharge point to the drainage along the northern
5A_DG-523	SETF	Drainage Along B Street	Soil Boring	0.5	X	X	X	X						X			X	X	X	X		Location targets the storm drain discharge point to the drainage along the northern edge of B Street; storm drain conveys surface water collected from the areas east and south of B4024. Bedrock anticipated <5'. Collect at 5' intervals to bedrock
311_50 323	SEII	Southeast of Building 4024	Son Bonnig	5	X	X	X	X						X			X	X	X	X		with deepest sample just above bedrock; analyze all depths.
5A DC 504	appr	Conthocat of Devil 11 4004	Coll De l'	0.5	X	X	X	X						X					X	X		Same as 5A_DG-528.
5A_DG-524	SETF	Southeast of Building 4024	Soil Boring	5 10	X	X	H H	X X						X X					X	X	ľ	
				0.5	X	X	X	X						X					X	X		Location targets fill from unknown origin in location of former underground radioactive gas hold-up tanks (samples of fill contain dioxins, PAHs, TPH, and/or
5A_DG-525	SETF	East of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	✓	metals above screening criteria). Bedrock anticipated ~15'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to
				10	X	X	X	X						X					X	X		characterize fill.
				0.5	X	X	X	X						X					X	X		Location targets fill from unknown origin with dioxins, PAHs, TPH, and metals detected above screening criteria based on surrounding sample results; and
5A_DG-526	SETF	East of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	~	characterizes fenced open storage. Bedrock anticipated at 15'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to
				10	X	X	X	X						X					X	X		characterize fill.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (4 of 39)

												Ana	alytical N	1ethod								T
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metaks ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1.4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	IPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X	•				1.0	X		I O		70	X	X		Stepup at SL-113-SA5A for 0' and 5' samples (Zinc and TPH detected above ISLs at depth) to characterize fill in location of former underground radioactive gas hold-
5A_DG-527	SETF	Open Storage East of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	✓	up tanks (samples of fill contain dioxins, PAHs, TPH, and/or metals above screening criteria) and fenced open storage observed first in 1990 aerial photo.
				10	X	X	X	X						X					X	Х		Bedrock anticipated at 15'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill.
				0.5	X	X	X	X						X					X	X		Representative location characterizing operational area; positioned south of fill from unknown origin in location of former underground radioactive gas hold-up
5A_DG-528	SETF	Southeast of Building 4024	Soil Boring	5	X	X	X	X						X					X	Х	✓	tanks (samples of fill contain dioxins, PAHs, TPH, and/or metals above screening criteria). Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with
				10	X	X	X	Х						X					X	х		deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	Х		Location targets ground penetrating radar anomaly and fill from unknown origin in location of former underground radioactive gas hold-up tanks (samples of fill
5A_DG-529	SETF	East of Building 4024	Soil Boring	5	X	X	X	X						X					X	Х	✓	contain dioxins, PAHs, TPH, and/or metals above screening criteria); and characterizes fenced open storage. Bedrock anticipated at 15'. Collect samples at 5'
				10	X	X	X	X						X					X	X		intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill.
5.4 D.G. 520	GE TO	G 1	a up	0.5	X	X	X	X						X					X	X		Location targets fenced open storage southeast of B4024. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above
5A_DG-530	SETF	Southeast of Building 4024	Soil Boring	5 10	X	X	H H	X						X					X	X X	*	bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Location targets drain discharge from the southern track of the gantry crane pad
5A_DG-531	SETF	Open Storage East of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	✓	and characterizes fenced open storage. Bedrock anticipated at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
				10	Н	Н	Н	Н						Н					Н	Н		deeper samples pending shallower results.
				0.5	X	X	X	X						X					X	X		Location targets area east of the Hot Waste Storage vaults and stepout from SL-117-SA5A and SL-118-SA5A (TPH detected above ISL). Bedrock anticipated ~10'.
5A_DG-532	SETF	East of the Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	✓	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				10	X	X	Н	X						X					X	X		
				0.5	X	X	X	X						X					X	X		Stepout from SL-118-SA5A (TPH detected above ISLs) and U5BS1127 (metals, TPH, and PAHs above ISLs); previous RFI stepouts not analyzed for TPH.
5A_DG-533	SETF	East of the Building 4024	Soil Boring	5	X	X	Н	X						X					X	Х	\	Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				0.5	X	X	X	X						X					X	X		Stepout from U5BS1127 (metals, TPH, and PAHs detected above ISLs); previous RFI stepouts not analyzed for TPH. Location also targets undefined feature
5A_DG-534	SETF	East of Building 4024	Soil Boring	5	X	X	Н	X						X					X	X	✓	observed in aerial photos (i.e, 1980). Bedrock is anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
				10	Н	Н	Н	Н						Н					Н	Н		hold deeper samples pending shallower results.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (5 of 39)

												Ana	alytical M	1ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	Х	X	Х	X						X					Х	X		Location targets removed fuel oil UST (UT-19) located northeast of B4024. Tank depth anticipated ~8'. Location based on facility drawing; previous location targeting UST (U5BS1126) had bedrock refusal above the tank bottom depth.
5A_DG-535	SETF	Northeast of Building 4024	Soil Boring	5	X	X	X	X						X					X	X	✓	Bedrock at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill of unknown origin and
				0.5	X	X	X	X						X					X	X		potential release from tank. Conduct geophysical survey prior to sampling to determine location of removed UST.
5A_DG-536	SETF	Northwest of Building 4024	Soil Boring	5	X X H	X X H	X X H	X X H						X X H					X X H	X X H	✓	Same as 5A_DG-537.
5A_DG-537	SETF	Northwest of Building 4024	Soil Boring	0.5 5	X	X	X H	X X						X					X	X	✓	Representative location to characterize operational area northwest of B4024; positioned near storage observed in 1978 photograph (HDMSm000000249). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
				10	Н	Н	Н	Н						Н					Н	Н		hold deeper samples pending shallower results. Stepout from U5BS1129 (TPH detected above ISL); also will provide stepout
5A_DG-538	SETF	North of Building 4024	Soil Boring	0.5	X	X	X	X						X					X	X	✓	information for SL-120-SA5A (dioxins detected above ISLs). Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		
				0.5	X	X	X	X						X					X	X		Stepout from drainage (dioxins, metals, and PAHs detected above ISLs in existing samples within drainage); positioned outside of drainage and south of location with highest concentrations detected above ISLs (SL-119-SA5A) in the vicinity.
5A_DG-539	SETF	Northeast of Building 4024	Soil Boring	10	X H	X H	Н	X H						X H					X H	X H	•	Bedrock is anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				0.5	X	X	X	X						X			X	X	X	X		Location targets surface water pathway from RMHF upstream of drainage (dioxins, metals, and PAHs detected above ISLs in existing samples within drainage).
5A_DG-540	SETF	Northeast of Building 4024	Soil Boring	5	X	X	X	X						X			X	X	X	X	✓	Bedrock is anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	Х		Location targets low spot at end of surface water pathway from RMHF which flows into drainage (dioxins, metals, and PAHs detected above ISLs in existing samples within drainage). Bedrock is anticipated <5'. Collect samples at 5' intervals to
5A_DG-541	SETF	Northeast of Building 4024	Soil Boring	5	X	X	X	X						X					X	Х	*	bedrock with deepest sample just above bedrock; analyze all depths.
			Soil Boring /	0.5	X	X	X	X						X					X	X		Location targets linear magnetometer anomaly; positioned on the "Existing Test Shed" identified on facility drawings. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper
5A_DG-542	SETF	North of Building 4027	Test Pit	5	X	X	X	X						X					X	х	*	samples pending shallower results, if collected. Conduct adjacent test pit for linear magnetometer anomaly and adjust 5' sample to target feature (or sample pit as appropriate).
5.4 D.S 1-	275-	D	0.12	0.5	X	X	X	X						X					X	Х		Representative location characterizing operational area; positioned near apparent spill present on 1980 aerial photo and probable containers present on 1999 aerial photo (both noted by EPA). Bedrock anticipated ~5'. Collect samples at 5' intervals
5A_DG-543	SETF	East of Building 4024	Soil Boring	5	X	X	X	X						X					X	Х	•	to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (6 of 39)

												Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A DG-544	SETF	West of Duilding 4027	Cail Davina	0.5	X	X	X	X						X	,	,	, , _		X	X	1	Location targets sanitary sewer pipe connection to B4027; positioned near open storage along east side of B4027. Bedrock anticipated ~5'. Collect samples at 5'
5A_DG-544	SEIF	West of Building 4027	Soil Boring	5	X	X	X	Х						X					X	X	ľ	intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-545	SETF	Between Buildings 4024 and	Soil Boring	0.5	X	X	X	X						X					X	X	_	Stepout from SL-118-SA5A that targeted the Hot Waste Storage vaults (TPH detected above ISLs); positioned near entrance to B4027. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
3A_DG-343	SEIF	4027	Soft Borning	5	X	X	Н	X						X					X	X	ľ	hold deeper samples pending shallower results, if collected.
5A DC 546	CETE	Neigh of Pullding 4007	Call Davis	0.5	X	X	X	X						X					X	X	1	Stepout from SL-121-SA5A (dioxins detected above ISLs at 0.5'); positioned near concrete apron identified on facility drawings. Bedrock anticipated <5'. Collect
5A_DG-546	SETF	North of Building 4027	Soil Boring	5	X	X	X	X						X					X	X	ľ	samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-547	SETF	Drainage Northeast of Building	g Soil Boring /	0.5	X	X	X	Х						X					X	Х	√	Location targets point magnetometer anomaly and drainage (dioxins, metals, and PAHs detected above ISLs in existing samples within drainage); also stepout from SL-121-SA5A (dioxins detected above ISLs). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
3/1_50 347	SET	4027	Test Pit	5	X	X	X	X						X					X	X		all depths. Conduct adjacent test pit for linear terrain conductivity anomaly and adjust 5' sample to target feature (or sample pit as appropriate).
5A_DG-548	SETF	Within Building 4027	Soil Boring /	0.5	X	Х	X	Х						Х					X	Х	·	Location targets linear magnetometer anomaly beneath B4027; also a stepout from U5BS1105 (TPH detected above ISL at 0.5') and targets linear magnetometer anomaly. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results,
3/1_50 340	SEIT	Footprint	Test Pit	5	X	X	X	X						X					X	X		if collected. Conduct adjacent test pit for linear magnetometer anomaly and adjust 5' sample to target feature (or sample pit as appropriate).
				0.5	X	X	X	X	X					X			X	X	X	X		Representative location to characterize operational area; positioned along western side of B4027 footprint which was used as a hazardous waste storage facility near
5A_DG-549	SETF	West of Building 4027	Soil Boring	5	X	X	Н	X	X					X			X	X	X	X	✓	high bay door and possible drums observed in 1978 photo (HDMSm000000249). Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower
				10	Н	Н	Н	Н	Н					Н			Н	Н	Н	Н		results. Location targets former location of floor trench located beneath B4027 which was
5A_DG-550	SETF	Within Building 4027	Soil Boring	0.5	X	X	X	X	X					X			X	X	X	X	✓	used as a hazardous waste storage facility; also a stepout from U5BS1118 (TPH detected above ISL at 0.5'). Bedrock anticipated ~10'. Collect samples at 5'
	SEII	Footprint	Don Boring	10	X	X	X	X	X					X			X	X	X	X		intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A DC 551	gerre	Within Building 4027	Cail Davin	0.5	X	X	X	X	X					X			X	X	X	X		Location targets former location of floor trench located beneath B4027 which was used as a hazardous waste storage facility. Bedrock anticipated ~5'. Collect
5A_DG-551	SETF	Footprint	Soil Boring	5	X	X	X	X	X					X			X	X	X	X	*	samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-552	SETF	Drainage Northeast of Building	g Soil Boring	0.5	X	X	X	X						X					X	X	*	Stepout from SL-122-SA5A (dioxins detected above ISL at 0.5'); positioned within drainage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with
		4027	38	5	X	X	X	X						X					X	X		deepest sample just above bedrock; analyze all depths.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (7 of 39)

													Ana	alytical M	ethod]
Sample	Location ID	Area	Location Description			PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
Section Sect	5.5.5.0	gpmp			0.5	X		X															shower. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with
Sample S	5A_DG-553	SETF	Southeast of Building 4027	Soil Boring	5	X	X	X	X	X					X			X	X	X	X		
Section of Building 4027 South of Building					0.5	X	X	X	X	X					X			X	X	X	X		
SA_DG-556 SFT	5A_DG-554	SETF	South of Building 4027	Soil Boring	5	X	X	X	X	X					X			X	X	X	X	✓	
SA_DG.558 STF South of fluiding 4072 South fluiding 4072					10	Н	Н	Н	Н	Н					Н			Н	Н	Н	Н		
A					0.5	X	X	X	X	X					X			X	X	X	X		
SA_DG 556 SETF West of Building 4012 Soil Boring	5A_DG-555	SETF	South of Building 4027	Soil Boring	5	X	X	X	X	X					X			X	X	X	X	✓	
Sample S					10	Н	Н	Н	Н	Н					Н			Н	Н	Н	Н		
Sa_DG-556 SeTF West of Building 4032 Soil Boring Soil Northwest Building 4032 Soil Boring Soil Borin					0.5	X	X	X	X						X					X	X		
Section Sect	5A_DG-556	SETF	West of Building 4032	Soil Boring	5	X	X	X	X						X					X	X	✓	
Set F West of Building 4032 Soil Boring 5 X X X X X					10	Н	Н	Н	Н						Н					Н	Н		
Section Sett					0.5	X	X	X	X						X					X	X		
Set	5A_DG-557	SETF	West of Building 4032	Soil Boring	5	X	X	X	X						X					X	X	✓	to bedrock with deepest sample just above bedrock; hold deeper samples pending
Sa_DG-558 SeTF Southwest of Building 4032 Soil Boring Soil Bor					10	Н	Н	Н	Н						Н					Н	Н		snallower results.
Set					0.5	X	X	X	X											X	X		*
Sef Northwest Building 4032 Soil Boring Sef	5A_DG-558	SETF	Southwest of Building 4032	Soil Boring	-										-								bedrock with deepest sample just above bedrock; hold deeper samples pending
SETF Northwest Building 4032 Soil Boring Silboring Soil Boring Soil Boring SL 249-SA5A (TPH detected above ISLs at 2.5' [fill from unknown origin]). Soil Boring																							
Set Northwest Building 4032 Soil Boring Set Northwest Building 4032 Northwest Building 4032 Soil Boring Set Northwest Building 4032 Northwest Building 4032 Soil Boring Set Northwest Building 4032 Soil Boring Set Northwest Building 4032 Northwest Building 4032 Soil Boring Set Northwest Building 4032 So	5. B3 550	a====	N	G 115 :																			from SL-249-SA5A (TPH detected above ISLs at 2.5' [fill from unknown origin]).
SETF Within Building 4032 Footprint SETF Within Building 4032 Footprint Set Pootprint	5A_DG-559	SETF	Northwest Building 4032	Soil Boring																		'	
SETF Within Building 4032 Footprint Soil Boring 5 X X X X X X X X X X X X X X X X X X													-										Pennacantativa location to characterize feathwint of P4022. Pedrack anti-
Footprint 10	5A DC 560	CETE	Within Building 4032	Soil Domin -																			~10'. Collect samples at 5' intervals to bedrock with deepest sample just above
SETF Within Building 4032 Footprint SETF Within Building 4032 Footprint SETF Soil Boring O.5 X X X X X X X X X X X X X	JA_DG-300	SEIF	Footprint	Son bornig	-			1															bedrock; hold deeper samples pending shallower results.
5A_DG-561 SETF Within Building 4032 Footprint Signature Soil Boring Signature Signature Soil Boring Signature Soil Boring Signature Signature Soil Boring Signature Signature Signature Soil Boring Signature Si																							
rootprint deepest sample just above bedrock; analyze all depths to characterize fill.	5A_DG-561	SETF	· ·	Soil Boring				1														/	2.5'). Bedrock anticipated >10'. Collect samples at 5' intervals to bedrock with
			rootprint		10		X	X	X						X					X	X		deepest sample just above bedrock; analyze all depths to characterize fill.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (8 of 39)

												Ana	lytical N	lethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/741B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-562	SETF	Within Building 4032 Footprint	Soil Boring	0.5 5			X Н							X X H						X X H	*	Resample SL-235-SA5A for TPH; ~5' of fill from unknown origin present at SL-235-SA5A and SL-249-SA5A and fill at SL-249-SA5A had TPH detected above ISL. Location also targets light toned mounded material identified in EPA tech memo. Bedrock anticipated at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze 0.5' and 5' sample for TPH (hold other analyses) and hold deeper samples pending shallower results.
5A_DG-563	SETF	Southeast Corner of Building 4032	Soil Boring	0.5 5 10	X X X	X X X	X X X	X X X						X X X					X X X	X X X	√	Location targets sanitary sewer pipe connection to B4032 and characterizes fill observed in borings south of B4032; positioned near B4032 entrance. Bedrock anticipated >10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill.
5A_DG-564	SETF	East of Building 4032	Soil Boring	0.5	X X X	X X X	X X X	X X X						X X					X X X	X X X	√	Location targets removed UST UT-22 (used for fuel oil); positioned within light toned mounded material identified in EPA tech memo. Bedrock is anticipated at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths. Conduct geophysical survey prior to sampling to determine location of removed UST, shown in two different locations in separate documents.
5A_DG-565A	SETF	Transformer Pad 4727 (North of Building 4032)	Soil Boring	0.5 3 5	X X X	X X X	X X X	X X X						X X X			X X X	X X X	X X X	X X X		Transformers in Area IV with previous ND results are being resampled with discrete samples. Collect samples at four discrete locations and analyze 0.5' samples for PCBs; hold deeper samples pending shallower results. Northern sample (5A_DG-565A) also targets drainage and western sample (5A_DG-565D)
5A_DG-565B	SETF	Transformer Pad 4727 (North of Building 4032)	Soil Boring	0.5 3 0.5		X H														X H	✓	targets light toned mounded material identified in the EPA tech memo. At these location locations, bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with bottom sample collected just above bedrock; analyze all depths.
5A_DG-565C	SETF	Transformer Pad 4727 (North of Building 4032)	Soil Boring	3 0.5	X	X H X	X	X						X					X	X H X		bedrock with bottom sample concered just above bedrock, analyze an depuis.
5A_DG-565D	SETF	Transformer Pad 4727 (North of Building 4032)	Soil Boring	3 5	X X	X X	H H	X X						X X					X X	X X		
5A_DG-569	SETF	South of Building 4036	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Representative location to characterize operational area; positioned near entrance to B4036. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepers sample just above bedrock; hold deeper samples pending shallower results,
		Within Building 4036		0.5	X	X	X	X						X					X	X		if collected. Representative location to characterize Building 4036 footprint. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just
5A_DG-570	SETF	Footprint	Soil Boring	5	X	X	Н	X						X					X	X	✓	above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-571	SETF	Within Building 4036 Footprint	Soil Boring	0.5	X	X X	X H	X						X					X X	X	✓	Representative location to characterize Building 4036 footprint. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-572	SETF	Within Building 4036 Footprint	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Representative location to characterize Building 4036 footprint. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
		Pootprint		5	X	X	Н	X						X					X	X		,

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (9 of 39)

	1				1							Ans	alytical M	Tothod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 5010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)			Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
		W. 1. D . 11. 4022		0.5	X	X	X	X	X			X		X			X	X	X	X		Representative location to characterize former B4037 footprint which was used as a hazardous waste storage facility. Bedrock anticipated ~5'. Collect samples at 5'
5A_DG-573	SETF	Within Building 4037 Footprint	Soil Boring	5	X	X	X	X	X			X		X			X	X	X	X	~	intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
		Within Building 4037		0.5	X	X	X	X	X			X		X			X	X	X	X		Representative location to characterize former B4037 footprint which was used as a hazardous waste storage facility. Bedrock anticipated ~5'. Collect samples at 5'
5A_DG-574	SETF	Footprint	Soil Boring	5	X	X	X	X	X			X		X			X	X	X	X	_	intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A DG-575	SETF	East of Building 4037	Soil Dowing	0.5	X	X	X	X	X			X		X			X	X	X	Х		Location positioned along south side of 12th Street, downslope of RMHF entrance/roadway. Location targets doors on north side of B4037 (former hazardous waste storage facility) and addresses surface water runoff from RMHF roadway where storage was observed in historical photographs. Bedrock
3A_DG-373	SEIF	East of Building 4057	Soil Boring	5	X	X	X	X	X			X		X			X	X	X	X	·	anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-576	SETF	North of Building 4023	Soil Boring	0.5	X	X	X	X						X					X	X		Representative location to characterize former operational area east of B4037. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if
			, and the second	5	X	X	X	X						X					X	X		collected.
				0.5	X	X	X	X	X					X	X	X			X	X		Representative location to characterize equipment north of B4023; positioned near former cooling unit. Bedrock anticipated ~10'. Collect samples at 5' intervals to
5A_DG-577	SETF	North of Building 4023	Soil Boring	5	X H	X H	X H	X H	X H					X H	X H	X H			X H	X H	*	bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				0.5	X	X	X	X	X					X	X	X			X	X		Representative location to characterize operational area between B4032 and
5A_DG-578	SETF	West of Building 4023	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	B4023; positioned near high bay door to B4032 and potential cooling tower on facility drawing (only present on one drawing). Bedrock anticipated ~10'. Collect
				10	Н	Н	Н	Н	Н					Н	Н	Н			Н	Н		samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets sanitary sewer pipe connection to B4023 and characterizes fill of unknown origin observed in borings within B4023. Bedrock anticipated >10'.
5A_DG-579	SETF	Southwest Corner of Building 4023	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill.
				10	X	X	X	X	X					X	X	X			X	X		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (10 of 39)

	I	<u> </u>	1									And	alvtical N	Mothod								T
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)		Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X						X		10			X	X		Stepout from SL-001-SA5A (PCBs, TPH detected above ISLs), SL-004-SA5A (PCBs and dioxins detected above ISLs), and SL-002-SA5A (PCBs, dioxins
5A_DG-580	SETF	Within Building 4023 Footprint	Soil Boring	5	X	X	Н	X						X					X	X	✓	detected above ISLs). Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending
				10	Н	Н	Н	Н						Н					Н	Н		shallower results.
5A_DG-581	SETF	Within Building 4023 Footprint	Soil Boring	0.5 5	X	X X	X H	X X						X					X X	X	✓	Same as 5A_DG-586.
		rootprint		10	Н	Н	Н	Н						Н					Н	Н		Stepout from SL-004-SA5A (dioxins, PCBs detected above ISLs); positioned
5A_DG-582	SETF	North of Building 4023	Soil Boring	0.5	X	X	X	X						X					X	X	~	outside drainage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results if collected.
5A_DG-583	SETF	North of Building 4023	Soil Boring	0.5	X X	X X	Х	X						X					X X	X	*	Representative location to characterize open area north of B4023; area observed to have asphalt with cracks in aerial photos, but little storage. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results if collected.
				0.5	X	X	X	X						X					X	X		Location targets two ASTs with unknown contents (Unknown-AT-L9-1, -2) located north of B4023. Bedrock is anticipated at ~10'. Collect samples at 5'
5A_DG-584	SETF	North of Building 4023	Soil Boring	5	X	X	X	X						X					X	X	~	intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		Stepout from SL-018-SA5A (dioxins, PCBs detected above ISLs); positioned
5A_DG-585	SETF	North of Building 4023	Soil Boring	0.5	X	X	X	X						X					X	X	✓	within drainage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				5	X	X	X	X						X					X	X		Stepout from SL-001-SA5A (PCBs, TPH detected above ISLs) and characterizes
		Within Building 4023		0.5	X	X	X	X						X					X	X		fill of unknown origin observed in borings within B4023; positioned within medium toned mounded material. Bedrock anticipated ~10'. Collect samples at 5'
5A_DG-586	SETF	Footprint	Soil Boring	5	X	X	X	X						X					X	X	_	intervals to bedrock with deepest sample just above bedrock; analyze all depths to characterize fill.
				10	X	X	X	X						X					X	X		Location targets AST with unknown contents (Unknown-AT-L9-3) and linear
		Wishin Desilation 4000	Coil Desire	0.5	X	X	X	X						X					X	X		magnetometer anomaly; positioned within medium toned mounded material identified in EPA tech memo and fill of unknown origin observed in borings within
5A_DG-587	SETF	Within Building 4023 Footprint	Soil Boring / Test Pit	5	X	X	X	X						X					X	X	*	B4023. Bedrock is anticipated at ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths. Conduct adjacent test pit for linear magnetometer anomaly and adjust 5' sample to target feature (or
				10	X	X	X	X						X					X	X		sample pit as appropriate).

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (11 of 39)

												Ana	alytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane EPA Method 8360B SIM)	Ferphenyls (EPA Method 8015B)	(EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-588	SETF	Within Building 4023 Footprint	Soil Boring	0.5	X	X	X	X)				X)	Į.			X	X X	<u>-</u>	Stepout from SL-009-SA5A (dioxins, PCBs, Hg, Zn detected above ISLs); positioned within medium toned mounded material identified in EPA tech memo. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-589	SETF	South of Building 4023	Soil Boring	0.5	X X	X X	X X	X X						X X					X X	X X	~	Same as 5A_DG-588; positioned near entrance to B4023.
5A_DG-590	SETF	Southeast of Building 4023	Soil Boring	0.5	X X	X X	X X	X						X					X	X	*	Location targets hole in asphalt slope adjacent to catch basin (southeast) welded shut; also a stepout from SL-016-SA5A (dioxins and Zn detected above ISLs). Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-591	SETF	East of Building 4023	Soil Boring	0.5										X						X	~	Resample SL-013-SA5A for TPH and stepout for SL-012-SA5A (TPH detected above ISL). Bedrock anticipated at <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-592	SETF	Northeast of Building 4023	Soil Boring	0.5	X	X	X	X						X					X	X	~	Stepout from SL-012-SA5A (dioxins, PCBs, TPH detected above ISLs); positioned outside drainage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results, if collected.
5A_DG-593	SETF	East of Building 4023	Soil Boring	0.5 5	X X H	X X H	X X H	X X H						X X H					X X H	X X H	*	Representative location to characterize open storage east of B4023 observed in post-1980 aerial photos. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper samples pending shallower results.
5A_DG-594	PDU Area	Drainage at Corner of 17th and B Street	Soil Boring	0.5	X X X	X X X	X X X	X X X						X X X			X X X	X X X	X X X	X X X	~	Stepout for dioxins in drainage west near HMSA [Subarea 5B] and targets lined drainage receiving flow from south via unlined drainage and north and west via underground pipe. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-595	PDU Area	Drainage Along 17th Street Northwest of Building 4005	Soil Boring	0.5 5 10	X X X	X X X	X X X	X X X	X X X					X X X	X X X				X X X	X X X	/	Location targets previously unlined drainage flowing north to culvert (see information layer in GIS). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-596	PDU Area	Northwest of Building 4005	Soil Boring	0.5	X X	X X	X H	X X	X					X X					X X	X X	✓	Stepout for mercury and TPH in nearby samples and targets ASTs with unknown contents; also characterizes open storage/operational area. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths; hold deeper sample pending shallower results, if collected.
5A_DG-597	PDU Area	Northwest of Building 4005	Soil Boring	0.5	X	X	X	X	X					X					X	X		Location targets adjacent to B4005 floor trench (dioxins, metals, PAHs, and PCBs detected above ISLs in previous lined trench sediment samples); positioned between storm drain line and floor trench. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
				5	X	X	X	X	X					X					X	X		all depths; hold deeper sample pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (12 of 39)

					1							Ana	alytical Me	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 5010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	FPH FPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X			<u> </u>		1	X	I)	Į)	H C	H O	X	X		Location targets adjacent to B4005 floor trench (dioxins, metals, PAHs, and PCBs
5A_DG-598	PDU Area	Northwest of Building 4005	Soil Boring	5	X	X	Н	X						X					X	X	/	detected above ISLs in previous lined trench sediment samples); also stepout for PAHs and characterizes operational area. Bedrock anticipated between 5' and 10'.
_				10	Н	Н	Н	Н						Н					Н	Н		Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X	X	X	X						X					X	X	\vdash	Same as 5A_DG-602.
5A_DG-599	PDU Area	West of Building 4005	Soil Boring	5 10	X X	X X	X X	X X						X X					X X	X X	✓	
																						Location targets B4005 floor trench conveyance pipe (dioxins, metals, PAHs, and
				0.5	X	X	X	X						X					X	X		PCBs detected above ISLs in previous lined trench sediment samples); also stepout from septic tank (dioxins detected above ISLs) and characterizes operational area;
5A_DG-600	PDU Area	West of Building 4005	Soil Boring	5	X	X	X	X						X					X	X	✓	positioned between underground stormwater and floor trench conveyance pipes. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
				10																		analyze all depths to assess potential subsurface release and migration along
				10	X	X	X	X						X					X	X		bedrock.
5A DG-601	PDU Area	West Side of Building 4005	Soil Boring	0.5 5	X	X	X	X						X X					X	X	/	Location targets sewer discharge location from B4005. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				10	X	X	X	X						X					X	X		
				0.5	X	X	X	X						X					X	X		Stepout from septic tank (dioxins); also characterizes operational area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
5A_DG-602	PDU Area	West of Building 4005	Soil Boring	5	X	X	X	X						X					X	X	\	all depths to assess potential subsurface release and migration along bedrock.
				10	X	X	X	X						X					X	X	<u> </u>	Representative location to characterize operational area. Collect samples at 5'
5A_DG-603	PDU Area	Southwest of Building 4005	Soil Boring	0.5 5	X	X	X H	X X						X					X	X		intervals to bedrock with deepest sample just above bedrock; hold deeper sample
_		C		10	Н	Н	Н	Н						Н					Н	Н		pending shallower results.
				0.5	X	X	X	X	X					X	X	X			X	X		Stepout from Clearly Contaminated Area; and located near cooling tower. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just
5A_DG-604	PDU Area	South of Building 4005	Soil Boring	5	X	X	Н	X	X					X	X	X			X	X		above bedrock; hold deeper sample pending shallower results, if collected.
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets adjacent to B4005 drain line and floor trench (dioxins, metals,
5A_DG-605	PDU Area	East of Building 4005	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	PAHs, and PCBs detected above ISLs in previous lined trench sediment samples); also stepout for Clearly Contaminated Area and located near cooling tower.
				10	X	X	Н	X	X					X	X	X			X	X		Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X	X					X	X	X			X	X		Representative location to characterize open storage/operational area; also stepout
5A_DG-606	PDU Area	East of Building 4005	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	for Clearly Contaminated Area and located near cooling tower. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample
				10	Н	Н	Н	Н	Н					Н	Н	Н			Н	Н	L	pending shallower results.
				0.5	X	X	X	X						X					X	X		Location targets adjacent to B4005 floor trench; also characterizes operational area. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to
5A_DG-607	PDU Area	North of Building 4005	Soil Boring	5	X	X	X	X						X					X	X	✓	bedrock with deepest sample just above bedrock; hold deeper sample pending
		Ţ		10	X	X	Н	X						X					X	X		shallower results.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (13 of 39)

					1							Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-608	PDU Area	North of Building 4005	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout for mercury and TPH in nearby samples and targets ASTs with unknown contents; also characterizes open storage/operational area. Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
				5	X	X	Н	X						X					X	X		
		D : Al DG (M d		0.5	X	X	X	X	X					X	X		X	X	X	X		Location targets lined drainage. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths based on potential for
5A_DG-609	PDU Area	Drainage Along B Street North of Building 4005	Soil Boring	5	X	X	X	X	X					X	X		X	X	X	X	✓	vertical migration of surface water/contaminants.
				10	X	X	X	X	X					X	X		X	X	X	X		
5A_DG-610	PDU Area	North of Building 4005	Soil Boring	0.5	X	X	X	X	X					X	X				X	X	 	Location targets AST with unknown contents and undefined feature area (possible staining); also stepout for Clearly Contaminated Area and characterizes open storage/operational area. Shallow bedrock anticipated. Collect samples at 5'
		, and the second	J	5	X	X	Н	X	X					X	X				X	X		intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
				0.5	X	X	X	X						X					X	X		Location targets two liquid hold-up tanks and undefined feature area (possible staining); also stepout for Clearly Contaminated Area. Bedrock anticipated
5A_DG-611	PDU Area	Northeast of Building 4005	Soil Boring	5	X	X	X	X						X					X	X	~	between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess potential depth of impacts (previous samples were shallow and for metals only).
				10	X	X	X	X						X					X	X		(previous samples were shanow and for metals only).
		Drainage North of Clearly		0.5	X	X	X	X						X	X				X	X		Stepout from Clearly Contaminated Area; also targets drainage along B Street and undefined feature area (possible staining). Collect samples at 5' intervals to
5A_DG-612	PDU Area	Contaminated Area East of	Soil Boring	5	X	X	X	X						X	X				X	X		bedrock with deepest sample just above bedrock; analyze all depths to assess
		Building 4005		10	X	X	X	X						X	X				X	X		potential migration along bedrock.
5A_DG-613	PDU Area	North of Clearly Contaminated	Soil Boring	0.5	X	X	X	X						X					Х	X	_	Location targets undefined feature area (possible staining); also stepout from Clearly Contaminated Area (note previous nearby samples not analyzed for dioxins). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with
512_5 0 015	13011104	Area East of Building 4005	2 3 3 2 3 3 3 3 3	5	X	X	Н	X						X					X	X		deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-614	PDU Area	Northeast of Clearly Contaminated Area East of	Soil Boring	0.5	X	X	X	X						X		_			X	X		Location targets B4793 footprint; also stepout from Clearly Contaminated Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if
2.1_D0 014	150 mea	Building 4005	Jon Boring	5	X	X	Н	X						X					X	X		collected.
. n - · · ·		Drainage Northeast of Clearly		0.5	X	X	X	X						X			X	X	X	X		Location targets stormwater conveyance pipe discharge point into drainage. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-615	PDU Area	Contaminated Area East of Building 4005	Soil Boring	5	X	X	X	X X						X			X	X	X	X	′	analyze all depths to assess potential subsurface release and migration along bedrock.
	1			0.5	X	X	X	X						X			Λ	Λ	X	X		Location targets sewer discharge location from B4042; also characterizes
5A_DG-616	PDU Area	West Side of Building 4042	Soil Boring	5	X	X	X	X						X					X	X	✓	operational area. Collect samples at 5' intervals to bedrock with deepest sample
				10	X	X	X	X						X					X	X		just above bedrock; analyze all depths.
		Within Building 4042		0.5	X	X	X	X						X					X	X		Stepout for B(a)P and TPH; also characterizes B4042 footprint. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample
5A_DG-617	PDU Area	Footprint	Soil Boring	5	X	X	X	X						X				-	X	X		pending shallower results.
				10	Н	Н	Н	Н						Н					Н	H		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (14 of 39)

												Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	(EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X					, ,	X					X	X		Stepout for B(a)P and TPH; positioned adjacent to underground stormwater
5A_DG-618	PDU Area	North of Building 4042	Soil Boring	5	X	X	X	X						X					X	X		conveyance pipe from SETF. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess possible leakage
				10	X	X	Н	X						X					X	X		from pipe.
				0.5	X	X	X	X	X					X	X				X	X		Location targets intersection of two former floor trenches and is a stepout for B(a)P and TPH; positioned near operations associated with alcohol ASTs. Note previous
5A_DG-619	PDU Area	Within Building 4042	Soil Boring	5	X	X	X	X	X					X	X				X	X	✓	sample U5BS1107 analyzed for metals only. Collect samples at 5' intervals to
		Footprint		10	X	X	Н	X	X					X	X				X	X		bedrock with deepest sample just above bedrock; analyze all depths to assess possible leakage from trenches.
				0.5	X	X	X	X	Λ					X	Λ				X	X		Representative location to characterize operational area. Collect samples at 5'
5A_DG-620	PDU Area	West of Building 4042	Soil Boring	5	X	X	X	X						X					X	X	V	intervals to bedrock with deepest sample just above bedrock; hold deeper sample
				10	Н	Н	Н	Н						Н					Н	Н		pending shallower results.
5A_DG-621	PDU Area	East of Clearly Contaminated Area East of Building 4005	Soil Boring	0.5	X	X	X	X					X	X					X	X	✓	Representative sample to characterize open storage/operational area near B4049 which had terphenyl use. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess
		Area East of Building 4005		5	X	X	Н	X					X	X					X	X		vertical extent of potential impacts.
				0.5	X	X	X	X						X					X	X		Same as 5A_DG-620.
5A_DG-622	PDU Area	Southwest of Building 4042	Soil Boring	5	X	X	X	X						X					X	X	✓	
				10	Н	Н	Н	Н						Н					Н	Н		
5A_DG-623	PDU Area	East of Clearly Contaminated Area East of Building 4005	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Location targets open storage; also stepout for Clearly Contaminated Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess vertical extent of potential
		Thea East of Building 1005		5	X	X	Н	X						X					X	X		impacts.
5A_DG-624A	PDU Area	Transformer Southwest	Soil Boring	0.5		X														X		Transformers in Area IV with previous ND results are being resampled with
		of Building 4042 Transformer Southwest		3 0.5		H X														H X		discrete samples. Collect samples at four discrete locations and analyze 0.5' samples for PCBs; hold deeper samples pending shallower results.
5A_DG-624B	PDU Area	of Building 4042 Transformer Southwest	Soil Boring	3 0.5		H X														H X	✓	
5A_DG-624C	PDU Area	of Building 4042	Soil Boring	3		Н														Н		
5A_DG-624D	PDU Area	Transformer Southwest of Building 4042	Soil Boring	0.5		X H														X H		
		Eastern Portion of Open		0.5	X	X	X	X						X					X	X		Location targets magnetic anomaly, dark toned material, and open storage.
5A_DG-625	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5	X	X	Н	X						X					X	X	/	Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
		Eastern Portion of Open		0.5	X	X	X	X						X					X	X		Location targets dark toned material and open storage. Bedrock anticipated ~5'.
5A_DG-626	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5	X	X	Н	X						X					X	X	′	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
		Eastern Portion of Open	a v =	0.5	X	X	X	X						X					X	X		Location targets magnetic anomaly, dark toned material, and open storage; positioned adjacent to Old Conservation Pipeline (diesel fuel). Bedrock
5A_DG-627	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5	Х	X	Н	X						X					X	X	1	anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (15 of 39)

												Ana	alytical Me	ethod								1
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	FPH EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X		H O	H O	<u> </u>	1	X)	ľ			X	X		Location targets former B4042 footprint and adjacent to operations associated with
5A_DG-628	PDU Area	Within Building 4042 Footprint	Soil Boring	5	X	X	X	X						X					X	X	✓	alcohol ASTs. Analyze 0.5' and 5' samples due to D&D soil disturbance. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
		1		10	Н	Н	Н	Н						Н					Н	Н		deeper sample pending shallower results.
5A_DG-629	PDU Area	Building 4042	Soil Boring	0.5 5	X	X	X	X X						X					X	X		Same as 5A_DG-628.
0.1_0 0 029	12011101		Son Bonng	10	X	X	Н	X						X					X	X		
5A_DG-630A	PDU Area	Transformer Southeast of Building 4042	Soil Boring	0.5		X H														X H		Transformers in Area IV with previous ND results are being resampled with discrete samples. Collect samples at four discrete locations and analyze 0.5'
5A_DG-630B	PDU Area	Transformer Southeast of Building 4042	Soil Boring	0.5		X H														X H		samples for PCBs; hold deeper samples pending shallower results.
5A_DG-630C	PDU Area	Transformer Southeast	Soil Boring	0.5		X														X	*	
_		of Building 4042 Transformer Southeast		3 0.5		H X														H X		
5A_DG-630D	PDU Area	of Building 4042	Soil Boring	3		Н														Н		
5A_DG-631	PDU Area	Eastern Portion of Open Storage / Parking Area Near	Soil Boring	0.5	X	X	X	X						X					X	X		Location targets drainage adjacent to medium toned material and open storage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
		12th and G Street		5	X	X	Н	X						X					X	X		Location targets drainage along G street south of Open Storage/Parking Area
				0.5	X	X	X	X	X					X	X		X	X	X	X		upstream of Clearly Contaminated Area south of Coal Storage/Parking Area and downstream of PAH and dioxin impacts; positioned adjacent to the Old
5A_DG-632	PDU Area	Drainage Along G Street South of Open Storage / Parking Area	Soil Boring	5	X	X	X	X	X					X	X		X	X	X	X	✓	Conservation Pipeline (diesel fuel). Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess potential migration along bedrock.
				10	X	X	X	X	X					X	X		X	X	X	X		
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets AST with unknown contents; also characterizes area around cooling tower identified in facility drawings. Collect samples at 5' intervals to
5A_DG-634	PDU Area	Southeast of Building 4042	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	bedrock with deepest sample just above bedrock; hold deeper sample pending
				10	Н	Н	Н	Н	Н					Н	Н	Н			Н	Н		shallower results.
				0.5	X	X	X	X						X					X	X		Location targets geophysical anomaly; also characterizes operational area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
5A_DG-635	PDU Area	Within Building 4042 Footprint	Soil Boring / Test Pit	5	X	X	X	X						X					X	X	~	deeper sample pending shallower results. Conduct adjacent test pit for geophysical anomaly. Adjust 5' sample to target feature (or sample pit as appropriate).
				10	Н	Н	Н	Н						Н					Н	Н		
5A DC (2)	DDII A	Fact of Duilding 4040	Soil Boring /	0.5	X	X	X	X						X					X	X		Same as 5A_DG-635.
5A_DG-636	PDU Area	East of Building 4042	Test Pit	5 10	X H	X H	X H	X H						X H					X H	X H	ľ	
				0.5	X	X	X	X						X					X	X		Location targets disturbed vegetation/soil noted in aerial photographs; also
5A_DG-637	PDU Area	East of Building 4042	Soil Boring	5	X	X	Н	X						X					X	X	✓	characterizes operational area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (16 of 39)

												Ano	lytical M	othod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A DG-638	PDU Area	Southeast of Clearly Contaminated Area East of	Soil Boring	0.5	X	X	X	X	X					X	X	X			X	X		Stepout from Clearly Contaminated Area; also characterizes open storage/operational area and area around cooling towers identified in facility drawings. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with
JA_DG-036	1 DO Alea	Building 4005	Soli Bornig	5	X	X	Н	X	X					X	X	X			X	X		deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A DG-639	PDU Area	Southeast of Clearly Contaminated Area East of	Soil Boring	0.5	X	X	X	X	X					X	X	X			X	X		Stepout from Clearly Contaminated Area, characterizes area around cooling towers identified in facility drawings, and targets possible light toned mounded material. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest
3A_DG-039	PDU Area	Building 4005	Soil Borning	5	X	X	Н	X	X					X	X	X			X	X	ľ	sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A DG-640	PDU Area	Southeast of Clearly Contaminated Area East of	Soil Boring	0.5	X	X	X	X	X					X	X	X			X	X	_	Stepout from Clearly Contaminated Area, characterizes area around cooling towers identified in facility drawings, and targets possible light toned mounded material and surface drainage discharge. Bedrock anticipated <5'. Collect samples at 5'
JA_DG-040	1 DO Alea	Building 4005	Soli Bornig	5	X	X	Н	X	X					X	X	X			X	X		intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-641	PDU Area	South of Building 4005	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout from Clearly Contaminated Area; positioned between B4005 floor trench and stormwater conveyance line. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample
				5	X	X	Н	X						X					X	X		pending shallower results, if collected.
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets adjacent to B4005 floor trench (dioxins, metals, PAHs, and PCBs detected above ISLs in previous lined trench sediment samples); also located near
5A_DG-642	PDU Area	South of Building 4005	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	*	cooling tower and characterizes operational area. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A DG-643	PDU Area	South of Building 4005	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout from Clearly Contaminated Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
JA_DO-043	1 DO Aica	South of Building 4003	Son Donnig	5	X	X	Н	X						X					X	X		deeper sample pending shallower results, if collected.
5A_DG-644	PDU Area	South of Building 4005	Soil Boring	0.5 5	X	X	X H	X						X					X	X		Same as 5A_DG-643.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (17 of 39)

												Ana	lytical M	ethod								1
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/741B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	IPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-645A	PDU Area	Transformer 4705 (South of Building 4005)	Soil Boring	0.5		X	по	0	00	ЩО	H ()	70		E)	E C) (що	I (<u> </u>	X H	I	Location targets two former transformers. Transformers in Area IV with previous ND results are being resampled with discrete samples. Collect samples at six
5A_DG-645B	PDU Area	Transformer 4705	Soil Boring	0.5		X														X		discrete locations and analyze 0.5' samples for PCBs; hold deeper samples pending
5A_DG-645C	PDU Area	(South of Building 4005) Transformer 4705	Soil Boring	0.5		H X														H X		shallower results.
5A_DG-645D	PDU Area	(South of Building 4005) Transformer 4705	Soil Boring	3 0.5		H X														H X	✓	
		(South of Building 4005) Transformer 4705	+	3 0.5		H X														H X		
5A_DG-645E	PDU Area	(South of Building 4005) Transformer 4705	Soil Boring	3 0.5		H X														H X		
5A_DG-645F	PDU Area	(South of Building 4005)	Soil Boring	3		H														Н		
5A_DG-651	PDU Area	Drainage Southwest of Building 4005	Soil Boring	0.5	X	X	X	X X	X					X X	X	X X			X	X	✓	Location targets drainage downslope of operational area with a cooling tower; positioned between underground stormwater and floor trench conveyance pipes. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess potential subsurface release and migration along
				10	X	X	X	X	X					X	X	X			X	X		bedrock.
5A DG-652	PDU Area	South of Building 4005	Soil Boring	0.5	X X	X X	X H	X X						X X					X X	X X		Same as 5A_DG-643.
3A_DG-032	1 Do Alca	South of Building 4005	Soil Boiling	10	Н	Н	Н	Н						Н					Н	Н		
				0.5	X	X	X	X						X					X	X		Representative location to characterize operational area; positioned downslope of Clearly Contaminated Area. Collect samples at 5' intervals to bedrock with deepest
5A_DG-653	PDU Area	South of Building 4005	Soil Boring	5	X	X	Н	X						X					X	X		sample just above bedrock; hold deeper sample pending shallower results.
				0.5	H X	H X	H X	H X						H X					H X	H X		Location targets a potential AST and undefined features observed in 1978 aerial.
5A_DG-654	PDU Area	Northwest of Coal Storage / Parking Area Near 17th and G	Soil Boring	5	X	X	Н	X						X					X	X	✓	Analyze 0.5' and 5' samples based on potential for disturbed soils noted in aerial. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
		Street		10	Н	Н	Н	Н						Н					Н	Н		hold deeper sample pending shallower results.
				0.5	X	X	X	X						X					X	X		Location targets potential storage area based on aerial photographs. Analyze 0.5' and 5' samples based on potential for disturbed soils noted in aerial. Collect
5A_DG-655	PDU Area	North of Coal Storage / Parking Area Near 17th and G Street	Soil Boring	5	X	X	Н	X						X					X	X	✓	samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
				10	Н	Н	Н	Н						Н					Н	Н		deeper sample pending shallower results.
		Drainage Along 17th Street		0.5	X	X	X	X	X					X	X	X			X	X		Location targets drainage west of open storage observed in 1978 aerial photograph and downslope of B4005 cooling tower; positioned between underground
5A_DG-656	PDU Area	Northeast of Coal Storage/Parking Area	Soil Boring	5	X	X	X	X	X					X	X	X			X	X	✓	stormwater and floor trench conveyance pipes. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess
				10	X	X	X	X	X					X	X	X			X	X		potential migration along bedrock.
				0.5	X	X	X	X						X					X	X		Location targets potential storage area based on aerial photographs. Analyze 0.5' and 5' samples based on potential for disturbed soils noted in aerial. Collect
5A_DG-657	PDU Area	North of Coal Storage / Parking Area Near 17th and G Street		5	X	X	X	X						X					X	X	✓	samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (18 of 39)

	<u> </u>		<u> </u>									And	alvtical	Method								T
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)			Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist ³	Rationale / Comments ^{4,5}
5A_DG-658	PDU Area	North of Coal Storage / Parking	Soil Boring	0.5	X	X	X	X						X		H O			X	X		Location targets unlined surface water flow pathway along the northern perimeter of the Coal Storage/Parking Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths
		Area Near 17th and G Street	·	5	X	X	X	X						X					X	X		based on potential for vertical migration of surface water/contaminants.
		Northwest of Coal Storage /		0.5	X	X	X	X						X					X	X		Stepout from Clearly Contaminated Area west of Coal Storage/Parking Area; positioned between underground stormwater and floor trench conveyance pipes
5A_DG-659	PDU Area	Parking Area Near 17th and G Street	Soil Boring	5	X	X	X	X						X					X	X		and in-line with surface water pathway along northern perimeter of Coal Storage/Parking Area. Collect samples at 5' intervals to bedrock with deepest
				10	X	X	X	X						X					X	X		sample just above bedrock; analyze all depths to assess potential migration along bedrock.
5A_DG-660	PDU Area	Clearly Contaminated Area West of Coal Storage / Parking	Soil Boring	0.5	X X	X	X	X						X					X	X		Stepdown within Clearly Contaminated Area (dioxins, metals, PAHs, PCBs at depth near two adjacent surface-only samples; TPH not previously analyzed). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
3A_DG-000	FDO Alea	Area Near 17th and G Street	Soft Borning	10	X	X	X	X						X					X	X		analyze all depths to assess potential migration along bedrock from adjacent sand trap feature.
5A_DG-661	DDU Area	Drainage Along 17th Street	Soil Doning	0.5	X	X	X	X						х					X	X		Stepout for dioxins, PCBs, metals, PAHs detected in Coal Storage/Parking Area perimeter samples (Clearly Contaminated Area) and characterizes drainage downslope of operational areas; positioned between underground stormwater and
3A_DG-001	PDU Area	West of Coal Storage / Parking Area	Son Bornig	5	X	X	X	X						X					X	X		floor trench conveyance pipes. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Representative sample to characterize the Coal Storage/Parking Area; also stepout
5A_DG-662	PDU Area	Coal Storage / Parking Area Near 17th and G Street	Soil Boring	5	X	X	Н	X						X					X	X	✓	for Clearly Contaminated Area west of Coal Storage/Parking Area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
				0.5	H Y	H	H	H						H					H	H		deeper sample pending shallower results. Stepout from Clearly Contaminated Area west of Coal Storage/Parking Area.
5A_DG-663	PDU Area	Coal Storage / Parking Area Near 17th and G Street	Soil Boring	5	X	X	X H	X						X					X	X	1	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
		Footprint		10	X	X	Н	X						X					X	X		analyze all depths.
		Coal Storage / Parking Area		0.5	X	X	X	X						X					X	X		Stepout for Clearly Contaminated Area south of Coal Storage/Parking Area and targets surface flow pathway from Coal Storage/Parking Area to drainage along
5A_DG-664	PDU Area	Near 17th and G Street	Soil Boring	5	X	X	X	X						X					X	X	✓	17th Street. Collect samples at 5' intervals to bedrock with deepest sample just
		Footprint		10	X	X	X	X						X					X	X		above bedrock; analyze all depths.
		Drainage at Intersection		0.5	X	X	X	X	X					X	X	X	X	X	X	X		Location targets low spot before culvert in drainage along G street immediately downslope of Clearly Contaminated Area south of Coal Storage/Parking Area and downstream of B4005 cooling tower; also targets Old Conservation Pipeline (diesel
5A_DG-665	PDU Area	of 17th and G Street South of Coal Storage / Parking Area	Soil Boring	5	X	X	X	X	X					X	X	X	X	X	X	X	✓ fue	fuel). Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess
		11100		10	X	X	X	X	X					X	X	X	X	X	X	X		potential migration along bedrock.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (19 of 39)

												Ana	alvtical M	Iethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X					1.0	X		H O			X	X		Location targets geophysical anomaly and drainage along G Street upstream of Clearly Contaminated Area south of Coal Storage/Parking Area; positioned
5A_DG-666	PDU Area	Drainage Along G Street South of Coal Storage / Parking Area	Soil Boring	5	X	X	X	X						Х					X	X	✓	adjacent to Old Conservation Yard fuel pipeline. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess potential migration along bedrock.
				10	X	X	X	X						X					X	X		
54 DC 667	DDII A	Coal Storage / Parking Area	Call Davins	0.5	X	X	X	X						X					X	X		Representative sample to characterize the Coal Storage/Parking Area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
5A_DG-667	PDU Area	Near 17th and G Street	Soil Boring	5 10	X H	X H	H	X H						X H					X H	X H	*	deeper sample pending shallower results.
		Coal Storage / Parking Area		0.5	X	X	X	X						X					X	X		Same as 5A_DG-667.
5A_DG-668	PDU Area	Near 17th and G Street	Soil Boring	5 10	X H	X H	H	X H						X H					X H	X H	_	
5A_DG-669	PDU Area	North of Coal Storage / Parking	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Location targets unlined surface water flow pathway along the northwestern perimeter of the Coal Storage/Parking Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
		Area Near 17th and G Street		5	X	X	X	X						X					X	X		all depths to assess potential for vertical migration of surface water/contaminants.
5A_DG-670	PDU Area	Coal Storage / Parking Area	Soil Boring	0.5 5	X X	X X	X H	X X						X X					X X	X X	-	Same as 5A_DG-667; also targets former structures.
	1 DO THOU	Near 17th and G Street	Bon Bonng	10	Н	Н	Н	Н						Н					Н	Н		
		Coal Storage / Parking Area		0.5	X	X	X	X						X					X	X	,	Representative sample to characterize the Coal Storage/Parking Area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
5A_DG-671	PDU Area	Near 17th and G Street	Soil Boring	5	X	X	Н	X						X					X	X	_	deeper sample pending shallower results.
				0.5	H X	H X	H X	H X						H X					H X	H X	-	Same as 5A_DG-666.
5A_DG-672	PDU Area	Drainage Along G Street South	Soil Boring	5	X	X	X	X						X					X	X	/	Same as 3/1_50 000.
		of Coal Storage / Parking Area	_	10	X	X	X	X						X					X	X		
5A_DG-673	PDU Area	East of Coal Storage / Parking Area Near 17th and G Street	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Location targets unlined surface water flow pathway along the eastern perimeter of the Coal Storage/Parking Area. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to
		Area Near 17th and G Street		5	X	X	X	X						X					X	X		assess potential for vertical migration of surface water/contaminants.
5A_DG-674	PDU Area	Northeast of Coal Storage / Parking Area Near 17th and G	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Location targets an unlined surface water flow pathway along the northeastern perimeter of the Coal Storage/Parking Area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
		Street		5	X	X	X	X						X					X	X		all depths to assess potential for vertical migration of surface water/contaminants.
5A_DG-675	PDU Area	East of Coal Storage / Parking	Soil Boring	0.5	X X	X X	X H	X X						X X					X X	X X		Location targets open space east of Coal Storage/Parking Area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample
3A_DO-073	1 DO AICA	Area Near 17th and G Street	Jon Dornig	10	Н	Н	Н	Н					+	Н					Н	Н		pending shallower results.
				0.5	X	X	X	X					1	X					X	X		Same as 5A_DG-675.
5A_DG-676	PDU Area	East of Coal Storage / Parking Area Near 17th and G Street	Soil Boring	5	X	X	Н	X						X					X	X		
	1	Area real 1/111 and G Street		10	Н	Н	Н	Н						Н					Н	Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (20 of 39)

												Ana	lytical M	lethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X	<u> </u>		<u> </u>	1	I O	X		20			X	X		Location targets drainage along G street; positioned upstream of Clearly Contaminated Area south of Coal Storage/Parking Area and adjacent to Old
5A_DG-677	PDU Area	Drainage Along G Street	Soil Boring	5	X	X	X	X						X					X	X	✓	Conservation Yard fuel pipeline. Bedrock anticipated ~10'. Collect samples at 5'
				10	X	X	X	X						X					X	X		intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess potential migration along bedrock.
5A_DG-678	PDU Area	East of Coal Storage / Parking	Soil Boring	0.5 5	X X	X X	X H	X						X					X X	X		Same as 5A_DG-675.
		Area Near 17th and G Street		10	Н	Н	Н	Н						Н					Н	Н		Location towards disturbed proportion/soil noted in parish above growth a slee
5 A DC (70	DDII A	Fort of Decition 4042	Call Davis	0.5	X	X	X H	X						X					X	X		Location targets disturbed vegetation/soil noted in aerial photographs; also characterizes operational area. Collect samples at 5' intervals to bedrock with
5A_DG-679	PDU Area	East of Building 4042	Soil Boring	10	X H	X H	Н	X H						X H					X H	X H	•	deepest sample just above bedrock; hold deeper sample pending shallower results.
		Western Portion of Open		0.5	X	X	X	X						X					X	X		Location targets open storage observed along western fence in aerial photos.
5A_DG-680	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5 10	X	X H	H H	X H						X H					X H	X H	✓	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
54 DC 601	DDIIA	Drainage West of Open	G IID :	0.5	H X	X	X	X	X					X	X		X	X	X	X		Location targets unlined surface water flow pathway along western perimeter of open storage. Collect samples at 5' intervals to bedrock with deepest sample just
5A_DG-681	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	10	X	X X	X	X	X					X	X X		X X	X X	X	X	•	above bedrock; analyze all depths.
54 DG 602	DDII 4	Western Portion of Open	G 11 D 1	0.5	X	X	X	X						X					X	X		Location targets open storage observed along western fence in aerial photos. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-682	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5 10	X H	X H	H H	X H						X H					X H	X H	•	hold deeper sample pending shallower results.
		Drainage Along G Street South		0.5	X	X	X	X	X					X	X		X	X	X	X	,	Same as 5A_DG-677.
5A_DG-683	PDU Area	of Open Storage / Parking Area	Soil Boring	5 10	X	X	X	X X	X					X	X		X X	X X	X	X	~	
5.A. D.C. 60.4	DDIIA	Western Portion of Open	G 31D :	0.5	X	X	X	X						X					X	X	,	Location targets open storage. Collect samples at 5' intervals to bedrock with
5A_DG-684	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5 10	X H	X H	H H	X H						X H					X H	X H	>	deepest sample just above bedrock; hold deeper sample pending shallower results.
5A DC 605	DDU	Northeastern Portion of Open	C-IID :	0.5							X									X		Collect sample at SL-215-SA5A to confirm previous perchlorate detection at 5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-685	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5							X H									X H	•	hold deeper sample pending shallower results.
5A DC 696	DDII Area	Eastern Portion of Open	Cail Davina	0.5	X	X	X	X						X			X	X	X	X	1	Location targets dark toned material and open storage. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-686	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5	X	X	Н	X						X			X	X	X	X	v	hold deeper sample pending shallower results, if collected.
54 DG 605	DDII 4	Eastern Portion of Open	G 11 D 1	0.5	X	X	X	X						X					X	X		Location targets drainage adjacent to medium toned material and open storage. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest
5A_DG-687	PDU Area	Storage / Parking Area Near 12th and G Street	Soil Boring	5	X	X	Н	X						X					X	X		sample just above bedrock; analyze all depths.
5A_DG-688	PDU Area	Eastern Portion of Open Storage / Parking Area Near	Soil Boring	0.5	X	X	X	X						X					X	X	1	Stepout (upstream) for dioxins; positioned in surface water pathway downslope of portion of Storage Area/Parking Area that flows toward 12th Street. Shallow
JA_DU-000	1 DO Alea	12th and G Street	Son Bornig	5	X	X	X	X						X					X	X	,	bedrock anticipated. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Representative location to characterize drainage. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above
5A_DG-689	B4641 Area	Drainage Along 12th Street	Soil Boring	5	X	X	X	X						X					X	X	~	bedrock; analyze all depths.
				10	X	X	X	X						X					X	X		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (21 of 39)

												Ana	alytical Me	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X					1	X		<u> </u>			X	X		Stepout for SL-126-SA5A and SL-127-SA5A (dioxins detected above ISLs).
5A_DG-690	B4641 Area	East of Building 4073	Soil Boring	5	X	X	X	X						X					X	X	✓	Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
				10	Н	Н	Н	Н						Н					Н	Н		results.
				0.5	X	X	X	X						X					X	X		Representative location to characterize open space downslope of operational areas. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock
5A_DG-691	B4641 Area	East of Building 4073	Soil Boring	5	X	X	X	X						X					X	X		with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		
				0.5	X	X	X	X						X			X	X	X	X		Location targets drainage downstream of operational area. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample
5A_DG-692	B4641 Area	Southeast of Building 4073	Soil Boring	5	X	X	X	X						X			X	X	X	X	*	just above bedrock; analyze all depths.
				10	X	X	X	X						X			X	X	X	X	-	Stepdown at SL-110-SA5A (dioxins and PAHs detected above ISLs shallow; no
				0.5	Н	Н	Н	Н						X					Н	X		deeper sample). Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze 0.5' sample
5A_DG-693	B4641 Area	Drainage Along 12th Street	Soil Boring	5	X	X	X	X						X					X	X	_	for TPH only and analyze all samples deeper than 0.5' for full suite.
				10	X	X	X	X						X					X	X		
51 DG (01	D. C. C. L.	G . d	G 11 P .	0.5	X	X	X	X						X			X	X	X	X		Location targets discharge from cooling water hold-up tank drain line. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with
5A_DG-694	B4641 Area	Southeast of Building 4073	Soil Boring	10	X	X	X	X						X			X	X	X	X	ľ	deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X			- 11	71	X	X		Location targets stormwater flow path along road downstream of B4073 area
5A_DG-695	B4641 Area	Southeast of Building 4073	Soil Boring	5	X	X	X	X						X					X	X	/	(metals [Hg up to 4.8 ppm], TPH, PAHs, and dioxins detected above ISLs). Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock
****				10	X	X	X	X						X					X	X		with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X	-	Location targets B4123 footprint (KEWB Waste Storage Yard); also characterizes
		Within Building 4123		0.3		Λ	Λ	Λ						Λ					Λ	Λ		and/or delineates fill of unknown origin. Note that RFI and EPA collocated sample locations targeting B4123 were inadvertently placed ~50' east of former building
5A_DG-696	B4641 Area	Footprint	Soil Boring	5	X	X	X	X						X					X	X	\	footprint. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				10	X	X	X	X						X					X	X		to occurrent deepest sample just noove bedrock, analyze an ucpuis.
				0.5	X	X	X	X						X					X	X		Stepout for (metals [Hg up to 4.8 ppm], TPH, PAHs, and dioxins detected in the area; also characterizes fill of unknown origin observed in adjacent borings.
5A_DG-697	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	✓	Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				10	X	X	X	X						X					X	X		with deepest sample just above bedrock, analyze an depuis.
				0.5	X	X	X	X						X					X	X		Stepout for SL-127-SA5A (dioxins detected above ISLs). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-698	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	'	hold deeper sample pending shallower results, if collected.
				J	Λ	Λ	Λ	Λ						Λ					Λ	Λ		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (22 of 39)

			1 1									Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)		(EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X						X		1			X	X		Stepup and stepdown at SL-128-SA5A to characterize fill of unknown origin and
5A_DG-699	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	✓	native soil beneath fill. Bedrock anticipated ~15'. Collect samples at 5' intervals to bedrock with the deepest sample just above bedrock; analyze all depths.
				10	X	X	X	X						X					X	X		
		5 WW 40 5 0		0.5	X	X	X	X						X					X	X		Same as 5A_DG-697.
5A_DG-700	B4641 Area	Building 4073 Area	Soil Boring	5 10	X	X	X	X X						X X					X	X	–	
				0.5	X	X	X	X						X					X	X		Same as 5A_DG-699.
5A_DG-701	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	✓	
				0.5	X	X X	X X	X						X X					X X	X X		Same as 5A_DG-699.
5A_DG-702	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	✓	
				10	X	X	X	X						X					X	X		5 DG (00
5A_DG-703	B4641 Area	Building 4073 Area	Soil Boring	0.5 5	X	X	X	X X						X X					X X	X X	✓	Same as 5A_DG-699.
		gg	~~~~~	10	X	X	X	X						X					X	X		
5A_DG-704	B4641 Area	Building 4073 Area	Soil Boring	0.5 5	X	X	X	X						X X					X X	X X		Same as 5A_DG-699.
3A_DG-704	B4041 Alea	Building 4073 Area	Son Bornig	10	X	X	X	X						X					X	X	•	
				0.5	X	X	X	X						X					X	X		Same as 5A_DG-697; positioned on undefined feature present in aerials from 1959 to 1967. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with
5A_DG-705	B4641 Area	Building 4073 Area	Soil Boring	5	X	X	X	X						X					X	X	✓	deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
				0.5	X	X	X	X						X					X	X		Location targets former road downslope of the former leachfield and upslope of the
5A_DG-706	D4641 Area	Open Space South of Building	Soil Boring	<i>E</i>	v																	drainage along 12th St (dioxins and PAHs detected above ISLs); also serves as stepout from SL-143-SA5A (dioxins and PAHs detected above ISLs). Bedrock
3A_DG-700	B4641 Area	4093 Leach Field	Soil Boring	10	X H	X H	X H	X H						X H					X H	Н	ľ	anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
	_																					Same as 5A_DG-706.
5A_DG-707	B4641 Area	Open Space South of Building	Soil Boring	0.5	X	X	X H	X X						X X					X	X	/	Same as SA_DG-700.
3A_DG-707	B4041 Alea	4093 Leach Field	Son Bornig	10	Н	Н	Н	Н						Н					Н	Н	•	
				0.5	X	X	X	X						X					X	X		Stepout from SL-111-SA5A (dioxins detected above ISLs) and SL-253-SA5A
5A_DG-708	B4641 Area	Open Space South of Building	Soil Boring	5	X	X	Н	X						X					X	X	✓	(dioxins and pesticides detected above ISLs); also characterizes area downslope of operations. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock
		4093 Leach Field		10	Н	Н	Н	Н						Н					Н	Н		with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X	X	X	X					X	X					X	X		Recollect at SL-148-SA5A to analyze for terphenyls within B4093 leach field (terphenyl tank present in B4093). Bedrock anticipated <15'. Collect samples at 5'
5A_DG-709	B4641 Area	Building 4093 Leach Field	Soil Boring	5	Н	Н	Н	Н					X	Н					Н	Н	✓	intervals to bedrock with deepest sample just above bedrock; analyze all samples for terphenlys and analyze 0.5' sample for full suite since shallow sample at SL-148-
				10	Н	Н	Н	Н					Х	Н					Н	Н		SA5A not collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (23 of 39)

					I							Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X			, , =			X					X	X		Location targets former road downslope of the former leachfield and upslope of the drainage along 12th St (dioxins and PAHs detected above ISLs); also characterizes
5A_DG-710	B4641 Area	Open Space South of Building 4093 Leach Field	Soil Boring	5	X	X	X	X						X					X	X	~	area downslope of disturbed ground identified by EPA in the 1995 aerial photo. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		
5A DC 711	D4641 A	North of Building 4093 Leach	Call Davins	0.5	X	X	X	X						X					X	X	1	Location targets geophysical anomaly (terrain conductivity) and leachfield and associated components; and stepout for SL-156-SA5A (dioxins and TPH detected above ISLs). Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock
5A_DG-711	B4641 Area	Field	Soil Boring	5	X	X	X	X						X					X	X	ľ	with deepest sample just above bedrock; analyze all depths.
5A_DG-712	B4641 Area	North of Building 4093 Leach	Soil Boring	0.5	X	X	X	X						X					X	X	/	Same as 5A_DG-711; positioned within drainage.
		Field		5	X	X	Н	X						X					X	X		
5A_DG-713	B4641 Area	Parking Area between Buildings 4073 and 4083	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Representative location to characterize former parking lot and open storage observed in 1988 oblique photo; positioned downslope of operational area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest
		Buildings 4073 and 4063		5	X	X	Н	X						X					X	X		sample just above bedrock; analyze all depths.
		Drainage Between Buildings		0.5	X	X	X	X						X					X	X		Stepout for SL-146-SA5A (dioxins, metals, PAH, and TPH detected above ISLs); positioned within drainage upstream of sample. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
5A_DG-714	B4641 Area	4073 and 4074	Soil Boring	5	X	X	X	X						X					X	X	_	all depths.
				0.5	X	X	X	X	X					X	X	X			X	X		Location targets former B4633, the Reactor Cooling Water Pad. Bedrock
5A_DG-715	B4641 Area	Building 4633	Soil Boring	5	X	X	Н	X	X					X	X	X			X	X	*	anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-716	B4641 Area	North of Building 4093	Soil Boring	0.5	X	X	X	X						X					X	X	_	Same as 5AN_DG-125; positioned near end of asphalt path from B4003 and upslope of SL-167-SA5A. Bedrock anticipated ~5'. Collect samples at 5' intervals
JA_DG-/10	D+0+1 Alca	Notifi of Building 4093	Son Doring	5	X	X	Н	X						X					X	X	'	to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-717	D4641 Amor	Northwest of Building 4093	Soil Boring	0.5	X	X	X	X					X	X					X	X		Same as 5AN_DG-125; positioned in surface water pathway downslope of SL-167-SA5A (terphenyl tank present in B4093). Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all
3A_DG-/1/	B4641 Area	Northwest of Building 4093	SOII BOTHING	5	X	X	Н	X					X	X					X	X		depths.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (24 of 39)

												An	alvtical I	Method								<u> </u>
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)			Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X			, , <u> </u>		X	X					X	X		Location targets sewer connection to B4093 (terphenyl tank present in B4093); note many surrounding samples to north and east do not have shallow sample and
5A_DG-718	B4641 Area	Building 4093	Soil Boring	5	X	X	X	X					X	X					X	X	✓	~2' of fill observed in borings. Bedrock anticipated between 10' and 15'. Collect
				10	Н	Н	Н	Н					Н	Н					Н	Н		samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X	X	X	X					X	X					X	Х		Stepout from SL-167-SA5A (metals [Hg 15x ISL] and TPH detected above ISLs); positioned near entrance to B4093 (terphenyl tank present in B4093). Bedrock
5A_DG-719	B4641 Area	Building 4093	Soil Boring	5	X	X	Н	X					X	X					X	X	*	anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-720	D4641 Area	Southeast of Puilding 4002	Soil Poring	0.5	X	X	X	X					X	X					X	Х		Representative location to characterize operational area (terphenyl tank present in B4093). Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with
3A_DG-720	B4641 Area	Southeast of Building 4093	Soil Boring	5	X	X	X	X					X	X					X	X		deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X	X	X	X						X					X	Х		Representative location to characterize operational area; note many surrounding samples to north and east do not have shallow sample and ~2' of fill observed in
5A_DG-721	B4641 Area	Southwest of Building 4093	Soil Boring	5	X	X	Н	X						X					X	X		borings. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending
				10	X	X	Н	X						X					X	X		shallower results.
5A DG-722	B4641 Area	Drainage East of Building 4093	Soil Boring	0.5	X	X	X	X						X					X	X	/	Representative location to characterize drainage downslope of operational area. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest
311_00 722	B 10 11 1 I Cu	Leach Field	Bon Bonng	5	X	X	X	X						X					X	X		sample just above bedrock; analyze all depths.
5A_DG-723	B4641 Area	Southeast of Building 4093	Soil Boring	0.5	X	X	X	X						X					X	X	/	Representative location to characterize operational area between B4093 and 4453; positioned near a former road. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample
3A_DG-723	D-10-11 Alca	Southeast of Building 4073	50ff Borning	5	X	X	X	X						X					X	X		pending shallower results, if collected.
5A_DG-724	B4641 Area	Southeast of Building 4093	Soil Boring	0.5	X	X	X	X						X					X	X	/	Same as 5A_DG-723.
		January 1975	g	5	X	X	X	X						X					X	X		
5A_DG-725	B4641 Area	Building 4453	Soil Boring	0.5	X	X	X	X						X					X	х	✓	Stepout from SL-171-SA5A and SL-173-SA5A (dioxins, metals, PAHs, and pesticides detected above ISLs); positioned near end of asphalt path from B4641. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest
				5	X	X	X	X						X					X	X		sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-726	B4641 Area	Building 4453	Soil Boring	0.5	X	X	X	X					1	X					X	X	V	Same as 5A_DG-725.
211_30.20			309	5	X	X	X	X						X					X	X		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (25 of 39)

												Ana	alytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	FPH EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-727	B4641 Area	Building 4453	Soil Boring	0.5	1	X	I	200			1			X	1		1	1		X	-	Reanalysis at SL-173-SA5A for PCBs due to elevated reporting limits. Both SL-171-SA5A and SL-173-SA5A had samples with elevated reporting limits for PCBs. Recollecting at SL-173-SA5A due to location having highest reporting limit and positioned near entrance to B4453. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-728	B4641 Area	Building 4453	Soil Boring	0.5	X	X	X	X						X			X	X	X	X	✓	Same as 5A_DG-725; positioned in access road to B4093.
				0.5	X	X	X	X						X			X	X	X	X		Representative location to characterize open space downslope of operational areas; positioned in possible surface water flow path from operation area into open space
5A_DG-729	B4641 Area	Open Space West of Building 4453	Soil Boring	5	X	X	Н	X						X			X	X	X	X	✓	(based on topography and aerial photos). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Location targets three point magnetometer anomalies and inline with interpreted drain remnant. Bedrock anticipated between 5' and 10'. Collect samples at 5'
5A_DG-730	B4641 Area	Open Space West of Building 4453	Soil Boring / Test Pit	5	X	X	X	X						X					X	X	✓	intervals to bedrock with deepest sample just above bedrock; analyze all depths. Conduct adjacent test pit for three point magnetometer anomalies and interpreted drain remnant and adjust 5' sample to target feature (or sample pit as appropriate).
				10	X	X	X	X						X					X	X		
5A_DG-731	B4641 Area	Building 4453	Soil Boring	0.5	X H	X H	X H	X H						X H			X H	X H	X H	X H	✓	Same as 5A_DG-725; positioned in surface water flow path not captured by SL-172-SA5A.
				0.5	X	X	X	X						X					X	X		Location targets former road and vegetation clearance area observed in 1980 aerial
5A_DG-732	B4641 Area	Open Space Southwest of Building 4453	Soil Boring	5	X	X	Н	X						X					X	X	✓	photo. Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н	Н						Н					Н	Н		
				0.5	X	X	X	X	X					X					X	X		Stepout from SL-111-SA5A and SL-109-SA5A (dioxins and hexavalent chromium). Bedrock anticipated between 5' and 10'. Collect samples at 5' interval.
5A_DG-733	B4641 Area	Drainage Along 12th Street	Soil Boring	5	X	X	X	X	X					X					X	X	✓	to bedrock with deepest sample just above bedrock; analyze all depths.
				10	X	X	X	X	X					X					X	X		
5A_DG-734	B4641 Area	Open Space South of Building	Soil Boring	0.5 5	X	X	X	X						X					X X	X	1	Same as 5A_DG-732.
3A_DG-/34	D4041 Area	4453	Son boring	10	X H	X H	H H	X H						X H					H	X H		
5A_DG-735	B4641 Area	Open Space Southeast of	Soil Boring	0.5	X	X	X	Х						X					X	Х		Representative location to characterize open space downslope of operational areas; positioned on flat area adjacent to road. Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper
_		Building 4453		5	X	X	X	X						X					X	X		sample pending shallower results, if collected.
				0.5	X	X	X	X						X					X	X		Location targets vegetation clearance area observed in 1980 aerial photo. Bedrock
5A_DG-736	B4641 Area	Open Space Southeast of Building 4453	Soil Boring	5	X	X	Н	X						X					X	X	✓	anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
		Daniang 1100		10	Н	Н	Н	Н						Н					Н	Н		, 1 1 1 6

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (26 of 39)

		Γ			1							A 200	alvtical M	[othed								1
												Ana	aryticai iv	letnoa								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5										X	X					X		Stepdown at SL-107-SA5A (dioxins and PAHs detected above ISLs shallow; no deeper sample). Bedrock anticipated ~10'. Collect samples at 5' intervals to
5A_DG-737	B4641 Area	Drainage Along G Street and 11th Street	Soil Boring	5	X	X	X	X	X					X	X				X	X	✓	bedrock with deepest sample just above bedrock; analyze 0.5' sample for TPH only
		Tiui Sueet		10	X	X	X	X	X					X	X				X	X		and all samples deeper than 0.5' for all analyses.
				0.5	X	X	X	X						X					X	X		Location targets disturbed ground area identified in EPA technical memorandum
5A DG-738	B4641 Area	South of Building 4641	Soil Boring	5	X	X	Н	X						X					X	X	/	present in the 1995 aerial photo (possible location of leach field) and characterizes open space downslope of an operational area. Bedrock anticipated between 5' and
3A_DG-730	D4041 Alca	South of Building 4041	Son Doring	10	Н	Н	Н	Н						Н					Н	Н		10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
																	37	v				Location targets stormwater pipe discharge location and delineates extent of fill of
5.4. D.C. 720	DACAL A	G 4 CD 'H' 4641	G 31D 3	0.5	X	X	X	X						X			X	X	X	X		unknown origin. Bedrock anticipated between 5' and 10'. Collect samples at 5'
5A_DG-739	B4641 Area	South of Building 4641	Soil Boring	5	X	X	X	X						X			X	X	X	X	*	intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				10		X	X	X									A	A	X	X		Location targets linear terrain conductivity and characterizes fill of unknown
54 DG 540	D. C. C. L.	B 777 4644	Soil Boring /	0.5	X	X	X	X						X					X	X		origin. Collect samples at 5' intervals to bedrock with deepest sample just above
5A_DG-740	B4641 Area	Building 4641	Test Pit	5	X	X	X	X						X					X	X	•	bedrock; analyze all depths Conduct adjacent test pit for linear terrain conductivity anomaly and adjust 5' sample to target feature (or sample pit as appropriate).
				0.5	X	X	X	X						X					X	X		Location targets linear terrain conductivity and characterizes fill of unknown
5A DG-741	B4641 Area	Building 4641	Soil Boring	5	X	X	X	X X						X					X	X X	/	origin. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to
3/1_23 7 11	Bioirrica	Building 1011	Bon Boring	10	X	X	X	X						X					X	X		bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					Х	Х		Location targets terminus of lined drainage and entrance to B4641; also characterizes fill of unknown origin and open storage along west side of B4641
5A_DG-742	B4641 Area	Building 4641	Soil Boring																		✓	observed in 1974 oblique photo. Bedrock anticipated ~5'. Collect samples at 5'
				5	X	X	X	X						X					X	X		intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Representative location to characterize operational area and open storage identified in EPA HSA (open storage area offset to northeast in GIS). Bedrock
5A_DG-743	B4641 Area	Building 4046	Soil Boring	5	X	X	X	X						X					X	X	✓	anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
																				igsquare		Representative location to characterize fill of unknown origin. Bedrock anticipated
5A_DG-744	B4641 Area	Building 4641	Soil Boring	0.5 5	X	X	X	X X						X					X	X X	 	between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample
37 <u>1</u> 20 / ++	D to ri riioa	Dunanig TOT1	Son Bornig	10	X	X	X	X						X					X	X		just above bedrock; analyze all depths to characterize fill.
				0.5	X	X	X	X						X					X	X		Location targets drainage downstream of operational area and open storage. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest
5A_DG-745	B4641 Area	North of Building 4641	Soil Boring	5	X	X	X	X						X					X	X	~	sample just above bedrock; analyze all depths.
				3	Λ	Λ	A	А						A					Λ	^		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (27 of 39)

					1							Ana	lytical N	Iethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metak ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-746A	B4641 Area	North of Building 4641	Soil Boring	0.5		X					' ' -									X		Transformers in Area IV with previous ND results are being resampled with discrete samples. Collect samples at four discrete locations and analyze 0.5'
				0.5		H X														H X		samples for PCBs; hold deeper samples pending shallower results.
5A_DG-746B	B4641 Area	North of Building 4641	Soil Boring	3		Н														Н		Northern sample (5A_DG-151C) also characterizes open storage and fill of
5A DG-746C	B4641 Area	North of Building 4641	Soil Boring	0.5	X	X	X X	X X						X					X	X	~	unknown origin. At this location, bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
3A_DG-740C	D4041 Alea	North of Building 4041	Son Bornig	10	X	X	X	X						X					X	X		milet vans to bedrook wan deepest sample just doore bedrook, analyze an depails.
5A DG-746D	B4641 Area	North of Building 4641	Soil Boring	0.5		X														X		
				5		Н														Н		Stepout for SL-221-SA5A and SL-222-SA5A (dioxins, metals, PCBs, and PAH
5A_DG-750	B4641 Area	Open Storage North of Building 4641	Soil Boring	0.5	X	X	X	X						X					X	X	✓	detected above ISLs) and characterizes open storage and fill of unknown origin. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock
		Dunding 4041		10	X	X	X	X						X					X	X		with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X						X					X	X		Same as 5A_DG-750.
5A_DG-751	B4641 Area	South of Building 4030	Soil Boring	5 10	X	X	X	X X						X					X	X	~	
5A DG-752	B4641 Area	Building 4030	Soil Boring	0.5	X	X	X	X						X					X	X	/	Location targets sewer connection to B4030 and open storage identified in EPA memo (open storage area offset to northeast in GIS). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
3A_DG-132	D-0-11 Alca	Building 4030	Son Boring	5	X	X	X	X						X					X	X		analyze all depths.
5A_DG-753	B4641 Area	Building 4046	Soil Boring	0.5	X	X	X	X						X					X	X	/	Same as 5A_DG-743.
	210111100	Bunding 1010	Son Boring	5	X	X	X	X						X					X	X		
5A_DG-754	B4641 Area	South of Building 4035	Soil Boring	0.5	X	X	X	X						X					X	X	✓	Representative location to characterize open storage and fill of unknown origin (metals, dioxins, and TPH above ISLs). Bedrock anticipated <5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all
				5	X	X	X	X						X					X	X		depths.
5A_DG-755	B4641 Area	South of Building 4035	Soil Boring	0.5	X	X	X	X						X					X	X	/	Same as 5A_DG-754; also targets linear magnetometer anomaly.
JH_DU-133	D=U+1 Alca	South of Building 4033	Son Borning	5	X	X	X	X						X					X	X	Ľ	
5A_DG-756	B4641 Area	Between Buildings 4030 and	Soil Boring	0.5 5	X X	X X	X X	X X						X X					X X	X X	/	Same as 5A_DG-750.
311_DG-130	D TOTI AICA	4641	Jon Bornig	10	X	X	X	X						X					X	X	Ļ.	
	2444	Between Buildings 4030 and	Soil Boring /	5	X	X	X	X						X					X	X		Stepout for SL-221-SA5A and SL-222-SA5A (dioxins, metals, PCBs, and PAH detected above ISLs) and characterizes open storage and fill of unknown origin. Excavate test pit to investigate linear magnetometer anomalies and adjust 5' sample to target features observed in the field (or sample pit as appropriate). Collect
5A_DG-757	B4641 Area	4641	Trench	10	X	X	X	X						X					X	X	Í	samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths. Conduct trench according to orientation shown; adjust to north based on existing sewer line location.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (28 of 39)

			<u> </u>									Ana	alytical N	1ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-758	B4641 Area	Between Buildings 4030 and 4641	Soil Boring	0.5 5 10	X X X	X X X	X X X	X X X						X X X					X X X	X X X	✓	Same as 5A_DG-750.
5A_DG-759	B4641 Area	Building 4641	Soil Boring	0.5 5 10	X X X	X X X	X X X	X X X						X X X					X X X	X X X	1	Representative location in area surrounding B4641. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-760	B4641 Area	Building 4641	Soil Boring	0.5	X X X	X X X	X X X	X X X						X X X					X X X	X X X	✓	Same as 5A_DG-759.
5A_DG-761	B4641 Area	Building 4641	Soil Boring	0.5 5	X X X	X X X	X X X	X X X						X X X					X X X	X X X	✓	Same as 5A_DG-759.
5A_DG-762	B4641 Area	Building 4641	Soil Boring	0.5	X X X	X X X	X X X	X X X						X X X					X X X	X X X	√	Same as 5A_DG-759.
5A_DG-763	B4641 Area	East of Building 4641	Soil Boring	0.5 5	X X X	X X X	X X X	X X X						X X X					X X X	X X X	1	Location targets stormwater pipe discharge location. Bedrock anticipated between 5' and 10'.Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-764	B4641 Area	Building 4641	Soil Boring	0.5	X X X	X X X	X X X	X X X						X X X					X X X	X X X		Location targets southern end of loading dock area and high bay door at B4641. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-765	B4641 Area	South of Building 4641	Soil Boring	0.5	X X	X X	X X	X X						X					X X	X X		Location targets magnetometer anomaly and further characterizes fill of unknown origin. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-766	B4641 Area	South of Building 4641	Soil Boring	10 0.5 5	X X X	X X X	X X H	X X X						X X X					X X X	X X X	✓	Location targets magnetometer anomaly and characterizes open space downslope of an operation area. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
5A_DG-767	B4641 Area	South of Building 4641	Soil Boring	0.5	H X X	H X X	H X X	H X X						H X X					H X X	H X X	✓	Representative location to characterize open area downslope of an operational area; positioned at intersection of two surface flow pathways. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
5A_DG-768	B4641 Area	Drainage Along G Street and 11th Street	Soil Boring	10 0.5 5	X	X	X	X	X					X X X	X X				X	X X X	✓	Stepdown at SL-105-SA5A (dioxins and PAHs detected above ISLs shallow; no deeper sample). Bedrock anticipated ~10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze 0.5' sample for TPH only and all samples deeper than 0.5' for all analyses.
5A_DG-769	B4641 Area	South of Building 4641	Soil Boring	10 0.5 5	X X X	X X X	X X X	X X X	X					X X X	X		X X	X X	X X X	X X X		Location targets stormwater pipe discharge location and delineates extent of fill of unknown origin. Bedrock anticipated between 5' and 10'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
_		Į ,		10	X	X	X	X					†	X			X	X	X	X		inici vais to bedrock with deepest sample just above bedrock; analyze an depths.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (29 of 39)

	1		1		1						Anc	alvtical M	othod								1
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)		EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-770	B4641 Area	Drainage Along 10th Street	Soil Boring	0.5	X	X	X	X					X					X	X	~	Representative location to characterize drainage. Bedrock anticipated ~5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths.
				0.5	X	X	X	X					X			X	X	X	X		Stepout for SL-105-SA5A (dioxins, metals, and PAH detected above ISLs); positioned upstream of SL-105-SA5A. Bedrock anticipated between 5' and 10'.
5A_DG-771	B4641 Area	Drainage Along G Street and 10th Street	Soil Boring	5	X	X	X	X					X			X	X	X	X	✓	Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
				10	X	X	X	X					X			X	X	X	X		analyze all depths.
5A_DG-772	B4029	West of Open Storage Area	Soil Boring	0.5	X		X	X					X					X	X		Representative location in open field. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
3A_DG-772	D4029	Along G Street	Son Bornig	5	X		Н	X					X					X	X		results, if collected.
5A_DG-773	B4029	West of Open Storage Area Along G Street	Soil Boring	0.5	X		Х	X					X			X		X	X	٧	Stepout for dioxins, PAHs, and pesticides at SL-031-SA5A; location also assesses potential disposal along south side of G Street adjacent to the open storage area identified as "Waste Disposal Area" in EPA HSA. Shallow bedrock anticipated based on previous sampling in the area. Collect samples at 5' intervals to bedrock
		Along G Street		5	X		Н	X					X			X		X	X		with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
		Southwest of Open Storage		0.5	X		X	X					X			X		X	X		Stepout for dioxins, PAHs, and pesticides at SL-031-SA5A and dioxins at SL-024-SA5A. Collect samples at 5' intervals to bedrock with deepest sample just above
5A_DG-774	B4029	Area Along G Street	Soil Boring	5	X		Н	X					X			X		X	X		bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-775	B4029	Southwest of Open Storage	Soil Boring	0.5	X		Х	X					X					X	X	V	Stepout for dioxins at SL-024-SA5A; location also characterizes area downslope from open storage area identified as "Waste Disposal Area" in EPA HSA. Shallow bedrock anticipated based on previous sampling in the area. Collect samples at 5'
3.1_56 773	B 1023	Area Along G Street	Bon Bonng	5	X		Н	X					X					X	X	ľ	intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-776	B4029	Open Storage Area Along G	Soil Boring	0.5	X		Х	X					X			X		X	X	V	Stepout for PAHs, dioxins, and pesticides at SL-031-SA5A and dioxins and PAHs (BaP) at SL-026-SA5A; location also characterizes western portion of open storage area identified as "Waste Disposal Area" in EPA HSA and potential staining or low
3/ 1_DG 770	D402)	Street	Son Boring	5	X		Н	X					X			X		X	X	Ĺ	spot observed in aerial photos between 1967 and 1972. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
				0.5	X		X	X					X			X		X	X		Location targets open storage area identified as "Waste Disposal Area" in EPA HSA; location also serves as stepout for dioxins at SL-040-SA5A, and dioxins and
5A_DG-777	B4029	Open Storage Area Along G Street	Soil Boring	5	X		Н	X					X			X		X	X	٧	pesticides at SL-037-SA5A. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if
				10	Н		Н	Н					Н			Н		Н	Н		collected.
		Open Storage Area Alone C		0.5						X									X		Collect sample at SL-036-SA5A to confirm previous perchlorate detection at 0.5'. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
5A_DG-778	B4029	Open Storage Area Along G Street	Soil Boring	5						Н									Н	٧	hold deeper sample pending shallower results.
				10						Н									Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (30 of 39)

Location ID Area Location Description 5A_DG-779 B4029 East of Open Stora Along G Streen	orage Area	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs EPA Method 8082)	ans d 1613)	020/6020A/7471A/7471B)			(0)		alytical Me	ethod						160.3)		-
5A DG-779 R4029 East of Open Stora	orage Area	-		AHS including NDMA PA Method 8270C [SIM])	PCTs (ethod 8082)	ans d 1613)	471A/7			(0:	G G								3)		
1 5A DG=7/9 1 B/009 1 -	-			Z E	PCBs /] (EPA M	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Ferphenyls (EPA Method 8015B)	IPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	thod	Data Gap Checklist³	Rationale / Comments ^{4,5}
5 A D(+=7/Q R/ID/Q -	-		0.5	X		X	X						X			X)	X	X		Stepout for dioxins at SL-040-SA5A and SL-051-SA5A, and dioxins and pesticide at SL-037-SA5A; location also characterizes eastern extent of open storage area
1	Street	Soil Boring	5	X		Н	X						X			X		X	X	٧	identified as "Waste Disposal Area" in EPA HSA and open field near former dirt road (observed in aerial photos in 1957 and 1995). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending
			10	Н		Н	Н						Н			Н		Н	Н		shallower results.
5A_DG-780 B4029 East of Open Stora Along G Stre		Soil Boring	0.5	X		X H	X X						X					X	X X		Stepout for dioxins at SL-051-SA5A. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
South of Open Stor	torage Area		0.5	X		X	X						X					X	X		Stepout for dioxins at SL-050-SA5A. Collect samples at 5' intervals to bedrock
5A_DG-781 B4029 South of open stor		Soil Boring	5	X		Н	X						X					X	X		with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-782 B4029 South of Open Stor Along G Stre		Soil Boring	0.5	X		X	X						X					X	X	٧	One of three locations targeting rill along dirt road downslope from open storage area identified as "Waste Disposal Area" in EPA HSA. Locate drainage feature (e.g. rill, topographic low, etc.) and map with GPS prior to collection of samples. Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with
	, acce		5	X		X	X						X					X	X		deepest sample just above bedrock; analyze all depths.
5A DG-783 B4029 South of Open Stor	torage Area	Soil Boring	0.5	X	X	X	X	X					X	X				X	X	V	Stepout for dioxins at SL-021-SA5A and SL-022-SA5A; location also characterize former road and area of cleared vegetation (observed in 1959 aerial photo). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
Along G Stree	Street	Son Bornig	5	X	X	Н	X	X					X	X				X	X	·	deeper sample pending shallower results, if collected.
5A_DG-784 B4029 Southeast of Open Area South of G	-	Soil Boring	0.5	X		X	X						X					X	X	٧	Same as 5A_DG-782.
			5	X		X	X						X					X	X		Same as 5A_DG-783.
5A_DG-785 B4029 South of Open Stor Along G Stree		Soil Boring	0.5 5	X		X H	X						X					X	X	٧	Same as 27_00-103.
5A_DG-786 B4029 Southwest of Open		Soil Boring	0.5	X		X	X						X					X	х	٧	Stepout for dioxins at SL-024-SA5A; location also characterizes area downslope from open storage area identified as "Waste Disposal Area" in EPA HSA. Shallow bedrock anticipated based on previous sampling in the area. Collect samples at 5'
Area Along G S	G Street	20mg	5	X		Н	X						X					X	X		intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-787 B4029 South of Open Stor Along G Stre	_	Soil Boring	0.5	X		X	X						X					X	Х	٧	Location targets area of cleared vegetation and potential dirt road observed in aerial photos between 1959 and 1965. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
Along G Stre	ou cet		5	X		Н	X						X					X	X		results, if collected.
Northeast of Cl 5A_DG-788 B4029 Contaminated Are Street Pond	Area (17th	Soil Boring	0.5	X	X	X H	X						X					X	X		Representative location in open field. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (31 of 39)

												Ana	alytical Mo	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)		Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane EPA Method 8360B SIM)	Ferphenyls EPA Method 8015B)	FPH EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-789	B4029	Northeast of Clearly Contaminated Area (17th Street Pond)	Soil Boring	0.5	X	X	Х	X	X]			X	X	I]	X	X		Same as 5A_DG-788. Location along sanitary sewer pipeline near manhole to assess potential northeast extension of the 17th Street Pond Clearly Contaminated Area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
		Northeast of Clearly		0.5	X	Λ	Х	X	Λ					X	Λ				X	X		Same as 5A_DG-788.
5A_DG-790	B4029	Contaminated Area (17th Street Pond)	Soil Boring	5	X		Н	X						X					X	X		
5A DG-791	B4029	Northeast of Clearly Contaminated Area (17th	Soil Boring	0.5	X		X	X						X					X	X		Same as 5A_DG-788.
3A_DG-/91	Б4029	Street Pond)	Soil Boring	5	X		Н	X						X					X	X		
5A_DG-792	B4029	Northeast of Clearly Contaminated Area (17th Street Pond)	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout for dioxins and metals (Ag) at SL-206-SA5B and SL-207-SA5B; location also defines eastern extent of Clearly Contaminated Area (17th Street Pond) in Subarea 5B. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected
		Sueet Folia)		5	X	X	X	X						X					X	X		
5A_DG-793	B4029	Northeast of Clearly Contaminated Area (17th	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout to characterize Clearly Contaminated Area (17th Street Pond); location also targets area of cleared vegetation (observed only in 1959 aerial photo). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
		Street Pond)		5	X	X	Н	X						X					X	X		hold deeper sample pending shallower results, if collected.
5A_DG-794	B4029	Northwest of Clearly Contaminated Area (Eastern	Soil Boring	0.5	X	X	X	X						X					X	X	٧	Stepout to characterize area between two Clearly Contaminated Areas (Eastern Hummocky Area and 17th Street Pond); location also placed on historical dirt road. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
		Hummocky Area)	8	5	X	X	X	X						X					X	X		hold deeper sample pending shallower results, if collected.
5A_DG-795	B4029	Northwest of Clearly Contaminated Area (Eastern	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout for dioxins at CFBS1030 and dioxins and metals (Ag) at SL-207-SA5B; location also defines eastern extent of the 17th Street Pond Clearly Contaminated Area and characterizes area between two Clearly Contaminated Areas (Eastern
3A_DG-793	Б4029	Hummocky Area)	Soil Boring	5	X	X	X	X						X					X	X		Hummocky Area and 17th Street Pond). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
54 DC 704	D 1020	West of Clearly Contaminated		0.5	X	X	X	X						X					X	X		Stepout for dioxins at CFBS1030; location also characterizes area between two Clearly Contaminated Areas (Eastern Hummocky Area and 17th Street Pond).
5A_DG-796	B4029	Area (Eastern Hummocky Area)	Soil Boring	5	X	X	X	X						X					X	X		Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-797	B4029	West of Clearly Contaminated Area (Eastern Hummocky	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout for dioxins at SL-272-SA5B and CFBS1030; location also characterizes area between two Clearly Contaminated Areas (Eastern Hummocky Area and 17th Street Pond). Collect samples at 5' intervals to bedrock with deepest sample just
2.2.2.2.0 171	2.027	Area)	2011 Zoring	5	X	X	X	X						X					X	X		above bedrock; hold deeper sample pending shallower results, if collected.
5A_DG-798	B4029	West of Clearly Contaminated Area (Eastern Hummocky	Soil Boring	0.5	X	X	X	X						X					X	X		Stepout to characterize area between two Clearly Contaminated Areas (Eastern Hummocky Area and 17th Street Pond). Collect samples at 5' intervals to bedrock
21= 0 //0	02/	Area)	2011 2011119	5	X	X	X	X						X					X	X		with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (32 of 39)

			1											F /1 1								T
												Ana	lytical M	iethod	1	1						-
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X	X						X					X	X		Location characterizes identified hummocky area adjacent to Clearly Contaminated Area (Eastern Hummocky Area) observed during site walk (May, 2012). Excavate
5A_DG-799	B4029	Southwest of Clearly Contaminated Area (Eastern	Soil Boring / Trench	5	X	X	X	X						X					X	X	٧	exploratory trench to investigate hummocky area for potential pond dredge sediment and log depth of native soil. Collect one sample in sediment (if observed), one sample in native soil just below contact with sediment, and deepest
		Hummocky Area)		10	X	X	X	X						X					X	X		sample just above bedrock (bedrock anticipated between 5' and 10').
		Southwest of Clearly		0.5	X	X	X	X						X					X	X		Same as 5A_DG-799.
5A_DG-800	B4029	Contaminated Area (Eastern	Soil Boring / Trench	5	X	X	X	X						X					X	X	٧	
		Hummocky Area)		10	X	X	X	X						X					X	X		54 PG 500
5A DG-801	B4029	Southwest of Clearly Contaminated Area (Eastern	Soil Boring /	0.5 5	X	X	X	X						X					X	X	V	Same as 5A_DG-799.
3A_DG-001	D+02)	Hummocky Area)	Trench	10	X	X	X	X						X					X	X	'	
		Southwest of Clearly	G :1D : /	0.5	X	X	X	X						X					X	X		Same as 5A_DG-799.
5A_DG-802	B4029	Contaminated Area (Eastern	Soil Boring / Trench	5	X	X	X	X						X					X	X	٧	
		Hummocky Area)		0.5	X	X	X	X						X					X	X		Same as 5A_DG-799.
5A_DG-804	B4029	Southwest of Clearly Contaminated Area (Eastern	Soil Boring /	5	X	X	X	X						X					X	X	V	Same as JA_DO-177.
		Hummocky Area)	Trench	10	X	X	X	X						X					X	X		
				0.5	X	X	X	X						X					X	X		Location targets Clearly Contaminated Area (Eastern Hummocky Area) to complete coverage / definition within extent. Excavate exploratory trench to
5A_DG-807	B4029	Clearly Contaminated Area (Eastern Hummocky Area)	Soil Boring	5	X	X	X	X						X					X	X	٧	investigate hummocky area for potential pond dredge sediment and log depth of native soil. Collect one sample in sediment (if observed), one sample in native soil just below contact with sediment, and deepest sample just above bedrock (bedrock
				10	X	X	X	X						X					X	X		anticipated between 5' and 10').
				0.5	X	X	X	X						X					X	Х		Stepout to characterize northern extent of Clearly Contaminated Area (Eastern Hummocky Area); location also characterizes identified hummocky area observed
5A_DG-808	B4029	Northwest of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Boring / Trench	5	X	X	X	X						X					X	Х	٧	during site walk (May, 2012). Excavate exploratory trench to investigate hummocky area for potential pond dredge sediment and log depth of native soil. Collect one sample in sediment (if observed), one sample in native soil just below
		Hummoony Area)		10	X	X	X	X						X					X	X		contact with sediment, and deepest sample just above bedrock (bedrock anticipated between 5' and 10').
		North of Clearly Contaminated		0.5	X	X	X	X						X					X	X		Stepout for dioxins at SL-041-SA5A and CFBS1029; location also characterizes area between two Clearly Contaminated Areas (Eastern Hummocky Area and 17th
5A_DG-809	B4029	Area (Eastern Hummocky Area)	Soil Boring	5	X	X	X	X						X					X	X		Street Pond). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results, if collected.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (33 of 39)

Leading ID Annual Leading Aeroligina Supplies													Ana	lytical N	lethod								
Martin M	Location ID	Area	Location Description		•	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	360B	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Gap	Rationale / Comments ^{4,5}
SADE 18-229 Contaminance Area Liberton Substitution Subs			Northwest of Clearly	G 11 P	0.5										X		H C		1				
A	5A_DG-810	B4029		-	3	-									-							٧	F21859.
No.			Hummocky Area)		10	X	X	X	X						X					X	X		Stangult for digwins at SL 041 SASA and CERS1020: location also targets adm of
SA_DG-S11 SA_DG-S11 SA_DG-S12 Sale Decision of Humanocky Area Sa					0.5	X	X	X	X						X					X	X		hummocky area observed during site walk (May, 2012) and characterizes northern
Northeast of Closely Seal Burling Seal Burlin	5A_DG-811	B4029	Area (Eastern Hummocky		5	X	X	X	X						X					X	X	٧	material / sediments observed in boring, collect one sample in sediment, one
SA DG 812 B4229 Contaminated Are (Eastern Hummock) Hermorcky Area) Decided to be decided with a part of the process of			,		10	X	X	X	X						X					X	X		above bedrock (bedrock anticipated between 5' and 10').
Humancity Area Flat Fla	54 DC 812	P4020		Soil Boring /	0.5	X	X	X	X						X					X	Х	-1	Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with
Sal DG 813 B4129 Area (Fastern Humanocky Area) Area (Fastern Humanocky Area) Area (Fastern Humanocky Area) Soil Boring Sal DG 814 B4129 Contaminated Area (Fastern Humanocky Area) Soil Boring Sal DG 816 Sal Boring Sal DG 816	3A_DG-812	D4029		Trench	5	X	X	X	X						X					X	X	V	
April																							
Northeast of Clearly	5A_DG-813	B4029	` '	Soil Boring	3										+								
SA_DG-814 B4029 Comminated Area (Eastern Hummocky Area) Soil Boring S X X X X X X X X X																							Stepout for dioxins at SL-049-SA5A; location also targets surface water pathway
Hummocky Area	5A_DG-814	B4029		Soil Boring																		V	with GPS prior to collection of samples. Collect samples at 5' intervals to bedrock
SA_DG-815 B4029 Area (Eastern Hummocky Area) Soil Boring S X H X X X X X X X X			Hummocky Area)		10	X		X	X						X					X	X		
Area) Ar			East of Clearly Contaminated		0.5	X		X	X						X					X	X		
East of Clearly Contaminated Area (Eastern Hummocky Area). If pond dredge material / social Boring / Area) Soil Boring / Area) Soil Boring / Area / Battor Clearly Contaminated Area (Eastern Hummocky Area). If pond dredge material / social ments of the properties	5A_DG-815	B4029		Soil Boring	5																		
East of Clearly Contaminated Area (Eastern Hummocky Area) Soil Boring Soil Boring			7 Hear)				X																
Soil Boring French Frenc	5A_DG-816	B4029	Area (Eastern Hummocky	Soil Boring	5	X	X	X	X						X					X	X	٧	sediments observed in boring, collect one sample in sediment, one sample in native
East of Clearly Contaminated Area (Eastern Hummocky Area) Soil Boring/ Trench Soil Boring/ Area (Eastern Hummocky Area) Soil Boring/ Trench Soil Boring/			Area)		10	X	X	X	X						X					X	X		(bedrock anticipated between 5' and 10').
SA_DG-817 B4029 Area (Eastern Hummocky Area) Soil Boring/ Trench Tench Soil Boring/ Trench Soil Boring/ Soil Boring/ Trench Soil Boring/ Trench Soil Boring/ Trench Soil Boring/ Trench Soil Boring/ Soil Boring/ Trench Soil Boring/			East of Clearly Contaminated	a n =	0.5	X	X	X	X						X					X	X		trench to investigate mound for potential pond dredge sediment and log depth of
East of Clearly Contaminated Area (Eastern Hummocky Area) Soil Boring / Trench Soil Boring / Trench Soil Boring / Trench Targets area of low-profile mounded soil observed during site walk (May, 2012). X X X X X X X X X X X X X X X X X X X	5A_DG-817	B4029	Area (Eastern Hummocky	-	-																	٧	just below contact with sediment, and deepest sample just above bedrock (bedrock
East of Clearly Contaminated Area (Eastern Hummocky Area) Soil Boring / Trench Soil Bo																							Targets area of low-profile mounded soil observed during site walk (May, 2012).
Area) sample just above bedrock (bedrock anticipated between 5' and 10').	5A DG-818	B4029		Soil Boring /																		v	sediment and log depth of native soil. Collect one sample in sediment (if
	2.1_20 010	5.02)		Trench	10	X	X	X	X						X					X	X		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (34 of 39)

	1		<u> </u>		1							Ans	alvtica	l Method								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs EPA Method 8082)	Dioxins/Furans EPA Method 1613)	Metals ² EPA Methods 5010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	[-4 Dioxane EPA Method 8360B SIM)		EPA Method 8015B) IPH EPA Method 8015B)	Formaldehyde EPA Method 8315A)	Morpholine EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides EPA Method 8151A)	pH (EPA Method 9045C)	oil Moisture ASTM D2216/EPA Method 160.3)	Gap Checklist³	Rationale / Comments ^{4,5}
		East of Clearly Contaminated				PCBs / PC (EPA Met			Cr(VI) (EPA Met	Energetic (EPA Met	Perchlora (EPA Met	1-4 Dioxaı (EPA Met	Terpheny		Formalde (EPA Met	Morpholii (EPA Met	Pesticides (EPA Met	Herbicide (EPA Met		9 2 —	Data Gap	
5A_DG-819	B4029	Area (Eastern Hummocky	Soil Boring	0.5 5	X		X	X						X					X	X	٧	Same as 5A_DG-782.
		Northeast of Clearly	Soil Boring /	0.5	X	X	X	X						X					X	X		Same as 5A_DG-818.
5A_DG-820	B4029	Contaminated Area (Eastern	Trench	5	X	X	X	X						X					X	X	٧	
		Hummocky Area)		10	X	X	X	X						X					X	X		Targets hummocky area observed during site walk (May, 2012). Excavate
5.4 P.G.001	D 4000	Northeast of Clearly	Soil Boring /	0.5	X	X	X	X						X					X	X		exploratory trench to investigate hummocky area for potential pond dredge sediment and log depth of native soil. Collect one sample in sediment (if
5A_DG-821	B4029	Contaminated Area (Eastern Hummocky Area)	Trench	10	X	X	X	X						X					X	X	observed), one sample in native soil just below contact with sedim	observed), one sample in native soil just below contact with sediment, and deepest sample just above bedrock (bedrock anticipated between 5' and 10').
				0.5	X		X	X						X					X	X		Representative location in open field. Hold deeper sample pending shallower
5A_DG-822	B4029	Northeast of Open Storage Area Along G Street	Soil Boring	5	X		Н	X						X					X	X		results. Collect samples at 5' intervals to bedrock with deepest sample just above
		Area Along O Street		10	Н		Н	Н						Н					Н	Н		bedrock; hold deeper sample pending shallower results.
		East of Open Storage Area		0.5	X		X	X						X					X	X		Representative location in open field; location also positioned adjacent to historical dirt road observed in aerial photographs (1957 - 1965). Collect samples at 5'
5A_DG-823	B4029	Along G Street	Soil Boring	5	X H		Н	X H						X H					X H	X H	٧	intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10																		Same as 5A_DG-823.
5A_DG-824	B4029	Northwest of SE Drum Yard	Soil Boring	0.5 5	X		X H	X						X					X	X	V	Same as JA_DO-023.
				10	Н		Н	Н						Н					Н	Н		
				0.5	X		X	X						X					X	X		Representative location in open field. Collect samples at 5' intervals to bedrock
5A_DG-825	B4029	West of SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X		with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н		Н	Н						Н	1				Н	Н		Targets shallow drainage pathway in open field. Locate drainage feature (e.g. rill,
5A_DG-826	B4029	West of SE Drum Yard	Soil Boring	0.5	X		X	X						X					X	X	V	topographic low, etc.) and map with GPS prior to collection of samples. Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with deepest sample
				5	X		X	X						X					X	X		just above bedrock; analyze all depths given location within surface water pathway
				0.5	X		X	X						X					X	X		Representative location in open field; location also placed on historical dirt road
5A_DG-827	B4029	West of SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X	٧	observed in aerial photograph (2005). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
				10	Н		Н	Н						Н					Н	Н		results.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (35 of 39)

												Ana	lytical M	lethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/741B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-828	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5 5	X		X X	X X						X X					X X	X X	٧	Transect/stepout for dioxins at SL-241-SA5A to characterize overbank deposits. Four lateral stepout locations comprise a drainage transect (with previous drainage sample in the middle); collect stepouts 5 feet and 10 feet laterally from location SL-
5A_DG-829	B4029	Drainage Southwest of SE	Soil Boring	0.5	X		X	X						X					X	X X		241-SA5A/5A_DG-830. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess historical deposition over
JA_DU-029	D4U29	Drum Yard	Soil DOTHIS	10 0.5	X		X	X						X X X					X	X X X		time. 5A_DG-830 also serves as a stepdown for dioxins at SL-241-SA5A (previously,
5A_DG-830	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	5	X X		X X	X X						X					X X	X		only 0.5 ft sample collected). Analyze shallow sample for TPH since not previously sampled. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths since located in unlined surface water
5A_DG-831	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5 5 10	XXX		X X	XXX						X X					X	X X X	٧	pathway.
5A_DG-832	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5	X X X		X X X	X X X						X X X					X X X	X X X	٧	
5A_DG-833	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	10 0.5 5	X		X	X						X					X	X	٧	Transect/stepout for dioxins at SL-100-SA5A to characterize overbank deposits. Four lateral stepout locations comprise a drainage transect (with previous drainage
5A_DG-834	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5	X X X		X X X	X X X						X X X					X X X	X X X	٧	sample in the middle); collect stepouts 5 feet and 10 feet laterally from location SL-100-SA5A/5A_DG-835. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths to assess historical deposition over
5A_DG-835	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5	X		X	X						X					X	X	٧	time.
5A_DG-836	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5 5	X X		X X	X X						X X					X X	X X		5A_DG-835 also serves as a stepdown for dioxins at SL-100-SA5A (previously, only 0.5 ft sample collected). Analyze shallow sample for TPH since not previously sampled. Collect samples at 5' intervals to bedrock with deepest sample
5A_DG-837	B4029	Drainage Southwest of SE Drum Yard	Soil Boring	0.5 5	X		X	X						X					X X	X	V	just above bedrock; analyze all depths given location within unlined surface water pathway. Representative location in open field. Collect samples at 5' intervals to bedrock
5A_DG-838	B4029	Northeast of Clearly Contaminated Area (Eastern	Soil Boring	0.5	X		X H	X						X					X	X X		with deepest sample just above bedrock; hold deeper sample pending shallower results.
		Hummocky Area)		10	Н		Н	Н						Н					Н	Н		Representative location in open field. Collect samples at 5' intervals to bedrock
5A_DG-839	B4029	Southwest of SE Drum Yard	Soil Boring	0.5	X		X H	X						X					X	X X		with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н		Н	Н						Н					Н	Н		December 1 to 1 t
5A_DG-840	B4029	East of Clearly Contaminated Area (Eastern Hummocky	Soil Boring	0.5	X		X H	X X						X					X	X X	٧	Representative location in open field; location also positioned on historical dirt road (observed in aerial photos in 1967 and between 1977 and 1990). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
		Area)		10	Н		Н	Н						Н					Н	Н		deeper sample pending shallower results.
5A_DG-841	B4029	South of SE Drum Yard	Soil Boring	0.5	X		X H	X X						X					X X	X X	٧	Representative location in open field; location also targets low spot/drainage pathway from northeast (near 5AS_DG-386) and positioned on historical dirt road (observed in aerial photos between 1953 and 1977). Collect samples at 5' intervals
	02/		2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	10	Н		Н	Н						Н					Н	Н		to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (36 of 39)

												Ana	lytical M	Iethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Ferphenyls (EPA Method 8015B)	IPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A DG-842	B4029	South of SE Drum Yard	Soil Boring	0.5	X		X	X						X					X	X	V	Representative location in open area; also targets area of cleared vegetation observed in 1980 aerial photo. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
JA_DG-042	D4029	South of SE Druin Taid	Son Boring	10	Н		H	Н						Н					Н	H	•	
				0.5			X	11						1						X		Recollect at SEBS1002 located within area of cleared vegetation east of the SE
5A_DG-843	B4029	Southeast of SE Drum Yard	Soil Boring	5			X													X	٧	Drum Yard and analyze for dioxins to complete the analytical suite. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
				10			Н													Н		deeper sample pending shallower results.
				0.5	X		X	X						X					X	X		Location targets rilling along dirt road and provides dioxin data near/upslope of elevated dioxins in drainage sample location SL-098-SA5A. Collect samples at 5'
5A_DG-844	B4029	South of SE Drum Yard	Soil Boring	5	X		X	X						X					X	X	intervals to bedrock with deepest sample just above bedrock; analyze all desince located in unlined surface water pathway.	intervals to bedrock with deepest sample just above bedrock; analyze all depths
				10	X		X	X						X					X	X		
				0.5			X													X		Recollect at SEBS1001 located within area of cleared vegetation east of the SE Drum Yard and analyze for dioxins to complete the analytical suite. Collect
5A_DG-845	B4029	East of SE Drum Yard	Soil Boring	5			X													X	٧	samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X		H X	X						X					X	H X		Stepout for PAHs (BaP) at SEBS1000; location also characterizes eastern SE
5A_DG-846	B4029	East of SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X	٧	Drum Yard storage area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н		Н	Н						Н					Н	Н		
				0.5	X		X	X						X					X	X		One of three samples characterizing the northern portion of the SE Drum Yard (previous historical [1988] samples had elevated RLs for NDMA and PAHs) but
5A_DG-847	B4029	SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X	٧	were not analyzed for comprehensive suite; location also serves as stepout for PAHs (BaP) at SEBS1000 and targets containers / cleared vegetation (observed in
				10	Н		Н	Н						Н					Н	Н		aerial photos between 1960 and 1965). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X		X	X						X					X	X		Same as 5A_DG-847.
5A_DG-848	B4029	SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X	٧	
				10	Н		Н	Н						Н					Н	Н		
				0.5	X		X	X						X					X	X		One of three samples characterizing the northern portion of the SE Drum Yard (previous historical [1988] samples had elevated RLs for NDMA and PAHs) but
5A_DG-849	B4029	SE Drum Yard	Soil Boring	5	X		Н	X						X					X	X	٧	were not analyzed for comprehensive suite. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending
				10	Н		Н	Н						Н					Н	Н		shallower results.
				0.5	X		X	X						X					X	X		Characterizes potential surface water pathway along dirt road south of B402 Locate drainage feature (e.g. rill, topographic low, etc.) if identifiable; other
5A_DG-850	B4029	South of B4029	Soil Boring	5	X		X	X						X					X	X	٧	collect at GPS coordinates shown on figure to characterize open field area. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze
				10	X		X	X						X					X	X		all depths given area receives surface water runoff.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (37 of 39)

												Ana	lytical M	lethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist ³	Rationale / Comments ^{4,5}
				0.5	X		X	X						X		<u> </u>			X	X		Location targets area of potential sheet flow between two parallel drainages
5A_DG-851	B4029	Drainage Southwest of B4029	Soil Boring	5	X		Н	X						X					X	X	٧	southwest of B4029 (observed in aerial photos between 1978 and 1988). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold
		0.2		10	Н		Н	Н						Н					Н	Н		deeper sample pending shallower results.
				0.5	X	X	X	X						X					X	X		Location targets one of two drainages southwest of B4029; analyze PCBs since drainage potentially receives runoff from operational areas to the north of G Street. Locate drainage feature (e.g. rill, topographic low, etc.) and map with GPS prior to collection of samples. Shallow bedrock anticipated. Collect samples at 5' intervals
5A_DG-852	B4029	Drainages Southwest of B4029	Soil Boring	5	X	X	X	X						X					X	X	√	to bedrock with deepest sample just above bedrock; analyze all depths since located in surface water pathway.
5A_DG-853	B4029	Drainage Southwest of B4029	Soil Boring	0.5 5	X X	X X	X X	X X						X X					X X	X X	٧	Same as 5A_DG-852.
5A_DG-854	B4029	West of B4029	Soil Boring	0.5 5	X		Х	X X						X X					X X	X X	Stepout for surficial dioxins detected at SL-053-SA5A; loadjacent to historical dirt road observed in aerial photogramum Collect samples at 5' intervals to bedrock with deepest samples at 5' intervals at 5'	Stepout for surficial dioxins detected at SL-053-SA5A; location also positioned adjacent to historical dirt road observed in aerial photographs (1957 - 1965). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze 5-foot sample since dioxins RLs were >ISLs at SL-053-SA5A and hold other samples pending shallower results
				10	Н		H	Н						Н					H	Н		Same as 5A_DG-854; location also positioned on historical dirt road observed in
5A_DG-855	B4029	West of B4029	Soil Boring	0.5 5 10	X X H		X H H	X X H						X X H					X X H	X X H	٧	aerial photographs (1957 and 1959). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	X	X	X	X						X					X	X		Stepout for PAHs, dioxins, and metals (Pb, Zn) at SL-096-SA5A; location also
5A_DG-856	B4029	Northwest of B4029 Near G Street	Soil Boring	5	X	X	Н	X						X					X	X	٧	downslope of culvert discharge at SL-096-SA5A. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				0.5	H X	H X	H X	H X						H X					H X	H X		Same as 5A_DG-856.
5A_DG-857	B4029	Northwest of B4029 Near G Street	Soil Boring	5	X	X	Н	X						X					X	X	٧	
				10	Н	Н	Н	Н						Н					Н	Н		Stepdown for dioxins and PAHs at SL-096-SA5A; location also targets culvert
5A_DG-858	B4029	Northwest of B4029 Near G	Soil Boring	0.5	X		X	X						X					X	X	V	discharge point. Analyze shallow sample for TPH since not previously sampled. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock;
JA_DO-030	D+023	Street	Son Boning	10	X		X	X						X					X	X		analyze all depths given location at culvert discharge point.
				0.5	X		X	X						X					X	X		Stepout for PAHs, dioxins, and metals (Pb, Zn) at SL-096-SA5A. Collect samples
5A_DG-859	B4029	Northwest of B4029 Near G Street	Soil Boring	5	X		Н	X						X					X	X		at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
		Succi		10	Н		Н	Н						Н					Н	Н		
5A_DG-860	B4029	West of B4029 Access Road	Soil Boring	0.5	X		X	X						X					X	X	٧	Characterizes potential surface water pathway in vegetated area south of G Street. Target drainage feature (e.g. rill, topographic low, etc.) if identifiable; otherwise collect at GPS coordinates shown on figure to characterize open field area. Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with
				5	X		X	X						X					X	X		deepest sample just above bedrock; analyze all depths given area receives surface water runoff.

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (38 of 39)

												Ana	lytical M	ethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics EPA Method 8330A)	Perchlorate EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls EPA Method 8015B)	IPH EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Festicities (EPA Method 8081)	Herbicides EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
5A_DG-861	B4029	North of B4029	Soil Boring	0.5	X	X	X X	X						X					X X	X X	٧	Location targets discharge from culvert which receives runoff from B4064 operational areas in the north (located in Subarea 6) and unlined surface water pathway along south side of G Street. Shallow bedrock anticipated. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths given location at surface water discharge point.
5A_DG-862	B4029	North of B4029 Access Road	Soil Boring	0.5	X		X	X						X					X X	X		Stepout upstream of culvert inlet in unlined surface water pathway for dioxins at SL-095-SA5A. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths given location within unlined drainage.
5A_DG-863	B4029	Southwest of B4029 Access Road	Soil Boring	0.5 5 10	X X X		X X X	X X X						X X X					X X X	X X X	٧	Targets discharge from existing culvert downslope of B4029 access road. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths given location at culvert discharge point.
5A_DG-864	B4029	Southwest of B4029 Access Road	Soil Boring	0.5	X X X		X X X	X X X						X X X					X X X	X X X	Targets discharge from two historical culver Collect samples at 5' intervals to bedrock wi analyze all depths given location at culvert d	Targets discharge from two historical culverts downslope of B4029 access road. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths given location at culvert discharge point.
5A_DG-865	B4029	B4029 Access Road	Soil Boring	0.5	X		X	X						X X					X X	X X		Stepout for dioxins at SL-056-SA5A and dioxins and PAHs at SL-057-SA5A; also characterizes possible fill along slope and area of cleared vegetation south of B4029 access road (observed in aerial photos from 1980 and 1995) and identified in EPA's HSA 5A Tech Memo as "ground scar". Collect samples at 5' intervals to
				0.5	X		X	X						X					X	X		bedrock with deepest sample just above bedrock; analyze all depths to characterize fill. Stepout for TPH at SFBS0012 and PAHs and dioxins at SL-057-SA5A; also characterizes possible fill along slope and area of cleared vegetation south of the B4029 access road (observed only in aerial photos from 1980 and 1995) and
5A_DG-866	B4029	South of B4029 Access Road	Soil Boring	5	X		X	X						X					X	X	٧	identified in EPA's HSA 5A Tech Memo as "ground scar". Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths since TPH detected at depth in previous samples and to characterize fill.
5A_DG-867	B4029	South of B4029 Access Road	Soil Boring	5	X		X	X						X					X X	X	٧	Stepout for TPH at SFBS0011 and SFBS0012; also characterizes possible fill along slope and area of cleared vegetation south of the B4029 access road (observed only in aerial photos from 1980 and 1995) and identified in EPA's HSA 5A Tech Memo as "ground scar". Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths since TPH detected at depth in previous
				0.5	X		X	X						X					X	X		samples and to characterize fill. Location targets potential surface water feature on slope south of B4029 (linear feature observed in 1980 aerial photo); location also characterizes possible fill along slope and area of cleared vegetation south of the B4029 access road
5A_DG-868	B4029	South of B4029 Access Road	Soil Boring	5	X		X	X						X					X	X	٧	(observed only in aerial photos from 1980 and 1995) and identified in EPA HSA as "ground scar". Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; analyze all depths since TPH detected at depth in previous samples and to characterize fill.
5A_DG-869	B4029	South of B4029	Soil Boring	0.5	X X		X H	X X						X X					X X	X X		Location targets historical dirt road leading to cleared vegetation area on slope south of B4029 (observed in 1980 aerial photo). Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower results.
				10	Н		Н	Н						Н					Н	Н		

Table 1 Subarea 5A Phase 3 Proposed Sample Locations (39 of 39)

							•			Ana	lytical M	lethod								
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082) Dioxins/Furans (FDA Mathod 1613)	Metals ² (EPA Methods 60108/6010C/6020/6020A/7471A/7471B)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyls (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTIM D2216/EPA Method 160.3)	Data Gap Checklist³	Rationale / Comments ^{4,5}
				0.5	X	X	X					X		70			X	X		Same as 5A_DG-869.
5A_DG-870	B4029	South of B4029	Soil Boring	5	X	Н	X					X					X	X	٧	
				10	Н	Н	Н					Н					Н	Н		
				0.5	X	X	X					X					X	X		Representative location in open field. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
5A_DG-871	B4029	East of B4029	Soil Boring	5	X	Н	X					X					X	X		results.
				10	Н	Н	Н					Н					Н	Н		
				0.5	X	X	X					X					X	X		Representative location in open field. Collect samples at 5' intervals to bedrock with deepest sample just above bedrock; hold deeper sample pending shallower
5A_DG-872	B4029	East of B4029	Soil Boring	5	X	Н	X					X					X	X		results.
				10	Н	Н	Н					Н					Н	Н		
				0.5	X	X	X					X					X	X		Location targets dirt road south of G Street and upslope from elevated detections (L4BS1014) in Subarea 6. Collect samples at 5' intervals to bedrock with deepest
5A_DG-873	B4029	North of B4029	Soil Boring	5	X	Н	X					X					X	X	٧	sample just above bedrock; hold deeper sample pending shallower results.
				10	Н	Н	Н					Н					Н	Н		

Footnotes

1. Sampling will generally be at 5 foot intervals to bedrock. In areas where fill is encountered or anticipated, samples will be collected from the top of native soil (beneath fill) and soil just above bedrock. Samples collected at 0.5' and 5' will be analyzed, with deeper samples placed on hold pending shallower results, unless otherwise stated. If deeper soils are encountered, additional sampling will be added as needed. Sample intervals may be added or adjusted based on field conditions.

- 2. Standard metals analysis includes silver and mercury, but does not include hexavalent chromium.
- 3. A check mark in column indicates sample was proposed based on review of information source indicated in the Data Gap Checklist, Table 4.
- 4. The Subarea 5A analytical suite for general operations includes primary chemical groups: PAHs, PCBs/PCTs, Metals, and TPH. The corrosion inhibitor suite includes formaldehyde and NDMA to address potential hydrazine use, and arsenic, hexavalent chromium, and morpholine (EPA Method 8260 TIC). PCBs/PCTs are proposed at locations associated with potential pond dredge material/mounds based on detections in previous sampling.
- 5. Dioxin analysis at depth is generally on hold pending shallower results unless warranted by observed site conditions (e.g. fill, subsurface features, or historical drainages).

Acronyms and Abbreviations

Ag = silver

AST = above-ground storage tank

B = building (e.g. B4005 is Building 4005)

B(a)P = benzo(a)pyrene

bgs = below ground surface

Cr(VI) = hexavalent chromium

D&D = decommissioning and demolition

EPA = Environmental Protection Agency

ft = foot/feet

H = sample on hold for corresponding analysis

HDMS - Historical Document Management System

Hg = mercury

HMSA = Hazardous Materials Storage Area

HSA = Historical Site Assessment

ISL = interim screening level

KEWB = Kinetic Experiment Water Boiler

ND = analyte not detected above method reporting limit

NDMA = n-nitrosodimethylamine

PAHs = polyaromatic hydrocarbons

Pb = lead

PCBs = polychlorinated biphenyls

PCTs = polychlorinated terphenyls

PDU = Coal Gasification Process Development Unit

ppm = parts per million

RCRA = Resource Conservation and Recovery Act

RFI = RCRA Facility Investigation

RL = reporting limit

RMHF = Radioactive Materials Handling Facility

SETF = SNAP Environmental Test Facility

SM = soil matrix

SV = soil vapor

TPH = total petroleum hydrocarbons

UST = underground storage tank

VOC = volatile organic compound

X = sample to be analyzed by corresponding analytical method

Zn = zinc

Table 2 Subarea 5A Phase 3 Proposed Soil Vapor Sample Locations (1 of 4)

Location ID	Area	Location Description	Depth (ft bgs) ¹	Data Gap Checklist ²	Rationale / Comments
5ASV_DG-501	SETF	North of B4024	5 10	٧	Representative location within operational area and near drainage; shallow bedrock anticipated (~5').
			5		Targets open storage area where most storage observed in aerial photos along fence.
5ASV_DG-502	SETF	Open Storage West of B4024	10	V	
5ASV_DG-503	SETF	West of B4024	5 10	٧	Targets terrain conductivity anomaly and open storage identified in EPA HSA and aerial photos; shallow bedrock anticipated (~5').
			5		Targets potential "stain" or "storage" observed in aerial photos (i.e., 1999) identified in EPA HSA, terrain conductivity anomaly, localized depression with cracked asphalt, linear patched asphalt observed on site walk, and
5ASV_DG-504	SETF	West of B4024	10 15	٧	fill from unknown origin west of B4024 observed at SL-245-SA5A to 30' (fill extent shown on 1961 B4024 facility drawing and likely placed during original construction activities of B4024).
			30	1	
5ASV_DG-505	SETF	Southwest of B4024	5 10	٧	Targets asphalt swale that directs surface water runoff west of B4024 into culvert west of the transformer pad; shallow bedrock anticipated shallow (~5').
5ASV_DG-506	SETF	Southwest of B4024	5	٧	Targets AST with unknown contents (AT-HS-5) identified in the Sitewide Tank Inventory (CH2M Hill, 2011); positioned adjacent to undefined feature observed in 1978 photograph (HDMSm000000249); shallow bedrock
3.151_50 300	5211		10 5	•	amticipated (~5). Targets the drainage along the northern edge of B Street immediately prior to flowing into the culvert diverting flow
5ASV_DG-507	SETF	Drainage Along B Street South of Building 4024	10	٧	south under B Street.
5ASV_DG-508	SETF	Southwest of B4024	5	٧	Targets removed fuel oil UST (UT-18); tank bottom depth expected ~8' with bedrock anticipated at ~10'. Collect deepest sample just above bedrock to assess potential leak from former UST.
			5 10		Targets fill from unknown origin west of B4024 observed at SL-245-SA5A to 30' (fill extent shown on 1961 B4024 facility drawing and likely placed during original construction activities); positioned near high bay ramp into B4024
5ASV_DG-509	SETF	West of B4024	15 20	٧	and adjacent to subsurface reactor vault complex.
			30		
5ASV_DG-510	SETF	Southeast of B4024	5	٧	Targets fill from unknown origin (in area following removal of underground tanks) and area of fenced open storage identified in EPA HSA and observed in aerial photos.
5ASV_DG-511	SETF	Southeast of B4024	5	٧	Same as 5ASV_DG-587; positioned adjacent to fill from unknown origin.
5ASV_DG-512	SETF	East of B4024	5 10	٧	Targets former radioactive liquid waste hold up tanks and retention basin; also located in area of open storage.
5 4 GW DQ 513	QPTF.	N. d CD4004	5		Targets removed fuel oil UST (UT-19) located northeast of B4024. Tank depth anticipated ~8'. Location based on facility drawing; previous location targeting UST (USSV1110) had bedrock refusal above the tank bottom depth.
5ASV_DG-513	SETF	Northeast of B4024	10	٧	Collect deepest sample just above bedrock to assess potential leak from former UST.
5ASV_DG-514	SETF	North of B4024	5	٧	Targets sanitary sewer pipe exit from B4024. Collect deepest sample just above bedrock to assess potential leak from sanitary sewer.
5ASV_DG-515	SETF	West of Building 4027	5	٧	Targets sanitary sewer pipe exit to B4027 and open storage along east side of B4027. Collect deepest sample just above bedrock to assess potential leak from sanitary sewer.
FACY DO SIG	CETE	Wishin P4027 Francisco	10	V	Same as 5ASV_DG-614.
5ASV_DG-516	SETF	Within B4027 Footprint	10 5		Targets former location of floor trench located beneath B4027 which was used as a hazardous waste storage facility.
5ASV_DG-517	SETF	Within B4027 Footprint	10 5	٧	Representative location in operational area south of B4027.
5ASV_DG-518	SETF	East of B4024	10	٧	
5ASV_DG-519	SETF	West of B4032	5 10	٧	Representative location near B4032 footprint.
5ASV_DG-520	SETF	Within B4032 Footprint	5	٧	Representative location within B4032 footprint (note: fill of unknown origin observed in adjacent borings).
			5		Targets removed fuel oil UST UT-22 and positioned within light toned mounded material identified in EPA HSA.
5ASV_DG-521	SETF	East of B4032	10	٧	Collect deepest sample just above bedrock to assess potential leak from former UST.
5ASV_DG-522	SETF	Within B4036 Footprint	5	- v	Representative location within former B4036 footprint.
5ASV_DG-523	SETF	North of B4023	5 10	٧	Representative location in open space area (no storage or other operations observed in aerial photos).
5ASV_DG-524	SETF	Within B4023	5	V	Representative location in former B4023 footprint.
5ASV_DG-525	SETF	South of B4023	10 5	٧	Targets sanitary sewer pipe exit from B4023. Collect deepest sample just above bedrock to assess potential leak
5ASV_DG-526	SETF	North of B4023	10 5	- V	from sanitary sewer. Targets ASTs with unknown contents (Unknown-AT-L9-1 and -2).
5ASV_DG-527	SETF	East of B4023	10 5	V	Targets former radioactive gas holdup tank vault.
			10 5		Targets area of open storage observed in post-1980 aerial photos.
5ASV_DG-528	SETF	East of B4023	10 5	٧	Targets confluence of multiple drainages receiving surface water runoff from operational areas to the northeast,
5ASV_DG-529	PDU	Drainage Along 17th Street Northwest of B4005	10	٧	north, and northwest, eventually discharging to the 17th Street Pond. Collect deepest sample just above bedrock to assess potential migration to groundwater.
5ASV_DG-530	PDU	Northwest of B4005	5	٧	Targets tank area; also addresses previous sampling with detections (PUSV04 and PUSV1010).
5ASV_DG-531	PDU	North of B4005	5	٧	Targets B4005 floor trench.
5ASV_DG-532	PDU	West of B4005	5	- V	Targets sanitary sewer pipe exit from B4023 and removed fuel oil UST (UT-01).
			10 5		Targets lined drainage along 17th Street, operational area south of B4005, and former road.
5ASV_DG-533	PDU	South of B4005	10	٧	

Table 2 Subarea 5A Phase 3 Proposed Soil Vapor Sample Locations (2 of 4)

Location ID	Area	Location Description	Depth (ft bgs) ¹	Data Gap Checklist ²	Rationale / Comments
5ASV_DG-534	PDU	South of B4005	5 10	٧	Same as 5ASV_DG-652.
5ASV_DG-535	PDU	Clearly Contaminated Area (PDU)	5 10	٧	Representative location within Clearly Contaminated Area; also addresses previous sampling with detection (PUSV1013).
5ASV_DG-536	PDU	Clearly Contaminated Area (PDU)	5 10	٧	Targets sump east of B4005.
5ASV_DG-537	PDU	Northern Portion of Clearly Contaminated Area (PDU)	5 10	٧	Targets for R/A Liquid waste holdup tanks and adjacent to location SL-189-SA5A (VOCs in soil matrix at 120x ISL).
5ASV_DG-538	PDU	Clearly Contaminated Area (PDU)	5	٧	Representative location within Clearly Contaminated Area; also addresses previous sampling with detection (PUSV1004).
5ASV_DG-539	PDU	Northeast of Clearly Contaminated Area (PDU)	5	٧	Targets B4793 footprint and area adjacent to Clearly Contaminated Area; shallow bedrock anticipated (~5°).
5ASV_DG-540	PDU	Within B4042 Footprint	5	٧	Targets former floor trench within B4042.
5ASV_DG-541	PDU	South of B4042	5	٧	Representative location in B4042 operational area.
5ASV_DG-542	PDU	Within B4042 Footprint	5	٧	Targets location SL-223-SA5A (TPH at 13x ISL); also characterizes fill of unknown origin and former road.
5ASV_DG-543	PDU	East of B4042	5	٧	Targets area of disturbed vegetation/soil observed in aerial photographs; shallow bedrock anticipated (~5').
5ASV_DG-544	PDU	Open Storage / Parking Area at 12th and G Street	5	٧	Targets open storage observed in aerial photos along western fence.
5ASV_DG-545	PDU	Open Storage / Parking Area at 12th and G Street	5	٧	Same as 5ASV_DG-665; shallow bedrock anticipated (~5').
5ASV_DG-546	PDU	Drainage Along G Street South of Open Storage / Parking Area	5	٧	Representative location in open area; shallow bedrock anticipated (-5').
5ASV_DG-547	PDU	Open Storage / Parking Area at 12th and G Street	5	٧	Targets geophysical anomalies and open storage.
5ASV_DG-548	PDU	East of Open Storage/Parking Area	10 5 10	٧	Targets "storage / dark toned material" identified in EPA HSA.
5ASV_DG-549	PDU	Drainage Along G Street, East of Open Storage / Parking Area	5	٧	Targets drainage along G Street. Collect deepest sample just above bedrock to assess potential migration to groundwater.
5ASV_DG-550	PDU	Open Storage / Parking Area at 12th and G Street	5	٧	Representative location in fenced open storage area.
5ASV_DG-551	PDU	Open Storage / Parking Area at 12th and G Street	5	٧	Same as 5ASV_DG-662.
5ASV_DG-552	PDU	Open Field East of Coal Storage / Parking Area	5	٧	Targets discharge from lined drainage into open field.
5ASV_DG-553	PDU	Drainage Along G Street, East of Coal	10 5	V	Same as 5ASV_DG-668.
5ASV_DG-554	PDU	Storage / Parking Area East of Coal Storage / Parking Area at	10 5	V	Targets unlined surface water pathway along the northeastern perimeter of Coal Storage/Parking Area; shallow bedrock anticipated (-5').
5ASV_DG-555	PDU	17th and G Street Coal Storage / Parking Area at 17th	10 5	V	Representative location in Coal Storage/Parking Area and adjacent to unlined drainage; shallow bedrock anticipated (-5°).
5ASV_DG-556	PDU	and G Street Northwest of Coal Storage / Parking	10 5	٧	Targets lined drainage along 17th Street and potential storage area to the northeast based on aerial photographs.
5ASV_DG-557	PDU	Area at 17th and G Street Coal Storage / Parking Area at 17th	10	. v	Representative location in Coal Storage / Parking Area; also addresses elevated RLs in previous sampling
		and G Street Drainages at Corner of 17th and G	10 5		(PUSV1403). Targets confluence of drainages to the northeast and northwest downslope of operational areas in PDU, SETF, and
5ASV_DG-558	PDU	Street	10	٧	B4641. Collect deepest sample just above bedrock to assess potential migration to groundwater.
5ASV_DG-559	B4641 Area	Southwest of B4073	5		Representative location in open field; shallow bedrock anticipated (~5').
5ASV_DG-560	B4641 Area	Southeast of Building 4073	5 10 5	٧	Targets discharge onto unlined surface from cooling water hold-up tank drain line. Targets drainage along former road. Collect deepest sample just above bedrock to assess potential migration to
5ASV_DG-561	B4641 Area	Drainage Along 12th Street	10 5	٧	l argets drainage along former road. Collect deepest sample just above bedrock to assess potential migration to groundwater. Targets fill (observed in nearby previous borings) and operational area north of B4073.
5ASV_DG-562	B4641 Area	North of B4073	10	٧	Targets former parking lot and open storage observed in 1988 oblique photo.
5ASV_DG-563	B4641 Area	Parking Area Between B4073 and 4083	10	٧	Representative location downslope from operational area to the northeast.
5ASV_DG-564	B4641 Area	West of B4083	10 5	V	Targets B4093 Leach Field. Collect deepest sample just above bedrock since potential input location to
5ASV_DG-565	B4641 Area	B4093 Leach Field	10 5	٧	groundwater. Targets sanitary sewer pipe exit from B4093. Collect deepest sample just above bedrock to assess potential leak
5ASV_DG-566	B4641 Area	B4093	10	٧	from sanitary sewer. Representative location along former road / dirt area southeast of B4093; shallow bedrock anticipated (~5').
5ASV_DG-567	B4641 Area	Southeast of B4093 Drainage East of Building 4093 Leach	10 5	٧	Location targets discharge of lined drainage onto unlined soils downslope of B4083 operational area. Collect
5ASV_DG-568	B4641 Area	Field	10	٧	deepest sample just above bedrock to assess potential input to groundwater at unlined drainage feature. Targets geophysical anomalies in field south of B4093 operational area.
5ASV_DG-569	B4641 Area	Open Field West of B4453	10	٧	
5ASV_DG-570	B4641 Area	Open Field South of B093 Leach Field	5 10		Representative location in open field south of B4093.
5ASV_DG-571	B4641 Area	Open Field South of B4453	5 10	٧	Representative location in open field; also positioned on former road.

Table 2 Subarea 5A Phase 3 Proposed Soil Vapor Sample Locations (3 of 4)

Location ID	Area	Location Description	Depth (ft bgs) ¹	Data Gap Checklist ²	Rationale / Comments
5ASV_DG-572	B4641 Area	Drainage Along 12th Street	5	٧	Targets drainage along 12th Street. Collect deepest sample just above bedrock to assess unlined drainage feature.
5ASV_DG-573	B4641 Area	Drainage at Intersection of 12th and G Street	5	٧	Targets collection point of two unlined drainages along 12th and G Streets. Collect deepest sample just above bedrock to assess potential migration to groundwater.
5ASV_DG-574	B4641 Area	Open Field Southeast of B4453	5		Representative location in open field south of 11th Street.
5ASV_DG-575	B4641 Area	Drainage Along G Street	10 5 10	٧	Targets drainage along G Street. Collect deepest sample just above bedrock to assess potential migration to groundwater.
5ASV_DG-576	B4641 Area	South of B4641	5 10	٧	Targets disturbed ground area identified in EPA HSA and visible in the 1995 aerial photo and potential leach field location.
5ASV_DG-577	B4641 Area	B4641 Footprint	5	٧	Representative location within B4641 footprint.
5ASV_DG-578	B4641 Area	B4046 Footprint	5	٧	Targets B4046 footprint and open storage identified in EPA HSA; shallow bedrock anticipated (~5').
5ASV_DG-579	B4641 Area	B4030 Footprint	5	٧	Targets sewer pipe exit from B4030 and open storage identified in EPA HSA; shallow bedrock anticipated (~5').
5ASV_DG-580	B4641 Area	Between B4030 and 4641	10 5 10	٧	Representative location in operational area adjacent to B4035; shallow bedrock anticipated (~5').
5ASV_DG-581	B4641 Area	Between B4030 and 4641	5	. V	Targets area of open storage and linear geophysical anomalies.
5ASV_DG-582	B4641 Area	South of B4641	10 5		Representative location in open field.
5ASV DG-583	B4641 Area	South of B4641	10 5	٧	Targets collection point of two unlined drainages receiving surface water runoff from B4641 and B4093 operational
5ASV_DG-584	B4641 Area	Drainage Along 10th Street	10 5	· v	areas to the north and west, respectively. Targets unlined drainage along 10th Street that receives surface water runoff from B4035 and B4641 operational
5ASV_DG-585	B4029 Area	West of Open Storage Area Along G	10 5		areas to the north. Same as 5ASV_DG-537.
5ASV_DG-586	B4029 Area	Street Open Storage Area Along G Street	10 5 10	٧	Targets western extent of "Waste Disposal Area" identified in EPA's HSA; shallow bedrock anticipated (~5').
5ASV_DG-587	B4029 Area	Open Storage Area Along G Street	5	٧	Representative location in "Waste Disposal Area" identified in EPA HSA.
5ASV_DG-588	B4029 Area	Open Storage Area Along G Street	5	v	Targets edge of hummocky area and "Waste Disposal Area" identified in EPA HSA. Shallow bedrock anticipated (~5'); collect deepest sample just above bedrock since assessing potential disposal area.
5ASV_DG-589	B4029 Area	Northeast of Open Storage Area Along	5	٧	Same as 5ASV_DG-550; also assesses former road and area of cleared vegetation observed in aerial photos between 1959 and 1972.
5ASV_DG-590	B4029 Area	G Street South of Open Storage Area Along G	10 5	٧	Same as 5ASV_DG-532; shallow bedrock anticipated (~5').
5ASV_DG-591	B4029 Area	Street South of Open Storage Area Along G Street	10 5 10		Same as 5ASV_DG-537.
5ASV_DG-592	B4029 Area	South of Open Storage Area Along G Street	5		Representative location in open field southwest of Open Storage Area along G Street; shallow bedrock anticipated (~5').
5ASV_DG-593	B4029 Area	West of Clearly Contaminated Area (Eastern Hummocky Area)	5 10		Representative location in area between two Clearly Contaminated Areas (17th Street Pond and Eastern Hummocky Area); shallow bedrock anticipated (~5').
5ASV_DG-594	B4029 Area	Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Targets Clearly Contaminated Area (Eastern Hummocky Area).
5ASV_DG-595	B4029 Area	Southwest of Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Targets hummocky area to investigate potential pond dredge sediment adjacent to Clearly Contaminated Area (Eastern Hummocky Area).
5ASV_DG-598	B4029 Area	Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Same as 5ASV_DG-501.
5ASV_DG-599	B4029 Area	Clearly Contaminated Area	5	٧	Same as 5ASV_DG-501.
5ASV_DG-600	B4029 Area	(Eastern Hummocky Area) North of Clearly Contaminated Area	10 5		Same as 5ASV_DG-514.
		(Eastern Hummocky Area) Southeast of Open Storage Area South	10 5		Targets surface water pathway downslope from "Waste Disposal Area" identified in EPA HSA.
5ASV_DG-601	B4029 Area	of G Street	10	٧	
5ASV_DG-602	B4029 Area	Northeast of Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Targets edge of hummocky area observed during site walk in May 2012 and surface water pathway that receives runoff from "Waste Disposal Area" identified in EPA HSA.
5ASV_DG-603	B4029 Area	Northeast of Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Targets hummocky area (low-profile) observed during site walk in May 2012.
5ASV_DG-604	B4029 Area	East of Clearly Contaminated Area (Eastern Hummocky Area)	5		Representative location in area adjacent to Clearly Contaminated Area (Eastern Hummocky Area).
5ASV_DG-605	B4029 Area	Northeast of Open Storage Area Along G Street	5		Representative location in open field south of G Street.
5ASV_DG-606	B4029 Area	Northeast of Open Storage Area Along G Street	5		Same as 5ASV_DG-550.
5ASV_DG-607	B4029 Area	West of SE Drum Yard	5	٧	Same as 5ASV_DG-550.
5ASV_DG-608	B4029 Area	Drainage Southwest of SE Drum Yard	5	٧	Targets open field next to drainage downsstream of SE Drum Storage Area.

Table 2 Subarea 5A Phase 3 Proposed Soil Vapor Sample Locations (4 of 4)

Location ID	Area	Location Description	Depth (ft bgs) ¹	Data Gap Checklist ²	Rationale / Comments
5ASV_DG-609	B4029 Area	East of Clearly Contaminated Area (Eastern Hummocky Area)	5	٧	Representative location in open field near hummocky areas observed during site walk in May 2012.
5ASV_DG-610	B4029 Area	South of SE Drum Yard	5 10		Representative location in open field south of drainage.
5ASV_DG-611	B4029 Area	South of SE Drum Yard	5 10		Same as 5ASV_DG-556; shallow bedrock anticipated (~5').
5ASV_DG-612	B4029 Area	South of SE Drum Yard	5 10	٧	Targets area of cleared vegetation observed in aerial photo from 1980.
5ASV_DG-613	B4029 Area	Southeast of SE Drum Yard	5	٧	Targets area of cleared vegetation observed in aerial photos between 1965 and 1972; also addresses elevated RLs in previous sampling (SESV02).
5ASV_DG-614	B4029 Area	Drainages Southwest of B4029	5	٧	Targets area of potential sheet flow / ponding (area of dense vegetation) between two parallel drainages (observed in aerial photos between 1978 and 1988).
5ASV_DG-615	B4029 Area	SE Drum Yard	5	٧	Targets SE Drum Yard and containers (observed in 1962-1963 aerial photo); also addresses elevated RLs in previous sampling (SESV01). Shallow bedrock anticipated (-5').
5ASV_DG-616	B4029 Area	West of SE Drum Yard	5 10		Same as 5ASV_DG-550.
5ASV_DG-617	B4029 Area	Drainages Southwest of B4029	5 10	٧	Targets one of two parallel drainages southwest of B4029; shallow bedrock anticipated (~5').
5ASV_DG-618	B4029 Area	Drainages Southwest of B4029	5	٧	Targets one of two parallel drainages southwest of B4029 and edge of ground scar identified in EPA HSA; shallow bedrock anticipated (-5).
5ASV_DG-619	B4029 Area	West of B4029	5		Representative location in open field.
5ASV_DG-620	B4029 Area	Northwest of B4029 Near G Street	5	٧	Targets discharge from culvert receiving surface water runoff from the B4641 operational area to the north. Collect deepest sample just above bedrock since assessing unlined drainage feature.
5ASV_DG-621	B4029 Area	West of B4029	5 10	٧	Same as 5ASV_DG-572.
5ASV_DG-622	B4029 Area	Southwest of B4029 Access Road	5	٧	Targets discharge from historical and current storm drain culverts along slope southwest of B4029 access road. Collect deepest sample just above bedrock since assessing unlined drainage feature.
5ASV_DG-623	B4029 Area	North of B4029	5	٧	Targets discharge from culvert receiving surface water runoff from the B4064 operational area to the north. Collect deepest sample just above bedrock since assessing unlined drainage feature.
5ASV_DG-624	B4029 Area	West of B4029	5	٧	Same as 5ASV_DG-577.
5ASV_DG-625	B4029 Area	South of B4029	5 10	٧	Targets ground scar identified in EPA HSA and area downslope from B4029 access road.
5ASV_DG-626	B4029 Area	West of B4029	5	٧	Targets road base/fill beneath B4029 access road and assesses elevated TPH detections within fill to the west; also targets storage/containers observed in aerial photo from 1980.
5ASV_DG-627	B4029 Area	South of B4029	5	٧	Representative location downslope of B4029.
5ASV_DG-628	B4029 Area	East of B4029	5		Representative location in open field south of B4029.
5ASV_DG-629	B4029 Area	East of B4029	5		Same as 5ASV_DG-570.
5ASV_DG-630	B4029 Area	North of B4029	5	٧	Targets dirt road north of B4029 and upslope of Subarea 6.

1. Soil vapor sampling field protocols still being defined; proposed sampling included in table to be implemented after DTSC approval of Soil Vapor SOP. It is anticipated that soil vapor samples will be collected at 5-foot intervals to a depth of 20 feet bgs, and at 10-foot intervals thereafter to bedrock with the deepest sample targeting soil just above bedrock. All soil vapor samples will be collected and analyzed in accordance with approved procedures in a Soil Vapor SOP. In areas where soils are not deep enough for soil vapor analysis, soil matrix samples will be collected for VOC analysis using EPA Method 8260B if soils are more than 2 feet thick.

2. Checkmark in column indicates sample was proposed based on review of information source indicated in Table 2 for the area listed in "Location Description" (GIS or aerial photo review layers).

Acronyms

AST = aboveground storage tank
bgs = below ground surface
DTSC = California Department of Toxic Substances Control
EPA = Environmental Protection Agency
ft = foot/feet

GIS = geographic information system HSA = Historical Site Assessment ISL = interim screening level

LF = leach field PDU = Process Demonstration Unit

PDU = Process Demonstration Unit
RL = reporting limit
SETF = SNAP Environmental Test Facility
SOP = standard operating procedure
SV = soil vapor
TPH = total petroleum hydrocarbons
UST = underground storage tank
VOC = volatile organic compound

Table 3 Subarea 5A Phase 3 Proposed Sample Locations for Future Collection (1 of 1)

													Analytica	al Metho	i										
Location ID	Area	Location Description	Sample Type	Depth (ft bgs) ¹	PAHs including NDMA (EPA Method 8270C [SIM])	PCBs / PCTs (EPA Method 8082)	Dioxins/Furans (EPA Method 1613)	Metals ² (EPA Methods 6010B/6010C/6020/6020A/7471A/7471B)	Cr(VI) (EPA Method 7196A)	Energetics (EPA Method 8330A)	Perchlorate (EPA Method 6850/6860)	1-4 Dioxane (EPA Method 8360B SIM)	Terphenyk (EPA Method 8015B)	TPH (EPA Method 8015B)	Formaldehyde (EPA Method 8315A)	Morpholine (EPA Method 8260 TIC)	VOCs (SV) (EPA Method 8260B)	VOCs (SM) (EPA Method 8260B)	Pesticides (EPA Method 8081)	Herbicides (EPA Method 8151A)	pH (EPA Method 9045C)	Soil Moisture (ASTM D2216/EPA Method 160.3)	Data Gap Checklist	Rationale / Comments ^{4,5}	
5A_DG-805	B4029	South of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Boring	0.5 5	X X H	X X H	X X H	X X H						X X							X X H	X X H		Future Location. Stepout to characterize southern extent of Clearly Contaminated Area (Eastern Hummocky Area).	
5A_DG-806	B4029	South of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Boring	0.5 5	X X H	X X H	X X H	X X H						X X H							X X H	X X H		Future Location. Same as 5A_DG-805.	
5A_DG-803	B4029	Southwest of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Boring	0.5 5 10	X X H	X X H	X X H	X X H						X X H							X X H	X X H		Future Location. Stepout for PCBs and TPH at P2TS48 and characterizes southern extent of hummocky area.	
5ASV_DG-596	B4029 Area	Southwest of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Vapor	5 10													X X						٧	Future Location. Representative location downslope of hummocky area observed during site walk in May 2012.	
5ASV_DG-597	B4029 Area	South of Clearly Contaminated Area (Eastern Hummocky Area)	Soil Vapor	5 10													X X						٧	Future Location. Representative location downslope of Clearly Contaminated Area (Eastern Hummocky Area).	

Footnotes

1. If deeper soils are encountered, additional sampling will be added as needed. Sampling will generally be at 5 foot intervals to bedrock, but will target the top of native soil (beneath fill) and soil just above bedrock. Therefore, sample intervals may be added or adjusted

- 2. Standard metals analysis includes silver and mercury, but does not include hexavalent chromium.
- 3. A check mark in column indicates sample was proposed based on review of information source indicated in the Data Gap Checklist, Table 3.
- 4. The Subarea 5A analytical suite for general operations includes primary chemical groups: PAHs, PCBs/PCTs, Metals, and TPH. The corrosion inhibitor suite includes formaldehyde and NDMA to address potential hydrazine use, and arsenic, hexavalent chromium, and morpholine (EPA Method 8260 TIC). PCBs/PCTs are proposed at locations associated with potential pond dredge material/mounds based on detections in previous sampling.
- 5. Dioxin analysis at depth is generally on hold pending shallower results unless warranted by observed site conditions (e.g. fill, subsurface features, or historical drainages).

Acronyms and Abbreviations
B = building (e.g. B4005 is Building 4005)
bgs = below ground surface
EPA = Environmental Protection Agency
ft = foot/feet

H = sample on hold for corresponding analysis

NDMA = n-nitrosodimethylamine

PAHs = polyaromatic hydrocarbons PCBs = polychlorinated biphenyls

PCTs = polychlorinated terphenyls

SM = soil matrix

SV = soil vapor TPH = total petroleum hydrocarbons

VOC = volatile organic compound
X = sample to be analyzed by corresponding analytical method

Table 4 Subarea 5A Data Gap Checklist (Page 1 of 2)

Subarea 5A Data Gap Evaluation Areas ¹

INFORMATION SOURCE

	SETF	B4641 Area	PDU Area	Subarea 5A South
GIS Base Map Layers				
Tanks (and Sitewide Tank Inventory Table)	٧	٧	٧	V
Transformers	٧	V	√	V
Structures	V	V	٧	V
Sumps	٧	٧	√	V
Vaults	V	٧	٧	V
Pipes	V	٧	٧	V
Undefined features	V	V	٧	٧
Chemical Use Areas (RFI)	V	V	٧	V
Streams/ditches	V	V	٧	V
Leachfields	٧	V	٧	٧
Storage Yard Areas	V	V	٧	V
Roads	٧	V	٧	V
Soil Disturbance (Veg clearance, excavation, grading, etc)	٧	٧	٧	√
Migration Pathways				
Surface Water	٧	٧	٧	V
Aerial Dispersion ²	V	٧	٧	٧
Subsurface Soil	٧	٧	٧	٧
Site-wide Infrastructure				
IWW - spray fields	٧	٧	٧	V
Natural Gas Pipelines (site-wide approach also in progress)	٧	٧	٧	V
Sewer (site-wide approach also in progress)	√	√	٧	٧
Aerial Photo Review				
Historical aerial photographs from 17 years (1953 - 2005)	٧	√	٧	V
EPA Layers				
Gamma Scan	٧	V	٧	V
Potential Gamma Anomalies (PGRAY)	N/A	N/A	N/A	N/A
Tank Points (Subarea 5C specific)	N/A	N/A	N/A	N/A
HSA Line Layer (HSA linear features)	N/A	N/A	N/A	N/A
HSA Photo Layer (HSA aerial photo review features)	٧	٧	√	٧
Historical Use Data (chem use, storage, leach fields, releases, interviews, etc.)	٧	٧	٧	٧
Area IV Conduit (pipelines)	٧	√	٧	٧
Geophysical Survey (EM, GPR, TC)	٧	٧	٧	٧

Table 4 Subarea 5A Data Gap Checklist (Page 2 of 2)

Subarea 5A Data Gap Evaluation Areas ¹

INFORMATION SOURCE

	SETF	B4641 Area	PDU Area	Subarea 5A South
Other ³				_
Existing Building Feature Documentation - process info reviewed	√	V	٧	٧
Historical Facility Diagrams - deep feature info reviewed	√	√	٧	√
Groundwater Impacts / Potential Inputs to Groundwater Evaluated ⁴	٧	٧	٧	٧
Site-wide Tank Inventory Table for unlocated tanks (viewed with Tanks Base Map layer)	√	٧	٧	٧
EPA Area IV radiological sampling results ⁵	N/A	N/A	N/A	N/A
Uncollected EPA Phase 1 sample locations ⁶	٧	٧	٧	٧
Field reconnaissance / mapping ⁷	٧	V	٧	V

Notes

- **v** Feature reviewed during data gaps evaluation
- **∨** Indicates sampling proposed based on reviewed feature
- "--" No buildings present for inspection

N/A - Information source not available for this subarea

- 1. Data gap evaluations were performed over smaller footprints within each subarea. For Subarea 5AN this includes: SETF Area includes B4023, B4024, B4027, B4032, B4036, B4037, cooling tower (B4928), and the area surrounding these buildings; B4641 Area includes B4030, B4035, B4046, B4073, B4074, B4083, B4093, B4103, B4123, B4453, B4633, B4641, B4643, B4793, B4893, and the area surrounding these buildings; and PDU Area includes 4005, B4042, B4048, B4049, B4185, B4636, B4793, B4823, transformer substation (B4705), two parking lots (B4501 and B4536), and surrounding buildings and features. For Subarea 5AS this includes: B4029 and the area surrounding this building; the SE Drum Yard RFI Site and the area surrounding this site; the Clearly Contaminated Area (Eastern Hummocky Area) and surrounding area; and the Open Storage Area (identified as the "Waste Disposal Area" in EPA's HSA 5A Tech Memo) and surrounding area.
- 2. Evaluation of air dispersion migration pathways was performed using existing sampling results, or proposing additional sampling as warranted along predominant wind directions (NW-SE), and/or in adjacent drainages. For Subarea 5AN, five air dispersion sources were evaluated: stacks at B4005 (2), B4024, B4023, and B4643. Additional future sampling is recommended in Subarea 7 and the NBZ to assess this pathway, but existing data along with newly proposed Phase 3 locations is considered sufficient to assess potential contamination within Subarea 5AN from this pathway. No sampling proposed in 5AS due to lack of significant air dispersion migration pathways (e.g. no stacks present) within the subarea.
- 3. Other notes and resources used in the data gap process included data dotmaps, a co-located sampling boring log summary table (including analytical and sample depth info), boring and trench logs from the RFI, EPA boring logs from co-located sampling, filterable dataset, the EPA HSA document, and previous RFI SAPs (e.g Group 8 for B4056 drainage north of B4100). Previous RFI Group reports were used as a reference on an as-needed basis in evaluation of selected features (e.g. building use descriptions).
- 4. Feature/area identified that may warrant further consideration of groundwater input sources and threat to groundwater sampling requirements by DTSC and SSFL groundwater teams. Identification based on type of feature (typically, a liquid waste disposal or storage feature), and soil detections of mobile chemicals (e.g., VOCs, NDMA, perchlorate, 1,4-dioxane), and/or multiple chemical detections significantly above ISLs.
- 5. EPA radiological sampling results summaries will be included as part of chemical data gap evaluation process. Validated data for Subarea 5A is not currently available and will be reviewed when provided by EPA.
- 6. Proposed Phase 1 sampling locations where no radiological sample was collected by EPA (due to refusal, safety concerns, etc.) were evaluated to determine if a chemical data gap still existed, with additional sampling proposed in Phase 3 if a gap was identified.
- 7. Information captured during site walks or other field observations and included in supplemental GIS layers for surface water drainages/pathways, soil disturbance areas (e.g. hummocky areas potentially containing pond dredge material), and other relevant features.



