Comparison of Fuel Cell Technologies

Fuel Cell Type	Common Electrolyte	Operating Temperature	Typical Stack Size	Electrical Efficiency (LHV)	Applications	Advantages	Challenges
Polymer Electrolyte Membrane (PEM)	Perfluorosulfonic acid	<120°C	<1 kW - 100 kW	60% direct H_2;[i] 40% reformed fuel[ii]	• Backup power • Portable power • Distributed generation • Transportation • Specialty vehicles	• Solid electrolyte reduces corrosion & electrolyte management problems • Low temperature • Quick start-up and load following	• Expensive catalysts • Sensitive to fuel impurities
Alkaline (AFC)	Aqueous potassium hydroxide soaked in a porous matrix, or alkaline polymer membrane	<100°C	1 - 100 kW	60%[iii]	• Military • Space • Backup power • Transportation	• Wider range of stable materials allows lower cost components • Low temperature • Quick start-up	• Sensitive to CO_2 in fuel and air • Electrolyte management (aqueous) • Electrolyte conductivity (polymer)
Phosphoric Acid (PAFC)	Phosphoric acid soaked in a porous matrix or imbibed in a polymer membrane	150 - 200°C	5 - 400 kW, 100 kW module (liquid PAFC); <10 kW (polymer membrane)	40%[iv]	• Distributed generation	• Suitable for CHP • Increased tolerance to fuel impurities	• Expensive catalysts • Long start-up time • Sulfur sensitivity
Molten Carbonate (MCFC)	Molten lithium, sodium, and/or potassium carbonates, soaked in a porous matrix	600 - 700°C	300 kW - 3 MW, 300 kW module	50%[v]	• Electric utility • Distributed generation	• High efficiency • Fuel flexibility • Suitable for CHP • Hybrid/gas turbine cycle	• High temperature corrosion and breakdown of cell components • Long start-up time • Low power density
Solid Oxide (SOFC)	Yttria stabilized zirconia	500 - 1000°C	1 kW - 2 MW	60%[vi]	• Auxiliary power • Electric utility • Distributed generation	• High efficiency • Fuel flexibility • Solid electrolyte • Suitable for CHP • Hybrid/gas turbine cycle	• High temperature corrosion and breakdown of cell components • Long start-up time • Limited number of shutdowns

i NREL Composite Data Product 8, "Fuel Cell System Efficiency," http://www.nrel.gov/hydrogen/docs/cdp/cdp_8.jpg
ii Panasonic Headquarters News Release, "Launch of New 'Ene-Farm' Home Fuel Cell Product More Affordable and Easier to Install," http://panasonic.co.jp/corp/news/official.data/data.dir/2013/01/en130117-5/en130117-5.html
iii G. Mulder et al., "Market-ready stationary 6 kW generator with alkaline fuel cells," ECS Transactions 12 (2008) 743-758
iv Doosan PureCell Model 400 Datasheet, http://www.doosanfuelcell.com/attach_files/link/PureCell%20Model%20400%20Datasheet.pdf
v FuelCell Energy DFC300 Product Specifications, http://www.fuelcellenergy.com/assets/DFC300-product-specifications1.pdf
vi Ceramic Fuel Cells Gennex Product Specifications, http://www.cfcl.com.au/Assets/Files/Gennex_Brochure_%28EN%29_Apr-2010.pdf

For More Information

More information on the Fuel Cell Technologies Office is available at http://www.hydrogenandfuelcells.energy.gov.

April 2016
Printed with a renewable-source ink on paper containing at least 50% wastepaper, including 10% post consumer waste.