

Biomass – Material Handling Considerations

Overview of the Efforts in Feedstock & Materials Handling - Key Technical and Economic Challenges Identified for Different Processes Biorefinery Optimization Workshop October 2016 DOE

Carrie Hartford, P.E.
Senior Project Engineer
chartford@jenike.com



BIOMASS "FLOWABILITY"

Biomass types can vary significantly!

- ▶ Particle size, shape, and moisture variation
- Differences affect material flowability

Flowability is a function of the material AND the equipment

- "Poor flowing" material can be handled easily in properly designed equipment
- "Easy flowing" material can present flow problems in poorly designed equipment


























EXTENT OF HANDLING PROBLEMS



¹Rand Study: Sample of **40 plants** in US and Canada over a **6 year** duration. Merrow, E., "*Problems and progress in particle processing*", Chemical Innovation, Jan. 2000 & Chemical Engineering; Oct. 1988, Vol. 95, Issue 15



RAND STUDY CONCLUSIONS


- ▶80% experienced solids handling problems
- Average startup time 18 months
 - vs. 3 months for liquids
 - ► Average cost per month delay ≈ \$350,000¹
- Typical performance 40 to 50% of design
- Problems related to "physics and mechanics of processes rather than to chemistry"

¹ \$350,000 in "1988 dollars"; today's value ≈ \$1,000,000



CAPABILITY MAP

Key reasons that specific technology development programs fail are²:




- ► Lack of strategic alignment with business → lack of adequate support and resources
- ► Lack of a disciplined phasing during development → projects progress that should not
- Lack of a corporate champion to maintain momentum over the years
- Not bringing the best possible minds and experience to the program

²Twigge-Molecey, C."Knowledge, Technology and Profit" 2003 - Cobre 2003; Fifth International Conference; Santiago; Chile; 30 Nov.-3 Dec. 2003. pp. 41-57. 2004 ³ Wellwood, Grant. "Fail to plan?; Plan to fail!-The case for Capability Mapping", LinkedIn Post March 2016.




COST OF MODIFICATION



Kennedy, M., Harris, C., MacRaw, A., (2013); Risk-weighted cash flow: a communication tool for engineers and financial professionals on new technology projects, CIM Journal, Vol. 3, No. 4, 2012




GRAVITY FLOW SYSTEMS FLOW PROBLEMS - NO FLOW/ERRACTIC FLOW









Ratholing



FUNNEL FLOW


Issues

- ► Some material is stagnant
 - ▶ Biomass may oxidize, ferment/have runaway bioactive reactions, smolder, ignite
- Arching, ratholing, and erratic flow can occur
- Limited live capacity
- Varying bulk density

Features

- ► Low headroom
- First-in, last-out
- Ratholes may develop
- Fine powders will flood








MASS FLOW

- Allows for uniform velocity of the material
- Can design for even distribution of air injected into the moving bed of material
- Constant bulk density at the outlet
- ▶ Reliable flow




TEST & DESIGN




- ► Test to measure relevant properties
- ▶ Set design spec window of acceptable material
- ▶ Determine appropriate flow pattern
- Use proven design methodology
- Consider different approaches if gravity flow is not possible
- Consider processing and storing in one bin design (purge vessel)



CONSTANT PITCH SCREW FEEDER




MASS FLOW SCREW FEEDER



CONCLUSION

- Set aside sufficient money and time to measure the flow characteristics.
 - ▶ If material changes mid project test again!
- Establish an acceptance criteria for incoming material
- Reliable handling silos can also act as a processing vessel
- Don't forget the feeder design!
- Get a bulk materials expert involved early on





Carrie Hartford, P.E.
Senior Project Engineer
+1 805 541 0901
chartford@jenike.com

