#### Geothermal Technologies Office 2017 Peer Review

**ENERGY** Energy

Energy Efficiency & Renewable Energy



Acoustic Sensor Arrays

Autonomous monitoring of wellbore integrity applying Time Reverse Nonlinear Elastic Wave Spectroscopy (TR NEWS) and Fiber Optic Sensing and Communication

Project Officer: Alexandra Prisjatchew

Total Project Funding: \$3My

November 14 . 2017

#### Pls: P. Johnson & G. Guthrie Presenter Name : P. Johnson

Track Name

This presentation does not contain any proprietary confidential, or otherwise restricted information.

Objective: development of an autonomous system that can be deployed in wells for long-term (e.g., decades), unattended monitoring both wellbore integrity and associated stress changes

- targets the lack of an affordable autonomous system that can be used to wellbore integrity, particularly post closure.
- Impacts leakage-related issues in C0<sub>2</sub> monitoring efforts and impact geothermal energy development in regards to damage and stress assessment

**Innovation**: Combination of (i) passive long term monitoring of seismic signals associated with leakage applying machine learning approaches; (ii) fiber optics to follow anomalous stress evolution near the borehole; (iii) Time Reversal and Nonlinear Elasticity for localized damage assessment [*Time Reversal Nonlinear Elastic Wave Spectroscopy, TR NEWS*]

# Relevance to Industry Needs and GTO Objectives

**ENERGY** Energy Efficiency & Renewable Energy

Impact the Geothermal Technologies Office's goal(s)

We develop a system applied to wellbore and near wellbore leakage monitoring. [note project is funded by DOE C02]–

Research Collaboration and Technology Transfer: we are working with Chevron and our goal is to develop the system

Methods/Approach: The novel approach is a combination of stress monitoring, listening to leakage and diagnostics applying TR-NEWS

Based on nonlinear elastic behavior of rock: Primary contribution to nonlinearity is mechanical damage. "Distributed" "Localized"

10853-1 2 Sov

### Methods/Approach



scientific/technical approach:



# Methods/Approach

U.S. DEPARTMENT OF

Energy Efficiency & Renewable Energy



# Methods/Approach

**ENERGY** Energy Efficiency & Renewable Energy

 Key issues we are addressing: This proposal targets the lack of an affordable autonomous system that can be used to wellbore integrity, particularly post closure

Implementation of combined technologies in the borehole



We are only beginning our project tasks

### Technical Accomplishments and Progress

**ENERGY** Energy Efficiency & Renewable Energy

Describe the most important technical accomplishments and progress and their significance. **Stay tuned!** 

#### Tasks:

- Task 1: Integration and Technical Project Management.
- Task 2. Literature review and evaluation of proposed technology strategies.
- Task 3: Detect small seismo-acoustic signals associated with fluid flow in a damaged wellbore annulus.
- Task 4: Use time reversal to focus energy within a wellbore system.
- Task 5: Detect nonlinear responses of wellbore system as a function of integrity.
- Task 6: Measure changes in stress along a wellbore system.
- Task 7: Assess design for prototype field system.



• Summarize any industry or academic engagement that is taking place under this project

We are working with Chevron to take this to completion. Partners are Chevron, LBNL, Clemson University and Los Alamos.

 Describe opportunities or efforts currently underway to transition technology to the private sector.

Stay tuned for this aspect of work.....



# **Future Directions**

- Describe deployment strategy or expected outcome of this effort. Discuss future research, development or deployment needs.
- We intend to get to the design stage for a prototype system
  - Explain key activities for the rest of FY2018 and to project completion.

[see next slide]



#### Milsestones and deliverables



Table	1. Timeline for project b	y ta	sk ar	nd p	proje	ct ye	ar (P	Y) <i>,</i> wit	h twc	go/r	10-go	o (G/	NG) (	decisi	on points.	
Task	Task Description	PY1					PY2				РҮЗ				Product	Dependencies
		Q1	Q2	G/NG	Q3	Q4	Q5	Q6 N/9	Q7	Q8	Q9	Q10	Q11	Q12		
1.0	Technical Project Management (200)														<ul> <li>Quarterly reports; other sponsor requests</li> </ul>	
2.0	Literature Review & Technology Evaluation (250)														<ul> <li>Briefing with detail to assess 1<sup>st</sup> go/no-go</li> </ul>	
3.0	Detect Fluid Flow (250)														<ul> <li>Report documenting lab results on detecting small signals</li> </ul>	"Go" at 1 <sup>st</sup> go/no-go
4.0	Use TR to Focus Energy (200)														<ul> <li>Report documenting lab results on TR focusing of acoustic energy</li> </ul>	"Go" at 1 <sup>st</sup> go/no-go
5.0	Detect nonlinear Properties (750+														<ul> <li>Final report summarizing lab and field results and data</li> </ul>	Successful completion of 4.0
5.1	Lab-scale Experiments (														<ul> <li>Initial report on lab results as needed to assess 2<sup>nd</sup> go/no-go</li> </ul>	Successful completion of 4.0
5.2	Field-scale Experiments														<ul> <li>Data documenting field performance</li> </ul>	"Go" at 2 <sup>nd</sup> go/no-go
6.0	Measure Stress Field														<ul> <li>Final report summarizing lab and field results and data</li> </ul>	
6.1	Lab-scale Experiments														<ul> <li>Initial report on lab results as needed to assess 2<sup>nd</sup> go/no-go</li> </ul>	
6.2	Field-scale Experiments														<ul> <li>Data documenting field performance</li> </ul>	"Go" at 2 <sup>nd</sup> go/no-go
7.0	Re-assess design criteria														<ul> <li>Report assessing feasibility of commercial system based system, along with a development pathway</li> </ul>	

#### Take Away

- Develop an autonomous system for long-term deployment in wells for unattended monitoring wellbore integrity and associated stress changes
- System consisting of wellhead and downhole components based on the combined signals of piezoelectric and/or optical sensors
- Signal target: (i) seismo-acoustic signals associated with moving (leaking) fluids; (ii) the stress field along the wellbore where changes in stress may presage damage and leakage; (iii) nonlinear properties in the nearwellbore region that arise when damage develops and progresses.