## WATER EVALUATION DATA COLLECTION FORM

## Plumbing Fixtures - Restrooms, Locker Rooms and/or Kitchenettes

## Building number and name

Danian g manibor and manib						
Location of plumbing fixtures:					Restroom type:	Male / Female / Unisex
	Toilets	Urinals	Faucets*	Showers	Co	omments
Count of fixtures						
Primary fixture type (circle )	Tank (Gravity) / Tank (Pressure Assisted) / Flush Valve		With Aerator / Without Aerator	Threaded Fixed / Hand Held Wall Mount/ Gang		
Flush valve only - Primary flush valve type (circle)	Diaphragm / Piston	Diaphragm / Piston / Non-water				
Flush valve only - Fixture mount type (circle)	Floor Mount / Wall Mount / Floor with Rear Discharge	Floor Mount / Wall Mount				
Operation type (circle)	Manual / Sensor/ Dual Flush	Manual / Sensor	Manual / Sensor / Metered			
Urinal only - Discharge tube diameter (check)		34"; 11⁄4"				
Rated flush rate - gallons per flush (gpf)						
Rated flow rate - gallons per minute (gpm)						
Flush valve only - Average flush time (sec)						
Measured average flow rate (gpm)						
Percentage of occupants showering daily, weekdays						
Percentage of occupants showering daily, weekends						

<sup>\*</sup>This includes faucets located in bathroom, locker room and/or kitchenettes.