



Certificate of Analysis

Certified Reference Material U005A (10mg) Uranium (U₃O₈) Isotopic Standard, 0.5% U-235, 10 mg U

	²³⁴ U	²³⁵ U	²³⁶ U	²³⁸ U
Atom Percent:	0.00340	0.5064	0.00118	99.4890
Uncertainty:	±0.00007	±0.0003	±0.00001	±0.0003
Weight Percent:	0.00334	0.5000	0.00117	99.4955

This Certified Reference Material (CRM) is primarily intended for the calibration of mass spectrometers used to perform uranium isotopic measurements. The specific purpose of this isotopic standard is for the determination of mass discrimination effects for uranium isotopes being measured under similar analytical conditions. Each unit of U005A consists of approximately 10 milligrams of uranium, in the form of highly purified U₃O₈, contained in a glass bottle.

The indicated uncertainties for the isotopic composition of the CRM are 95% confidence intervals for the mean. For the minor isotopes (²³⁴U and ²³⁶U), these uncertainties take into account the uncertainties associated with separated and spike isotopes used in this certification work.

This CRM was originally issued in 1984 by the National Bureau of Standards (NBS) as Standard Reference Material (SRM) U-005a. The measurements made at NBS leading to the certification were performed by J.W. Gramlich, L. A. Machlan, and J.R. Moody, under the direction of E.L. Garner. The statistical analyses were performed by W. S. Liggett, NBS. In 1987, the technical and administrative transfer of NBS Special Nuclear SRMs into the NBL CRM Program was coordinated by the NBS Office of Standard Reference Materials and N. M. Trahey, NBL.

The certified isotopic abundance values were determined using a solid-sample thermal ionization mass spectrometer equipped with a Faraday cup detection system. The measured ²³⁵U/²³⁸U values were corrected for mass discrimination effects by intercomparison with synthetic calibration mixtures of similar ²³⁵U levels, prepared from high-purity ²³⁵U and ²³⁸U separated isotopes. The ²³⁵U/²³⁸U value for this standard, 0.005090, is known to at least 0.03%.

The ²³⁴U and ²³⁶U abundances were determined by isotope dilution mass spectrometry using high-purity ²³³U as the spike.

Expiration of Certificate: When stored in its original, unopened container, the certification of this material is valid indefinitely. The NBL PO will periodically monitor the materials in inventory and notify customers should degradation be detected.

Stability and Storage: This material should be stored in its original packaging under normal laboratory environmental conditions.

Minimum Sample Size: The NBL Program Office has validated that samples of 1 mg of oxide or larger are isotopically homogenous. The NBL Program Office recommends sampling of oxide of 1 mg or more for use of this material as an isotopic Certified Reference Material.